

RF Exposure Evaluation



Applicant : Cyber Power Systems, Inc.
Product : Wireless USB Dongle
Model : SNWDG001, EMWD-U01
FCC ID : 2AFG8SNWDG001

In accordance with
FCC rule Part §1.13101

RESPONSIBLE FOR	NAME	SIGNATURE	DATE
Approved By	Jack Chang		2025.08.28
Prepared By	Ariel Hsu		2025.08.28

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service control rules.

EXECUTIVE SUMMARY

TÜV SÜD Asia Ltd., reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Asia Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Asia Ltd. issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

Contents

1	General Information	3
1.1	Report Modification Record.....	3
1.2	Introduction.....	3
1.3	Applied Standard.....	4
1.4	Deviation from standards	4
1.5	Reference Test Report.....	4
2	General EUT Information	5
2.1	Technical Specification of EUT	5
2.2	Antenna List	5
3	FCC Maximum Permissible Exposure Evaluation	6
3.1	Introduction.....	6
3.2	Reference Levels	6
3.3	Power Density Calculation (Worst Case)	6

1 General Information

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

History of this test report

Issue	Description of Change	Date of Issue
1	Initial Issue	2025-08-28

1.2 Introduction

The information contained in this report is intended to show verification of RF qualification approval. The testing requirements of the standards for the tests listed in Section 1.5.

Applicant : Cyber Power Systems, Inc.
Address : 11F, No. 26,, Jinzhuang Rd., Neihu Dist., Taipei, Taiwan
Manufacturer : CyberPower (ShenZhen) System Inc.
Brand Name : CyberPower
Product Name : Wireless USB Dongle
Model Number(s) : SNWDG001, EMWD-U01
Date of Receipt of EUT : 2025-07-10
Start of Test : 2025-07-15
Finish of Test : 2025-07-24
Test Laboratory : TÜV SÜD Asia Ltd., Taiwan Branch
Address : 7F., No. 37, Sec. 2, Zhongyang S. Rd., Beitou District, Taipei City 11270, R.O.C. Taiwan
Test Location : TÜV SÜD Asia Ltd., Taiwan Branch, Guishan Laboratory
Address : No. 31, Dinghu Road, Guishan District, Taoyuan City, TAIWAN (R.O.C.)

The test facility is accredited by TAF (member of ILAC), under number 2573 according to ISO/IEC 17025: 2017.

FCC Designation Number No.: TW2573

1.3 Applied Standard

FCC rule Part §2.1091
FCC Part §1.1310 FCC KDB 447498 D04 Interim General RF Exposure Guidance v01

1.4 Deviation from standards

None

1.5 Reference Test Report

Test Lab	TÜV SÜD Asia Ltd., Taiwan Branch
Report Number	6128625041301

2 General EUT Information

All information in this chapter was provided by the applicant.

2.1 Technical Specification of EUT

Items	EUT information
Operating Frequency	2402 ~ 2475 MHz
Channel number	15
Maximum Output Power (dBm)	Zigbee: 4.38dBm
Operation Voltage	5Vdc
Modulation	O-QPSK
Test Software Version	STM32CubeMonitor-RF: Version 2.12.0

2.2 Antenna List

	Antenna Type	Brand	Model	Connector	Freq. (MHz)	Peak Antenna Gain (dBi)
Main	Chip Antenna	WALSIN	MULTILAYER CERAMIC ANTENNA	Permanently attached antenna	2400 - 2500	2.13

3 FCC Maximum Permissible Exposure Evaluation

3.1 Introduction

This Standard specifies requirements for, and provides guidance on, assessing compliance with the exposure limits of radiofrequency (RF) safety standards such as IEEE Std C95.1. This includes methodologies for making an assessment (by measurement or computation) of human exposure to ambient RF fields and induced body currents in the frequency range of 0 kHz to 300 GHz.

This Standard may also be used as a guide for making low-level environmental exposure assessments in areas around RF sources listed above, as well as other sources such as Wi-Fi devices.

3.2 Reference Levels

According to 447498 D04 Interim General RF Exposure Guidance v01 B.4 SAR-based Exemption, The formula defines the thresholds in general for either available maximum timeaveraged power or maximum time-averaged ERP, whichever is greater.

Table B.2—Example Power Thresholds (mW)

Table B.2—Example Power Thresholds (mW)											
Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

3.3 Power Density Calculation (Worst Case)

Chain 0	Frequency (MHz)	Distance (cm)	Max. tune-up power (dBm)	Max. tune-up power (mW)	Peak gain (dBi)	ERP (dBm)	ERP (mW)	P _{th} (mW)	P or ERP /P _{th}
ZigBee	2405	0.5	4.38	2.742	2.13	4.36	2.729	2.79	0.983