



TEST REPORT

Applicant Name : Bytech NY Inc.
Address : 2585 West 13th Street, Brooklyn NY 11223, New York, United States
Report Number : 2604P40770E-RF
FCC ID: 2AHN6-KBWS115

Test Standard (s)

47 CFR §2.1093

Sample Description

Product Type: Animal Wireless Keyboard-ASST
Model No.: BY-KB-WS-115-AC, BY-KB-WS-115-BR, BY-KB-WS-115-PK
Trade Mark: N/A
Date Received: 2026-01-12
Report Date: 2026-01-19

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Jason Fan

Jason Fan
EMC Engineer

Approved By:

Bob. Liao

Bob.Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked. This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY..... 3

GENERAL INFORMATION..... 4

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

 OBJECTIVE 4

 TEST FACILITY 4

RF EXPOSURE 5

 APPLICABLE STANDARD..... 5

 TEST RESULT 5

EXHIBIT A-EUT PHOTOGRAPHS 6

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2604P40770E-RF	Original Report	2026-01-19

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Animal Wireless Keyboard-ASST
Tested Model	BY-KB-WS-115-AC
Multiple Model	BY-KB-WS-115-BR, BY-KB-WS-115-PK
Model Difference [#]	Only the model number and colors are different. Please refer to DOS letter for details. The applicant provided model "BY-KB-WS-115-AC" for testing.
Frequency Range	2.4G SRD: 2402-2479MHz
Maximum E-Field Strength (Peak)	87.51 dBuV/m@3m
Antenna Specification [#]	Internal Antenna, Antenna gain: 2.34 dBi (It is provided by the applicant.)
Voltage Range [#]	DC 3.0V from battery
UPC Number	805112143047,805112143054
SKU Number	9233348
Lot Number	BY011026
Sample Serial Number	3FVL-1 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts C and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC §2.1093 rules.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

RF EXPOSURE

Applicable Standard

According to FCC §2.1093, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- 1. f(GHz) is the RF channel transmit frequency in GHz.
- 2. Power and distance are rounded to the nearest mW and mm before calculation.
- 3. The result is rounded to one decimal place for comparison.
- 4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Test result

For worst case:

Frequency (MHz)	Tune-Up Conducted Output Power# (dBm)	Tune-Up Conducted Output Power# (mW)	Tune-Up EIRP		Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
			(dBm)	(mW)				
2479	/	/	-7	0.20	5	0.1	3	Yes

Note 1: $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$ for $d = 3 \text{ m}$.
For $\text{EIRP} = 87.51 \text{ dBuV/m} - 95.2 = -7.69\text{dBm}$
Note: The tune-up EIRP is declared by the applicant.

Result: No SAR test is required.

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2604P40770E-RF EUT External Photos and Attachment No.2 2604P40770E-RF EUT Internal Photos

***** END OF REPORT *****