

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093) and
IEEE Std 1528-2013**

Product Name : Smartphone

Brand Name : CUBOT

Model Name : KINGKONG Dura

Family Model : KINGKONG Dura 3, KINGKONG Dura Pro, A50,
A60, NOTE 70, NOTE 80, P100

Report No. : N26051506110E

FCC ID : 2AHZ5DURA

Prepared for

Shenzhen Huafurui Technology Co., Ltd.

Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993 Jiaxian Road,
Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, P.R. China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District,
Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name** Shenzhen Huafurui Technology Co., Ltd.

Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993

Address Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District,
Shenzhen, P.R. China**Manufacturer's Name** . Shenzhen Huafurui Technology Co., Ltd.

Unit 601-03, 6/F, Block A, Building 1, Ganfeng Technology Building, No. 993

Address Jiaxian Road, Xiangjiaotang Community, Bantian Street, Longgang District,
Shenzhen, P.R. China**Product description**

Product name Smartphone

Brand Name CUBOT

Model and/or type KINGKONG Dura
reference

Family Model KINGKONG Dura 3, KINGKONG Dura Pro, A50, A60, NOTE 70, NOTE 80, P100

FCC 47 CFR Part 2(2.1093)

Standards IEEE Std 1528-2013

Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number S2605200329-1#

Date of Test

Date (s) of performance of tests .. Jun. 03, 2026~Jun. 11, 2026

Date of Issue July. 09, 2026

Test Result **Pass**Prepared
By*Owen Xiao*Owen Xiao
(Project Engineer)Reviewed
By*Aaron Cheng*Aaron Cheng
(Supervisor)Approved
By*Alex Li*Alex Li
(Manager)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	July. 09, 2026	Owen Xiao

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition	9
1.6. Facilities And Accreditations	9
1.6.1. Facilities	9
1.6.2. Laboratory Accreditations And Listings	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	18
3.1. Power Reference	18
3.2. Area scan & Zoom scan	18
3.3. Description of interpolation/extrapolation scheme	20
3.4. Volumetric Scan	20
3.5. Power Drift	20
4. System Verification Procedure	21
4.1. Tissue Verification	21
4.1.1. Tissue Dielectric Parameter Check Results	22
4.2. System Verification Procedure	23
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	25
5.1. SAR measurement variability	25
5.2. SAR measurement uncertainty	25
6. RF Exposure Positions	26
6.1. Ear and handset reference point	26
6.2. Definition of the cheek position	26
6.3. Definition of the tilt position	28
6.4. Body Worn Accessory	28
6.5. Wireless Router Devices	29
7. RF Output Power	30

7.1. GSM Conducted Power	30
7.2. WCDMA Conducted Power.....	30
7.3. LTE Conducted Power.....	32
7.4. WLAN & Bluetooth Output Power	45
8. Antenna Location.....	47
9. Stand-alone SAR test exclusion	48
10. SAR Results	49
10.1. SAR measurement Result	49
10.1.1. SAR measurement Result of GSM850.....	49
10.1.2. SAR measurement Result of GSM1900.....	50
10.1.3. SAR measurement Result of WCDMA Band 2	51
10.1.4. SAR measurement Result of WCDMA Band 4	52
10.1.5. SAR measurement Result of WCDMA Band 5	53
10.1.6. SAR measurement Result of LTE Band 2	54
10.1.7. SAR measurement Result of LTE Band 4	56
10.1.8. SAR measurement Result of LTE Band 5	58
10.1.9. SAR measurement Result of LTE Band 7	60
10.1.10. SAR measurement Result of LTE Band 12	62
10.1.11. SAR measurement Result of LTE Band 17	63
10.1.12. SAR measurement Result of LTE Band 41	65
10.1.13. SAR measurement Result of WLAN2.4G.....	67
10.1.14. SAR measurement Result of WLAN5.2G.....	68
10.1.15. SAR measurement Result of WLAN5.8G.....	69
10.2. Simultaneous Transmission Analysis	71
11. Appendix A. Photo documentation	73
12. Appendix B. System Check Plots	74
13. Appendix C. Plots of High SAR Measurement	91
14. Appendix D. Calibration Certificate.....	152

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE

HEAD AND TRUNK LIMIT

1.6 W/kg

APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for KINGKONG Dura are as follows.

RF Exposure Conditions		Equipment Class -Highest Reported SAR (W/kg)				Max. Reported SAR (W/kg)
		PCE	DTS	NII	DSS	
1-g Head		0.312	0.500	0.531	0.133	0.531
1-g Body-Worn (Separation distance of 10mm)		0.751	0.382	0.357	0.066	0.751
1-g Hotspot (Separation distance of 10mm)		0.751	0.382	0.357	0.066	
Max Simultaneous Tx	Head	0.843	0.812	0.843	0.445	0.843
	Body-Worn	1.133	1.133	1.108	0.817	1.133
	Hotspot	1.133	1.133	1.108	0.817	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093), and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.


1.3. EUT Description

Device Information	
Product Name	Smartphone
Brand Name	CUBOT
Model Name	KINGKONG Dura
Family Model	KINGKONG Dura 3, KINGKONG Dura Pro, A50, A60, NOTE 70, NOTE 80, P100
Model Difference	All models have the same circuit and RF module, except for model names and appearances.
FCC ID	2AHZ5DURA
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna Type	PIFA Antenna
Battery Information	DC4.45V,4850mAh,21.58Wh
HW Version	G2510T-UF-V1.1
SW Version	CUBOT_KINGKONG_Dura_G051_V1.0
Device Operating Configurations	
Supporting Mode(s)	GSM850/1900,WCDMA Band2/4/5,LTEBand2/4/5/7/12/17/41,WLAN 2.4G/5G, Bluetooth

Test Modulation	GSM(GMSK),WCDMA(QPSK),LTE(QPSK/16QAM),WLAN(DSSS/OFDM),Bluetooth(GFSK, π/4-DQPSK, 8DPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	LTE Band 41	2535-2655	
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
	NFC	13.56	
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control “all 1”(WCDMA Band 2)		
	3, tested with power control “all 1”(WCDMA Band 4)		
	3, tested with power control “all 1”(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 17)		
	3, tested with power control all Max.(LTE Band 41)		

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe 4024-EPGO-448 with following specifications is used



- Dynamic range: 0.01-100 W/kg
- Tip Diameter : 2.5 mm
- Distance between probe tip and sensor center: 1 mm
- Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
- Probe linearity: ± 0.06 dB
- Axial isotropy: ± 0.01 dB
- Hemispherical Isotropy: ± 0.01 dB
- Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
- Lower detection limit: 8mW/kg

Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by Mobile Phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	
☒	MVG	E FIELD PROBE	SSE2	4024-EPGO-442	Jun. 20, 2025	☒
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Feb. 21, 2024	☒
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Feb. 21, 2024	☐
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Feb. 21, 2024	☒
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Feb. 21, 2024	☒
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Feb. 21, 2024	☐
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Feb. 21, 2024	☒
☐	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Feb. 22, 2024	☒
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Feb. 21, 2024	☒
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Feb. 21, 2024	☒
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Feb. 21, 2024	☒
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	☒
☒	MVG	Power Amplifier	N/A	AMPLISAR_28/14_003	NCR	☒
☒	KEITHLEY	Millivoltmeter	2000	4072790	May. 7, 2026	☒
☒	R&S	Universal radio communication tester	CMU200	105747	Apr. 8, 2026	☒
☒	R&S	Wideband radio	CMW500	103917	Apr.27,	☒

		communication tester			2026	
☐	Anritsu	4G LTE comprehensive tester	MT8821C	6262192315	Apr.8 2026	☐
☐	Anritsu	5G NR comprehensive tester	MT8000A	6262186364	Apr.8 2026	☐
☒	Hp/Agilent	Network Analyzer	8753D	3410J01136	Apr.15 , 2026	☒
☒	Agilent	Calibration Kit	85033E	N/A	May. 31, 2024	☒
☒	Agilent	MXG Vector Signal Generator	N5182A	MY47070317	Apr.8 2026	☒
☒	Agilent	Power sensor	E4419B	MY45102538	Apr.8 2026	☒
☒	Agilent	Power sensor	E9301A	US39212148	Apr.8 2026	☒
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Apr. 26, 2024	☒
☒	N/A	Thermometer	N/A	LES-085	Mar. 15, 2026	☒
☒	MVG	SAM Phantom	SSM2	SN 16/15 SAM119	NCR	☒
☒	MVG	Device Holder	SMPPD	SN 16/15 MSH100	NCR	☒
	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	

Measurement Software

Manufacturer	Software Name	Software Version
SATIMO	OpenSAR	V5.3.15.11

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	≤ 1.5 · $\Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Delta(%)		Liquid Temp.	Test Date
		ϵ_r	σ (S/m)	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)		
Head 750	750	41.90	0.89	42.85	0.93	2.27	4.49	21.8 °C	Jun. 07, 2026
Head 835	835	41.50	0.90	42.79	0.92	3.11	2.22	21.0 °C	Jun. 08, 2026
Head 1800	1800	40.00	1.40	40.31	1.40	0.78	0.00	21.0 °C	Jun. 09, 2026
Head 1900	1900	40.00	1.40	39.05	1.45	-2.38	3.57	21.1 °C	Jun. 10, 2026
Head 2450	2450	39.20	1.80	41.04	1.82	4.69	1.11	21.1 °C	Jun. 11, 2026
Head 2600	2600	39.01	1.96	39.85	1.91	2.15	-2.55	21.7 °C	Jun. 03, 2026
Head 5200	5200	36.00	4.66	37.18	4.64	3.28	-0.43	21.3 °C	Jun. 04, 2026
Head 5800	5800	35.30	5.27	36.07	5.21	2.18	-1.14	21.4 °C	Jun. 05, 2026


NOTE: 1. The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

2. Tested by : Max Zhou , Jack Peng

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W)		Measured SAR			Measured SAR		Delta (%)		Liquid Temp.	Test Date
						(Normalized to 1W)					
	1-g (W/Kg)	10-g (W/Kg)	Input Power (mW)	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)	1-g (%)	10-g (%)		
750MHz	8.60	5.78	100.00	0.89	0.57	8.88	5.68	3.26	-1.73	21.8 °C	Jun. 07, 2026
835MHz	9.40	6.28	100.00	0.98	0.62	9.77	6.23	3.94	-0.80	21.0 °C	Jun. 08, 2026
1800MHz	37.06	20.01	100.00	3.87	2.04	38.74	20.43	4.53	2.10	21.0 °C	Jun. 09, 2026
1900MHz	39.69	20.92	100.00	4.11	2.10	41.14	21.03	3.65	0.53	21.1 °C	Jun. 10, 2026
2450MHz	50.05	23.80	100.00	5.21	2.43	52.07	24.27	4.04	1.97	21.1 °C	Jun. 11, 2026
2600MHz	54.16	24.85	100.00	5.29	2.43	52.86	24.31	-2.40	-2.17	21.7 °C	Jun. 03, 2026
5200MHz	162.59	56.21	10.00	1.47	0.53	146.90	53.20	-9.65	-5.35	21.3 °C	Jun. 04, 2026
5800MHz	182.20	61.32	10.00	1.67	0.61	166.70	60.60	-8.51	-1.17	21.4 °C	Jun. 05, 2026

Tested by : Max Zhou , Jack Peng

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	128	189	251	Tune-up	128	189	251
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8
GSM (GMSK)	32.50	32.14	31.91	31.96	23.47	23.09	22.87	22.93
GPRS(GMSK,1 Tx slot)	30.50	30.00	29.84	30.14	23.47	23.11	22.88	22.93
GPRS(GMSK,2 Tx slot)	28.00	27.54	27.63	27.46	24.48	23.98	23.82	24.12
GPRS(GMSK,3 Tx slot)	25.50	25.14	25.32	25.08	23.74	23.28	23.37	23.20
GPRS(GMSK,4 Tx slot)	32.50	32.14	31.91	31.96	22.49	22.13	22.31	22.07
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	512	661	810	Tune-up	512	661	810
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8
GSM (GMSK)	29.50	29.09	29.16	29.15	20.47	20.06	20.13	20.12
GPRS(GMSK,1 Tx slot)	29.50	29.06	29.17	29.14	20.47	20.03	20.14	20.11
GPRS(GMSK,2 Tx slot)	27.00	26.86	26.59	26.33	20.98	20.84	20.57	20.31
GPRS(GMSK,3 Tx slot)	25.50	25.17	24.89	24.58	21.24	20.91	20.63	20.32
GPRS(GMSK,4 Tx slot)	23.00	22.85	22.75	22.19	19.99	19.84	19.74	19.18

7.2. WCDMA Conducted Power

WCDMA Band 2	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC12.2K	23.50	22.78	23.26	23.37
HSDPA Sub 1	23.00	22.81	22.81	22.78
HSDPA Sub 2	22.50	22.39	22.48	22.33
HSDPA Sub 3	22.50	22.17	22.32	22.22
HSDPA Sub 4	22.50	21.97	22.24	22.07
HSUPA Sub 1	23.00	22.66	22.59	22.51
HSUPA Sub 2	23.00	22.58	22.71	22.59
HSUPA Sub 3	22.50	22.24	22.28	22.37
HSUPA Sub 4	23.00	22.47	22.71	22.63
HSUPA Sub 5	23.00	22.21	22.54	22.38
WCDMA Band 4	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up	1312	1413	1513

Frequency (MHz)	(dBm)	1712.4	1732.6	1752.6
RMC12.2K	23.00	22.95	22.72	22.86
HSDPA Sub 1	23.50	22.89	23.03	22.89
HSDPA Sub 2	23.00	22.61	22.75	22.48
HSDPA Sub 3	22.50	22.08	22.23	22.27
HSDPA Sub 4	22.50	22.13	22.35	22.24
HSUPA Sub 1	23.00	22.75	22.78	22.65
HSUPA Sub 2	23.00	22.76	22.97	22.87
HSUPA Sub 3	23.00	22.46	22.70	22.46
HSUPA Sub 4	23.00	22.71	22.96	22.64
HSUPA Sub 5	23.00	22.27	22.62	22.54
WCDMA Band 5	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	22.50	22.32	22.33	22.28
HSDPA Sub 1	22.50	22.13	22.05	21.71
HSDPA Sub 2	22.00	21.85	21.85	21.58
HSDPA Sub 3	22.00	21.49	21.64	21.49
HSDPA Sub 4	21.50	21.43	21.36	21.44
HSUPA Sub 1	22.50	22.17	21.88	21.65
HSUPA Sub 2	22.50	22.05	22.01	21.72
HSUPA Sub 3	22.00	21.64	21.98	21.32
HSUPA Sub 4	22.50	22.03	22.01	21.68
HSUPA Sub 5	22.00	21.95	21.80	21.44

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	23.00	21.26	22.79	22.89
			1	2	23.00	21.27	22.75	22.48
			1	5	23.00	21.24	22.74	22.05
			3	0	23.00	21.30	22.54	22.65
			3	1	23.00	21.36	22.46	22.36
			3	2	23.00	21.26	22.43	22.17
			6	0	22.00	20.25	21.45	21.79
		16QAM	1	0	21.00	20.46	20.95	20.38
			1	2	21.00	20.44	20.96	20.34
			1	5	21.00	20.31	20.88	20.86
			3	0	21.50	20.47	21.43	21.12
			3	1	21.50	20.47	21.38	21.17
			3	2	21.50	20.44	21.24	21.05
			6	0	21.00	19.20	20.34	20.63
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	23.00	21.26	22.69	22.87
			1	7	23.00	21.24	22.62	22.84
			1	14	23.00	21.29	22.44	21.85
			8	0	22.00	20.27	21.48	21.84
			8	4	22.00	20.14	21.37	21.89
			8	7	22.00	20.23	21.26	21.79
			15	0	22.00	20.24	21.45	21.89
		16QAM	1	0	22.50	20.91	21.59	22.34
			1	7	22.50	20.82	21.38	22.36
			1	14	22.50	20.75	21.30	21.90
			8	0	21.00	19.52	20.59	20.05
			8	4	21.00	19.37	20.47	20.99
			8	7	21.00	19.45	20.39	20.99
			15	0	21.00	19.28	20.54	20.04
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE	5MHz	QPSK	1	0	23.00	21.65	22.71	22.92

Band 2			1	12	23.00	21.59	22.50	22.87
			1	24	23.00	21.75	22.37	21.63
			12	0	22.00	20.25	21.45	21.81
			12	6	22.00	20.25	21.28	21.78
			12	11	22.00	20.19	21.30	21.89
			25	0	22.00	20.31	21.45	21.82
		16QAM	1	0	22.50	21.42	22.18	22.37
			1	12	22.50	21.20	21.98	22.39
			1	24	22.50	21.30	21.63	21.85
			12	0	21.00	19.32	20.66	20.08
			12	6	21.00	19.35	20.43	20.02
			12	11	21.00	19.29	20.36	20.98
			25	0	21.00	19.60	20.46	20.88
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	23.50	21.51	23.19	22.84
			1	24	23.50	21.55	22.62	23.12
			1	49	23.50	21.95	22.16	22.39
			25	0	22.00	20.23	21.63	21.63
			25	12	22.00	20.31	21.35	21.86
			25	24	22.00	20.50	21.15	21.91
			50	0	22.00	20.35	21.51	21.90
		16QAM	1	0	22.00	20.27	21.93	21.58
			1	24	22.00	20.29	21.44	21.77
			1	49	22.00	20.73	21.02	21.78
			25	0	21.50	19.54	20.98	21.00
			25	12	21.50	19.70	20.69	21.14
			25	24	21.50	19.79	20.47	21.13
			50	0	21.00	19.39	20.51	20.88
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band 2	15MHz	QPSK	1	0	23.50	22.34	23.23	22.11
			1	37	23.50	22.57	22.42	22.96
			1	74	23.50	22.37	21.84	22.48
			36	0	22.00	20.37	21.72	21.45
			36	18	22.00	20.56	21.41	21.65
			36	37	22.00	20.84	21.09	21.82
			75	0	22.00	20.61	21.44	21.66

		16QAM	1	0	23.00	21.81	22.69	21.72
			1	37	23.00	21.03	22.02	22.32
			1	74	23.00	22.03	21.93	22.24
			36	0	21.00	19.36	20.75	20.43
			36	18	21.00	19.53	20.45	20.74
			36	37	21.00	19.94	20.07	20.98
			75	0	21.00	19.67	20.62	20.82
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	23.50	21.55	23.35	22.13
			1	49	23.50	22.04	22.60	22.81
			1	99	23.50	23.19	22.01	22.75
			50	0	22.00	20.28	21.84	21.08
			50	24	22.00	20.73	21.36	21.37
			50	49	22.00	21.43	21.04	21.83
			100	0	21.50	20.96	21.44	21.46
		16QAM	1	0	22.50	21.39	21.66	20.77
			1	49	22.50	21.68	21.87	21.59
			1	99	22.50	22.12	21.28	21.96
			50	0	21.00	19.41	20.91	20.16
			50	24	21.00	19.84	20.53	20.52
			50	49	21.00	20.45	20.03	20.93
			100	0	21.00	19.99	20.59	20.54

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	23.50	22.54	23.05	22.47
			1	2	23.50	22.74	23.09	22.49
			1	5	23.50	22.58	23.16	22.42
			3	0	23.50	22.59	23.05	22.32
			3	1	23.50	22.68	23.11	22.36
			3	2	23.50	22.64	23.16	22.29
			6	0	22.50	21.68	22.01	21.28
		16QAM	1	0	23.50	22.66	23.00	22.06
			1	2	23.50	22.29	23.11	22.04
			1	5	23.50	22.05	23.19	22.04
			3	0	22.50	21.95	22.31	21.45
			3	1	22.50	21.91	22.35	21.47

			3	2	22.50	21.86	22.22	21.42
			6	0	21.00	20.62	20.83	20.29
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	23.50	22.46	23.38	22.34
			1	7	23.50	22.76	23.36	22.42
			1	14	23.50	22.66	23.36	22.43
			8	0	22.50	21.60	22.10	21.42
			8	4	22.50	21.62	22.06	21.34
			8	7	22.50	21.65	22.02	21.36
			15	0	22.50	21.67	22.13	21.39
		16QAM	1	0	23.00	22.55	22.57	22.32
			1	7	23.00	22.96	22.57	22.39
			1	14	23.00	22.68	22.52	22.48
			8	0	21.50	20.93	21.27	20.52
			8	4	21.50	20.77	21.24	20.45
			8	7	21.50	20.78	21.25	20.60
			15	0	21.50	20.74	21.17	20.53
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	23.50	22.16	23.06	22.60
			1	12	23.50	22.69	23.12	22.61
			1	24	23.50	22.67	23.14	22.55
			12	0	22.50	21.69	22.02	21.34
			12	6	22.50	21.67	22.09	21.28
			12	11	22.50	21.56	22.18	21.41
			25	0	22.50	21.63	22.05	21.30
		16QAM	1	0	23.50	22.38	23.13	21.87
			1	12	23.50	23.15	23.12	21.94
			1	24	23.50	22.61	23.01	21.91
			12	0	21.50	20.66	21.21	20.50
			12	6	21.50	20.67	21.14	20.32
			12	11	21.50	20.65	21.22	20.40
			25	0	21.00	20.60	20.93	20.59
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE	10MHz	QPSK	1	0	23.50	22.37	23.24	22.57

Band 4			1	24	23.50	22.79	23.40	22.42
			1	49	23.50	22.94	23.32	22.35
			25	0	22.50	21.62	21.98	21.44
			25	12	22.50	-27.42	22.05	21.46
			25	24	22.50	-44.47	22.00	21.24
			50	0	22.00	-44.48	21.96	21.45
		16QAM	1	0	23.00	22.68	22.59	22.73
			1	24	23.00	22.01	22.62	22.55
			1	49	23.00	22.74	22.49	22.53
			25	0	21.50	20.60	21.24	20.51
			25	12	21.50	20.51	21.33	20.45
			25	24	21.50	20.59	21.28	20.36
			50	0	21.50	20.68	21.05	20.60
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	23.50	22.63	23.22	23.01
			1	37	23.50	22.54	23.38	22.77
			1	74	23.50	22.82	23.27	22.53
			36	0	22.50	21.54	21.97	21.71
			36	18	22.50	21.56	22.15	21.59
			36	37	22.50	21.72	21.96	21.44
			75	0	22.50	21.60	22.05	21.58
		16QAM	1	0	23.00	22.80	22.53	22.35
			1	37	23.00	22.56	22.72	21.97
			1	74	23.00	22.88	22.44	21.99
			36	0	21.50	20.59	21.12	20.83
			36	18	21.50	20.52	21.20	20.60
			36	37	21.50	20.76	21.08	20.45
			75	0	21.50	20.73	21.05	20.61
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	23.50	22.64	23.23	23.11
			1	49	23.50	22.59	23.25	22.73
			1	99	23.50	23.03	23.18	22.55
			50	0	22.50	21.58	22.03	21.94
			50	24	22.50	21.54	22.10	21.59
			50	49	22.50	21.88	21.95	21.52
			100	0	22.50	21.74	22.01	21.74

		16QAM	1	0	23.50	22.75	22.43	23.13
			1	49	23.50	22.60	22.63	22.79
			1	99	23.50	23.16	22.46	22.49
			50	0	21.50	20.56	21.02	20.91
			50	24	21.50	20.64	21.10	20.67
			50	49	21.50	20.85	21.09	20.53
			100	0	21.50	20.84	21.02	20.72

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	24.00	23.58	23.82	23.61
			1	2	24.00	23.57	23.86	23.04
			1	5	24.00	23.53	23.84	23.06
			3	0	24.00	23.64	23.64	23.18
			3	1	24.00	23.68	23.68	23.25
			3	2	24.00	23.65	23.54	23.16
		16QAM	6	0	23.00	22.58	22.63	22.23
			1	0	24.00	23.67	23.00	22.99
			1	2	24.00	23.60	23.08	23.01
			1	5	24.00	23.58	23.02	23.07
			3	0	23.00	22.95	22.75	22.30
			3	1	23.00	22.99	22.89	22.29
			3	2	23.00	22.92	22.88	22.26
			6	0	21.50	21.49	21.46	20.95
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.00	23.23	23.09	23.69
			1	7	24.00	23.16	23.15	23.18
			1	14	24.00	23.08	23.11	23.11
			8	0	22.50	22.24	22.10	22.29
			8	4	22.50	22.10	22.11	22.18
			8	7	22.50	22.18	22.18	22.21
			15	0	22.50	22.19	22.13	22.24
		16QAM	1	0	23.50	23.05	23.03	23.30
			1	7	23.50	22.99	23.09	23.32
			1	14	23.50	23.08	23.03	23.10
			8	0	22.00	21.30	21.16	21.40
			8	4	22.00	21.23	21.18	21.26

			8	7	22.00	21.25	21.72	21.28
			15	0	22.00	21.32	21.68	21.37
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.00	23.52	23.43	23.48
			1	12	24.00	23.35	23.37	23.61
			1	24	24.00	23.41	23.31	23.53
			12	0	22.50	22.08	21.97	22.27
			12	6	22.50	22.21	22.02	22.26
			12	11	22.50	22.06	22.02	22.25
			25	0	22.50	22.10	22.02	22.24
		16QAM	1	0	23.50	22.75	22.64	23.27
			1	12	23.50	22.61	22.69	23.18
			1	24	23.50	22.50	22.60	23.19
			12	0	22.00	21.11	21.13	21.28
			12	6	22.00	21.20	21.19	21.33
			12	11	22.00	21.11	21.50	21.28
			25	0	22.00	21.39	21.94	21.11
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band 5	10MHz	QPSK	1	0	23.50	23.46	23.13	23.23
			1	24	23.50	23.30	23.16	23.31
			1	49	23.50	23.29	23.19	23.13
			25	0	22.50	22.10	22.06	22.26
			25	12	22.50	21.98	22.02	22.34
			25	24	22.50	22.04	22.17	22.20
			50	0	22.50	21.98	22.00	22.42
		16QAM	1	0	23.50	22.61	23.08	22.76
			1	24	23.50	22.40	23.08	22.89
			1	49	23.50	22.52	23.32	22.69
			25	0	22.00	21.35	21.11	21.68
			25	12	22.00	21.23	21.13	21.48
			25	24	22.00	21.24	21.05	21.42
			50	0	21.50	21.02	21.31	21.25

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5

LTE Band 7	5MHz	QPSK	1	0	24.50	24.19	24.40	24.26
			1	12	24.50	24.03	24.43	24.17
			1	24	24.50	24.04	24.44	23.43
			12	0	23.50	23.32	23.09	22.92
			12	6	23.50	23.15	23.14	22.98
			12	11	23.50	23.14	23.23	23.00
			25	0	23.50	23.10	23.15	22.92
		16QAM	1	0	24.00	23.84	23.76	23.53
			1	12	24.00	23.71	23.66	23.61
			1	24	24.00	23.65	23.70	23.19
			12	0	22.50	22.48	22.46	22.16
			12	6	22.50	22.34	22.19	22.08
			12	11	22.50	22.42	22.34	22.12
			25	0	22.50	22.44	22.46	22.01
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	24.50	24.29	24.25	24.08
			1	24	24.50	24.09	24.14	24.06
			1	49	24.50	24.02	24.12	23.93
			25	0	23.50	23.12	23.25	23.00
			25	12	23.50	23.17	23.11	23.02
			25	24	23.50	23.15	23.16	22.88
			50	0	23.50	23.12	23.19	22.97
		16QAM	1	0	24.50	24.12	24.23	23.78
			1	24	24.50	24.07	24.21	23.66
			1	49	24.50	23.73	24.30	23.59
			25	0	23.00	22.45	22.24	21.65
			25	12	23.00	22.56	22.14	22.10
			25	24	23.00	22.41	22.21	22.07
			50	0	22.50	22.33	22.32	22.20
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	24.50	24.47	24.43	24.16
			1	37	24.50	24.24	24.33	23.95
			1	74	24.50	23.99	24.28	23.92
			36	0	23.50	23.07	23.32	23.13
			36	18	23.50	22.96	23.18	23.01
			36	37	23.50	23.12	23.13	22.86

		16QAM	75	0	23.50	23.06	23.09	22.95
			1	0	24.00	23.64	23.80	23.83
			1	37	24.00	23.72	23.66	23.80
			1	74	24.00	23.48	23.66	23.68
			36	0	22.50	22.38	22.48	21.61
			36	18	22.50	22.25	22.34	22.05
			36	37	22.50	22.19	22.40	21.99
			75	0	22.50	22.22	22.21	22.15
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	24.50	24.44	24.44	24.29
			1	49	24.50	24.18	24.28	24.14
			1	99	24.50	24.10	24.31	24.04
			50	0	23.50	23.15	23.21	23.07
			50	24	23.50	23.15	23.10	22.99
			50	49	23.50	23.20	23.15	22.97
			100	0	23.50	23.14	23.12	22.82
		16QAM	1	0	24.50	24.26	23.86	23.75
			1	49	24.50	23.73	23.73	23.50
			1	99	24.50	23.82	23.78	22.97
			50	0	22.50	22.22	22.32	22.17
			50	24	22.50	22.25	22.32	22.18
			50	49	22.50	22.28	22.21	22.10
			100	0	22.50	22.33	22.33	22.25

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	23.50	22.96	23.42	23.30
			1	2	23.50	22.99	23.39	23.24
			1	5	23.50	23.00	23.40	23.26
			3	0	23.50	23.11	23.33	23.24
			3	1	23.50	23.17	23.19	23.23
			3	2	23.50	23.17	23.29	23.18
			6	0	22.50	22.19	22.07	21.97
		16QAM	1	0	23.00	22.67	22.18	21.96
			1	2	23.00	22.77	22.13	21.94
			1	5	23.00	22.73	22.15	22.04
			3	0	23.00	22.45	22.27	22.18

			3	1	23.00	22.63	22.39	22.23
			3	2	23.00	22.57	22.39	22.08
			6	0	21.50	21.04	20.97	21.37
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.00	23.15	23.32	23.19
			1	7	24.00	23.23	23.50	23.11
			1	14	24.00	23.24	23.48	23.11
			8	0	22.50	22.17	22.29	22.15
			8	4	22.50	22.20	22.29	22.15
			8	7	22.50	22.25	22.27	22.05
			15	0	22.50	22.10	22.30	22.12
		16QAM	1	0	23.00	22.21	22.71	22.60
			1	7	23.00	22.28	22.46	22.50
			1	14	23.00	22.19	22.52	22.58
			8	0	22.00	21.37	21.47	21.19
			8	4	22.00	21.37	21.30	21.19
			8	7	22.00	21.85	21.21	21.75
			15	0	21.50	21.31	21.29	21.27
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.00	23.24	23.50	23.58
			1	12	24.00	23.23	23.45	23.50
			1	24	24.00	23.21	23.53	23.43
			12	0	22.50	22.34	22.38	22.16
			12	6	22.50	22.21	22.35	22.13
			12	11	22.50	22.22	22.17	22.17
			25	0	22.50	22.20	22.24	22.11
		16QAM	1	0	23.00	22.65	22.41	22.08
			1	12	23.00	22.67	22.20	22.18
			1	24	23.00	22.52	22.04	21.97
			12	0	22.00	21.29	21.29	21.17
			12	6	22.00	21.75	21.15	21.25
			12	11	22.00	21.75	21.15	21.17
			25	0	22.00	21.74	21.40	21.46
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711

LTE Band 12	10MHz	QPSK	1	0	23.50	23.43	23.38	23.33
			1	24	23.50	23.41	23.18	23.26
			1	49	23.50	23.38	23.17	23.27
			25	0	22.50	22.33	22.34	22.13
			25	12	22.50	22.10	22.06	22.11
			25	24	22.50	22.27	22.13	22.16
			50	0	22.50	22.14	22.06	22.13
		16QAM	1	0	23.00	22.27	22.66	22.20
			1	24	23.00	22.18	22.52	21.95
			1	49	23.00	22.17	22.54	22.00
			25	0	22.00	21.88	21.27	21.36
			25	12	22.00	21.46	21.11	21.30
			25	24	22.00	21.46	21.08	21.35
			50	0	21.50	21.27	21.23	21.18

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	24.00	23.20	23.45	23.48
			1	12	24.00	23.10	23.50	23.49
			1	24	24.00	23.04	23.45	23.38
			12	0	22.50	22.32	22.09	22.21
			12	6	22.50	22.21	22.16	22.17
			12	11	22.50	22.10	22.24	21.94
			25	0	22.50	22.27	22.18	22.04
		16QAM	1	0	22.50	22.25	22.15	22.09
			1	12	22.50	22.17	22.24	22.10
			1	24	22.50	22.11	22.08	22.01
			12	0	21.50	21.34	21.19	21.20
			12	6	21.50	21.33	21.12	21.16
			12	11	21.50	21.12	21.12	21.07
			25	0	21.50	21.47	21.29	21.39
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	24.00	23.51	23.29	23.24
			1	24	24.00	23.41	23.35	23.27
			1	49	24.00	23.48	23.15	23.13
			25	0	22.50	22.38	22.34	22.28
			25	12	22.50	22.23	22.21	22.14

			25	24	22.50	22.19	22.02	22.18
			50	0	22.50	22.18	22.13	22.06
		16QAM	1	0	23.00	22.18	22.38	22.70
			1	24	23.00	22.09	22.14	22.57
			1	49	23.00	22.03	22.08	22.41
			25	0	21.50	21.49	21.41	21.12
			25	12	21.50	21.34	21.40	21.06
			25	24	21.50	21.39	21.30	21.09
			50	0	21.50	21.13	21.10	21.10

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		40065/2537.5	40370/2568	40640/2595	41215/2652.5
LTE Band 41	5MHz	QPSK	1	0	24.50	24.12	24.24	23.92	23.81
			1	12	24.50	24.14	23.63	23.85	23.97
			1	24	24.50	24.1	24.23	23.86	23.78
			12	0	23.50	23.18	23.18	22.88	22.9
			12	6	23.50	23.17	22.37	22.91	22.82
			12	11	23.50	23.18	22.9	22.94	22.79
			25	0	23.50	23.2	22.85	22.96	22.94
		16QAM	1	0	24.00	23.52	23.24	22.7	22.79
			1	12	24.00	23.59	21.62	22.76	22.69
			1	24	24.00	23.55	23.59	22.73	22.62
			12	0	22.50	22.24	21.38	21.89	21.77
			12	6	22.50	22.26	21.86	21.92	21.78
			12	11	22.50	22.29	21.71	22.01	21.97
			25	0	22.50	22.33	21.97	22.11	22.01
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		40090/2540	40370/2568	40640/2595	41190/2650
LTE Band 41	10MHz	QPSK	1	0	25.00	24.51	24.37	24.38	24.36
			1	24	25.00	24.5	24.33	24.32	24.22
			1	49	25.00	24.54	24.31	24.26	24.33
			25	0	23.50	23.21	23.18	22.98	23.06
			25	12	23.50	23.04	23.39	22.86	23.01
			25	24	23.50	23.09	22.93	22.95	23.05
			50	0	24.00	22.8	23.61	22.6	22.7

		16QAM	1	0	24.00	23.61	22.34	23.38	23.4
			1	24	24.00	23.53	23.34	23.29	23.44
			1	49	24.00	23.57	22.73	23.29	23.39
			25	0	23.00	22.31	22.46	22.14	22.18
			25	12	23.00	22.29	22.04	22.06	22.26
			25	24	23.00	22.24	22.52	22.09	22.02
			50	0	22.50	21.96	22.04	21.78	21.82
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		40115/2542.5	40370/2568	40640/2595	41165/2647.5
LTE Band 41	15MHz	QPSK	1	0	25.00	24.54	24.37	24.31	24.5
			1	37	25.00	24.53	24.26	24.25	24.48
			1	74	25.00	24.48	24.45	24.32	24.2
			36	0	23.50	23.18	23.14	23.02	23.11
			36	18	23.50	23.05	22.61	22.93	23.04
			36	37	23.50	22.74	22.69	22.99	22.94
			75	0	23.50	22.73	23.01	22.57	22.76
		16QAM	1	0	24.00	23.63	23.27	23.32	23.54
			1	37	24.00	23.54	22.51	23.3	23.43
			1	74	24.00	23.44	22.46	23.27	23.34
			36	0	23.00	22.21	22.16	22.12	22.12
			36	18	23.00	22.13	22.81	22.07	22.04
			36	37	23.00	22.19	22.04	22	21.99
			75	0	22.50	21.93	22.14	21.85	21.89
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		40140/2545	40370/2568	40640/2595	41140/2645
LTE Band 41	20MHz	QPSK	1	0	25.00	24.24	24.13	24.4	24.59
			1	49	25.00	24.23	23.77	24.32	24.36
			1	99	25.00	24.07	23.67	24.26	24.28
			50	0	24.00	23.25	22.94	23.06	23.12
			50	24	24.00	23.29	23.69	23.05	22.94
			50	49	24.00	23.17	23.1	23.02	23.03
			100	0	23.00	22.97	22.46	22.61	22.7
		16QAM	1	0	24.00	23.09	22.03	23.4	23.52
			1	49	24.00	23.02	22.62	23.23	23.49
			1	99	24.00	22.97	21.54	23.36	23.36

			50	0	22.50	22.32	21.46	22.16	22.19
			50	24	22.50	22.4	21.73	22.16	22.14
			50	49	22.50	22.35	21.9	22.16	22.2
			100	0	22.50	22.34	21.47	22.06	22.2

7.4. WLAN & Bluetooth Output Power

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	15.50	14.98
	6	2437	15.50	15.28
	11	2462	15.50	14.91
802.11g	1	2412	15.00	14.19
	6	2437	15.00	14.70
	11	2462	15.00	14.40
802.11n HT20	1	2412	15.00	14.34
	6	2437	15.00	14.58
	11	2462	15.00	14.43
802.11n HT40	3	2422	14.50	14.44
	6	2437	14.50	14.46
	9	2452	14.50	13.29

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	36	5180	10.50	10.22
	40	5200	10.50	10.48
	48	5240	10.50	10.49
802.11n HT20	36	5180	10.50	10.02
	40	5200	10.50	10.25
	48	5240	10.50	10.43
802.11n HT40	38	5190	9.50	8.55
	46	5230	9.50	9.31
802.11ac VHT20	36	5180	10.50	9.57
	40	5200	10.50	9.77
	48	5240	10.50	10.20
802.11ac VHT40	38	5190	9.50	8.90
	46	5230	9.50	9.36
802.11ac VHT80	42	5210	8.50	8.08

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	149	5745	11.00	9.89

	157	5785	11.00	9.66
	165	5825	11.00	10.51
802.11n HT20	149	5745	11.00	9.77
	157	5785	11.00	9.50
	165	5825	11.00	10.54
802.11n HT40	151	5755	10.00	9.50
	159	5795	10.00	9.59
802.11ac VHT20	149	5745	10.50	9.72
	157	5785	10.50	9.55
	165	5825	10.50	10.49
802.11ac VHT40	151	5755	10.00	9.31
	159	5795	10.00	9.53
802.11ac VHT80	155	5775	8.50	8.35


NOTE: Power measurement results of WLAN 5.8G.

BR+EDR	Output Power (dBm)				
	Channel	Tune-up (dBm)	Data Rates		
			1M	2M	3M
	0CH	3.50	3.94	3.2	3.47
	39CH	4.50	4.46	4.31	3.94
	78CH	5.00	4.72	4.64	4.21

BLE	Output Power (dBm)				
	Data Rates	Tune-up (dBm)	Channe		
			0CH	19CH	39CH
	1M	1.50	1.06	-0.16	-0.30
	2M	1.00	0.60	-0.29	-0.43

NOTE: Power measurement results of Bluetooth.

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WWAN DIV ANT	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	> 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	Yes	Yes	Yes	Yes	NO	Yes
WWAN DIV ANT	Yes	Yes	Yes	NO	Yes	NO
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	5.00	3.162	5	2.480	0.996	3	Yes

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}/x]$ W/kg for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	5.00	3.162	5	2.48	7.5	0.133
Bluetooth	Body	5.00	3.162	10	2.48	7.5	0.066
Bluetooth	Hotspot	5.00	3.162	10	2.48	7.5	0.066

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement Result

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(±5%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Right Cheek	189/836.4	GPRS(GMSK 2TS)	0.078	0.063	4.15	29.84	30.50	0.091	2026/6/08	1#
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.044	0.036	0.37	29.84	30.50	0.051	2026/6/08	
Left Cheek	189/836.4	GPRS(GMSK 2TS)	0.072	0.056	-0.80	29.84	30.50	0.084	2026/6/08	
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.033	0.026	0.43	29.84	30.50	0.038	2026/6/08	

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	189/836.4	GPRS(GMSK 2TS)	0.091	0.055	-2.99	29.84	30.50	0.106	2026/6/08	
Back Side	189/836.4	GPRS(GMSK 2TS)	0.116	0.074	1.24	29.84	30.50	0.135	2026/6/08	2#

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	189/836.4	GPRS(GMSK 2TS)	0.091	0.055	-2.99	29.84	30.50	0.106	2026/6/08	
Back Side	189/836.4	GPRS(GMSK 2TS)	0.116	0.074	1.24	29.84	30.50	0.135	2026/6/08	2#
Left Side	189/836.4	GPRS(GMSK 2TS)	0.066	0.042	2.46	29.84	30.50	0.077	2026/6/08	

Right Side	189/836.4	GPRS(GMSK 2TS)	0.075	0.046	-3.46	29.84	30.50	0.087	2026/6/08	
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.012	0.010	-1.78	29.84	30.50	0.014	2026/6/08	

NOTE: 1.Hotspot SAR test results of GSM850

2. Tested by : Max Zhou

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Right Cheek	661/1880	GPRS(GMSK 3TS)	0.025	0.019	-0.31	24.89	25.50	0.029	2026/6/10	3#
Right Tilt 15 Degree	661/1880	GPRS(GMSK 3TS)	0.013	0.011	-1.67	24.89	25.50	0.015	2026/6/10	
Left Cheek	661/1880	GPRS(GMSK 3TS)	0.022	0.016	-2.52	24.89	25.50	0.025	2026/6/10	
Left Tilt 15 Degree	661/1880	GPRS(GMSK 3TS)	0.010	0.008	3.10	24.89	25.50	0.012	2026/6/10	

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 3TS)	0.093	0.046	-2.36	24.89	25.50	0.107	2026/6/10	
Back Side	661/1880	GPRS(GMSK 3TS)	0.271	0.136	-2.55	24.89	25.50	0.312	2026/6/10	4#

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducte d power (dBm)	Tune-up power (dBm)	Scale d SAR 1g (W/K g)	Date	Plot
			1-g	10-g						
Front Side	661/1880	GPRS(GMSK 3TS)	0.093	0.046	-2.36	24.89	25.50	0.107	2026/6/10	
Back	661/1880	GPRS(GMSK 3TS)	0.271	0.136	-2.55	24.89	25.50	0.312	2026/6/10	4#

Side		3TS)								
Left Side	661/1880	GPRS(GMSK 3TS)	0.060	0.030	0.90	24.89	25.50	0.069	2026/6/10	
Right Side	661/1880	GPRS(GMSK 3TS)	0.045	0.022	2.08	24.89	25.50	0.052	2026/6/10	
Bottom Side	661/1880	GPRS(GMSK 3TS)	0.154	0.077	0.66	24.89	25.50	0.177	2026/6/10	

NOTE: 1.Hotspot SAR test results of GSM1900

2.Tested by : Jack Peng

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Right Cheek	9400/1880	RMC12.2K	0.042	0.031	-0.63	23.26	23.50	0.044	2026/6/10	5#
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.022	0.016	-2.16	23.26	23.50	0.023	2026/6/10	
Left Cheek	9400/1880	RMC12.2K	0.040	0.029	-1.19	23.26	23.50	0.042	2026/6/10	
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.021	0.015	0.52	23.26	23.50	0.022	2026/6/10	

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	9400/1880	RMC12.2K	0.189	0.091	1.71	23.26	23.50	0.200	2026/6/10	
Back Side	9400/1880	RMC12.2K	0.619	0.312	-1.31	23.26	23.50	0.654	2026/6/10	6#

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	9400/1880	RMC12.2K	0.189	0.091	1.71	23.26	23.50	0.200	2026/6/10	
Back Side	9400/1880	RMC12.2K	0.619	0.312	-1.31	23.26	23.50	0.654	2026/6/10	6#

Left Side	9400/1880	RMC12.2K	0.130	0.062	-3.13	23.26	23.50	0.137	2026/6/10	
Right Side	9400/1880	RMC12.2K	0.093	0.046	-1.46	23.26	23.50	0.098	2026/6/10	
Bottom Side	9400/1880	RMC12.2K	0.363	0.181	3.70	23.26	23.50	0.384	2026/6/10	

NOTE: 1.Hotspot SAR test results of WCDMA Band 2

2. Tested by : Jack Peng

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Right Cheek	1413/1732.6	RMC12.2K	0.102	0.071	-1.55	22.72	23.00	0.109	2026/6/09	7#
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.056	0.039	3.47	22.72	23.00	0.060	2026/6/09	
Left Cheek	1413/1732.6	RMC12.2K	0.088	0.059	-2.03	22.72	23.00	0.094	2026/6/09	
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.046	0.031	0.33	22.72	23.00	0.049	2026/6/09	

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	1413/1732.6	RMC12.2K	0.141	0.077	2.69	22.72	23.00	0.150	2026/6/09	
Back Side	1413/1732.6	RMC12.2K	0.467	0.267	-0.78	22.72	23.00	0.498	2026/6/09	8#

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1413/1732.6	RMC12.2K	0.141	0.077	2.69	22.72	23.00	0.150	2026/6/09	
Back Side	1413/1732.6	RMC12.2K	0.467	0.267	-0.78	22.72	23.00	0.498	2026/6/09	8#
Left Side	1413/1732.6	RMC12.2K	0.100	0.057	-1.32	22.72	23.00	0.107	2026/6/09	
Right Side	1413/1732.6	RMC12.2K	0.077	0.044	-2.73	22.72	23.00	0.082	2026/6/09	
Bottom Side	1413/1732.6	RMC12.2K	0.275	0.151	1.37	22.72	23.00	0.293	2026/6/09	

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Right Cheek	4182/836.4	RMC12.2K	0.101	0.076	2.48	22.33	22.50	0.105	2026/6/08	9#
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.055	0.040	-1.95	22.33	22.50	0.057	2026/6/08	
Left Cheek	4182/836.4	RMC12.2K	0.096	0.072	1.86	22.33	22.50	0.100	2026/6/08	
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.046	0.034	3.46	22.33	22.50	0.048	2026/6/08	

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.147	0.111	-2.48	22.33	22.50	0.153	2026/6/08	
Back Side	4182/836.4	RMC12.2K	0.181	0.137	-0.05	22.33	22.50	0.188	2026/6/08	10#

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.147	0.111	-2.48	22.33	22.50	0.153	2026/6/08	
Back Side	4182/836.4	RMC12.2K	0.181	0.137	-0.05	22.33	22.50	0.188	2026/6/08	10#
Left Side	4182/836.4	RMC12.2K	0.127	0.091	-0.02	22.33	22.50	0.132	2026/6/08	
Right Side	4182/836.4	RMC12.2K	0.095	0.070	2.27	22.33	22.50	0.099	2026/6/08	
Bottom Side	4182/836.4	RMC12.2K	0.006	0.004	-0.39	22.33	22.50	0.006	2026/6/08	

NOTE: 1.Hotspot SAR test results of WCDMA Band 5

2.Tested by : Max Zhou

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	18900/1880	20M QPSK(1,0)	0.089	0.053	-2.00	23.35	23.50	0.092	2026/6/10	17#
Left Tilt 15 Degree	18900/1880	20M QPSK(1,0)	0.047	0.027	-1.18	23.35	23.50	0.049	2026/6/10	
Right Cheek	18900/1880	20M QPSK(1,0)	0.080	0.048	-1.71	23.35	23.50	0.083	2026/6/10	
Right Tilt 15 Degree	18900/1880	20M QPSK(1,0)	0.042	0.024	2.47	23.35	23.50	0.043	2026/6/10	
50%RB										
Left Cheek	18900/1880	20M QPSK(50,0)	0.045	0.029	-1.48	21.84	22.00	0.047	2026/6/10	
Left Tilt 15 Degree	18900/1880	20M QPSK(50,0)	0.024	0.014	3.62	21.84	22.00	0.025	2026/6/10	
Right Cheek	18900/1880	20M QPSK(50,0)	0.041	0.025	-3.31	21.84	22.00	0.043	2026/6/10	
Right Tilt 15 Degree	18900/1880	20M QPSK(50,0)	0.023	0.013	2.65	21.84	22.00	0.024	2026/6/10	

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	18900/1880	20M QPSK(1,0)	0.174	0.082	-1.51	23.35	23.50	0.180	2026/6/10	

Back Side	18900/1880	20M QPSK(1,0)	0.542	0.270	3.09	23.35	23.50	0.561	2026/6/10	18#
50%RB										
Front Side	18900/1880	20M QPSK(50,0)	0.097	0.042	-2.89	21.84	22.00	0.101	2026/6/10	
Back Side	18900/1880	20M QPSK(50,0)	0.324	0.145	0.38	21.84	22.00	0.336	2026/6/10	

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	18900/1880	20M QPSK(1,0)	0.174	0.082	-1.51	23.35	23.50	0.180	2026/6/10	
Back Side	18900/1880	20M QPSK(1,0)	0.542	0.270	3.09	23.35	23.50	0.561	2026/6/10	18#
Left Side	18900/1880	20M QPSK(1,0)	0.118	0.058	0.89	23.35	23.50	0.122	2026/6/10	
Right Side	18900/1880	20M QPSK(1,0)	0.084	0.042	-2.65	23.35	23.50	0.087	2026/6/10	
Bottom Side	18900/1880	20M QPSK(1,0)	0.319	0.154	-0.98	23.35	23.50	0.330	2026/6/10	
50%RB										
Front Side	18900/1880	20M QPSK(50,0)	0.097	0.042	-2.89	21.84	22.00	0.101	2026/6/10	
Back Side	18900/1880	20M QPSK(50,0)	0.324	0.145	0.38	21.84	22.00	0.336	2026/6/10	
Left Side	18900/1880	20M QPSK(50,0)	0.066	0.034	2.75	21.84	22.00	0.068	2026/6/10	
Right Side	18900/1880	20M QPSK(50,0)	0.049	0.025	-3.77	21.84	22.00	0.051	2026/6/10	
Bottom Side	18900/1880	20M QPSK(50,0)	0.177	0.086	-3.04	21.84	22.00	0.184	2026/6/10	

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.224	0.115	2.06	23.25	23.50	0.237	2026/6/09	19#
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.132	0.068	3.75	23.25	23.50	0.140	2026/6/09	
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.190	0.093	2.59	23.25	23.50	0.201	2026/6/09	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.088	0.044	-2.78	23.25	23.50	0.093	2026/6/09	
50%RB										
Left Cheek	20175/1732.5	20M QPSK(50,24)	0.127	0.064	1.94	22.10	22.50	0.139	2026/6/09	
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.075	0.040	0.10	22.10	22.50	0.082	2026/6/09	
Right Cheek	20175/1732.5	20M QPSK(50,24)	0.111	0.054	1.08	22.10	22.50	0.122	2026/6/09	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,24)	0.052	0.023	3.41	22.10	22.50	0.057	2026/6/09	

NOTE: Head SAR test results of LTE Band 4

Test Position of Body- Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.177	0.099	-0.94	23.25	23.50	0.187	2026/6/09	
Back	20175/1732.5	20M	0.552	0.309	0.43	23.25	23.50	0.585	2026/6/09	20#

Side		QPSK(1,49)								
50%RB										
Front Side	20175/1732.5	20M QPSK(50,24)	0.090	0.056	0.07	22.10	22.50	0.099	2026/6/09	
Back Side	20175/1732.5	20M QPSK(50,24)	0.295	0.156	-2.33	22.10	22.50	0.323	2026/6/09	

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.177	0.099	-0.94	23.25	23.50	0.187	2026/6/09	
Back Side	20175/1732.5	20M QPSK(1,49)	0.552	0.309	0.43	23.25	23.50	0.585	2026/6/09	20#
Left Side	20175/1732.5	20M QPSK(1,49)	0.120	0.067	-2.16	23.25	23.50	0.127	2026/6/09	
Right Side	20175/1732.5	20M QPSK(1,49)	0.087	0.047	-0.05	23.25	23.50	0.092	2026/6/09	
Bottom Side	20175/1732.5	20M QPSK(1,49)	0.314	0.169	-3.67	23.25	23.50	0.333	2026/6/09	
50%RB										
Front Side	20175/1732.5	20M QPSK(50,24)	0.090	0.056	0.07	22.10	22.50	0.099	2026/6/09	
Back Side	20175/1732.5	20M QPSK(50,24)	0.295	0.156	-2.33	22.10	22.50	0.323	2026/6/09	
Left Side	20175/1732.5	20M QPSK(50,24)	0.067	0.040	1.70	22.10	22.50	0.073	2026/6/09	
Right Side	20175/1732.5	20M QPSK(50,24)	0.049	0.025	-3.20	22.10	22.50	0.054	2026/6/09	
Bottom Side	20175/1732.5	20M QPSK(50,24)	0.177	0.096	2.09	22.10	22.50	0.194	2026/6/09	

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	20525/836.5	10M QPSK(1,24)	0.135	0.104	1.99	23.19	23.50	0.145	2026/6/08	21#
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.075	0.058	1.00	23.19	23.50	0.081	2026/6/08	
Right Cheek	20525/836.5	10M QPSK(1,24)	0.127	0.094	-1.08	23.19	23.50	0.136	2026/6/08	
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.069	0.051	-2.70	23.19	23.50	0.074	2026/6/08	
50%RB										
Left Cheek	20525/836.5	10M QPSK(25,24)	0.074	0.059	-3.44	22.17	22.50	0.080	2026/6/08	
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.039	0.031	-1.18	22.17	22.50	0.042	2026/6/08	
Right Cheek	20525/836.5	10M QPSK(25,24)	0.067	0.048	4.76	22.17	22.50	0.072	2026/6/08	
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.038	0.027	-2.14	22.17	22.50	0.041	2026/6/08	

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.147	0.094	-1.52	23.19	23.50	0.158	2026/6/08	

Back Side	20525/836.5	10M QPSK(1,24)	0.171	0.111	-1.50	23.19	23.50	0.184	2026/6/08	22#
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.062	0.043	3.66	22.17	22.50	0.067	2026/6/08	
Back Side	20525/836.5	10M QPSK(25,24)	0.095	0.056	0.53	22.17	22.50	0.102	2026/6/08	

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.147	0.094	-1.52	23.19	23.50	0.158	2026/6/08	
Back Side	20525/836.5	10M QPSK(1,24)	0.171	0.111	-1.50	23.19	23.50	0.184	2026/6/08	22#
Left Side	20525/836.5	10M QPSK(1,24)	0.105	0.067	3.67	23.19	23.50	0.113	2026/6/08	
Right Side	20525/836.5	10M QPSK(1,24)	0.090	0.056	3.90	23.19	23.50	0.097	2026/6/08	
Bottom Side	20525/836.5	10M QPSK(1,24)	0.084	0.048	0.39	23.19	23.50	0.090	2026/6/08	
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.062	0.043	3.66	22.17	22.50	0.067	2026/6/08	
Back Side	20525/836.5	10M QPSK(25,24)	0.095	0.056	0.53	22.17	22.50	0.102	2026/6/08	
Left Side	20525/836.5	10M QPSK(25,24)	0.054	0.031	4.08	22.17	22.50	0.058	2026/6/08	
Right Side	20525/836.5	10M QPSK(25,24)	0.043	0.027	-3.18	22.17	22.50	0.046	2026/6/08	
Bottom Side	20525/836.5	10M QPSK(25,24)	0.047	0.033	-0.34	22.17	22.50	0.051	2026/6/08	

NOTE: 1.Hotspot SAR test results of LTE Band 5

2.Tested by : Max Zhou

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	21100/2535	20M QPSK(1,0)	0.308	0.165	3.31	24.44	24.50	0.312	2026/6/03	23#
Left Tilt 15 Degree	21100/2535	20M QPSK(1,0)	0.156	0.081	-0.39	24.44	24.50	0.158	2026/6/03	
Right Cheek	21100/2535	20M QPSK(1,0)	0.289	0.152	3.43	24.44	24.50	0.293	2026/6/03	
Right Tilt 15 Degree	21100/2535	20M QPSK(1,0)	0.153	0.081	-3.78	24.44	24.50	0.155	2026/6/03	
50%RB										
Left Cheek	21100/2535	20M QPSK(50,0)	0.179	0.088	-3.50	23.21	23.50	0.191	2026/6/03	
Left Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.080	0.045	-2.67	23.21	23.50	0.086	2026/6/03	
Right Cheek	21100/2535	20M QPSK(50,0)	0.152	0.088	-0.77	23.21	23.50	0.162	2026/6/03	
Right Tilt 15 Degree	21100/2535	20M QPSK(50,0)	0.086	0.045	-4.06	23.21	23.50	0.092	2026/6/03	

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	21100/2535	20M QPSK(1,0)	0.284	0.135	3.15	24.44	24.50	0.288	2026/6/03	
Back	21100/2535	20M	0.664	0.316	4.10	24.44	24.50	0.673	2026/6/03	24#

Side		QPSK(1,0)								
50%RB										
Front Side	21100/2535	20M QPSK(50,0)	0.147	0.073	1.35	23.21	23.50	0.157	2026/6/03	
Back Side	21100/2535	20M QPSK(50,0)	0.381	0.183	3.14	23.21	23.50	0.407	2026/6/03	

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,0)	0.284	0.135	3.15	24.44	24.50	0.288	2026/6/03	
Back Side	21100/2535	20M QPSK(1,0)	0.664	0.316	4.10	24.44	24.50	0.673	2026/6/03	24#
Left Side	21100/2535	20M QPSK(1,0)	0.462	0.215	2.70	24.44	24.50	0.468	2026/6/03	
Right Side	21100/2535	20M QPSK(1,0)	0.068	0.032	1.61	24.44	24.50	0.069	2026/6/03	
Bottom Side	21100/2535	20M QPSK(1,0)	0.175	0.082	2.57	24.44	24.50	0.177	2026/6/03	
50%RB										
Front Side	21100/2535	20M QPSK(50,0)	0.147	0.073	1.35	23.21	23.50	0.157	2026/6/03	
Back Side	21100/2535	20M QPSK(50,0)	0.381	0.183	3.14	23.21	23.50	0.407	2026/6/03	
Left Side	21100/2535	20M QPSK(50,0)	0.261	0.118	3.28	23.21	23.50	0.279	2026/6/03	
Right Side	21100/2535	20M QPSK(50,0)	0.038	0.018	2.22	23.21	23.50	0.041	2026/6/03	
Bottom Side	21100/2535	20M QPSK(50,0)	0.091	0.041	-2.14	23.21	23.50	0.097	2026/6/03	

NOTE: 1.Hotspot SAR test results of LTE Band 7

2. Tested by : Max Zhou

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23095/707.5	10M QPSK(1,0)	0.099	0.083	-0.54	23.38	23.50	0.102	2026/6/07	25#
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.055	0.044	0.32	23.38	23.50	0.057	2026/6/07	
Right Cheek	23095/707.5	10M QPSK(1,0)	0.087	0.069	0.69	23.38	23.50	0.089	2026/6/07	
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.040	0.034	1.41	23.38	23.50	0.041	2026/6/07	
50%RB										
Left Cheek	23095/707.5	10M QPSK(25,0)	0.050	0.043	-4.28	22.34	22.50	0.052	2026/6/07	
Left Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.028	0.023	4.68	22.34	22.50	0.029	2026/6/07	
Right Cheek	23095/707.5	10M QPSK(25,0)	0.052	0.040	2.49	22.34	22.50	0.054	2026/6/07	
Right Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.023	0.019	-3.83	22.34	22.50	0.024	2026/6/07	

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.108	0.087	-1.09	23.38	23.50	0.111	2026/6/07	
Back Side	23095/707.5	10M QPSK(1,0)	0.161	0.131	-1.73	23.38	23.50	0.166	2026/6/07	26#
50%RB										
Front Side	23095/707.5	10M	0.058	0.044	4.75	22.34	22.50	0.060	2026/6/07	

		QPSK(25,0)								
Back Side	23095/707.5	10M QPSK(25,0)	0.093	0.067	3.90	22.34	22.50	0.096	2026/6/07	

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.108	0.087	-1.09	23.38	23.50	0.111	2026/6/07	
Back Side	23095/707.5	10M QPSK(1,0)	0.161	0.131	-1.73	23.38	23.50	0.166	2026/6/07	26#
Left Side	23095/707.5	10M QPSK(1,0)	0.153	0.121	-2.12	23.38	23.50	0.157	2026/6/07	
Right Side	23095/707.5	10M QPSK(1,0)	0.136	0.105	0.44	23.38	23.50	0.140	2026/6/07	
Bottom Side	23095/707.5	10M QPSK(1,0)	0.084	0.059	2.06	23.38	23.50	0.086	2026/6/07	
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.058	0.044	4.75	22.34	22.50	0.060	2026/6/07	
Back Side	23095/707.5	10M QPSK(25,0)	0.093	0.067	3.90	22.34	22.50	0.096	2026/6/07	
Left Side	23095/707.5	10M QPSK(25,0)	0.090	0.071	0.15	22.34	22.50	0.093	2026/6/07	
Right Side	23095/707.5	10M QPSK(25,0)	0.075	0.057	1.68	22.34	22.50	0.078	2026/6/07	
Bottom Side	23095/707.5	10M QPSK(25,0)	0.043	0.031	-2.38	22.34	22.50	0.045	2026/6/07	

NOTE:1. Hotspot SAR test results of LTE Band 12

2. Tested by : Jack Peng

10.1.11. SAR measurement Result of LTE Band 17

Test Position	Test channel	Test Mode	SAR Value (W/kg)	Power Drift	Conducted power	Tune-up power	Scaled SAR	Date	Plot
---------------	--------------	-----------	------------------	-------------	-----------------	---------------	------------	------	------

of Head	/Freq.		1-g	10-g	(±5%)	(dBm)	(dBm)	1g (W/Kg)		
1RB										
Left Cheek	23790/710	10M QPSK(1,24)	0.103	0.075	1.99	23.35	24.00	0.120	2026/6/07	27#
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.059	0.043	-3.92	23.35	24.00	0.069	2026/6/07	
Right Cheek	23790/710	10M QPSK(1,24)	0.097	0.067	-0.29	23.35	24.00	0.113	2026/6/07	
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.050	0.035	-2.94	23.35	24.00	0.058	2026/6/07	
50%RB										
Left Cheek	23790/710	10M QPSK(25,0)	0.058	0.044	-2.65	22.34	22.50	0.060	2026/6/07	
Left Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.033	0.025	-3.36	22.34	22.50	0.034	2026/6/07	
Right Cheek	23790/710	10M QPSK(25,0)	0.052	0.036	-0.07	22.34	22.50	0.054	2026/6/07	
Right Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.028	0.019	3.92	22.34	22.50	0.029	2026/6/07	

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.168	0.111	1.84	23.35	24.00	0.195	2026/6/07	
Back Side	23790/710	10M QPSK(1,24)	0.233	0.157	-2.20	23.35	24.00	0.271	2026/6/07	28#
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.096	0.062	-4.37	22.34	22.50	0.100	2026/6/07	
Back Side	23790/710	10M QPSK(25,0)	0.137	0.090	0.53	22.34	22.50	0.142	2026/6/07	

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.168	0.111	1.84	23.35	24.00	0.195	2026/6/07	
Back Side	23790/710	10M QPSK(1,24)	0.233	0.157	-2.20	23.35	24.00	0.271	2026/6/07	28#
Left Side	23790/710	10M QPSK(1,24)	0.225	0.146	2.07	23.35	24.00	0.261	2026/6/07	
Right Side	23790/710	10M QPSK(1,24)	0.200	0.131	-0.98	23.35	24.00	0.232	2026/6/07	
Bottom Side	23790/710	10M QPSK(1,24)	0.012	0.010	-3.21	23.35	24.00	0.014	2026/6/07	
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.096	0.062	-4.37	22.34	22.50	0.100	2026/6/07	
Back Side	23790/710	10M QPSK(25,0)	0.137	0.090	0.53	22.34	22.50	0.142	2026/6/07	
Left Side	23790/710	10M QPSK(25,0)	0.120	0.086	-0.94	22.34	22.50	0.125	2026/6/07	
Right Side	23790/710	10M QPSK(25,0)	0.108	0.071	0.77	22.34	22.50	0.112	2026/6/07	
Bottom Side	23790/710	10M QPSK(25,0)	0.007	0.005	3.95	22.34	22.50	0.007	2026/6/07	

NOTE: 1.Hotspot SAR test results of LTE Band 17

2. Tested by : Jack Peng

10.1.12. SAR measurement Result of LTE Band 41

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	40620/2593	20M QPSK(1,0)	0.247	0.140	0.57	24.40	25.00	0.284	2026/6/03	29#

NOTE: Head SAR test results of LTE Band 41

NOTE: Body-Worn SAR test results of LTE Band 41

Test Position of	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g	Date	Plot
			1-g	10-g						

Hotspot with 10mm								(W/Kg)		
1RB										
Front Side	40620/2593	20M QPSK(1,0)	0.288	0.136	1.93	24.40	25.00	0.331	2026/6/03	
Back Side	40620/2593	20M QPSK(1,0)	0.654	0.335	0.79	24.40	25.00	0.751	2026/6/03	30#
Left Side	40620/2593	20M QPSK(1,0)	0.482	0.226	1.57	24.40	25.00	0.553	2026/6/03	
Right Side	40620/2593	20M QPSK(1,0)	0.073	0.033	-2.08	24.40	25.00	0.084	2026/6/03	
Bottom Side	40620/2593	20M QPSK(1,0)	0.260	0.119	-0.31	24.40	25.00	0.299	2026/6/03	
50%RB										
Front Side	40620/2593	20M QPSK(50,0)	0.155	0.071	-3.46	23.06	24.00	0.192	2026/6/03	
Back Side	40620/2593	20M QPSK(50,0)	0.358	0.173	1.58	23.06	24.00	0.445	2026/6/03	
Left Side	40620/2593	20M QPSK(50,0)	0.271	0.133	3.32	23.06	24.00	0.336	2026/6/03	
Right Side	40620/2593	20M QPSK(50,0)	0.038	0.017	2.48	23.06	24.00	0.047	2026/6/03	
Bottom Side	40620/2593	20M QPSK(50,0)	0.135	0.064	-1.45	23.06	24.00	0.168	2026/6/03	

NOTE: 1.Hotspot SAR test results of LTE Band 41

2. Tested by : Jack Peng

10.1.13. SAR measurement Result of WLAN2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	6/2437	802.11b	0.475	0.234	4.23	15.28	15.50	0.500	2026/6/11	15#
Left Tilt 15 Degree	6/2437	802.11b	0.264	0.126	-2.25	15.28	15.50	0.278	2026/6/11	
Right Cheek	6/2437	802.11b	0.405	0.194	-0.24	15.28	15.50	0.426	2026/6/11	

Right Tilt 15 Degree	6/2437	802.11b	0.190	0.094	-1.53	15.28	15.50	0.200	2026/6/11	
----------------------------	--------	---------	-------	-------	-------	-------	-------	-------	-----------	--

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	6/2437	802.11b	0.166	0.093	0.15	15.28	15.50	0.175	2026/6/11	
Back Side	6/2437	802.11b	0.363	0.179	0.00	15.28	15.50	0.382	2026/6/11	16#

NOTE: Body-worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	6/2437	802.11b	0.166	0.093	0.15	15.28	15.50	0.175	2026/6/11	
Back Side	6/2437	802.11b	0.363	0.179	0.00	15.28	15.50	0.382	2026/6/11	16#
Right Side	6/2437	802.11b	0.103	0.058	-1.51	15.28	15.50	0.108	2026/6/11	
Top Side	6/2437	802.11b	0.117	0.066	-3.26	15.28	15.50	0.123	2026/6/11	

NOTE: 1.Hotspot SAR test results of WLAN2.4G

2. Tested by : Max Zhou

10.1.14. SAR measurement Result of WLAN5.2G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	40/5200	802.11a	0.529	0.201	0.74	10.48	10.50	0.531	2026/6/04	11#
Left Tilt 15 Degree	40/5200	802.11a	0.266	0.100	-2.22	10.48	10.50	0.267	2026/6/04	
Right	40/5200	802.11a	0.469	0.176	0.65	10.48	10.50	0.471	2026/6/04	

Cheek										
Right Tilt 15 Degree	40/5200	802.11a	0.232	0.088	-2.37	10.48	10.50	0.233	2026/6/04	

NOTE: Head SAR test results of WLAN5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	40/5200	802.11a	0.133	0.054	1.25	10.48	10.50	0.134	2026/6/04	
Back Side	40/5200	802.11a	0.355	0.148	-3.42	10.48	10.50	0.357	2026/6/04	12#

NOTE: Body-worn SAR test results of WLAN5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	40/5200	802.11a	0.133	0.054	1.25	10.48	10.50	0.134	2026/6/04	
Back Side	40/5200	802.11a	0.355	0.148	-3.42	10.48	10.50	0.357	2026/6/04	12#
Right Side	40/5200	802.11a	0.190	0.078	1.79	10.48	10.50	0.191	2026/6/04	
Top Side	40/5200	802.11a	0.167	0.067	-3.49	10.48	10.50	0.168	2026/6/04	

NOTE: 1.Hotspot SAR test results of WLAN5.2G

2. Tested by : Jack Peng

10.1.15. SAR measurement Result of WLAN5.8G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	165/5825	802.11a	0.172	0.075	-0.84	10.51	11.00	0.193	2026/6/05	13#
Left Tilt 15	165/5825	802.11a	0.094	0.041	2.38	10.51	11.00	0.105	2026/6/05	

Degree										
Right Cheek	165/5825	802.11a	0.153	0.065	-2.14	10.51	11.00	0.171	2026/6/05	
Right Tilt 15 Degree	165/5825	802.11a	0.075	0.032	4.98	10.51	11.00	0.084	2026/6/05	

NOTE: Head SAR test results of WLAN5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.112	0.045	1.14	10.51	11.00	0.125	2026/6/05	
Back Side	165/5825	802.11a	0.303	0.126	0.39	10.51	11.00	0.339	2026/6/05	14#

NOTE: Body-worn SAR test results of WLAN5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.112	0.045	1.14	10.51	11.00	0.125	2026/6/05	
Back Side	165/5825	802.11a	0.303	0.126	0.39	10.51	11.00	0.339	2026/6/05	14#
Right Side	165/5825	802.11a	0.155	0.063	3.88	10.51	11.00	0.174	2026/6/05	
Top Side	165/5825	802.11a	0.153	0.063	-2.25	10.51	11.00	0.171	2026/6/05	

NOTE: 1.Hotspot SAR test results of WLAN5.8G

2. Tested by : Max Zhou

10.2. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	0.674	0.312	0.500	0.812	N/A	N/A
	0.36	0.158	0.278	0.436	N/A	N/A
	0.768	0.293	0.426	0.719	N/A	N/A
	0.408	0.155	0.200	0.355	N/A	N/A
Body-Worn	0.307	0.331	0.175	0.506	N/A	N/A
	0.454	0.751	0.382	1.133	N/A	N/A
Hotspot	0.307	0.331	0.175	0.506	N/A	N/A
	0.454	0.751	0.382	1.133	N/A	N/A
	0.288	0.553	N/A	0.553	N/A	N/A
	0.145	0.232	0.108	0.340	N/A	N/A
	0.165	N/A	0.123	0.123	N/A	N/A
	0.101	0.384	N/A	0.384	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.312	0.531	0.843	N/A	N/A
	Left Tilt 15 Degree	0.158	0.267	0.425	N/A	N/A
	Right Cheek	0.293	0.471	0.764	N/A	N/A
	Right Tilt 15 Degree	0.155	0.233	0.388	N/A	N/A
Body-Worn	Front Side	0.331	0.134	0.465	N/A	N/A

	Back Side	0.751	0.357	1.108	N/A	N/A
Hotspot	Front Side	0.331	0.134	0.465	N/A	N/A
	Back Side	0.751	0.357	1.108	N/A	N/A
	Left Side	0.553	N/A	0.553	N/A	N/A
	Right Side	0.232	0.191	0.423	N/A	N/A
	Top Side	N/A	0.171	0.171	N/A	N/A
	Bottom Side	0.384	N/A	0.384	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.312	0.133	0.445	N/A	N/A
	Left Tilt 15 Degree	0.158	0.133	0.291	N/A	N/A
	Right Cheek	0.293	0.133	0.426	N/A	N/A
	Right Tilt 15 Degree	0.155	0.133	0.288	N/A	N/A
Body-Worn	Front Side	0.331	0.066	0.397	N/A	N/A
	Back Side	0.751	0.066	0.817	N/A	N/A
Hotspot	Front Side	0.331	0.066	0.397	N/A	N/A
	Back Side	0.751	0.066	0.817	N/A	N/A
	Left Side	0.553	N/A	0.553	N/A	N/A
	Right Side	0.232	0.066	0.298	N/A	N/A
	Top Side	N/A	0.066	0.066	N/A	N/A
	Bottom Side	0.384	N/A	0.384	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5800MHz

1# System check at 750 MHz
Date of measurement: 7/6/2026


A. Experimental conditions.

Probe	4024-EPGO-442
ConvF	2.42
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	750.00
Relative permittivity (real part)	42.85
Relative permittivity (imaginary part)	22.25
Conductivity (S/m)	0.93

C. SAR Surface and Volume




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 1.29 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.568
SAR 1g (W/Kg)	0.888
Variation (%)	0.58
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	66.64

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.339	0.905	0.572	0.413	0.291	0.223	0.162



F. 3D Image



2# System check at 835 MHz
Date of measurement: 8/6/2026


A. Experimental conditions.

Probe	4024-EPGO-442
ConvF	2.34
Area Scan	dx=15mm dy=15mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	CW
Channels/Frequency	Middle

B. Permittivity

Middle TX Frequency (MHz)	835.00
Relative permittivity (real part)	42.79
Relative permittivity (imaginary part)	19.94
Conductivity (S/m)	0.92

C. SAR Surface and Volume




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 1.42 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.623
SAR 1g (W/Kg)	0.977
Variation (%)	-0.60
Horizontal validation criteria: minimum distance (mm)	16.00
Vertical validation criteria: SAR ratio M2/M1 (%)	69.26

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.333	0.997	0.691	0.460	0.334	0.233	0.177



F. 3D Image

