

TEST REPORT

FCC ID: 2AIZN-DONGLE

Product: Infinix Space Max

Model No.: XEH1 Dongle

Trade Mark: Infinix

Report No.: WSCT-ANAB-R&E260700064A-15B

Issued Date: 07 July 2026

Issued for:

INFINIX MOBILITY LIMITED

FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B,Baoli'an Industrial Park,No.58 and 60,Tangtou Avenue, Shiyao Street,
Bao'an District, Shenzhen City, Guangdong Province, China

TEL: +86-755-26996192

FAX: +86-755-86376605



Note: This report shall not be reproduced except in full, without the written approval of World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. This document may be altered or revised by World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

1. Test Certification	3
2. GENERAL DESCRIPTION OF EUT	4
3. Test Result Summary	5
4. TEST METHODOLOGY	6
4.1. CONFIGURATION OF SYSTEM UNDER TEST	7
4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)	8
5. MEASUREMENT INSTRUMENTS	9
6. Facilities and Accreditations	10
6.1. FACILITIES	10
6.2. ACCREDITATIONS	10
6.3. MEASUREMENT UNCERTAINTY	11
7. EMC EMISSION TEST	12
7.1. CONDUCTED EMISSION MEASUREMENT	12
7.2. RADIATED EMISSION MEASUREMENT	12

Report No.: WSCT-ANAB-R&E260700064A-15B

Issued: 07 July 2026

Revised: None

1. Test Certification

Product: Infinix Space Max**Model No.:** XEH1 Dongle**Trade Mark:** Infinix**Applicant:** INFINIX MOBILITY LIMITEDFLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL
CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG**Manufacturer:** INFINIX MOBILITY LIMITEDFLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL
CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG**Date of Test:** 23 June 2026 ~ 07 July 2026**Applicable Standards:** FCC CFR Title 47 Part 15 Subpart B

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:
(Jiang Guanliang)**Checked By:**
(Chen Xu)**Approved By:**
(Qin Shuiquan)**Date:**

07 July 2026



2. GENERAL DESCRIPTION OF EUT

Product Name:	Infinix Space Max
Model :	XEH1 Dongle
Trade Mark:	Infinix
Software Version	V010
Hardware Version	V1.0
Operating Voltage	N/A
Remark:	N/A.

Note: All the test data in this report were done using the XEH1 and XEH1 Dongle together.

3. Test Result Summary

Requirement	CFR 47 Section	Result
CONDUCTED EMISSION	§15.107	N/A
RADIATED EMISSION	§15.109	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.


4. TEST METHODOLOGY

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Charging
Mode 2	Bluetooth

4.1. CONFIGURATION OF SYSTEM UNDER TEST

Configuration Setup 1:



Configuration Setup 2:



(EUT: Infinix Space Max)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
Power	1	0.5m USB cable,unshielded	/

4.2. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	XCU32	/	/
2	Laptop	/	YL613H	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5. MEASUREMENT INSTRUMENTS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibrated	Calibrated until
Test software	--	EZ-EMC	CON-03A	--	--
ESCI Test Receiver	R&S	ESCI	100005	11/05/2025	11/04/2026
LISN	AFJ	LS16	16010222119	11/05/2025	11/04/2026
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2025	11/04/2026
pre-amplifier	CDSI	PAP-1G18-38	--	11/05/2025	11/04/2026
System Controller	CT	SC100	-	11/05/2025	11/04/2026
Bi-log Antenna	Chase	CBL6111C	2576	11/05/2025	11/04/2026
Spectrum analyzer	R&S	FSU26	200409	11/05/2025	11/04/2026
Horn Antenna	SCHWARZBECK	9120D	1141	11/05/2025	11/04/2026
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	07/29/2025	07/28/2026
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2025	11/04/2026
9*6*6 Anechoic	--	--	--	11/05/2025	11/04/2026

6. Facilities and Accreditations

6.1. Facilities

All measurement facilities used to collect the measurement data are located at **World Standardization Certification & Testing Group (Shenzhen) Co., Ltd. Building A-B, Baoli'an Industrial Park, No.58 and 60, Tangtou Avenue, Shiyao Street, Bao'an District, Shenzhen City, Guangdong Province, China**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:2017.

USA

ANAB - Certificate Number: AT-3951

China

CNAS (Registration Number: L3732)

Canada

ISED(CAB identifier:CN0178)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>

6.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
5	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2.0\%$

7. EMC EMISSION TEST

7.1. CONDUCTED EMISSION MEASUREMENT

N/A

7.2. RADIATED EMISSION MEASUREMENT

7.2.1. Radiated Emission Limits

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz




7.2.2. Test Results

Temperature	20 °C	Relative Humidity	48%
Pressure	1010 hPa	Test Mode	Mode 2(the worst case)

Please refer to following diagram for individual


Below 1GHz

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	39.4026	49.79	-19.12	30.67	40.00	-9.33	QP
2	45.2364	45.65	-18.89	26.76	40.00	-13.24	QP
3	75.0506	38.33	-23.52	14.81	40.00	-25.19	QP
4	90.0230	38.43	-24.06	14.37	43.50	-29.13	QP
5	163.1818	30.15	-19.97	10.18	43.50	-33.32	QP
6	229.2931	33.92	-23.15	10.77	46.00	-35.23	QP

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	31.5510	40.11	-19.54	20.57	40.00	-19.43	QP
2	38.8198	38.30	-19.18	19.12	40.00	-20.88	QP
3	108.0297	41.70	-22.89	18.81	43.50	-24.69	QP
4	229.4942	36.77	-23.14	13.63	46.00	-32.37	QP
5	315.4808	38.41	-19.73	18.68	46.00	-27.32	QP
6	764.0452	26.89	-11.51	15.38	46.00	-30.62	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) - Limits (dBuV)

TEST RESULTS

Above 1GHz(1~26GHz) :(Mode 2—worst case)

Note: The spurious above 6G is noise only, do not show on the report.

Horizontal:




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1622.500	33.24	-7.37	25.87	74.00	-48.13	peak
2	1622.500	22.72	-7.37	15.35	54.00	-38.65	AVG
3	2156.250	32.04	-1.24	30.80	74.00	-43.20	peak
4	2156.250	23.40	-1.24	22.16	54.00	-31.84	AVG
5	2456.250	45.54	-3.82	41.72	74.00	-32.28	peak
6	2456.250	43.82	-3.82	40.00	54.00	-14.00	AVG
7	3041.250	33.68	-2.18	31.50	74.00	-42.50	peak
8	3041.250	22.80	-2.18	20.62	54.00	-33.38	AVG
9	3872.500	32.85	0.43	33.28	74.00	-40.72	peak
10	3872.500	23.66	0.43	24.09	54.00	-29.91	AVG
11	5179.375	47.34	5.83	53.17	74.00	-20.83	peak
12 *	5179.375	40.90	5.83	46.73	54.00	-7.27	AVG

Report No.: WSCT-ANAB-R&E260700064A-15B

Issued: 07 July 2026

Revised: None

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1631.250	32.43	-7.36	25.07	74.00	-48.93	peak
2	1631.250	22.85	-7.36	15.49	54.00	-38.51	AVG
3	2061.250	32.53	-2.65	29.88	74.00	-44.12	peak
4	2061.250	23.32	-2.65	20.67	54.00	-33.33	AVG
5	2475.625	46.95	-3.72	43.23	74.00	-30.77	peak
6	2475.625	41.13	-3.72	37.41	54.00	-16.59	AVG
7	3241.250	33.10	-1.74	31.36	74.00	-42.64	peak
8	3241.250	23.50	-1.74	21.76	54.00	-32.24	AVG
9	4121.250	32.98	1.48	34.46	74.00	-39.54	peak
10	4121.250	23.15	1.48	24.63	54.00	-29.37	AVG
11	5246.875	43.35	6.06	49.41	74.00	-24.59	peak
12 *	5246.875	37.10	6.06	43.16	54.00	-10.84	AVG

Remark:

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Freq. = Emission frequency in MHz

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over= Emission Level - Limit.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

*******END OF REPORT*******