

RF EXPOSURE REPORT

Applicant:	Clear Touch Interactive Inc		
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States		
Manufacturer:	Clear Touch Interactive Inc		
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States		
Product Description:	Command Studio Digital Console		
Brand Name:	Clear Touch		
Tested Model/HVIN:	CTI-CMST01-SCRN		
FCC ID:	2AL27-CMSTSCRN		
Report No.:	JCF250916081-005		
Received Date:	Sep. 22, 2025		
Tested Date:	Sep. 22, 2025 - Dec. 18, 2025		
Issued Date:	Dec. 18, 2025		
Test Standards:	KDB 447498 D01 General RF Exposure Guidance v06		
Test Result:	Pass		

Prepared By:



Kennys Zhang/Engineer
Date: Dec. 18, 2025

Reviewed By:



Roger Li/Engineer
Date: Dec. 18, 2025

Approved By:



Talent Zhang/Engineer
Date: Dec. 18, 2025

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 18, 2025	Original Report	/

Table of Contents

1. Test Report Declare	4
2. Equipment Under Test	5
2.1. Description of EUT	5
2.2. Description of Available Antennas	5
3. Test Laboratory	6
4. RF Exposure Measurement	6
4.1. Requirement	6
4.2. Limits for Maximum Permissible Exposure (MPE)	6
4.3. MPE Calculation Formula	6
4.4. Classification	7
5. RF Exposure Calculation	7

1. Test Report Declare

Applicant:	Clear Touch Interactive Inc
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States
Manufacturer:	Clear Touch Interactive Inc
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States
Product Name	Command Studio Digital Console
Brand Name:	Clear Touch
Model Name:	CTI-CMST01-SCRN
Difference Description:	N/A

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

2. Equipment Under Test

2.1. Description of EUT

EUT* Name:	Command Studio Digital Console
Model Number:	CTI-CMST01-SCRN
EUT Function Description:	Please refer to user manual of this device
Power Supply:	Input: 24V $\pm$ 4A
Sample No.	250916081-01-01
Hardware Version:	N/A
Software Version:	N/A
Radio Specification:	SRD 2.4G IEEE 802.11b/g/a/n/ac/ax
Operation Frequency:	2.4G SRD: 2406MHz—2474MHz IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11a: 5180MHz—5825MHz IEEE 802.11n HT20: 5180MHz—5825MHz IEEE 802.11n HT40: 5190MHz—5795MHz IEEE 802.11ac VHT20: 5180MHz—5825MHz IEEE 802.11ac VHT40: 5190MHz—5795MHz IEEE 802.11ac VHT80: 5210MHz—5775MHz IEEE 802.11ax HE20: 5180MHz—5825MHz IEEE 802.11ax HE40: 5190MHz—5795MHz IEEE 802.11ax HE80: 5210MHz—5775MHz
Modulation:	GFSK IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac (VHT20/40/80): OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax (HE20/40/80): OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Antenna Type:	2.4G WiFi: External Antenna, MAX. Gain: 4.08 dBi 5G WiFi 1: External Antenna, MAX. Gain: 6.18 dBi 5G WiFi 2: External Antenna, MAX. Gain: 6.42 dBi 2.4G SRD: External Antenna, MAX. Gain: 5.73 dBi
Product Type:	☐ Portable device ☒ Mobile device ☐ Fixed device

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

2.2. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
2.4G SRD	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
2.4G WIFI	☒ 2TX, 2RX	ANT 1 and ANT2 can be used as transmitting/receiving antenna.
5G WIFI 1	☒ 2TX, 2RX	ANT 1 and ANT2 can be used as transmitting/receiving antenna.
5G WIFI 2	☒ 2TX, 2RX	ANT 1 and ANT2 can be used as transmitting/receiving antenna.

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

4. RF Exposure Measurement

4.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

4.2. Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
Limits For General Population / Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

* = Plane-wave equivalent power density.

4.3. MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * R^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4.4. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

Conducted Power

Band	Channel Frequency (MHz)	Average Power (dBm)
2.4G SRD	2474	3.48
2.4G WIFI	2422	24.95
5G WIFI 1	5580	15
5G WIFI 2	5700	9.49

5. RF Exposure Calculation

We used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

Band	Channel Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Power Density (mW/cm ²)	Limit (mW/cm ²)	PASS/FAIL
2.4G SRD	2474	3.48	5.73	0.0017	1	PASS
2.4G WIFI	2422	24.95	4.08	0.1591	1	PASS
5G WIFI 1	5580	15	6.18	0.0261	1	PASS
5G WIFI 2	5700	9.49	6.42	0.0078	1	PASS

Both of the WLAN and plug-in device can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1/LPD1 + CPD2/LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore the worst-case situation is $0.0017/1.00 + 0.1591/1.00 + 0.0261/1.00 + 0.0078/1.00 = 0.1947$, which is less than "1", This confirmed that the device comply with FCC 1.1310 MPE limit.

--END--