

TEST REPORT

Application No.: KSCR2512002598AT
FCC ID: 2AL8S-0231C20R
Applicant: Zhejiang Uniview Technologies Co., Ltd.
Address of Applicant: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
Manufacturer: Zhejiang Uniview Technologies Co., Ltd.
Address of Manufacturer: No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China
Equipment Under Test (EUT):
EUT Name: Card Reader
Model No.: OEC-R3H-MEK,OEC-R3H-ME,OEC-R3H-MEm-xxxxxxx-yyy-yyyy-zzz
("x","y","z","m" can be 0-9,A-Z,a-z or blank;"-" may be blank) ♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Standard(s) : 47 CFR Part 15, Subpart C
Date of Receipt: 2025-12-01
Date of Test: 2025-12-22 to 2025-12-29
Date of Issue: 2026-01-07

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2026-01-07	/

Authorized for issue by:			
Tested By		Maker Qi	
		Maker Qi /Project Engineer	
Approved By		Terry Hou	
		Terry Hou /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.209	N/A	47 CFR Part 15, Subpart C 15.203	Customer Declaration

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at Mains Terminals (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.209	ANSI C63.10 (2020)	47 CFR Part 15, Subpart C 15.207	Pass
20dB Bandwidth		ANSI C63.10 (2020)	47 CFR Part 15, Subpart C Section	Pass
Radiated Emissions (9kHz-30MHz)		ANSI C63.10 (2020)	47 CFR Part 15, Subpart C Section 15.205/15.209	Pass
Radiated Emissions (30MHz-1GHz)		ANSI C63.10 (2020)	47 CFR Part 15, Subpart C Section 15.205/15.209	Pass

Declaration of EUT Family Grouping:

There are series models mentioned in this report and they are the Identical in electrical and electronic characters. Only the model OEC-R3H-MEK was tested since their differences were the model number and appearance.

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Test Location	6
4.5 Test Facility	6
4.6 Deviation from Standards.....	6
4.7 Abnormalities from Standard Conditions.....	6
5 Equipment List	7
6 Radio Spectrum Matter Test Results	8
6.1 Antenna Requirement	8
6.2 Conducted Emissions at Mains Terminals (150kHz-30MHz).....	9
6.3 20dB Bandwidth	13
6.4 Radiated Emissions (9kHz-30MHz)	14
6.5 Radiated Emissions (30MHz-1GHz)	16
7 Test Setup Photo	18
8 EUT Constructional Details (EUT Photos).....	18
9 Appendix.....	19
9.1 20dB Bandwidth	19
9.2 Radiated Emissions.....	20

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 12V/1A
Test Voltage:	AC 120V/60Hz(Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case)
Operation Frequency:	125kHz
Modulation Type:	AM
Number of Channels:	1
Number of Antennas	1
Antenna Type:	Loop Antenna
Product Type:	☐ Portable device
	☐ Mobile device
	☒ Fixed device

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
AC Adapter	Zhuzhou Dachuan	DCT12W120100EU-A2	/

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz) 5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz) 4.5dB (30MHz-1GHz) 5.1dB (1GHz-18GHz) 5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1172)**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

- **VCCI (Member No:1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESCI	KS301196	07/09/2025	07/08/2026
2	LISN	R&S	ENV216	KS301197	01/15/2025	01/14/2026
3	LISN	Schwarzbeck	NNLK 8129	KS301091	01/15/2025	01/14/2026
4	Pulse Limiter	R&S	ESH3-Z2	KUS1902E001	12/04/2025	12/03/2026
5	CE test Cable	Thermax	/	CZ301102	01/14/2025	01/13/2026
6	Test Software	Farad	EZ-EMC	/	N.C.R	N.C.R
RF Radiated Test						
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	07/09/2025	07/08/2026
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	02/18/2025	02/17/2026
3	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
4	Loop Antenna (9KHz-30MHz)	COM-POWER	AL-130R	KUS1806E001	07/11/2025	07/10/2026
5	Bilog Antenna (30MHz-1GHz)	TESEQ	CBL 6112D	KUS1806E005	07/12/2025	07/11/2026
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	03/23/2024	03/22/2026
7	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	01/07/2024	01/06/2026
8	Amplifier(30MHz~1GHz)	TST	LNA009100G30	KSEM061	01/15/2025	01/14/2026
9	Amplifier(400MHz~8GHz)	TST	LNA004080G30	KSEM062	01/15/2025	01/14/2026
10	Amplifier(1GHz~18GHz)	TST	LNA010180G45	KSEM039	07/09/2025	07/08/2026
11	Amplifier(18~40GHz)	TST	LNA180400G40	KSEM038	07/09/2025	07/08/2026
12	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	02/26/2025	02/25/2026
13	Software	ESE	E3_V 6.111221a	/	NCR	NCR
14	Measurement Software	Tonscend	JS32-RE V5.0.0.1	/	NCR	NCR
15	Measurement Software	Tonscend	JS32-RSE V5.0.0.0	/	NCR	NCR

6 Radio Spectrum Matter Test Results

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Integrated antenna and no consideration of replacement.

Antenna location: Refer to Internal photos.

6.2 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.2 % RH

Atmospheric Pressure: 1010 mbar

6.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in transmitting mode

6.2.3 Test Setup Diagram




6.2.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark: Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 01; Line: Live line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1509	6.52	20.12	26.64	55.95	-29.31	Average
2	0.1509	25.92	20.12	46.04	65.95	-19.91	QP
3	0.1571	5.88	20.08	25.96	55.62	-29.66	Average
4	0.1571	25.10	20.08	45.18	65.62	-20.44	QP
5	0.1759	4.30	19.94	24.24	54.68	-30.44	Average
6	0.1759	23.33	19.94	43.27	64.68	-21.41	QP
7	0.2152	2.00	19.78	21.78	53.00	-31.22	Average
8	0.2152	20.53	19.78	40.31	63.00	-22.69	QP
9	0.3480	-3.32	19.70	16.38	49.01	-32.63	Average
10	0.3480	13.10	19.70	32.80	59.01	-26.21	QP
11	0.4719	2.30	19.68	21.98	46.48	-24.50	Average
12	0.4719	14.54	19.68	34.22	56.48	-22.26	QP

Test Mode: 01; Line: Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	6.47	20.07	26.54	56.00	-29.46	Average
2	0.1500	25.66	20.07	45.73	66.00	-20.27	QP
3	0.1671	4.99	19.99	24.98	55.10	-30.12	Average
4	0.1671	23.61	19.99	43.60	65.10	-21.50	QP
5	0.1979	3.25	19.87	23.12	53.70	-30.58	Average
6	0.1979	21.45	19.87	41.32	63.70	-22.38	QP
7	0.2810	-0.90	19.65	18.75	50.79	-32.04	Average
8	0.2810	16.05	19.65	35.70	60.79	-25.09	QP
9	0.3483	-2.76	19.61	16.85	49.00	-32.15	Average
10	0.3483	12.63	19.61	32.24	59.00	-26.76	QP
11	0.4578	-4.03	19.61	15.58	46.73	-31.15	Average
12	0.4578	8.16	19.61	27.77	56.73	-28.96	QP

6.3 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C Section

Test Method: ANSI C63.10 (2020)

Measurement Distance: 3m

6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C


Humidity: 48.2 % RH

Atmospheric Pressure: 1010 mbar

6.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode_Keep the EUT in transmitting mode

6.3.3 Test Setup Diagram



6.3.4 Measurement Procedure and Data

Please Refer to Appendix for Details

6.4 Radiated Emissions (9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020)

Measurement Distance: 3m

Limit:

Frequency	Magnetic field strength (H-Field) ($\mu\text{A/m}$)	Measurement distance (m)
9 - 490 kHz ¹	$6.37/F$ (F in kHz)	300
490 - 1705 kHz	$63.7/F$ (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Below 30MHz

If field strength is measured at only a single point, then that point shall be at the radial from the EUT that produces the maximum emission at the frequency being measured, as described in 5.4. If that point is closer to the EUT than $\lambda/2\pi$ and the limit distance is greater than $\lambda/2\pi$, the measurement shall be extrapolated to the limit distance by conservatively presuming that the field strength decreases at a 40 dB/decade of distance rate to the $\lambda/2\pi$ distance, and at a 20 dB/decade of distance rate beyond $\lambda/2\pi$. This shall be accomplished using Equation (2):

$$FS_{(3m)} = FS_{(30/300m)} + 40\log\{d_{(\text{near field})}/d_{(3m)}\} + 20\log\{d_{(30/300m)}/d_{(\text{near field})}\} \quad (2)$$

If the single point measured is at a distance greater than $\lambda/2\pi$, then extrapolation to the limit distance shall be calculated using Equation (3):

$$FS_{(3m)} = FS_{(30/300m)} + 20\log\{d_{(30/300m)}/d_{(3m)}\} \quad (3)$$

If both the single point and the limit distance are equal to or closer to the EUT than $\lambda/2\pi$, then extrapolation to the limit distance shall be calculated using Equation (4):

$$FS_{(3m)} = FS_{(30/300m)} + 40\log\{d_{(30/300m)}/d_{(3m)}\} \quad (4)$$

Remark:

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}$$

where f_{MHz} is the frequency of the emission being measured in MHz.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

$$FS_{\text{limit}} = FS_{\text{max}} - 40 \log \left(\frac{d_{\text{limit}}}{d_{\text{measure}}} \right)$$

where

FS_{limit} is the calculation of field strength at the limit distance, expressed in dBμV/m
 FS_{max} is the measured field strength, expressed in dBμV/m
 d_{measure} is the distance of the measurement point from the EUT
 d_{limit} is the reference distance or the distance of the $\lambda/2\pi$ point

6.4.1 E.U.T. Operation

Operating Environment:

Temperature: 20.8 °C


Humidity: 49.5 % RH

Atmospheric Pressure: 1010 mbar

6.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in transmitting mode

6.4.3 Test Setup Diagram



6.4.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

Please Refer to Appendix for Details

6.5 Radiated Emissions (30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020)

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands above 1000 MHz. Radiated emission limits in these three bands (9-90kHz,110-490kHz and Above 1GHz) are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.5.1 E.U.T. Operation

Operating Environment:

Temperature: 20.8 °C


Humidity: 49.5 % RH

Atmospheric Pressure: 1010 mbar

6.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in transmitting mode

6.5.3 Test Setup Diagram



6.5.4 Measurement Procedure and Data

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground for below 1GHz at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Please Refer to Appendix for Details



Report No.: KSCR251200259801

Page: 18 of 21

7 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2512002598AT

8 EUT Constructional Details (EUT Photos)


Refer to Appendix_Photographs of EUT Constructional Details for KSCR2512002598AT

9 Appendix

9.1 20dB Bandwidth


20dB bandwidth (Hz)	Result
256.58	Pass

Test plot as follows:




9.2 Radiated Emissions

9kHz-30MHz



Item ¹	Freq. ²	Read Level ³	Correct Factor ⁴	Result Level@3m ⁵	Result Level@SP EC ⁶	Limit Line@SPEC ⁷	Over Limit ⁸	Detector ⁹
(Mark) ¹	(MHz) ²	(dBuV) ³	(dB/m) ⁴	(dBuV/m) ⁵	(dBuV/m) ⁶	(dBuV/m) ⁷	(dB) ⁸	⁹
1 ¹	0.01 ²	42.09 ³	20.32 ⁴	62.41 ⁵	-17.59 ⁶	47.37 ⁷	-64.96 ⁸	AV ⁹
2 ¹	0.02 ²	38.72 ³	20.36 ⁴	59.08 ⁵	-20.92 ⁶	44.07 ⁷	-64.99 ⁸	AV ⁹
3 ¹	0.03 ²	28.81 ³	20.41 ⁴	49.22 ⁵	-30.78 ⁶	36.74 ⁷	-67.52 ⁸	AV ⁹
4 ¹	0.08 ²	23.11 ³	20.36 ⁴	43.47 ⁵	-36.53 ⁶	29.87 ⁷	-66.4 ⁸	AV ⁹
5 ¹	0.12 ²	61.22 ³	20.65 ⁴	81.87 ⁵	1.87 ⁶	25.65 ⁷	-23.78 ⁸	Peak ⁹
6 ¹	0.17 ²	29.58 ³	20.59 ⁴	50.17 ⁵	-29.83 ⁶	23.11 ⁷	-52.94 ⁸	AV ⁹
7 ¹	0.88 ²	42.04 ³	20.43 ⁴	62.47 ⁵	22.47 ⁶	28.76 ⁷	-6.29 ⁸	QP ⁹

Coaxial




Item ¹	Freq. ²	Read Level ³	Correct Factor ⁴	Result Level@3 m ⁵	Result Level@S PEC ⁶	Limit Line@SP EC ⁷	Over Limit ⁸	Detector ⁹	Polarity ¹⁰
(Mark) ¹	(MHz) ²	(dBuV) ³	(dB/m) ⁴	(dBuV/m) ⁵	(dBuV/m) ⁶	(dBuV/m) ⁷	(dB) ⁸	⁹	¹⁰
1 ¹	0.01 ²	36.04 ³	20.31 ⁴	56.35 ⁵	-23.65 ⁶	47.8 ⁷	-71.45 ⁸	AV ⁹	Vertica ¹⁰
2 ¹	0.03 ²	33.68 ³	20.46 ⁴	54.14 ⁵	-25.86 ⁶	38.01 ⁷	-63.87 ⁸	AV ⁹	Vertica ¹⁰
3 ¹	0.07 ²	28.21 ³	20.29 ⁴	48.49 ⁵	-31.51 ⁶	31.21 ⁷	-62.72 ⁸	AV ⁹	Vertica ¹⁰
4 ¹	0.12 ²	45.33 ³	20.64 ⁴	65.97 ⁵	-14.03 ⁶	25.68 ⁷	-39.71 ⁸	Peak ⁹	Vertica ¹⁰
5 ¹	0.17 ²	28.78 ³	20.59 ⁴	49.37 ⁵	-30.63 ⁶	23.15 ⁷	-53.78 ⁸	AV ⁹	Vertica ¹⁰
6 ¹	0.88 ²	34.14 ³	20.43 ⁴	54.57 ⁵	14.57 ⁶	28.76 ⁷	-14.19 ⁸	QP ⁹	Vertica ¹⁰
7 ¹	1.59 ²	25.24 ³	20.51 ⁴	45.75 ⁵	5.75 ⁶	23.63 ⁷	-17.88 ⁸	QP ⁹	Vertica ¹⁰

Coplanar


Note: SPEC represents the limit of the distance 3m converts to the standard.

Below 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	65.11	13.50	12.09	25.59	40.00	-14.41	QP
2	88.96	8.31	17.29	25.60	43.50	-17.90	QP
3	88.96	8.31	17.29	25.60	43.50	-17.90	QP
4	162.61	4.43	17.15	21.58	43.50	-21.92	QP
5	298.27	4.20	21.62	25.82	46.00	-20.18	QP
6	785.09	4.05	30.24	34.29	46.00	-11.71	QP

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.29	3.08	24.04	27.12	40.00	-12.88	QP
2	70.34	17.95	13.64	31.59	40.00	-8.41	QP
3	139.85	4.58	20.22	24.80	43.50	-18.70	QP
4	276.12	2.81	20.89	23.70	46.00	-22.30	QP
5	622.89	3.49	28.71	32.20	46.00	-13.80	QP
6	948.76	3.73	31.18	34.91	46.00	-11.09	QP

Vertical

- End of the Report -