

TEST REPORT

of

FCC Part 15 Subpart C §15.247
IC RSS-247 Issue 4 and RSS-Gen Issue 5

FCC ID: 2AMD4UTO-NBL-54L
IC Certification: 27695-UTONBL54L

Equipment Under Test : BLE module
Model Name : UTO-NBL-54L
Variant Model Name(s) : UTO-NBL-54LA
FCC Applicant : Utovertek Co.,Ltd.
IC Applicant : UTOVERTEK
Manufacturer : UTOVERTEK
Date of Receipt : 2026.03.10
Date of Test(s) : 2026.03.12 ~ 2026.05.07
Date of Issue : 2026.05.12

In the configuration tested, the EUT complied with the standards specified above.
This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer

Tested by:



Finn Nam

Technical
Manager:



Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

Table of contents

1. General Information -----	3
2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions -----	10
3. 6 dB Bandwidth and 99 % Bandwidth -----	53
4. Maximum Peak Conducted Output Power -----	60
5. Power Spectral Density -----	65
6. Antenna Requirement -----	69

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

FCC Applicant : Utovertek Co.,Ltd.

FCC Address : RM210, KETI Business Incubator, 25 seonari-ro, Bundang-gu, Seongnam-si,
Gyeonggi-do, South Korea

IC Applicant : UTOVERTEK

IC Address : RM1111, 24, Dunchon-daero 388 beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do,
Korea

Contact Person : Lee, Sung-Jae

Phone No. : +82 31 781 2593

1.3. Details of Manufacturer

Company : UTOVERTEK

Address : RM1111, 24, Dunchon-daero 388 beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do,
Korea

1.4. Description of EUT

Kind of Product		BLE module
Model Name		UTO-NBL-54L
Variant Model Name(s)		UTO-NBL-54LA
Serial Number		Conducted: C01 Radiated: R01
Power Supply		DC 3.0 V
Frequency Range		2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy)
Modulation Technique		GFSK
Number of Channels		40 channels (Bluetooth Low Energy)
Maximum measured E.I.R.P.		12.55 dB m
Antenna Type	Basic Model	Dipole Antenna
	Variant Model	Chip Antenna
Antenna Gain*	Basic Model	6.15 dB i
	Variant Model	1.99 dB i
H/W Version		1.0
S/W Version		1.0
FVIN		N/A

1.5. Test Equipment List

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Interval	Cal. Due
Signal Generator	R&S	SMA100B	106887	10/20/2025	Annual	10/20/2026
Spectrum Analyzer	R&S	FSV30	103455	02/02/2026	Annual	02/02/2027
Spectrum Analyzer	Agilent	N9020A	MY53421758	09/10/2025	Annual	09/10/2026
Spectrum Analyzer	Agilent	N9030A	US51350132	12/03/2025	Annual	12/03/2026
Attenuator	AEROFLEX/INMET	40AH2W-6	1	03/09/2026	Annual	03/09/2027
High Pass Filter	Wainwright Instrument GmbH	WHKX3.0/18G-6SS	4	06/09/2025	Annual	06/09/2026
High Pass Filter	Wainwright Instrument GmbH	WLKX10-6320-8000-26500-40CC	6	10/22/2025	Annual	10/22/2026
Power Sensor	R&S	NRP-Z81	100669	05/24/2025	Annual	05/24/2026
DC Power Supply	Agilent	U8002A	019258024	10/24/2025	Annual	10/24/2026
Preamplifier	H.P.	8447F	2944A03909	08/07/2025	Annual	08/07/2026
Preamplifier	TESTEK	TK-PA1840H	130016	03/06/2026	Annual	03/06/2027
Signal Conditioning Unit	R&S	SCU-18F	100959	01/05/2026	Annual	01/05/2027
Loop Antenna	Schwarzbeck Mess-Elektronik	FMZB 1519	1519-039	10/01/2025	Biennial	10/01/2027
Bilog Antenna	Schwarzbeck Mess-Elektronik	VULB 9163	01126	03/09/2026	Biennial	03/09/2028
Horn Antenna	R&S	HF906	100326	03/03/2026	Annual	03/03/2027
Horn Antenna	Schwarzbeck Mess-Elektronik	BBHA 9170	9170-540	12/05/2025	Annual	12/05/2026
EMI Test Receiver	R&S	ESU26	100109	01/21/2026	Annual	01/21/2027
Turn Table	Innco systems GmbH	DS 1200 S	N/A	N.C.R.	N/A	N.C.R.
Controller	Innco systems GmbH	CONTROLLER CO3000-4P	CO3000/963/38330516/L	N.C.R.	N/A	N.C.R.
Antenna Mast	Innco systems GmbH	MA4640-XP-ET	MA4640/536/38330516/L	N.C.R.	N/A	N.C.R.
Anechoic Chamber	SY Corporation	L × W × H (9.6 m × 6.4 m × 6.6 m)	N/A	N.C.R.	N/A	N.C.R.
Coaxial Cable	SENSORVIEW	NMST-13A26-NMST-5m	TPC2402190004	04/13/2026	Semi-Annual	10/13/2026
Coaxial Cable	SENSORVIEW	NMST-13A26-NMST-10m	TPC2402190001	04/13/2026	Semi-Annual	10/13/2026
Coaxial Cable	RFONE	PL360P-292M292M-1.5M-A	20200324002	04/13/2026	Semi-Annual	10/13/2026

Note;

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date

1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15 Subpart C, RSS-247 Issue 4 and RSS-Gen Issue 5			
Section in FCC	Section in IC	Test Item(s)	Result
15.205(a) 15.209 15.247(d)	RSS-247 Issue 4 6.6 RSS-Gen Issue 5 8.9	Transmitter Radiated Spurious Emissions and Conducted Spurious Emission	Pass
15.247(a)(2)	RSS-247 Issue 4 6.3.1(a) RSS-Gen Issue 5 6.7	6 dB Bandwidth & 99 % Bandwidth	Pass
15.247(b)(3)	RSS-247 Issue 4 6.3.2	Maximum Peak Conducted Output Power	Pass
15.247(e)	RSS-247 Issue 4 6.3.1(b)	Power Spectral Density	Pass
15.207	RSS-Gen Issue 5 8.8	AC Power Line Conducted Emission	N/A ¹⁾

Note;

- 1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

1.7. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020 for FCC and ANSI C63.10-2020+Cor.1-2023 +C63.10a-2024 + Errata to C63.10a-2024 for ISED), as well as the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02, were used in the measurement of the DUT.

All measurement procedures in the test report comply with both ANSI versions, with no effect on the test results

1.8. Sample Calculation

Where relevant, the following sample calculation is provided:

1.8.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.8.2. Radiation Test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB/m) + Cable loss (dB) - Amplifier gain (dB) + Duty factor (dB)

1.9. Information of software for test

- Using the software of nRF Connect for Desktop v5.2.1 to testing of EUT.

1.10. Declaration by the Manufacturer

- The EUT support BLE version 6.2 and operates all modes.

1.11. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty	
Maximum Peak Conducted Output Power	0.35 dB	
Power Spectral Density	0.64 dB	
99 % Bandwidth	0.01 MHz	
6 dB Bandwidth	0.02 MHz	
Conducted Spurious Emission	0.86 dB	
Radiated Emission, 9 kHz to 30 MHz	H	3.60 dB
	V	3.60 dB
Radiated Emission, below 1 GHz	H	5.50 dB
	V	5.10 dB
Radiated Emission, above 1 GHz	H	3.50 dB
	V	3.40 dB

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.

1.12. Test Report Revision

Revision	Report number	Date of Issue	Description
0	F690501-RF-RTL006837	2026.04.03	Initial
1	F690501-RF-RTL006837-1	2026.04.22	Additional pre-scan data for the 1 GHz ~ 25 GHz range
2	F690501-RF-RTL006837-2	2026.05.07	Additional pre-scan average data for the 1 GHz ~ 25 GHz range
3	F690501-RF-RTL006837-3	2026.05.12	Revision IC certification number

1.13. Worst-Case Configuration and Test Mode (Bluetooth 6.2)

Modulation	Bandwidth	Mode	Frequency (MHz)	RF Peak Output Power (dBm)
GFSK	1M	PHY 1M	2 402	<u>7.04</u>
		125k Coded	2 402	6.99
		500k Coded	2 402	6.98
	2M	PHY 2M	2 402	<u>6.94</u>

Remark;

The Bluetooth version of the EUT is 6.2.

All modes were investigated.

For PHY1M and PHY2M are tested as worst condition

Radiated emission below 1 GHz were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1 GHz was performed with the EUT set to transmit Low/Middle/High Channels as worst-case scenario.

Conducted tests were performed with the EUT set to transmit Low/Middle/High channels with highest output power.

All tests were performed with the EUT configured to transmit at its maximum rated output power setting.

1.14. Description of Variant model(s)

Model name		Description
Basic model	UTO-NBL-54L	- Representative production model
Variant model	UTO-NBL-54LA	Same as basic model except for the following differences - Antenna Gain - Antenna appearance (Antenna type / shape)

Remark;

Conducted measurements were performed on the basic model, while radiated measurements were performed on all models.

1.15. Duty Cycle of EUT

Regarding to KDB 558074 D01 15.247 Meas Guidance v05r02, 6, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below;

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.


Mode	Tx on time (ms)	Tx on + off time (ms)	Duty Cycle (%)	Correction factor (dB)
PHY 1M	2.130	2.490	85.54	0.68
PHY 2M	1.080	1.890	57.14	2.43

Remark;


- Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
- Correction Factor (dB) = 10 log (1 / Duty Cycle)

- Test plot(s)

PHY 1M



PHY 2M




2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions


2.1. Test Setup

2.1.1. Transmitter Radiated Spurious Emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.1.2. Conducted Spurious Emissions



2.2. Limit

2.2.1. FCC

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (Meters)
0.009-0.490	2 400/F(kHz)	300
0.490-1.705	24 000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.2.2. IC

According to RSS-247 Issue 4, 6.6, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement– provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

According to RSS-Gen Issue 5, 8.9, except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General Field Strength Limits at frequencies above 30 MHz

Frequency (MHz)	Field Strength ($\mu V/m$ at 3 m)
30-88	100
88-216	150
216-960	200
Above 960	500

Table 6 – General Field Strength Limits at frequencies below 30 MHz

Frequency	Magnetic Field Strength (H-Field) ($\mu A/m$)	Measurement Distance (meters)
9-490 kHz ¹	6.37/F (F in kHz)	300
490-1 705 kHz	63.7/F (F in kHz)	30
1.705-30 MHz	0.08	30

Note¹: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2020 (for FCC) and ANSI C63.10-2020 + Cor.1-2023 + Errata to C63.10a-2024 (for ISSED).

2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.
6. For measurements Above 1 GHz resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

1. Unwanted Emissions into Non-Restricted Frequency Bands

- The Reference Level Measurement refer to section 11.11.2

Set analyzer center frequency to DTS channel center frequency, SPAN ≥ 1.5 times the DTS bandwidth, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

- Unwanted Emissions Level Measurement refer to section 11.11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

2. Unwanted Emissions into Restricted Frequency Bands

- Peak Power measurement procedure refer to section 11.12.2.4

Set RBW = as specified in Table 9, VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

Table 9 – RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

If the peak – detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

- Average Power measurements procedure refer to section 11.12.2.5.2

The EUT shall be configured to operate at the maximum achievable duty cycle.

Measure the duty cycle D of the transmitter output signal as described in section 11.6.

Set RBW = 1 MHz, VBW $\geq 3 \times$ RBW, Detector = RMS, if span / (# of points in sweep) $\leq$ (RBW/2).

Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.
- 2) If a specific emission is demonstrated to be continuous (D $\geq$ 98%) rather than turning ON and OFF with the transmit cycle, then no duty cycled correction is required for that emission.

3. Definition of DUT Axis.

The radiation test of the EUT was investigated in three orthogonal orientations X, Y, and Z described in the test setup photo. All radiated testing of EUT was performed with worst case axis.

2.3.3. Test Procedures for Conducted Spurious Emissions

Per the guidance of ANSI C63.10-2020 (for FCC) and ANSI C63.10-2020 + Cor.1-2023 + Errata to C63.10a-2024 (for ISSED), section 11.11.1 & 11.11.2 & 11.11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 dB below the fundamental emission level measured in a 100 kHz bandwidth.

1. Conducted Emissions at Band Edge

- The Measurement refer to section 11.11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace mode = Max hold, The trace was allowed to stabilize.

2. Conducted Spurious Emissions

- The Measurement refer to section 11.11.3

Start frequency was set to 9 kHz and stop frequency was set to 25 GHz (separated into several plots per channel), RBW = 1 MHz, VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

3. TDF function

- For plots showing conducted spurious emissions from 9 kHz to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.
 So, the reading values shown in plots were final result.

2.4. Test Results

Ambient temperature : $(23 \pm 1) ^\circ\text{C}$
Relative humidity : 47 %

2.4.1. Radiated Spurious Emissions below 1 000 MHz

The frequency spectrum from 9 kHz to 1 000 MHz was investigated.

Basic Model (UTO-NBL-54L)

Radiated Emissions			Ant.	Correction (dB/m)	Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.		Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
143.92	35.82	Quasi Peak	H	-12.19	23.63	43.50	19.87
471.94	31.28	Quasi Peak	H	-2.93	28.35	46.00	17.65
Above 500.00	Not detected	-	-	-	-	-	-

Variant Model (UTO-NBL-54LA)



Radiated Emissions			Ant.	Correction (dB/m)	Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.		Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
32.10	39.71	Quasi Peak	V	-11.06	28.65	40.00	11.35
849.11	23.68	Quasi Peak	H	3.55	27.23	46.00	18.77
Above 900.00	Not detected	-	-	-	-	-	-

Remark;



1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Test from 30 MHz to 1 000 MHz was performed using the software of ELEKTRA(V5.02) from Rohde & Schwarz GmbH & Co. KG.
3. Reported spurious emissions are in **PHY1M / Low channel** as worst case among other modes and channels.
4. Radiated spurious emission measurement as below.
(Actual = Reading + Correction)
(Correction = Antenna Factor + AMP Factor + Cable Loss)
5. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plots

Basic Model (UTO-NBL-54L)



Variant Model (UTO-NBL-54LA)



30 MHz ~ 1 GHz

2.4.2. Radiated Spurious Emissions above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak and average values.

Basic Model (UTO-NBL-54L)

Test Mode: PHY 1M

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 310.00	16.92	Peak	H	28.06	7.33	-	52.31	74.00	21.69
*2 310.00	7.43	Average	H	28.06	7.33	0.68	43.50	54.00	10.50
*2 389.56	20.64	Peak	H	28.22	7.58	-	56.44	74.00	17.56
*2 386.03	10.91	Average	H	28.23	7.56	0.68	47.38	54.00	6.62
*2 390.00	19.13	Peak	H	28.22	7.59	-	54.94	74.00	19.06
*2 390.00	9.62	Average	H	28.22	7.59	0.68	46.11	54.00	7.89

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 804.44	49.81	Peak	V	32.72	-28.91	-	53.62	74.00	20.38
7 206.69	44.39	Peak	V	35.91	-24.98	-	55.32	74.00	18.68
*12 011.33	39.56	Peak	V	38.60	-21.40	-	56.76	74.00	17.24
*12 008.82	33.55	Average	V	38.60	-21.47	0.68	51.36	54.00	2.64
Above 12 100.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 880.44	44.09	Peak	V	33.02	-28.26	-	48.85	74.00	25.15
*7 319.13	44.37	Peak	V	36.24	-25.57	-	55.04	74.00	18.96
*7 302.57	37.08	Average	V	36.21	-25.14	0.68	48.83	54.00	5.17
9 761.11	40.71	Peak	V	37.52	-24.12	-	54.11	74.00	19.89
*12 201.23	40.15	Peak	V	38.60	-20.84	-	57.91	74.00	16.09
*12 198.95	34.45	Average	V	38.60	-20.85	0.68	52.88	54.00	1.12
14 638.44	38.00	Peak	H	41.32	-18.85	-	60.47	74.00	13.53
Above 14 700.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 483.50	29.60	Peak	H	28.40	7.58	-	65.58	74.00	8.42
*2 483.50	13.28	Average	H	28.40	7.58	0.68	49.94	54.00	4.06
*2 483.63	30.56	Peak	H	28.40	7.58	-	66.54	74.00	7.46
*2 487.99	14.43	Average	H	28.43	7.63	0.68	51.17	54.00	2.83
*2 500.00	18.03	Peak	H	28.50	7.74	-	54.27	74.00	19.73
*2 500.00	6.54	Average	H	28.50	7.74	0.68	43.46	54.00	10.54

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 959.55	43.19	Peak	V	33.22	-28.03	-	48.38	74.00	25.62
*7 439.42	44.24	Peak	H	36.22	-26.42	-	54.04	74.00	19.96
*7 440.49	38.24	Average	H	36.22	-26.42	0.68	48.72	54.00	5.28
*12 398.77	39.66	Peak	H	38.60	-21.09	-	57.17	74.00	16.83
*12 401.16	33.24	Average	H	38.60	-21.10	0.68	51.42	54.00	2.58
14 881.43	38.46	Peak	H	40.74	-17.67	-	61.53	74.00	12.47
Above 14 900.00	Not detected	-	-	-	-	-	-	-	-

Test Mode: PHY 2M

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*2 310.00	17.72	Peak	H	28.06	7.33	-	53.11	74.00	20.89
*2 310.00	7.50	Average	H	28.06	7.33	2.43	45.32	54.00	8.68
*2 388.60	21.15	Peak	H	28.22	7.58	-	56.95	74.00	17.05
*2 389.67	9.71	Average	H	28.22	7.58	2.43	47.94	54.00	6.06
*2 390.00	21.49	Peak	H	28.22	7.59	-	57.30	74.00	16.70
*2 390.00	9.82	Average	H	28.22	7.59	2.43	48.06	54.00	5.94

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 803.06	49.58	Peak	V	32.71	-28.91	-	53.38	74.00	20.62
7 207.66	43.86	Peak	H	35.92	-24.98	-	54.80	74.00	19.20
*12 007.46	41.86	Peak	V	38.60	-21.51	-	58.95	74.00	15.05
*12 007.59	33.27	Average	V	38.60	-21.51	2.43	52.79	54.00	1.21
Above 12 100.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 879.91	43.23	Peak	H	33.02	-28.26	-	47.99	74.00	26.01
*7 321.42	44.16	Peak	H	36.24	-25.63	-	54.77	74.00	19.23
*7 321.33	36.14	Average	H	36.24	-25.63	2.43	49.18	54.00	4.82
*12 197.67	41.07	Peak	V	38.60	-20.85	-	58.82	74.00	15.18
*12 202.42	32.65	Average	V	38.60	-20.82	2.43	52.86	54.00	1.14
Above 12 300.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 483.50	24.88	Peak	H	28.40	7.58	-	60.86	74.00	13.14
*2 483.50	9.90	Average	H	28.40	7.58	2.43	48.31	54.00	5.69
*2 483.57	24.52	Peak	H	28.40	7.58	-	60.50	74.00	13.50
*2 483.57	9.31	Average	H	28.40	7.58	2.43	47.72	54.00	6.28
*2 500.00	15.56	Peak	H	28.50	7.74	-	51.80	74.00	22.20
*2 500.00	5.87	Average	H	28.50	7.74	2.43	44.54	54.00	9.46

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 959.88	43.61	Peak	H	33.22	-28.03	-	48.80	74.00	25.20
*7 441.67	45.24	Peak	V	36.22	-26.43	-	55.03	74.00	18.97
*7 441.37	37.02	Average	V	36.22	-26.42	2.43	49.25	54.00	4.75
*12 402.75	38.85	Peak	H	38.59	-21.10	-	56.34	74.00	17.66
*12 402.33	29.74	Average	H	38.60	-21.10	2.43	49.67	54.00	4.33
Above 12 500.00	Not detected	-	-	-	-	-	-	-	-

Remarks;

1. “*” means the restricted band.
2. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.
7. AF = Antenna Factor, CL = Cable Loss, DF = Duty Correction Factor.

Variant Model (UTO-NBL-54LA)

Test Mode: PHY 1M

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*2 310.00	13.61	Peak	V	28.06	7.33	-	49.00	74.00	25.00
*2 310.00	3.53	Average	V	28.06	7.33	0.68	39.60	54.00	14.40
*2 374.36	15.58	Peak	V	28.25	7.47	-	51.30	74.00	22.70
*2 386.11	4.86	Average	V	28.23	7.56	0.68	41.33	54.00	12.67
*2 390.00	14.59	Peak	V	28.22	7.59	-	50.40	74.00	23.60
*2 390.00	3.87	Average	V	28.22	7.59	0.68	40.36	54.00	13.64

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 803.75	46.34	Peak	H	32.72	-28.91	-	50.15	74.00	23.85
*12 011.38	41.44	Peak	H	38.60	-21.40	-	58.64	74.00	15.36
*12 008.93	35.13	Average	H	38.60	-21.47	0.68	52.94	54.00	1.06
Above 12 100.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 880.53	40.79	Peak	H	33.02	-28.26	-	45.55	74.00	28.45
*7 320.95	41.55	Peak	H	36.24	-25.62	-	52.17	74.00	21.83
*12 198.58	41.30	Peak	H	38.60	-20.85	-	59.05	74.00	14.95
*12 198.92	34.44	Average	H	38.60	-20.85	0.68	52.87	54.00	1.13
Above 12 200.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*2 483.50	19.38	Peak	V	28.40	7.58	-	55.36	74.00	18.64
*2 483.50	4.75	Average	V	28.40	7.58	0.68	41.41	54.00	12.59
*2 483.86	21.07	Peak	V	28.40	7.59	-	57.06	74.00	16.94
*2 488.06	5.51	Average	V	28.43	7.63	0.68	42.25	54.00	11.75
*2 500.00	13.71	Peak	V	28.50	7.74	-	49.95	74.00	24.05
*2 500.00	3.99	Average	V	28.50	7.74	0.68	40.91	54.00	13.09

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 960.23	39.03	Peak	H	33.22	-28.03	-	44.22	74.00	29.78
*7 440.81	42.13	Peak	H	36.22	-26.42	-	51.93	74.00	22.07
*12 401.47	41.08	Peak	H	38.60	-21.10	-	58.58	74.00	15.42
*12 398.96	34.67	Average	H	38.60	-21.09	0.68	52.86	54.00	1.14
Above 12 400.00	Not detected	-	-	-	-	-	-	-	-

Test Mode: PHY 2M

Low Channel (2 402 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*2 310.00	13.83	Peak	V	28.06	7.33	-	49.22	74.00	24.78
*2 310.00	3.79	Average	V	28.06	7.33	2.43	41.61	54.00	12.39
*2 385.54	15.30	Peak	V	28.23	7.55	-	51.08	74.00	22.92
*2 385.66	4.19	Average	V	28.23	7.55	2.43	42.40	54.00	11.60
*2 390.00	14.41	Peak	V	28.22	7.59	-	50.22	74.00	23.78
*2 390.00	4.05	Average	V	28.22	7.59	2.43	42.29	54.00	11.71

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 805.03	45.93	Peak	H	32.72	-28.91	-	49.74	74.00	24.26
*12 007.49	42.04	Peak	H	38.60	-21.51	-	59.13	74.00	14.87
*12 007.66	33.40	Average	H	38.60	-21.51	2.43	52.92	54.00	1.08
Above 12 100.00	Not detected	-	-	-	-	-	-	-	-

Middle Channel (2 440 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dB μ V)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
*4 881.15	41.07	Peak	H	33.02	-28.26	-	45.83	74.00	28.17
*7 321.46	41.66	Peak	H	36.24	-25.63	-	52.27	74.00	21.73
*12 197.60	41.08	Peak	H	38.60	-20.85	-	58.83	74.00	15.17
*12 197.77	32.78	Average	H	38.60	-20.85	2.43	52.96	54.00	1.04
Above 12 200.00	Not detected	-	-	-	-	-	-	-	-

High Channel (2 480 MHz)

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*2 483.50	16.59	Peak	H	28.40	7.58	-	52.57	74.00	21.43
*2 483.50	5.26	Average	H	28.40	7.58	2.43	43.67	54.00	10.33
*2 483.68	19.37	Peak	H	28.40	7.58	-	55.35	74.00	18.65
*2 487.85	4.88	Average	H	28.43	7.62	2.43	43.36	54.00	10.64
*2 500.00	14.08	Peak	H	28.50	7.74	-	50.32	74.00	23.68
*2 500.00	3.86	Average	H	28.50	7.74	2.43	42.53	54.00	11.47

Radiated Emissions			Ant.	Correction Factors			Total	Limit	
Frequency (MHz)	Reading (dBμV)	Detect Mode	Pol.	AF (dB/m)	AMP+CL (dB)	DF (dB)	Actual (dBμV/m)	Limit (dBμV/m)	Margin (dB)
*4 959.26	38.71	Peak	H	33.22	-28.03	-	43.90	74.00	30.10
*7 438.50	39.32	Peak	H	36.22	-26.41	-	49.13	74.00	24.87
*12 402.65	40.90	Peak	H	38.59	-21.10	-	58.39	74.00	15.61
*12 402.40	32.11	Average	H	38.60	-21.10	2.43	52.04	54.00	1.96
Above 12 500.00	Not detected	-	-	-	-	-	-	-	-

Remarks;


1. "*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.
7. AF = Antenna Factor, CL = Cable Loss, DF = Duty Correction Factor.

- Test plots

Basic Model (UTO-NBL-54L)

Test Mode: PHY 1M


Low channel band edge (Peak)



Low channel band edge (Average)



Low channel 2nd harmonic (Peak)




Low channel 3rd harmonic (Peak)




Low channel 5th harmonic (Peak)



Low channel 5th harmonic (Average)




Middle channel 2nd harmonic (Peak)




Middle channel 3rd harmonic (Peak)




Middle channel 3rd harmonic (Average)



Middle channel 4th harmonic (Peak)




Middle channel 5th harmonic (Peak)



Middle channel 5th harmonic (Average)




Middle channel 6th harmonic (Peak)




High channel band edge (Peak)




High channel band edge (Average)




High channel 2nd harmonic (Peak)




High channel 3rd harmonic (Peak)



High channel 3rd harmonic (Average)



High channel 5th harmonic (Peak)



High channel 5th harmonic (Average)



High channel 6th harmonic (Peak)

