

ANTENNA

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
PCB Antenna

ISSUED TO
ShenZhen HuiJiaZhi Technology Co., Ltd

Room 1403, Building 3, COFCO Business Park, Liuxian 2nd Road,
Bao'an District, ShenZhen, China



Tested by: Shang Dandan

Shang Dandan
(Engineer)

Date: May. 31. 2019

Approved by: Wei Yanquan

Wei Yanquan
(Chief Engineer)

Date: May. 31. 2019

Report No: BL-EC1950331-901

EUT Name: PCB Antenna

Model Name: ANT-2.4G-1

Brand Name: HJZ

Test Standard: IEEE149-1979

Maximum: Gain: 2.64 (dBi)

Efficiency: 79%

Test Date: May 23, 2019

Date of Issue: May 31, 2019

NOTE: This test report of test results only related to the testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>May 31, 2019</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	Administrative Data (GENERAL INFORMATION).....	3
1.1	Identification of the Testing Laboratory.....	3
1.2	Identification of the Responsible Testing Location	3
1.3	Laboratory Condition	3
1.4	Announce.....	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information	4
2.3	Factory Information	4
2.4	General Description for Equipment under Test (EUT)	4
2.5	Ancillary Equipment.....	4
2.6	Technical Information	4
3	SUMMARY OF TEST RESULTS	5
3.1	Test Standards.....	5
3.2	Test Verdict.....	5
3.3	Test Uncertainty	5
4	GENERAL TEST CONFIGURATIONS	6
4.1	Test Condition	6
4.2	Test Equipment List.....	6
4.3	Test Setup.....	6
ANNEX A	TEST RESULTS.....	7
A.1	Gain and Efficiency	7
A.2	VSWR and Input Impedance	8
ANNEX B	RADIATION PATTERN	9
ANNEX C	TEST SETUP PHOTO.....	12
ANNEX D	EUT PHOTO	14

1 Administrative Data (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791. The laboratory is a testing organization accredited by China Metrology Accreditation (CMA). The accreditation certificate number is 2017192290Z.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	19°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	ShenZhen HuiJiaZhi Technology Co., Ltd
Address	Room 1403, Building 3, COFCO Business Park, Liuxian 2nd Road, Bao'an District, ShenZhen, China
Telephone Number	18825827134
Fax Number	(+86) 0755-86307651
E-mail Address	hj20@sz-huijia.com

2.2 Manufacturer Information

Manufacturer	N/A
Address	N/A

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	PCB Antenna
Model Name Under Test	ANT-2.4G-1
Antenna Type	PCB Antenna
Dimensions	25mm * 7mm
Polarization	Vertical

2.5 Ancillary Equipment

Note: Not applicable.

2.6 Technical Information

Frequency Range	2400MHz ~ 2500MHz
Test Frequencies	2400MHz, 2402MHz, 2404MHz, 2406MHz, 2408MHz, 2410MHz, 2412MHz, 2414MHz, 2416MHz, 2418MHz, 2420MHz, 2422MHz, 2424MHz, 2426MHz, 2428MHz, 2430MHz, 2432MHz, 2434MHz, 2436MHz, 2438MHz, 2440MHz, 2441MHz, 2442MHz, 2444MHz, 2446MHz, 2448MHz, 2450MHz, 2452MHz, 2454MHz, 2456MHz, 2458MHz, 2460MHz, 2462MHz, 2464MHz, 2466MHz, 2468MHz, 2470MHz, 2472MHz, 2474MHz, 2476MHz, 2478MHz, 2480MHz, 2482MHz, 2484MHz, 2486MHz, 2488MHz, 2490MHz, 2492MHz, 2494MHz, 2496MHz, 2498MHz, 2500MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	IEEE149-1979	IEEE Standard Test Procedures for Antennas

3.2 Test Verdict

Report Section	Description	Remark
ANNEX A.1	Gain and Efficiency	--
ANNEX A.2	VSWR	--
ANNEX B	Radiation Pattern	--

3.3 Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Item	Uncertainty
VSWR(S11)	± 0.2
Gain	$\pm 0.5\text{dB}$

ANNEX A TEST RESULTS


A.1 Gain and Efficiency

Frequency	Gain (dBi)	Efficiency (%)
2400MHz	1.97	77
2402MHz	2.16	77
2404MHz	2.32	77
2406MHz	2.47	76
2408MHz	2.58	77
2410MHz	2.64	77
2412MHz	2.62	77
2414MHz	2.59	77
2416MHz	2.53	77
2418MHz	2.45	78
2420MHz	2.39	78
2422MHz	2.39	78
2424MHz	2.39	78
2426MHz	2.59	79
2428MHz	2.56	79
2430MHz	2.49	79
2432MHz	2.45	79
2434MHz	2.42	79
2436MHz	2.42	79
2438MHz	2.34	78
2440MHz	2.31	78
2442MHz	2.31	78
2444MHz	2.28	78
2446MHz	2.34	78
2448MHz	2.38	78
2450MHz	2.42	78
2452MHz	2.46	79
2454MHz	2.49	79
2456MHz	2.45	79
2458MHz	2.50	79
2460MHz	2.52	79
2462MHz	2.50	79
2464MHz	2.47	78
2466MHz	2.39	78
2468MHz	2.39	78
2470MHz	2.35	77
2472MHz	2.32	77
2474MHz	2.33	77
2476MHz	2.32	77

2478MHz	2.28	76
2480MHz	2.28	76
2482MHz	2.27	76
2484MHz	2.23	75
2486MHz	2.20	75
2488MHz	2.18	74
2490MHz	2.16	74
2492MHz	2.15	74
2494MHz	2.12	74
2496MHz	1.98	73
2498MHz	1.96	73
2500MHz	1.95	73

A.2 VSWR


Frequency	VSWR
2402MHz	1.20
2441MHz	1.19
2480MHz	1.74




ANNEX B RADIATION PATTERN

B.1 3D Pattern


B1.1 3D Pattern for 2400MHz



B1.2 3D Pattern for 2450MHz




B1.3 3D Pattern for 2500MHz






B.2 1D Radiation Pattern

B2.1 PHI=0




ANNEX C TEST SETUP PHOTO





ANNEX D EUT PHOTO



--END OF REPORT--