



RF Exposure Evaluation

For

Conquer Industry Co., Ltd

Karaoke Microphone & Wireless Speaker

Test Model: 121399

Additional Model No.: KRMICBTH, CQL2382-B

Prepared for : Conquer Industry Co., Ltd
Address : ROOM 1502-109, EASEY COMMERCIAL BUILDING 253-261
HENNESSY ROAD, WANCHAI, Hong Kong

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : July 21, 2026
Number of tested samples : 2
Sample No. : A260720052-1, A260720052-2
Serial number : Prototype
Date of Test : July 21, 2026 ~ July 28, 2026
Date of Report : July 29, 2026

**RF Exposure Evaluation****Report Reference No.** : **LCSA07216089EC****Date of Issue** : July 29, 2026**Testing Laboratory Name** : **Shenzhen LCS Compliance Testing Laboratory Ltd.****Address** : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China**Testing Location/ Procedure** : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name** : **Conquer Industry Co., Ltd****Address** : ROOM 1502-109, EASEY COMMERCIAL BUILDING 253-261 HENNESSY ROAD, WANCHAI, Hong Kong**Test Specification****Standard** : FCC KDB publication 447498 D01 General RF Exposure Guidance v06
FCC CFR 47 part1 1.1310
FCC CFR 47 part2 2.1093**TRF Originator** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF** : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description : **Karaoke Microphone & Wireless Speaker****Trade Mark** : KUROMI**Test Model** : 121399**Ratings** : Please Refer to Page 6**Result** : **PASS****Compiled by:**

Martin Lee/ Administrator

Supervised by:

Kevin Huang/ RF Manager

Approved by:

Gavin Liang/ Manager



RF Exposure Evaluation

Test Report No. : LCSA07216089EC	<u>July 29, 2026</u> Date of issue
---	---------------------------------------

Test Model.....	: 121399
EUT.....	: Karaoke Microphone & Wireless Speaker
Applicant.....	: Conquer Industry Co., Ltd
Address.....	: ROOM 1502-109, EASEY COMMERCIAL BUILDING 253-261 HENNESSY ROAD, WANCHAI, Hong Kong
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: DONGGUAN KANGGE TECHNOLOGY CO., LTD
Address.....	: Room 302, Building 2, No.5 Fengping Road, Fenggang Town, Dongguan, Guangdong Sheng, 523690, China
Telephone.....	: /
Fax.....	: /
Factory.....	: DONGGUAN KANGGE TECHNOLOGY CO., LTD
Address.....	: Room 302, Building 2, No.5 Fengping Road, Fenggang Town, Dongguan, Guangdong Sheng, 523690, China
Telephone.....	: /
Fax.....	: /

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	July 29, 2026	Initial Issue	---



TABLE OF CONTENTS

Description	Page
1. Product Information	6
2. Evaluation method and Limit	6
3. Refer Evaluation Method	7
4. Conducted Power Results	8
5. Manufacturing Tolerance	8
6. Evaluation Results	9
7. Conclusion	9
8. Description of Test Facility	9
9. Measurement Uncertainty	9



1. Product Information

EUT	:	Karaoke Microphone & Wireless Speaker
Test Model	:	121399
Additional Model No.	:	KRMICBTH, CQL2382-B
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	:	Input: DC 5V, 1A DC 3.7V by Rechargeable Li-ion Battery, 500mAh
Hardware Version	:	/
Software Version	:	/
Bluetooth		
Frequency Range	:	2402MHz~2480MHz
Channel Number	:	79 channels for Bluetooth V6.0 (DSS) 40 channels for Bluetooth V6.0 (DTS)
Channel Spacing	:	1MHz for Bluetooth V6.0 (DSS) 2MHz for Bluetooth V6.0 (DTS)
Modulation Type	:	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V6.0 (DSS) GFSK for Bluetooth V6.0 (DTS)
Bluetooth Version	:	V6.0
Antenna Description	:	PCB Antenna, 0dBi(Max.)
Exposure category	:	General population/uncontrolled environment
EUT Type	:	Production Unit
Device Type	:	Portable Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF

TRF-4- E-215 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
 - 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below
- The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\sum \text{ of MPE ratios}]$ is ≤ 1.0 .
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}]$ is ≤ 1.0 .

3. Refer Evaluation Method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices



4. Conducted Power Results

BT

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	1.76
	39	2441	2.81
	78	2480	2.08
$\pi/4$ DQPSK	0	2402	3.05
	39	2441	4.05
	78	2480	3.27
8DPSK	0	2402	2.82
	39	2441	3.78
	78	2480	3.56

BT LE

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	-0.58
	19	2440	1.84
	39	2480	0.79

5. Manufacturing Tolerance

BT

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	2.0	2.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	3.0	4.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	2.0	3.0	3.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

<BLE 1M>

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

TRF-4- E-215 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6. Evaluation Results

6.1 Standalone Evaluation

Band/Mode		f (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
				dBm	mW		
BT	GFSK	2.480	5	3.0	1.9953	0.6284 < 3.0	Yes
	$\pi/4$ DQPSK	2.441	5	5.0	3.1623	0.9881 < 3.0	Yes
	8DPSK	2.480	5	4.0	2.5119	0.7911 < 3.0	Yes
BLE 1M	GFSK	2.440	5	2.0	1.5849	0.4951 < 3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

6.2 Simultaneous Transmission for SAR Exclusion

The sample support one BT modular. No need consider simultaneous transmission.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

9. Measurement Uncertainty

BT/BLE:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	± 0.57 dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....THE END OF REPORT.....

TRF-4- E-215 A/0

Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101/201, Building A, and Room 101/301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity