

FCC Radio Test Report

FCC ID : 2AQWT24000001300
Equipment : INBAY® - Gen5
Brand Name : INBAY®
Model Name : 240000-01-300, 240000-01-300-1, 240000-01-300-2,
240000-01-302
Applicant : acv GmbH
Strassburger Allee 10-12, 41812 Erkelenz, Germany
Manufacturer : acv GmbH
Strassburger Allee 10-12, 41812 Erkelenz, Germany
Standard : 47 CFR FCC Part 15, Subpart C

The product was received on Mar. 19, 2026, and testing was started from May 13, 2026 and completed on May 14, 2026. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.


Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Applied Standards	7
1.3 Testing Location Information	7
1.4 Measurement Uncertainty	7
2 TEST CONFIGURATION OF EUT.....	8
2.1 Test Channel Mode	8
2.2 The Worst Case Configuration	8
2.3 The Worst Case Measurement Configuration	9
2.4 Support Equipment.....	9
2.5 Test Setup Diagram	10
3 TRANSMITTER TEST RESULT	11
3.1 Transmitter Radiated Emissions	11
3.2 Emission Bandwidth	14
4 TEST EQUIPMENT AND CALIBRATION DATA.....	15
APPENDIX A. TEST RESULT OF TRANSMITTER RADIATED EMISSIONS	
APPENDIX B. TEST RESULT OF EMISSION BANDWIDTH	
APPENDIX C. TEST PHOTOS	
PHOTOGRAPHS OF EUT v01	



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
-	15.207	AC Power-line Conducted Emissions	Not Required	Only employ DC Power
3.1	15.209	Transmitter Radiated Emissions	PASS	-
3.2	15.215(c)	Emission Bandwidth	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Barry Hsiao

Report Producer: Amber Chiu

1 General Description

1.1 Information

1.1.1 General Information

Wireless Power Transfer General Information			
Frequency Range	Modulation	Operating Freq. (kHz)	Field Strength (dBuV/m)
360 kHz	FSK	359.4	50.8
Power Transfer Method	Output power from each primary coil	That may have multiple primary coils	Operating Method
Magnetic induction and only single primary coil	≤ 15W	No	Client directly contact
Note 1: Field strength performed peak level at 3m.			

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	Shenzhen Gaoyue Electronics Technology Co., Ltd.	Filter board-V11+	Wireless charging antenna coils	N/A

1.1.3 EUT Information

Operational Condition	
EUT Power Type	From DC power supply
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
☐	Other:

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
☒	Operated normally mode for worst duty cycle
☐	Operated test mode for worst duty cycle
Test Signal Duty Cycle (x)	
☒	100%

**1.1.5 Table for Multiple Listing**

The model names in the following table are all refer to the identical product.

Model Name	Description
240000-01-300	Fanless
240000-01-302	Fanless, Different Aluminum Enclosure Design
240000-01-300-2	With Fan, With Plastic Bottom Cover
240000-01-300-1	With Fan, Without Plastic Bottom Cover

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

The following reference test guidance is not within the scope of accreditation of TAF:

- ♦ KDB 680106 D01 Wireless Power Transfer v04
- ♦ KDB 414788 D01 v01r01

1.3 Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory				
☒ Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)			
	TEL: 886-3-327-3456		FAX: 886-3-327-0973	
Test site Designation No. TW3785 with FCC.				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH07-HY	Alan Chien	23.4~23.9°C / 52~55%	14/May/2026
Radiated	03CH03-HY	Simon Cheng	22.2~23.4°C / 50~52%	13/May/2026~14/May/2026

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Radiated Emission (9 kHz ~ 30 MHz)	1.76 dB	Confidence levels of 95%
Radiated Emission (30 MHz ~ 1 GHz)	5.38 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Channel Mode

Test Software Version	N/A
------------------------------	-----

Note: The EUT transmits RF signal continuously by itself

Mode	Power Setting
WPC	-
0.36MHz	default


2.2 The Worst Case Configuration

Mode	Field Strength (dBuV/m at 3 m)	Field Strength (dBuV/m at 300 m)	Charger Frequencies (kHz)
WPC	50.8	-29.20	359.4

Note.1: Wireless charger were performed all charging conditions including variable loading and non-charging operation, the worst mode is full charging loading.

Note.2: Wireless charger frequencies are variable frequency range (360 kHz) and depend on charging loading.

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Emissions, Emission Bandwidth		
Test Condition	Radiated measurement		
Operating Mode	CTX		
	1. DC Power supply mode		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT	V 240000-01-300 240000-01-302		V 240000-01-300-1 240000-01-300-2


2.4 Support Equipment

Support Equipment – Conducted					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	DC Power Supply	GW	GPS-3030DD	-	-
2	Power Cable	SANTEK OVERSEAS CORP	N/A	-	Provided by Customer
3	load	APPLE	A3258	-	Provided by Customer

Support Equipment – Radiated					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	AC Power Cable	PowerSync	PW-GPC180-3	-	-
2	DC Power Cable	MiSUMi	WTN1229-BLACK	-	-
3	DC Power Cable	MiSUMi	WTN1229-RED	-	-
4	DC Power Supply	GW	GPS-3030DD	-	-
5	Power Cable	SANTEK OVERSEAS CORP	N/A	-	Provided by Customer
6	load	APPLE	A3258	-	Provided by Customer

2.5 Test Setup Diagram

Test Setup Diagram - Radiated Test



Item	Connection	Shielded	Length(m)	Remark
1	AC Power cable	No	1.8	-
2	DC Power cable(+)	No	1.0	-
3	DC Power cable(-)	No	1.0	-
4	Power cable	No	2.0	-

3 Transmitter Test Result

3.1 Transmitter Radiated Emissions

3.1.1 Transmitter Radiated Emissions Limit

Transmitter Radiated Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: the frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 1GHz measurements employing a CISPR quasi-peak detector.

3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.



3.1.3 Test Procedures


Test Method	
☒	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1 GHz and test distance is 3m.
☒	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz the frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 30MHz measurements employing a CISPR quasi-peak detector. Test distance is 3 m.
☒	At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be following below methods.
☐	The results shall be extrapolated to the specified distance by making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor.
☒	The results shall be by using the square of an inverse linear distance extrapolation factor (40 dB/decade).
☒	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.
☒	The any unwanted emissions level shall not exceed the fundamental emission level.
☒	All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.
☒	KDB 414788 Open-Field Test Sites and Chamber Correlation Justification.
☒	Based on FCC 15.31(f)(2): measurements may be performed at a distance closer than that specified in regulations; however, an attempt should be made to avoid making measurements in the near field.
☒	Open-field site and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

3.1.4 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Raw(Read Level) + AF(Antenna Factor) + CL(Cable Loss) - PA(Preamplifier Factor)

3.1.5 Test Setup



3.1.6 Transmitter Radiated Emissions

Refer as Appendix A

3.2 Emission Bandwidth

3.2.1 Emission Bandwidth Limit

Emission Bandwidth Limit
N/A


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
☒ Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.
☒ For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

4 Test Equipment and Calibration Data

Instrument for Conducted Test

Instrument	Manufacturer / Brand	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Signal Analyzer	R&S	FSV 40	101515	10Hz~40GHz	05/Jan/2026	04/Jan/2027
SENSE-NFC	Sporton	V5.11.15	N/A	N/A	N/A	N/A

Instrument for Radiated Test

Instrument	Manufacturer / Brand	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz~1GHz 3m	13/Jul/2025	12/Jul/2026
EMI Test Receiver	R&S	ESR	102318	9kHz~3.6GHz	08/Dec/2025	07/Dec/2026
Signal Analyzer	ROHDE&SCHWARZ	FSV3044	101748	10Hz~44GHz	30/Apr/2026	29/Apr/2027
Loop Antenna	TESEQ	HLA 6121	65417	9kHz~30MHz	20/Oct/2025	19/Oct/2026
Bilog Antenna & 6dB Attenuator	SCHAFFNER / EMC	CBL6112B / N-6-05	22237 / AT-N-0603	30MHz~1GHz	11/Oct/2025	10/Oct/2026
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz~30MHz	10/Jun/2025	09/Jun/2026
RF Cable-R03m	Jye Bao	RG142	03CH03-cable-02	30MHz~1GHz	10/Jun/2025	09/Jun/2026
Amplifier	Aglient	8447D	2944A08033	100kHz~1.3GHz	12/Sep/2025	11/Sep/2026
SENSE-NFC	Sporton	V5.11.1	NA	NA	NA	NA



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
	-	-	-	-	-	-	-	-	-
WPC	Pass	PK	16.189M	3.07	29.54	-26.47	30	360	1.00

**Result**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
WPC	-	-	-	-	-	-	-	-	-
0.36MHz_TX	Pass	AV	360.1k	-30.12	16.48	-46.60	300	95	1.00
0.36MHz_TX	Pass	PK	359.4k	-29.20	36.48	-65.68	300	95	1.00
0.36MHz_TX	Pass	PK	62.58k	-44.39	51.68	-96.07	300	360	1.00
0.36MHz_TX	Pass	PK	84.012k	-48.11	49.12	-97.23	300	360	1.00
0.36MHz_TX	Pass	PK	104.88k	-46.39	27.18	-73.57	300	360	1.00
0.36MHz_TX	Pass	PK	276.48k	-39.99	38.76	-78.75	300	0	1.00
0.36MHz_TX	Pass	PK	394.12k	-42.10	35.68	-77.78	300	0	1.00
0.36MHz_TX	Pass	PK	458.72k	-42.34	34.36	-76.70	300	0	1.00
0.36MHz_TX	Pass	PK	5.035M	0.90	29.54	-28.64	30	360	1.00
0.36MHz_TX	Pass	PK	8.163M	-1.69	29.54	-31.23	30	360	1.00
0.36MHz_TX	Pass	PK	16.189M	3.07	29.54	-26.47	30	360	1.00

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)				
AV	360.1k	-30.12	16.48	-46.60	-59.53	300	Horizontal	95	1.00	29.41	20.39	0.08	-				
PK	359.4k	-29.20	36.48	-65.68	-59.53	300	Horizontal	95	1.00	30.33	20.39	0.08	-				

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)				
PK	62.58k	-44.39	51.68	-96.07	-60.99	300	Horizontal	360	1.00	16.60	18.94	0.07	-				
PK	84.012k	-48.11	49.12	-97.23	-60.64	300	Horizontal	360	1.00	12.53	19.28	0.08	-				
PK	104.88k	-46.39	27.18	-73.57	-60.17	300	Horizontal	360	1.00	13.78	19.75	0.08	-				


WPC

0.36MHz_TX



WPC

0.36MHz_TX





Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
	-	-	-	-	-	-	-	-	-
WPC	Pass	PK	39.7M	27.52	40.00	-12.48	3	0	1.00

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
WPC	-	-	-	-	-	-	-	-	-
0.36MHz_TX	Pass	PK	39.7M	27.52	40.00	-12.48	3	0	1.00
0.36MHz_TX	Pass	PK	152.22M	21.35	43.50	-22.15	3	0	1.00
0.36MHz_TX	Pass	PK	253.1M	22.39	46.00	-23.61	3	0	1.00
0.36MHz_TX	Pass	PK	410.24M	26.26	46.00	-19.74	3	0	1.00
0.36MHz_TX	Pass	PK	546.04M	28.91	46.00	-17.09	3	0	1.00
0.36MHz_TX	Pass	PK	666.32M	29.44	46.00	-16.56	3	0	1.00
0.36MHz_TX	Pass	PK	30M	24.63	40.00	-15.37	3	360	1.00
0.36MHz_TX	Pass	PK	115.36M	19.87	43.50	-23.63	3	360	1.00
0.36MHz_TX	Pass	PK	204.6M	21.35	43.50	-22.15	3	360	1.00
0.36MHz_TX	Pass	PK	336.52M	23.33	46.00	-22.67	3	360	1.00
0.36MHz_TX	Pass	PK	478.14M	28.02	46.00	-17.98	3	360	1.00
0.36MHz_TX	Pass	PK	615.88M	29.12	46.00	-16.88	3	360	1.00

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	39.7M	27.52	40.00	-12.48	-6.16	3	Vertical	0	1.00	33.68	19.45	1.24	26.85
PK	152.22M	21.35	43.50	-22.15	-7.88	3	Vertical	0	1.00	29.23	16.60	2.01	26.49
PK	253.1M	22.39	46.00	-23.61	-5.58	3	Vertical	0	1.00	27.97	18.84	2.69	27.11
PK	410.24M	26.26	46.00	-19.74	-3.17	3	Vertical	0	1.00	29.43	22.25	3.40	28.82
PK	546.04M	28.91	46.00	-17.09	0.35	3	Vertical	0	1.00	28.56	25.19	4.01	28.85
PK	666.32M	29.44	46.00	-16.56	2.04	3	Vertical	0	1.00	27.40	25.22	4.51	27.69

WPC

0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	24.63	40.00	-15.37	-1.69	3	Horizontal	360	1.00	26.32	24.52	1.04	27.25
PK	115.36M	19.87	43.50	-23.63	-6.70	3	Horizontal	360	1.00	26.57	17.85	1.77	26.32
PK	204.6M	21.35	43.50	-22.15	-9.04	3	Horizontal	360	1.00	30.39	15.40	2.36	26.80
PK	336.52M	23.33	46.00	-22.67	-4.87	3	Horizontal	360	1.00	28.20	19.95	3.13	27.95
PK	478.14M	28.02	46.00	-17.98	-2.16	3	Horizontal	360	1.00	30.18	23.30	3.69	29.15
PK	615.88M	29.12	46.00	-16.88	0.88	3	Horizontal	360	1.00	28.24	24.82	4.30	28.24



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
	-	-	-	-	-	-	-	-	-
WPC	Pass	PK	30M	28.26	40.00	-11.74	3	360	1.00

**Result**

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
WPC	-	-	-	-	-	-	-	-	-
0.36MHz_TX	Pass	PK	30M	28.26	40.00	-11.74	3	360	1.00
0.36MHz_TX	Pass	PK	154.16M	22.25	43.50	-21.25	3	360	1.00
0.36MHz_TX	Pass	PK	272.5M	22.88	46.00	-23.12	3	360	1.00
0.36MHz_TX	Pass	PK	377.26M	26.15	46.00	-19.85	3	360	1.00
0.36MHz_TX	Pass	PK	476.2M	28.16	46.00	-17.84	3	360	1.00
0.36MHz_TX	Pass	PK	594.54M	29.57	46.00	-16.43	3	360	1.00
0.36MHz_TX	Pass	PK	30M	25.97	40.00	-14.03	3	0	1.00
0.36MHz_TX	Pass	PK	123.12M	20.88	43.50	-22.62	3	0	1.00
0.36MHz_TX	Pass	PK	231.76M	22.20	46.00	-23.80	3	0	1.00
0.36MHz_TX	Pass	PK	394.72M	26.60	46.00	-19.40	3	0	1.00
0.36MHz_TX	Pass	PK	485.9M	28.18	46.00	-17.82	3	0	1.00
0.36MHz_TX	Pass	PK	592.6M	28.32	46.00	-17.68	3	0	1.00

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	28.26	40.00	-11.74	-1.69	3	Vertical	360	1.00	29.95	24.52	1.04	27.25
PK	154.16M	22.25	43.50	-21.25	-8.14	3	Vertical	360	1.00	30.39	16.34	2.03	26.51
PK	272.5M	22.88	46.00	-23.12	-5.62	3	Vertical	360	1.00	28.50	18.84	2.80	27.26
PK	377.26M	26.15	46.00	-19.85	-4.09	3	Vertical	360	1.00	30.24	21.08	3.28	28.45
PK	476.2M	28.16	46.00	-17.84	-2.12	3	Vertical	360	1.00	30.28	23.34	3.69	29.15
PK	594.54M	29.57	46.00	-16.43	0.25	3	Vertical	360	1.00	29.32	24.51	4.22	28.48

WPC

0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	25.97	40.00	-14.03	-1.69	3	Horizontal	0	1.00	27.66	24.52	1.04	27.25
PK	123.12M	20.88	43.50	-22.62	-6.30	3	Horizontal	0	1.00	27.18	18.25	1.78	26.33
PK	231.76M	22.20	46.00	-23.80	-7.82	3	Horizontal	0	1.00	30.02	16.60	2.55	26.97
PK	394.72M	26.60	46.00	-19.40	-3.78	3	Horizontal	0	1.00	30.38	21.56	3.33	28.67
PK	485.9M	28.18	46.00	-17.82	-2.22	3	Horizontal	0	1.00	30.40	23.19	3.73	29.14
PK	592.6M	28.32	46.00	-17.68	0.22	3	Horizontal	0	1.00	28.10	24.51	4.21	28.50



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
	-	-	-	-	-	-	-	-	-
WPC	Pass	PK	30M	28.31	40.00	-11.69	3	360	1.00

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
WPC	-	-	-	-	-	-	-	-	-
0.36MHz_TX	Pass	PK	30M	28.31	40.00	-11.69	3	360	1.00
0.36MHz_TX	Pass	PK	152.22M	21.35	43.50	-22.15	3	360	1.00
0.36MHz_TX	Pass	PK	282.2M	23.73	46.00	-22.27	3	360	1.00
0.36MHz_TX	Pass	PK	369.5M	25.25	46.00	-20.75	3	360	1.00
0.36MHz_TX	Pass	PK	551.86M	29.23	46.00	-16.77	3	360	1.00
0.36MHz_TX	Pass	PK	643.04M	30.04	46.00	-15.96	3	360	1.00
0.36MHz_TX	Pass	PK	30M	26.12	40.00	-13.88	3	0	1.00
0.36MHz_TX	Pass	PK	119.24M	21.98	43.50	-21.52	3	0	1.00
0.36MHz_TX	Pass	PK	220.12M	21.71	46.00	-24.29	3	0	1.00
0.36MHz_TX	Pass	PK	369.5M	25.19	46.00	-20.81	3	0	1.00
0.36MHz_TX	Pass	PK	482.02M	27.34	46.00	-18.66	3	0	1.00
0.36MHz_TX	Pass	PK	555.74M	28.56	46.00	-17.44	3	0	1.00

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	28.31	40.00	-11.69	-1.69	3	Vertical	360	1.00	30.00	24.52	1.04	27.25
PK	152.22M	21.35	43.50	-22.15	-7.88	3	Vertical	360	1.00	29.23	16.60	2.01	26.49
PK	282.2M	23.73	46.00	-22.27	-5.48	3	Vertical	360	1.00	29.21	19.00	2.86	27.34
PK	369.5M	25.25	46.00	-20.75	-3.99	3	Vertical	360	1.00	29.24	21.12	3.25	28.36
PK	551.86M	29.23	46.00	-16.77	0.50	3	Vertical	360	1.00	28.73	25.28	4.04	28.82
PK	643.04M	30.04	46.00	-15.96	1.60	3	Vertical	360	1.00	28.44	25.11	4.40	27.91

WPC

0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)
PK	30M	26.12	40.00	-13.88	-1.69	3	Horizontal	0	1.00	27.81	24.52	1.04	27.25
PK	119.24M	21.98	43.50	-21.52	-6.54	3	Horizontal	0	1.00	28.52	18.02	1.76	26.32
PK	220.12M	21.71	46.00	-24.29	-8.81	3	Horizontal	0	1.00	30.52	15.61	2.47	26.89
PK	369.5M	25.19	46.00	-20.81	-3.99	3	Horizontal	0	1.00	29.18	21.12	3.25	28.36
PK	482.02M	27.34	46.00	-18.66	-2.21	3	Horizontal	0	1.00	29.55	23.22	3.71	29.14
PK	555.74M	28.56	46.00	-17.44	0.42	3	Horizontal	0	1.00	28.14	25.16	4.05	28.79



Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
	-	-	-	-	-	-	-	-	-
WPC	Pass	PK	30M	28.62	40.00	-11.38	3	360	1.00

Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Azimuth (°)	Height (m)
WPC	-	-	-	-	-	-	-	-	-
0.36MHz_TX	Pass	PK	30M	28.62	40.00	-11.38	3	360	1.00
0.36MHz_TX	Pass	PK	154.16M	22.02	43.50	-21.48	3	360	1.00
0.36MHz_TX	Pass	PK	282.2M	23.33	46.00	-22.67	3	360	1.00
0.36MHz_TX	Pass	PK	385.02M	26.08	46.00	-19.92	3	360	1.00
0.36MHz_TX	Pass	PK	458.74M	27.55	46.00	-18.45	3	360	1.00
0.36MHz_TX	Pass	PK	546.04M	29.61	46.00	-16.39	3	360	1.00
0.36MHz_TX	Pass	PK	31.94M	25.32	40.00	-14.68	3	0	1.00
0.36MHz_TX	Pass	PK	117.3M	22.11	43.50	-21.39	3	0	1.00
0.36MHz_TX	Pass	PK	198.78M	22.10	43.50	-21.40	3	0	1.00
0.36MHz_TX	Pass	PK	375.32M	25.46	46.00	-20.54	3	0	1.00
0.36MHz_TX	Pass	PK	472.32M	28.18	46.00	-17.82	3	0	1.00
0.36MHz_TX	Pass	PK	540.22M	29.77	46.00	-16.23	3	0	1.00

WPC


0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)				
PK	30M	28.62	40.00	-11.38	-1.69	3	Vertical	360	1.00	30.31	24.52	1.04	27.25				
PK	154.16M	22.02	43.50	-21.48	-8.14	3	Vertical	360	1.00	30.16	16.34	2.03	26.51				
PK	282.2M	23.33	46.00	-22.67	-5.48	3	Vertical	360	1.00	28.81	19.00	2.86	27.34				
PK	385.02M	26.08	46.00	-19.92	-3.99	3	Vertical	360	1.00	30.07	21.26	3.30	28.55				
PK	458.74M	27.55	46.00	-18.45	-2.68	3	Vertical	360	1.00	30.23	22.88	3.61	29.17				
PK	546.04M	29.61	46.00	-16.39	0.35	3	Vertical	360	1.00	29.26	25.19	4.01	28.85				

WPC

0.36MHz_TX



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)				
PK	31.94M	25.32	40.00	-14.68	-2.56	3	Horizontal	0	1.00	27.88	23.56	1.05	27.17				
PK	117.3M	22.11	43.50	-21.39	-6.66	3	Horizontal	0	1.00	28.77	17.89	1.77	26.32				
PK	198.78M	22.10	43.50	-21.40	-9.21	3	Horizontal	0	1.00	31.31	15.23	2.32	26.76				
PK	375.32M	25.46	46.00	-20.54	-4.07	3	Horizontal	0	1.00	29.53	21.09	3.27	28.43				
PK	472.32M	28.18	46.00	-17.82	-2.26	3	Horizontal	0	1.00	30.44	23.22	3.67	29.15				
PK	540.22M	29.77	46.00	-16.23	0.20	3	Horizontal	0	1.00	29.57	25.11	3.98	28.89				

Summary

Mode	20dB (Hz)	Fl-20dB (Hz)	Fh-20dB (Hz)	OBW (Hz)	Limit (Range)
WPC	-	-	-	-	-
0.36MHz_TnomVnom	2.59k	358.71250k	361.30250k	2.192k	-

Max-N dB = Maximum 20dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 20dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	20dB (Hz)	FI-20dB (Hz)	Fh-20dB (Hz)	OBW (Hz)	FI-OBW (Hz)	Fh-OBW (Hz)	Limit (Range)
WPC	-	-	-	-	-	-	-	-
0.36MHz_TnomVnom	Pass	2.59k	358.71250k	361.30250k	2.192k	358.91123k	361.10360k	-


Port X-N dB = Port X 20dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

WPC

0.36MHz_TnomVnom

EBW

14/05/2026



20dB(Hz)	FI-20dB(Hz)	Fh-20dB(Hz)	OBW(Hz)	FI-OBW(Hz)	Fh-OBW(Hz)	Limit(Range)
2.59k	358.71250k	361.30250k	2.192k	358.91123k	361.10360k	-