

Power reduction mechanism verification

According to the May 2017 TCBC Workshop, Demonstration of proper functioning of the detection and triggering mechanisms is required to support the corresponding RF exposure conditions. The verification is through a base station simulator is used to establish a conducted RF connection and monitor output power under different operating conditions related to the power reduction mechanisms. Detail of power reduction mechanisms referring to Operational Description

1. Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

General Note:

1. This device uses different Exposure Condition Index (ECI) to configure different time averaged power levels based on certain exposure scenarios as the following table:

ECI	Trigger Conditions	Antenna No.	Exposure conditions
ECI2	Receiver on	All ant	Head Standalone
ECI3	Receiver on+WLAN	All ant	Head Simultaneous
ECI7	Receiver off/Sensor off	ant 14	Sensor Trigger Distance -1mm
	Receiver off/Sensor off		Body-worn/Extremity Standalone
	Receiver off/Sensor off	ant 11/12/13/101/21 /22/23/24/25/41	Body-worn/Extremity Standalone
ECI5	Receiver off/Sensor on	ant 14	Body-worn/Extremity Standalone
ECI8	Receiver off/Sensor on +WLAN	ant 14	Body-worn/Extremity Simultaneous
ECI10	Receiver off/Sensor off+WLAN	ant 14	Body-worn/Extremity Simultaneous
	Receiver off/Sensor off+WLAN	ant 11/12/13/101/21 /22/23/24/25/41	Body-worn/Extremity Simultaneous
	Hotspot on	All ant	Hotspot

2. Select the bands with the largest power reduction for power verification:
 - a. Establish voice call and audio routed through the earpiece to monitor output power under head transmitting power states.
 - Tradition voice call for GSM/WCDMA, voice over IP CMRS operations for LTE/5G FR1
 - GSM1900 is set to GPRS 4TX slot, LTE Band 66 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA II is set AMR 12.2Kbps, 5G FR1 n78 is set at highest BW, 1RB, RB offset = 1.
 - b. Establish data connection monitor hotspot power state.
 - GSM1900 is set to GPRS 4TX slot, LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA II is set RMC 12.2Kbps, 5G FR1 n78 is set at highest BW, 1RB, RB offset = 1.
 - c. Establish data connection monitor body worn power state.
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK' WCDMA IV is set RMC 12.2Kbps, 5G FR1 n41 is set at highest BW, 1RB, RB offset = 1.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table)
3. In this power validation purpose is to demonstrate of proper functioning of the detection and triggering mechanisms to support the corresponding RF exposure conditions.
4. Verification performed for one technology/Band to demonstrate that the power reduction applies for same technology/band and call origination.

2. Verification output Power Results

Head exposure conditions

Ear acoustic output Status:		OFF		ON	
Power state		WWAN ECI 7		WWAN ECI 2	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (4 Tx slots)	Ant 14	28.03	29.00	20.65	21.80
WCDMA II	Ant 14	24.37	25.00	17.04	18.00
LTE Band 66	Ant 12	22.46	23.80	19.79	21.00
n78	Ant 13	17.07	18.20	14.19	15.10

Hotspot exposure condition

Hotspot output Status:		OFF		ON	
Power state		WWAN ECI 7		WWAN ECI 10	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM1900 (4 Tx slots)	Ant 14	28.03	29.00	22.95	24.00
WCDMA II	Ant 14	24.37	25.00	21.12	22.00
LTE Band 7	Ant 14	24.14	25.00	18.98	20.00
n78	Ant 13	17.07	18.20	14.92	15.70

Body worn exposure condition

Sensor output Status:		OFF		ON	
Power state		WWAN ECI 7		WWAN ECI 5	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
WCDMA IV	Ant 14	24.26	25.00	21.53	22.50
LTE Band 7	Ant 14	24.14	25.00	21.25	22.70
n41	Ant 14	25.92	26.80	19.91	20.80