




13.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	² 240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-18

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC Below 1G\9

Memo:

Sample Numbler:S2508404-004



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	35.573	39.26	11.64	3.86	22.46	40.00	17.54	QP	Horizontal
2	77.252	46.18	8.07	4.18	26.13	40.00	13.87	QP	Horizontal
3	189.669	56.24	9.77	4.82	38.44	43.50	5.06	QP	Horizontal
4	293.773	57.43	13.25	5.26	43.54	46.00	2.46	QP	Horizontal
5	428.993	44.79	15.70	5.81	33.77	46.00	12.23	QP	Horizontal
6	767.711	42.54	19.77	6.84	36.46	46.00	9.54	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-18

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC Below 1G\10

Memo:

Sample Numbel:S2508404-004



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	44.552	41.82	13.40	3.95	26.87	40.00	13.13	QP	Vertical
2	85.220	49.69	9.29	4.22	30.90	40.00	9.10	QP	Vertical
3	247.751	50.53	11.94	5.07	35.14	46.00	10.86	QP	Vertical
4	293.568	52.41	13.24	5.25	38.50	46.00	7.50	QP	Vertical
5	564.703	37.5	17.84	6.27	28.85	46.00	17.15	QP	Vertical
6	712.721	42.77	19.65	6.67	36.07	46.00	9.93	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\70

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3890.000	46.30	30.78	4.43	-39.66	41.85	74.00	32.15	PK	Horizontal
2	4930.400	45.93	33.10	4.93	-39.79	44.17	74.00	29.83	PK	Horizontal
3	7400.500	44.11	36.70	6.08	-39.86	47.03	74.00	26.97	PK	Horizontal
4	9372.500	42.09	38.76	7.10	-39.01	48.94	74.00	25.06	PK	Horizontal
5	10713.800	41.02	39.43	7.21	-39.63	48.03	74.00	25.97	PK	Horizontal
6	12107.800	41.42	39.48	7.71	-39.51	49.10	74.00	24.90	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\71

Memo:

Sample Numbler:S2508404-004 Power Setting:186




Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3805.000	46.20	30.84	4.40	-39.62	41.82	74.00	32.18	PK	Vertical
2	4906.600	44.34	33.10	4.91	-39.79	42.56	74.00	31.44	PK	Vertical
3	7451.500	43.32	36.61	6.10	-39.85	46.18	74.00	27.82	PK	Vertical
4	9474.500	43.02	38.54	7.12	-39.12	49.56	74.00	24.44	PK	Vertical
5	10676.400	42.14	39.43	7.21	-39.63	49.15	74.00	24.85	PK	Vertical
6	12342.400	41.27	39.27	7.70	-39.33	48.91	74.00	25.09	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-27 **Tested By:** Lin Guoyuan
EUT: Wireless Music Streamer **Model Number:** LP20
Test Mode: TX 11N20 5200MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.5°C;Humi:54.1% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\72
Memo: Sample Numbler:S2508404-004 Power Setting:186

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3833.900	45.98	30.49	4.41	-39.63	41.25	74.00	32.75	PK	Horizontal
2	4158.600	45.97	31.41	4.54	-39.72	42.20	74.00	31.80	PK	Horizontal
3	4911.700	44.58	33.10	4.92	-39.79	42.81	74.00	31.19	PK	Horizontal
4	7383.500	43.67	36.80	6.08	-39.86	46.69	74.00	27.31	PK	Horizontal
5	10715.500	41.68	39.42	7.21	-39.63	48.68	74.00	25.32	PK	Horizontal
6	11880.000	42.14	38.52	7.66	-39.60	48.72	74.00	25.28	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5200MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\73

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3884.900	46.38	30.72	4.43	-39.65	41.88	74.00	32.12	PK	Vertical
2	4906.600	45.39	33.10	4.91	-39.79	43.61	74.00	30.39	PK	Vertical
3	7359.700	44.17	36.94	6.07	-39.86	47.32	74.00	26.68	PK	Vertical
4	9154.900	41.79	38.94	7.06	-38.77	49.02	74.00	24.98	PK	Vertical
5	11407.400	40.87	39.73	7.41	-39.60	48.41	74.00	25.59	PK	Vertical
6	12245.500	41.15	39.29	7.70	-39.40	48.74	74.00	25.26	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5240MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\74

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4024.300	45.77	31.05	4.47	-39.70	41.59	74.00	32.41	PK	Horizontal
2	4944.000	44.97	33.10	4.93	-39.79	43.21	74.00	30.79	PK	Horizontal
3	7400.500	44.56	36.70	6.08	-39.86	47.48	74.00	26.52	PK	Horizontal
4	9153.200	41.46	38.96	7.06	-38.77	48.71	74.00	25.29	PK	Horizontal
5	10865.100	41.39	39.39	7.20	-39.61	48.37	74.00	25.63	PK	Horizontal
6	12184.300	41.63	39.25	7.71	-39.45	49.14	74.00	24.86	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5240MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\75

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3803.300	46.26	30.86	4.40	-39.62	41.90	74.00	32.10	PK	Vertical
2	4724.700	46.25	31.74	4.82	-39.77	43.04	74.00	30.96	PK	Vertical
3	7456.600	44.06	36.64	6.10	-39.85	46.95	74.00	27.05	PK	Vertical
4	9047.800	41.47	38.88	7.04	-38.65	48.74	74.00	25.26	PK	Vertical
5	11580.800	41.84	38.64	7.50	-39.60	48.38	74.00	25.62	PK	Vertical
6	12301.600	41.81	39.40	7.70	-39.36	49.55	74.00	24.45	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5260MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\76

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3798.200	45.81	30.86	4.40	-39.62	41.45	74.00	32.55	PK	Horizontal
2	4104.200	46.34	31.13	4.51	-39.71	42.27	74.00	31.73	PK	Horizontal
3	4799.500	46.33	32.10	4.86	-39.78	43.51	74.00	30.49	PK	Horizontal
4	7444.700	43.39	36.61	6.09	-39.86	46.23	74.00	27.77	PK	Horizontal
5	11330.900	41.53	38.97	7.37	-39.60	48.27	74.00	25.73	PK	Horizontal
6	12169.000	41.79	39.29	7.71	-39.46	49.33	74.00	24.67	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5260MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\77

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3895.100	46.60	30.84	4.43	-39.66	42.21	74.00	31.79	PK	Vertical
2	4911.700	44.86	33.10	4.92	-39.79	43.09	74.00	30.91	PK	Vertical
3	7426.000	44.62	36.65	6.09	-39.86	47.50	74.00	26.50	PK	Vertical
4	9187.200	42.76	38.55	7.07	-38.81	49.57	74.00	24.43	PK	Vertical
5	11565.500	43.87	38.67	7.49	-39.60	50.43	74.00	23.57	PK	Vertical
6	12301.600	42.42	39.40	7.70	-39.36	50.16	74.00	23.84	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5280MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\78

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3830.500	46.89	30.53	4.41	-39.63	42.20	74.00	31.80	PK	Horizontal
2	4383.000	45.73	31.70	4.65	-39.74	42.34	74.00	31.66	PK	Horizontal
3	5030.700	46.05	33.06	4.98	-39.79	44.30	74.00	29.70	PK	Horizontal
4	7550.100	45.06	36.20	6.13	-39.84	47.55	74.00	26.45	PK	Horizontal
5	10797.100	41.99	39.01	7.20	-39.62	48.58	74.00	25.42	PK	Horizontal
6	12492.000	41.77	39.65	7.69	-39.21	49.90	74.00	24.10	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5280MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\79

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4085.500	45.98	31.13	4.50	-39.71	41.90	74.00	32.10	PK	Vertical
2	4921.900	46.07	33.10	4.92	-39.79	44.30	74.00	29.70	PK	Vertical
3	7461.700	43.60	36.67	6.10	-39.85	46.52	74.00	27.48	PK	Vertical
4	9149.800	41.88	39.00	7.06	-38.76	49.18	74.00	24.82	PK	Vertical
5	11393.800	41.17	39.73	7.40	-39.60	48.70	74.00	25.30	PK	Vertical
6	12248.900	41.14	39.30	7.70	-39.40	48.74	74.00	25.26	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5320MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\80

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3908.700	46.43	30.80	4.43	-39.66	42.00	74.00	32.00	PK	Horizontal
2	5027.300	44.97	33.05	4.97	-39.79	43.20	74.00	30.80	PK	Horizontal
3	7504.200	43.23	36.84	6.11	-39.85	46.33	74.00	27.67	PK	Horizontal
4	9472.800	42.42	38.52	7.12	-39.12	48.94	74.00	25.06	PK	Horizontal
5	10679.800	41.00	39.44	7.21	-39.63	48.02	74.00	25.98	PK	Horizontal
6	11988.800	42.37	38.94	7.71	-39.60	49.42	74.00	24.58	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5320MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\81

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3879.800	47.52	30.66	4.42	-39.65	42.95	74.00	31.05	PK	Vertical
2	5136.100	45.95	32.79	5.03	-39.77	44.00	74.00	30.00	PK	Vertical
3	7448.100	43.78	36.60	6.09	-39.86	46.61	74.00	27.39	PK	Vertical
4	9406.500	42.70	38.64	7.11	-39.05	49.40	74.00	24.60	PK	Vertical
5	11504.300	42.36	38.79	7.46	-39.60	49.01	74.00	24.99	PK	Vertical
6	12172.400	41.64	39.28	7.71	-39.46	49.17	74.00	24.83	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5500MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\82

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3805.000	46.71	30.84	4.40	-39.62	42.33	74.00	31.67	PK	Horizontal
2	4809.700	45.32	32.26	4.86	-39.78	42.66	74.00	31.34	PK	Horizontal
3	7397.100	43.48	36.72	6.08	-39.86	46.42	74.00	27.58	PK	Horizontal
4	9148.100	42.45	38.96	7.06	-38.76	49.71	74.00	24.29	PK	Horizontal
5	11579.100	42.53	38.64	7.50	-39.60	49.07	74.00	24.93	PK	Horizontal
6	12442.700	41.54	39.36	7.69	-39.25	49.34	74.00	24.66	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5500MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\83

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3776.100	46.84	30.37	4.39	-39.61	41.99	74.00	32.01	PK	Vertical
2	4808.000	46.17	32.23	4.86	-39.78	43.48	74.00	30.52	PK	Vertical
3	7106.400	43.20	36.67	5.99	-39.89	45.97	68.20	22.23	PK	Vertical
4	9160.000	42.54	38.88	7.06	-38.78	49.70	74.00	24.30	PK	Vertical
5	11387.000	40.85	39.64	7.40	-39.60	48.29	74.00	25.71	PK	Vertical
6	12286.300	42.02	39.37	7.70	-39.37	49.72	74.00	24.28	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5580MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\84

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3779.500	46.02	30.45	4.39	-39.61	41.25	74.00	32.75	PK	Horizontal
2	4294.600	46.86	31.91	4.61	-39.73	43.65	74.00	30.35	PK	Horizontal
3	5013.700	44.65	33.03	4.97	-39.80	42.85	74.00	31.15	PK	Horizontal
4	7446.400	43.23	36.61	6.09	-39.86	46.07	74.00	27.93	PK	Horizontal
5	11404.000	41.24	39.76	7.41	-39.60	48.81	74.00	25.19	PK	Horizontal
6	12002.400	41.22	39.01	7.72	-39.60	48.35	74.00	25.65	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5580MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\85

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3925.700	46.61	30.59	4.44	-39.67	41.97	74.00	32.03	PK	Vertical
2	5027.300	45.08	33.05	4.97	-39.79	43.31	74.00	30.69	PK	Vertical
3	7473.600	43.45	36.74	6.10	-39.85	46.44	74.00	27.56	PK	Vertical
4	9049.500	42.85	38.90	7.04	-38.65	50.14	74.00	23.86	PK	Vertical
5	11344.500	41.31	39.13	7.38	-39.60	48.22	74.00	25.78	PK	Vertical
6	12282.900	42.15	39.37	7.70	-39.37	49.85	74.00	24.15	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5700MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\86

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3793.100	46.77	30.75	4.40	-39.62	42.30	74.00	31.70	PK	Horizontal
2	4916.800	45.32	33.10	4.92	-39.79	43.55	74.00	30.45	PK	Horizontal
3	7252.600	43.11	37.00	6.04	-39.87	46.28	74.00	27.72	PK	Horizontal
4	9139.600	42.74	38.79	7.06	-38.75	49.84	74.00	24.16	PK	Horizontal
5	11183.000	41.82	38.82	7.30	-39.60	48.34	74.00	25.66	PK	Horizontal
6	12209.800	42.28	39.22	7.71	-39.43	49.78	74.00	24.22	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5700MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\87

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4094.000	46.64	31.11	4.51	-39.71	42.55	74.00	31.45	PK	Vertical
2	5119.100	45.27	32.65	5.02	-39.78	43.16	74.00	30.84	PK	Vertical
3	7344.400	43.24	37.00	6.06	-39.87	46.43	74.00	27.57	PK	Vertical
4	9151.500	41.67	38.98	7.06	-38.77	48.94	74.00	25.06	PK	Vertical
5	10975.600	41.03	39.68	7.20	-39.60	48.31	74.00	25.69	PK	Vertical
6	12201.300	41.13	39.20	7.71	-39.44	48.60	74.00	25.40	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5720MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\88

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4051.500	46.40	31.20	4.49	-39.71	42.38	74.00	31.62	PK	Horizontal
2	4906.600	45.65	33.10	4.91	-39.79	43.87	74.00	30.13	PK	Horizontal
3	7635.100	43.90	36.76	6.15	-39.84	46.97	74.00	27.03	PK	Horizontal
4	9051.200	41.72	38.88	7.04	-38.66	48.98	74.00	25.02	PK	Horizontal
5	11470.300	42.35	39.10	7.44	-39.60	49.29	74.00	24.71	PK	Horizontal
6	12359.400	41.34	39.22	7.69	-39.31	48.94	74.00	25.06	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5720MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\89

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3891.700	46.34	30.80	4.43	-39.66	41.91	74.00	32.09	PK	Vertical
2	4133.100	45.80	31.36	4.53	-39.71	41.98	74.00	32.02	PK	Vertical
3	4898.100	45.41	33.09	4.91	-39.79	43.62	74.00	30.38	PK	Vertical
4	7443.000	44.06	36.61	6.09	-39.86	46.90	74.00	27.10	PK	Vertical
5	10936.500	41.72	39.64	7.20	-39.61	48.95	74.00	25.05	PK	Vertical
6	12323.700	41.78	39.33	7.70	-39.34	49.47	74.00	24.53	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\90

Memo:

Sample Numble:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3786.300	46.39	30.60	4.40	-39.61	41.78	74.00	32.22	PK	Horizontal
2	4908.300	44.74	33.10	4.91	-39.79	42.96	74.00	31.04	PK	Horizontal
3	7325.700	43.87	37.00	6.06	-39.87	47.06	74.00	26.94	PK	Horizontal
4	9037.600	41.79	38.80	7.04	-38.64	48.99	74.00	25.01	PK	Horizontal
5	10722.300	41.31	39.39	7.21	-39.63	48.28	74.00	25.72	PK	Horizontal
6	12135.000	41.42	39.40	7.71	-39.49	49.04	74.00	24.96	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\91

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3794.800	46.50	30.79	4.40	-39.62	42.07	74.00	31.93	PK	Vertical
2	4814.800	45.68	32.34	4.87	-39.78	43.11	74.00	30.89	PK	Vertical
3	7672.500	43.16	36.87	6.16	-39.83	46.36	74.00	27.64	PK	Vertical
4	9348.700	41.94	38.79	7.10	-38.98	48.85	74.00	25.15	PK	Vertical
5	10718.900	41.08	39.41	7.21	-39.63	48.07	74.00	25.93	PK	Vertical
6	12335.600	41.51	39.29	7.70	-39.33	49.17	74.00	24.83	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5785MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\92

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3801.600	46.23	30.88	4.40	-39.62	41.89	74.00	32.11	PK	Horizontal
2	4923.600	44.77	33.10	4.92	-39.79	43.00	74.00	31.00	PK	Horizontal
3	7468.500	43.38	36.71	6.10	-39.85	46.34	74.00	27.66	PK	Horizontal
4	9149.800	42.41	39.00	7.06	-38.76	49.71	74.00	24.29	PK	Horizontal
5	10724.000	41.88	39.38	7.21	-39.63	48.84	74.00	25.16	PK	Horizontal
6	12184.300	41.23	39.25	7.71	-39.45	48.74	74.00	25.26	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5785MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\93

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3907.000	45.81	30.82	4.43	-39.66	41.40	74.00	32.60	PK	Vertical
2	5037.500	45.01	33.08	4.98	-39.79	43.28	74.00	30.72	PK	Vertical
3	7381.800	43.51	36.81	6.07	-39.86	46.53	74.00	27.47	PK	Vertical
4	9080.100	42.29	38.36	7.05	-38.69	49.01	74.00	24.99	PK	Vertical
5	10628.800	41.55	39.29	7.21	-39.64	48.41	74.00	25.59	PK	Vertical
6	12187.700	41.17	39.24	7.71	-39.45	48.67	74.00	25.33	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5825MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\94

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3864.500	46.12	30.47	4.42	-39.65	41.36	74.00	32.64	PK	Horizontal
2	4269.100	45.30	31.51	4.59	-39.73	41.67	74.00	32.33	PK	Horizontal
3	4923.600	45.37	33.10	4.92	-39.79	43.60	74.00	30.40	PK	Horizontal
4	7448.100	44.12	36.60	6.09	-39.86	46.95	74.00	27.05	PK	Horizontal
5	10817.500	41.67	39.11	7.20	-39.62	48.36	74.00	25.64	PK	Horizontal
6	12129.900	41.41	39.41	7.71	-39.50	49.03	74.00	24.97	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-27

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11N20 5825MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\95

Memo:

Sample Numbler:S2508404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3893.400	46.14	30.82	4.43	-39.66	41.73	74.00	32.27	PK	Vertical
2	4828.400	46.13	32.55	4.87	-39.78	43.77	74.00	30.23	PK	Vertical
3	7473.600	43.41	36.74	6.10	-39.85	46.40	74.00	27.60	PK	Vertical
4	9061.400	42.17	38.69	7.04	-38.67	49.23	74.00	24.77	PK	Vertical
5	11322.400	42.25	38.87	7.37	-39.60	48.89	74.00	25.11	PK	Vertical
6	12265.900	41.10	39.33	7.70	-39.39	48.74	74.00	25.26	PK	Vertical

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Band Edge Compliance

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
Radiation disturbance fully automated test software	Tonscend	JS32-RE	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

14.2. Block diagram of test setup



14.3. Limits

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

Same with Emissions in Restricted Frequency Bands except change investigated frequency range from 5.15-5.25 GHz, 5250-5350 GHz, 5470-5725 GHz, 5.725-5.85 GHz.
Remark: All restriction band have been tested, and only the worst case is shown in report.

14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-22

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11A 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\22

Memo:

Sample Numbler:S25081404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5148.060	49.51	32.88	5.03	-29.77	57.65	74.00	16.35	PK	Horizontal
2	5150.000	44.45	32.90	5.04	-29.77	52.62	68.20	15.58	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5148.298	40.84	32.88	5.03	48.98	54.00	5.02	AV	Horizontal	
2	5150.234	40.51	32.90	5.04	48.68	54.00	5.32	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-22

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11A 5180MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\23

Memo:

Sample Numbler:S25081404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5146.340	45.14	32.87	5.03	-29.77	53.27	74.00	20.73	PK	Vertical
2	5150.000	41.66	32.90	5.04	-29.77	49.83	68.20	18.37	PK	Vertical

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5146.340	40.35	32.87	5.03	48.48	54.00	5.52	AV	Vertical	
2	5150.000	40.76	32.90	5.04	48.93	54.00	5.07	AV	Vertical	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-22

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11A 5320MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\24

Memo:

Sample Numbler:S25081404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	43.73	32.50	5.14	-29.73	51.64	68.20	16.56	PK	Horizontal
2	5351.070	49.75	32.51	5.14	-29.73	57.67	74.00	16.33	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5349.991	40.26	32.50	5.14	48.17	54.00	5.83	AV	Horizontal	
2	5351.197	40.17	32.51	5.14	48.09	54.00	5.91	AV	Horizontal	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-22 **Tested By:** Lin Guoyuan
EUT: Wireless Music Streamer **Model Number:** LP20
Test Mode: TX 11A 5320MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.5°C;Humi:54.1% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\25
Memo: Sample Numbler:S25081404-004 Power Setting:186

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	41.03	32.50	5.14	-29.73	48.94	68.20	19.26	PK	Vertical
2	5387.180	44.82	32.80	5.15	-29.72	53.05	74.00	20.95	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5350.000	40.68	32.50	5.14	48.59	54.00	5.41	AV	Vertical
2	5387.180	40.16	32.80	5.15	48.39	54.00	5.61	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-22

Tested By:

Lin Guoyuan

EUT:

Wireless Music Streamer

Model Number:

LP20

Test Mode:

TX 11A 5500MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:22.5°C;Humi:54.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\26

Memo:

Sample Numbler:S25081404-004 Power Setting:186



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5458.526	44.38	32.89	5.19	-29.71	52.75	74.00	21.25	PK	Horizontal
2	5460.000	41.90	32.90	5.19	-29.71	50.28	68.20	17.92	PK	Horizontal

Final Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	5458.699	39.95	32.89	5.19	48.32	54.00	5.68	AV	Horizontal	
2	5460.000	40.21	32.90	5.19	48.59	54.00	5.41	AV	Horizontal	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-22 **Tested By:** Lin Guoyuan
EUT: Wireless Music Streamer **Model Number:** LP20
Test Mode: TX 11A 5500MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:22.5°C;Humi:54.1% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25081404-3E\FCC ABOVE 1G 5G\27
Memo: Sample Numbler:S25081404-004 Power Setting:186

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5408.840	45.13	32.88	5.16	-29.72	53.45	74.00	20.55	PK	Vertical
2	5460.000	42.03	32.90	5.19	-29.71	50.41	68.20	17.79	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5408.840	40.02	32.88	5.16	48.34	54.00	5.66	AV	Vertical
2	5460.000	40.57	32.90	5.19	48.95	54.00	5.05	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.