



RF Exposure Evaluation Declaration

FCC ID: 2BDOJ-COMBINE4HDR
Applicant: RF Venue, Inc.
Product: In-Ear Monitor Transmitter Combiner
Model No.: Combine4 HDR
Brand Name: RFVENUE
FCC Rule Part(s): FCC Part 2.1091
Result: Complies
Evaluation Date: 2026-06-30

Prepared By:

Aurora Ding

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report. Testing was performed in accordance with the applicable measurement procedures. The test results reported herein apply only to the specific item(s) tested.


The test report shall not be reproduced except in full without the written approval of MRT Technology (Shenzhen) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
R26S1035052-U401	V01	Initial Report	2026-07-09	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Testing Facility.....	4
1.4. Product Information	5
1.5. Antenna Details	5
1.6. Device Classification	5
1.7. Applied Standards	5
2. RF Exposure Evaluation.....	6
2.1. Limits	6
2.2. MPE Exemptions.....	7
2.3. Calculated Result	10



1.1. Applicant

1.2. Manufacturer

1.3. Testing Facility

4 of 10

1.4. Product Information

Product Name	In-Ear Monitor Transmitter Combiner
Model No.	Combine4 HDR
Radio Specification	Transmitter Combiner
Operating Temperature	-20 ~ 50 °C
Antenna Information	Refer to section 1.5
Power Type	120 ~ 240 V AC
Note: The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer.	

1.5. Antenna Details

Frequency Range (MHz)	Antenna Type	Max Declared Peak Gain (dBi)
470 ~ 608	Dipole	0.0

Note: The product is sold without an antenna.

1.6. Device Classification

According to the user manual, this device is classified as a Mobile Device. So, the RF exposure evaluation requirements of § 2.1091 for mobile device exposure conditions subject to MPE limits.

1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 2.1091
- KDB 447498 D04 Interim General RF Exposure Guidance v01

2. RF Exposure Evaluation

2.1. Limits

According to FCC §1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
0.3 ~ 3.0	614	1.63	*(100)	≤6
3.0 ~ 30	1842/f	4.89/f	*(900/f ²)	<6
30 ~ 300	61.4	0.163	1.0	<6
300 ~ 1500	--	--	f/300	<6
1500 ~ 100000	--	--	5	<6
(B) Limits for General Population/ Uncontrolled Exposures				
0.3 ~ 1.34	614	1.63	*(100)	<30
1.34 ~ 30	824/f	2.19/f	*(180/f ²)	<30
30 ~ 300	27.5	0.073	0.2	<30
300 ~ 1500	--	--	f/1500	<30
1500 ~ 100000	--	--	1.0	<30

f= frequency in MHz. * = Plane-wave equivalent power density.

2.2. MPE Exemptions

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph §1.1307(b)(2) of this section): A single RF source is exempt if:

(Option A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(ii)(A) of this section.

Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(ii)(A);

(Option B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P is given by:

$$P_{th}(mW) = \{ERP_{20cm}(d/20 \text{ cm})^x \quad d \leq 20 \text{ cm}$$

$$P_{th}(mW) = \{ERP_{20cm} \quad 20 \text{ cm} < d \leq 40 \text{ cm}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20cm}(mW) = \{2040f \quad 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz}$$

$$ERP_{20cm}(mW) = \{3060 \quad 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}$$

(Option C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency (MHz)	Threshold ERP (watts)
0.3 ~ 1.34	1920R ²
1.34 ~ 30	3450R ² /f ²
30 ~ 300	3.83R ²
300 ~ 1500	0.0128R ² f
1500 ~ 100000	19.2R ²

For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed,

mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from §1.1310 of this chapter.

2.3. Calculated Result

Product	In-Ear Monitor Transmitter Combiner
Test Item	RF Exposure Evaluation

Frequency Band (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	Max. ERP (dBm)	Max. ERP (W)
470 ~ 608	16.60	0.00	14.45	0.0279

Notes:

1. The Max. Conducted Power is referenced from report No.: R26S1035052-U201.
2. Max ERP (dBm) = Max Conducted Power (dBm) + Antenna Gain (dBi) - 2.15.

For single RF source, Option C

Frequency Band (MHz)	$\lambda / 2 \pi$ (m)	R (m)	Max. ERP (W)	Thresholds ERP (W)
470 ~ 608	0.10	0.20	0.0279	0.2406

Note: The distance R used in the MPE calculation is specified in the user manual.

CONCLUSION:

The device qualifies for RF exposure test exemption at 20 cm distance.

The End
