

TEST REPORT

Application No.: KSCR2601000024AT
FCC ID: 2BHGF-0235CC1A
Applicant: KeyLife International Technology Limited
Address of Applicant: Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG
Manufacturer: KeyLife International Technology Limited
Address of Manufacturer: Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG
Equipment Under Test (EUT):
EUT Name: Indoor Camera
Model No.: P370A,P370A XXXX XXXX XXXX,P370A-XXXX-XXXX-XXXX
 (where X may be '0-9' 'A-Z' 'a-z' '-' or blank; '-' is option) ♣
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-01-05
Date of Test: 2026-01-12 to 2026-02-02
Date of Issue: 2026-02-03

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2026-02-03	/

Authorized for issue by:			
Tested By		Maker Qi	
		Maker Qi /Project Engineer	
Approved By		Terry Hou	
		Terry Hou /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Customer Declaration

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.3 & 11.10.5	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

There are series models mentioned in this report, and they are identical in electrical and electronic characters. Only the model P370A was tested since their differences were the model number and appearance.

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Power level setting using in test.....	5
4.4 Measurement Uncertainty	6
4.5 Test Location.....	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	11
7.2 Radiated Emissions which fall in the restricted bands	15
7.3 Radiated Spurious Emissions Below 1GHz	57
7.4 Radiated Spurious Emissions Above 1GHz.....	61
7.5 Maximum Conducted Output Power	81
7.6 Minimum 6dB Bandwidth	83
7.7 Power Spectrum Density.....	84
7.8 Conducted Band Edges Measurement	85
7.9 Conducted Spurious Emissions	87
8 Test Setup Photo	89
9 EUT Constructional Details (EUT Photos).....	89
10 Appendix.....	90

4 General Information

4.1 Details of E.U.T.

Power supply:	Power Adapter1: Model: TPA-46B050100UU Input: 100~240V~,50-60Hz,0.15A Output: 5V/1A 5W Power Adapter2: Model: DCT06W050100US-C0 Input: 100~240V~,50-60Hz,200mA Output: 5V/1A
Operation Frequency:	802.11b/g/n(HT20)/ax(HE20):2412MHz to 2462MHz; 802.11n(HT40)/ax(HE40):2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK), 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK), 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HE20):11;802.11n(HT40)/ax(HE40):7
Channel Spacing:	5MHz
Antenna Type:	Iron plate antenna
Antenna Gain:	3.94dBi (Provided by the manufacturer)

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Notebook	LENOVO	K27	EB24537645

4.3 Power level setting using in test

Channel	802.11b	802.11g	802.11n(HT20)	802.11ax(HE20)
	Ant 1	Ant 1	Ant 1	Ant 1
1	15	5	5	5
6	15	5	5	5
11	15	5	5	5
Channel	802.11n(HT40)	802.11ax(HE40)		
	Ant 1	Ant 1		
3	5	5		
6	5	5		
9	5	5		

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	8.4×10^{-8}
2	Timeout	2s
3	Duty Cycle	0.37%
4	Occupied Bandwidth	3%
5	RF Conducted Power	0.6dB
6	RF Power Density	2.9dB
7	Conducted Spurious Emissions	0.75dB
8	RF Radiated Power	5.2dB (Below 1GHz)
		5.9dB (Above 1GHz)
9	Radiated Spurious Emission Test	4.2dB (Below 30MHz)
		4.5dB (30MHz-1GHz)
		5.1dB (1GHz-18GHz)
		5.4dB (Above 18GHz)
10	Temperature Test	1°C
11	Humidity Test	3%
12	Supply Voltages	1.5%
13	Time	3%
Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

4.5 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1172)**

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 2324E

- **VCCI (Member No:1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESCI	KS301196	07/09/2025	07/08/2026
2	LISN	R&S	ENV216	KS301197	01/08/2026	01/07/2027
3	LISN	Schwarzbeck	NNLK 8129	KS301091	01/08/2026	01/07/2027
4	Pulse Limiter	R&S	ESH3-Z2	KUS1902E001	12/18/2025	12/17/2026
5	CE test Cable	Thermax	/	CZ301102	12/18/2025	12/17/2026
6	Software	Faratronic	E3	/	N.C.R	N.C.R
RF Conducted Test						
1	Spectrum Analyzer	Keysight	N9020A	KUS1911E004-2	07/09/2025	07/08/2026
2	Spectrum Analyzer	Keysight	N9020A	KUS2001M001-2	07/09/2025	07/08/2026
3	Spectrum Analyzer	Keysight	N9030B	KSEM021-1	12/17/2025	12/16/2026
4	Signal Generator	R&S	SMBV100B	KSEM032	12/17/2025	12/16/2026
5	Signal Generator	R&S	SMW200A	KSEM020-1	07/09/2025	07/08/2026
6	Signal Generator	Agilent	N5182A	KUS2001M001-1	07/08/2025	07/07/2026
7	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
8	Radio Communication Test Station	Anritsu	MT8000A	KSEM001-1	07/09/2025	07/08/2026
9	Radio Communication Analyzer	Anritsu	MT8821C	KSEM002-1	12/17/2025	12/16/2026
10	Universal Radio Communication Tester	R&S	CMW500	KUS1911E004-1	07/08/2025	07/07/2026
11	Switcher	TST	FY562	KUS2001M001-4	12/17/2025	12/16/2026
12	Conducted Test Cable	Thermax	RF01-RF04	CZ301111-CZ301120	12/17/2025	12/16/2026
13	Temp. / Humidity Chamber	TERCHY	MHK-120AK	KS301190	07/15/2025	07/14/2026
14	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-5	12/30/2025	12/29/2026
15	Software	BST	TST-PASS	/	NCR	NCR
RF Radiated Test						
1	Spectrum Analyzer	R&S	FSV40	KUS1806E003	07/09/2025	07/08/2026
2	Universal Radio Communication Tester	R&S	CMW500	KSEM009-1	12/17/2025	12/16/2026
3	Signal Generator	Agilent	E8257C	KS301066	07/22/2025	07/21/2026
4	Loop Antenna (9KHz-30MHz)	COM-POWER	AL-130R	KUS1806E001	07/11/2025	07/10/2026
5	Bilog Antenna (30MHz-1GHz)	TESEQ	CBL 6112D	KUS1806E005	07/12/2025	07/11/2026
6	Horn-antenna(1-18GHz)	Schwarzbeck	BBHA9120D	KS301079	01/11/2026	01/10/2028
7	Horn Antenna(18-40GHz)	Schwarzbeck	BBHA9170	CZ301058	01/11/2026	01/10/2028

8	Amplifier(30MHz~1GHz)	TST	LNA009100G30	KSEM061	12/18/2025	12/17/2026
9	Amplifier(400MHz~8GHz)	TST	LNA004080G30	KSEM062	12/18/2025	12/17/2026
10	Amplifier(1GHz~18GHz)	TST	LNA010180G45	KSEM039	07/09/2025	07/08/2026
11	Amplifier(18~40GHz)	TST	LNA180400G40	KSEM038	07/09/2025	07/08/2026
12	Temperature & Humidity Recorder	Renke Control	RS-WS-N01-6J	KSEM024-4	12/30/2025	12/29/2026
13	Software	ESE	E3_V 6.111221a	/	NCR	NCR
14	Measurement Software	Tonscend	JS32-RE V5.0.0.1	/	NCR	NCR
15	Measurement Software	Tonscend	JS32-RSE V5.0.0.0	/	NCR	NCR

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is Iron plate antenna and no consideration of replacement. The best case gain of the antenna is 3.94dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 52.9 % RH

Atmospheric Pressure: 1010 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark : Level=Read Level+ Cable Loss+ LISN Factor

Test Mode: 00; Line: Live line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1621	5.21	20.51	25.72	55.36	-29.64	Average
2	0.1621	22.69	20.51	43.20	65.36	-22.16	QP
3	0.2288	2.10	20.25	22.35	52.49	-30.14	Average
4	0.2288	17.12	20.25	37.37	62.49	-25.12	QP
5	0.4838	10.78	20.18	30.96	46.27	-15.31	Average
6	0.4838	15.01	20.18	35.19	56.27	-21.08	QP
7	1.0570	-3.44	20.38	16.94	46.00	-29.06	Average
8	1.0570	8.55	20.38	28.93	56.00	-27.07	QP
9	16.0390	0.43	26.23	26.66	50.00	-23.34	Average
10	16.0390	9.48	26.23	35.71	60.00	-24.29	QP
11	18.9210	0.38	26.89	27.27	50.00	-22.73	Average
12	18.9210	9.07	26.89	35.96	60.00	-24.04	QP

Test Mode: 00; Line: Neutral Line



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1779	4.68	20.43	25.11	54.58	-29.47	Average
2	0.1779	22.46	20.43	42.89	64.58	-21.69	QP
3	0.4911	4.81	20.16	24.97	46.15	-21.18	Average
4	0.4911	17.80	20.16	37.96	56.15	-18.19	QP
5	2.1710	-3.22	20.63	17.41	46.00	-28.59	Average
6	2.1710	7.06	20.63	27.69	56.00	-28.31	QP
7	10.3640	7.28	23.92	31.20	50.00	-18.80	Average
8	10.3640	16.67	23.92	40.59	60.00	-19.41	QP
9	19.3360	5.51	26.90	32.41	50.00	-17.59	Average
10	19.3360	17.47	26.90	44.37	60.00	-15.63	QP
11	20.5440	4.99	27.14	32.13	50.00	-17.87	Average
12	20.5440	16.30	27.14	43.44	60.00	-16.56	QP

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

11b_TX_CH_01_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.31	55.60	26.66	-26.14	56.12	74.00	17.88	Horizontal
2	2389.17	55.92	26.69	-26.13	56.48	74.00	17.52	Horizontal

11b_TX_CH_01_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.01	43.61	26.65	-26.15	44.11	54.00	9.89	Horizontal
2	2389.17	43.58	26.69	-26.13	44.14	54.00	9.86	Horizontal


11b_TX_CH_01_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.7	56.36	26.67	-26.14	56.89	74.00	17.11	Vertical
2	2388.91	55.09	26.69	-26.13	55.65	74.00	18.35	Vertical




11b_TX_CH_01_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.09	43.39	26.67	-26.14	43.92	54.00	10.08	Vertical
2	2389.82	43.42	26.70	-26.13	43.99	54.00	10.01	Vertical


11b_TX_CH_11_ Horizontal _Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.1	56.35	27.16	-26.24	57.27	74.00	16.73	Horizontal
2	2486.5	55.52	27.14	-26.24	56.42	74.00	17.58	Horizontal




11b_TX_CH_11_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.28	44.06	27.16	-26.24	44.98	54.00	9.02	Horizontal
2	2485.66	44.26	27.14	-26.24	45.16	54.00	8.84	Horizontal

11b_TX_CH_11_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.22	55.67	27.16	-26.24	56.59	74.00	17.41	Vertical
2	2485.72	55.63	27.14	-26.24	56.53	74.00	17.47	Vertical



Report No.: KSCR260100002402


Page: 24 of 164

11b_TX_CH_11_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.16	43.64	27.16	-26.24	44.56	54.00	9.44	Vertical
2	2485.3	43.52	27.15	-26.24	44.43	54.00	9.57	Vertical


11n(HT20)_TX_CH_01_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2384.88	55.02	26.65	-26.15	55.52	74.00	18.48	Horizontal
2	2388.39	55.47	26.68	-26.13	56.02	74.00	17.98	Horizontal




11n(HT20)_TX_CH_01_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.7	43.54	26.67	-26.14	44.07	54.00	9.93	Horizontal
2	2388.65	43.98	26.69	-26.13	44.54	54.00	9.46	Horizontal




11n(HT20)_TX_CH_01_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.53	55.40	26.66	-26.15	55.91	74.00	18.09	Vertical
2	2389.56	55.62	26.70	-26.13	56.19	74.00	17.81	Vertical




11n(HT20)_TX_CH_01_Vetical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.18	43.49	26.66	-26.14	44.01	54.00	9.99	Vertical
2	2388.78	43.47	26.69	-26.13	44.03	54.00	9.97	Vertical

11n(HT20)_TX_CH_11_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.62	59.08	27.16	-26.24	60.00	74.00	14.00	Horizontal
2	2484.58	59.23	27.15	-26.24	60.14	74.00	13.86	Horizontal



Report No.: KSCR260100002402


Page: 30 of 164

11n(HT20)_TX_CH_11_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.86	44.12	27.16	-26.24	45.04	54.00	8.96	Horizontal
2	2485.06	43.80	27.15	-26.24	44.71	54.00	9.29	Horizontal


11n(HT20)_TX_CH_11_Vetical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.8	55.91	27.16	-26.24	56.83	74.00	17.17	Vertical
2	2484.82	55.99	27.15	-26.24	56.90	74.00	17.10	Vertical




11n(HT20)_TX_CH_11_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.62	43.62	27.16	-26.24	44.54	54.00	9.46	Vertical
2	2484.88	43.51	27.15	-26.24	44.42	54.00	9.58	Vertical

11n(HT40)_TX_CH_03_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.57	63.46	26.67	-26.14	63.99	74.00	10.01	Horizontal
2	2389.8	64.38	26.70	-26.13	64.95	74.00	9.05	Horizontal

11n(HT40)_TX_CH_03_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.43	45.57	26.65	-26.15	46.07	54.00	7.93	Horizontal
2	2388.47	46.65	26.68	-26.13	47.20	54.00	6.80	Horizontal


11n(HT40)_TX_CH_03_Vetical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.57	60.79	26.67	-26.14	61.32	74.00	12.68	Vertical
2	2389.8	61.80	26.70	-26.13	62.37	74.00	11.63	Vertical




11n(HT40)_TX_CH_03_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.24	42.65	26.65	-26.15	43.15	54.00	10.85	Vertical
2	2388.66	43.67	26.69	-26.13	44.23	54.00	9.77	Vertical

11n(HT40)_TX_CH_09_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.81	44.82	26.66	-26.15	45.33	74.00	28.67	Horizontal
2	2387.71	45.32	26.68	-26.14	45.86	74.00	28.14	Horizontal

11n(HT40)_TX_CH_09_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2384.86	32.72	26.65	-26.15	33.22	54.00	20.78	Horizontal
2	2389.23	32.40	26.69	-26.13	32.96	54.00	21.04	Horizontal


11n(HT40)_TX_CH_09_Vetical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.52	43.05	26.68	-26.14	43.59	74.00	30.41	Vertical
2	2389.8	43.08	26.70	-26.13	43.65	74.00	30.35	Vertical




11n(HT40)_TX_CH_09_Vetical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.14	30.06	26.67	-26.14	30.59	54.00	23.41	Vertical
2	2389.61	30.38	26.70	-26.13	30.95	54.00	23.05	Vertical


11(HE20)_TX_CH_01_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.01	55.45	26.65	-26.15	55.95	74.00	18.05	Horizontal
2	2388	56.92	26.68	-26.14	57.46	74.00	16.54	Horizontal




11(HE20)_TX_CH_01_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.66	43.40	26.66	-26.15	43.91	54.00	10.09	Horizontal
2	2389.56	43.90	26.70	-26.13	44.47	54.00	9.53	Horizontal


11(HE20)_TX_CH_01_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.05	54.93	26.66	-26.15	55.44	74.00	18.56	Vertical
2	2388.65	55.31	26.69	-26.13	55.87	74.00	18.13	Vertical




11(HE20)_TX_CH_01_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2384.75	43.36	26.65	-26.15	43.86	54.00	10.14	Vertical
2	2389.04	43.60	26.69	-26.13	44.16	54.00	9.84	Vertical

11(HE20)_TX_CH_11_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.04	55.54	27.16	-26.24	56.46	74.00	17.54	Horizontal
2	2484.94	56.71	27.15	-26.24	57.62	74.00	16.38	Horizontal

11(HE20)_TX_CH_11_Horizontal_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.16	43.80	27.16	-26.24	44.72	54.00	9.28	Horizontal
2	2485.6	43.70	27.14	-26.24	44.60	54.00	9.40	Horizontal


11(HE20)_TX_CH_11_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.28	55.67	27.16	-26.24	56.59	74.00	17.41	Vertical
2	2484.88	56.20	27.15	-26.24	57.11	74.00	16.89	Vertical




11(HE20)_TX_CH_11_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.4	43.47	27.16	-26.24	44.39	54.00	9.61	Vertical
2	2485.42	43.62	27.15	-26.24	44.53	54.00	9.47	Vertical


11n(HE40)_TX_CH_03_Horizontal_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2385.81	60.57	26.66	-26.15	61.08	74.00	12.92	Horizontal
2	2388.09	59.50	26.68	-26.14	60.04	74.00	13.96	Horizontal




11n(HE40)_TX_CH_03_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2387.52	45.24	26.68	-26.14	45.78	54.00	8.22	Horizontal
2	2389.61	46.49	26.70	-26.13	47.06	54.00	6.94	Horizontal

11n(HE40)_TX_CH_03_Vetical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386	64.52	26.66	-26.15	65.03	74.00	8.97	Vertical
2	2389.99	65.01	26.70	-26.13	65.58	74.00	8.42	Vertical


11n(HE40)_TX_CH_03_Vertical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2387.52	49.42	26.68	-26.14	49.96	54.00	4.04	Vertical
2	2389.42	50.66	26.69	-26.13	51.22	54.00	2.78	Vertical




11n(HE40)_TX_CH_09_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2386.19	43.98	26.66	-26.14	44.50	74.00	29.50	Horizontal
2	2389.99	44.00	26.70	-26.13	44.57	74.00	29.43	Horizontal

11n(HE40)_TX_CH_09_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2383.34	32.61	26.63	-26.16	33.08	54.00	20.92	Horizontal
2	2389.42	32.97	26.69	-26.13	33.53	54.00	20.47	Horizontal

11n(HE40)_TX_CH_09_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2381.82	47.51	26.62	-26.17	47.96	74.00	26.04	Vertical
2	2389.42	49.23	26.69	-26.13	49.79	74.00	24.21	Vertical

11n(HE40)_TX_CH_09_Verical_Average



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2382.96	36.18	26.63	-26.16	36.65	54.00	17.35	Vertical
2	2389.42	36.52	26.69	-26.13	37.08	54.00	16.92	Vertical

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
2. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.




Test Mode: 00; Polarity: Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	33.88	43.11	16.67	-32.49	27.29	40.00	12.71	Horizontal
2	94.505	54.64	11.65	-31.88	34.41	43.50	9.09	Horizontal
3	148.0975	57.49	11.19	-31.47	37.21	43.50	6.29	Horizontal
4	292.1425	48.20	14.56	-31.05	31.71	46.00	14.29	Horizontal
5	480.08	41.39	18.30	-30.48	29.21	46.00	16.79	Horizontal
6	739.3125	40.36	21.82	-29.52	32.66	46.00	13.34	Horizontal

Test Mode: 00; Polarity: Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	34.1225	50.55	16.48	-32.49	34.54	40.00	5.46	Vertical
2	88.9275	54.69	10.78	-31.92	33.55	43.50	9.95	Vertical
3	146.885	51.62	11.52	-31.47	31.67	43.50	11.83	Vertical
4	348.8875	40.45	15.48	-30.72	25.21	46.00	20.79	Vertical
5	480.08	40.97	18.30	-30.48	28.79	46.00	17.21	Vertical
6	759.44	41.56	21.72	-29.49	33.79	46.00	12.21	Vertical

7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3M

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 45.6 % RH

Atmospheric Pressure: 1010 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20). Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram




7.4.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Scan from 18GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
6. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.

11b_TX_CH_01_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17995	48.69	43.20	-41.25	50.64	54.00	3.36	Horizontal
2	1848.8333	46.38	24.25	-27.70	42.93	74.00	31.07	Horizontal
3	3618	69.02	28.51	-53.02	44.51	74.00	29.49	Horizontal
4	4824	63.33	31.45	-50.19	44.59	74.00	29.41	Horizontal
5	5225.5	62.90	31.75	-49.59	45.06	74.00	28.94	Horizontal
6	17996	56.07	43.20	-41.23	58.04	74.00	15.96	Horizontal


11b_TX_CH_01_Vertical



Data List


NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4824.5	64.77	31.45	-50.19	46.03	54.00	7.97	Vertical
2	17998	48.53	43.20	-41.19	50.54	54.00	3.46	Vertical
3	1808.1667	46.29	24.06	-27.63	42.72	74.00	31.28	Vertical
4	3618	69.28	28.51	-53.02	44.77	74.00	29.23	Vertical
5	4824	65.80	31.45	-50.19	47.06	74.00	26.94	Vertical
6	17971.5	57.08	43.20	-41.65	58.63	74.00	15.37	Vertical

11b_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17986	49.01	43.20	-41.40	50.81	54.00	3.19	Horizontal
2	1853.1667	46.32	24.30	-27.71	42.91	74.00	31.09	Horizontal
3	3655.5	67.48	28.72	-53.05	43.15	74.00	30.85	Horizontal
4	4874	64.36	31.45	-50.56	45.25	74.00	28.75	Horizontal
5	17990.5	56.73	43.20	-41.32	58.61	74.00	15.39	Horizontal

11b_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	1860	45.85	24.30	-27.72	42.43	74.00	31.57	Vertical
2	3655.5	68.65	28.72	-53.05	44.32	74.00	29.68	Vertical
3	4874	67.13	31.45	-50.56	48.02	74.00	25.98	Vertical
4	17999	57.16	43.20	-41.18	59.18	74.00	14.82	Vertical

11b_TX_CH_11_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17974	48.84	43.20	-41.61	50.43	54.00	3.57	Horizontal
2	1809.6667	46.54	24.09	-27.64	42.99	74.00	31.01	Horizontal
3	3693	68.44	28.87	-53.08	44.23	74.00	29.77	Horizontal
4	4924	64.77	31.50	-50.73	45.54	74.00	28.46	Horizontal
5	17718.5	56.85	42.76	-41.61	58.00	74.00	16.00	Horizontal

11b_TX_CH_11_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17994	48.15	43.20	-41.26	50.09	54.00	3.91	Vertical
2	1851.8333	45.75	24.30	-27.70	42.35	74.00	31.65	Vertical
3	3693	69.08	28.87	-53.08	44.87	74.00	29.13	Vertical
4	4924	66.22	31.50	-50.73	46.99	74.00	27.01	Vertical
5	17989	57.04	43.20	-41.35	58.89	74.00	15.11	Vertical

11n(HT20)_TX_CH_01_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17989	48.87	43.20	-41.35	50.72	54.00	3.28	Horizontal
2	1546.3333	45.56	23.90	-28.10	41.36	74.00	32.64	Horizontal
3	3618	66.67	28.51	-53.02	42.16	74.00	31.84	Horizontal
4	5246.5	63.91	31.79	-49.83	45.87	74.00	28.13	Horizontal
5	17999	56.40	43.20	-41.18	58.42	74.00	15.58	Horizontal

11n(HT20)_TX_CH_01_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17992.5	48.58	43.20	-41.29	50.49	54.00	3.51	Vertical
2	1783.5	45.15	23.84	-27.69	41.30	74.00	32.70	Vertical
3	3618	67.39	28.51	-53.02	42.88	74.00	31.12	Vertical
4	4827	61.58	31.45	-50.21	42.82	74.00	31.18	Vertical
5	17987.5	57.27	43.20	-41.38	59.09	74.00	14.91	Vertical

11n(HT20)_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	18000	48.90	43.20	-41.16	50.94	54.00	3.06	Horizontal
2	1728.6667	45.57	23.53	-27.93	41.17	74.00	32.83	Horizontal
3	3655.5	66.98	28.72	-53.05	42.65	74.00	31.35	Horizontal
4	6504.5	56.91	34.25	-46.29	44.87	74.00	29.13	Horizontal
5	17700.5	56.54	42.80	-41.18	58.16	74.00	15.84	Horizontal

11n(HT20)_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17994.5	48.76	43.20	-41.25	50.71	54.00	3.29	Vertical
2	1805.3333	45.92	24.01	-27.63	42.30	74.00	31.70	Vertical
3	3655.5	67.30	28.72	-53.05	42.97	74.00	31.03	Vertical
4	4876.5	61.95	31.45	-50.58	42.82	74.00	31.18	Vertical
5	17996	56.10	43.20	-41.23	58.07	74.00	15.93	Vertical

11n(HT20)_TX_CH_11_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17991.5	48.72	43.20	-41.31	50.61	54.00	3.39	Horizontal
2	1939.5	47.30	24.40	-27.51	44.19	74.00	29.81	Horizontal
3	3693	66.96	28.87	-53.08	42.75	74.00	31.25	Horizontal
4	5247	61.17	31.79	-49.84	43.12	74.00	30.88	Horizontal
5	17993.5	55.91	43.20	-41.27	57.84	74.00	16.16	Horizontal

11n(HT20)_TX_CH_11_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17997.5	48.84	43.20	-41.20	50.84	54.00	3.16	Vertical
2	1979.3333	47.21	25.15	-27.23	45.13	74.00	28.87	Vertical
3	3693	66.69	28.87	-53.08	42.48	74.00	31.52	Vertical
4	4931	61.12	31.50	-50.73	41.89	74.00	32.11	Vertical
5	17977	57.07	43.20	-41.56	58.71	74.00	15.29	Vertical

11ax(HE20)_TX_CH_01_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17997.5	49.26	43.20	-41.20	51.26	54.00	2.74	Horizontal
2	2006.6667	46.79	25.20	-27.08	44.91	74.00	29.09	Horizontal
3	3618	67.07	28.51	-53.02	42.56	74.00	31.44	Horizontal
4	5233.5	64.51	31.77	-49.68	46.60	74.00	27.40	Horizontal
5	17660.5	57.09	42.88	-42.02	57.95	74.00	16.05	Horizontal

11ax(HE20)_TX_CH_01_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17993	48.98	43.20	-41.28	50.90	54.00	3.10	Vertical
2	2011.3333	47.17	25.19	-27.07	45.29	74.00	28.71	Vertical
3	3618	67.18	28.51	-53.02	42.67	74.00	31.33	Vertical
4	4825	59.59	31.45	-50.20	40.84	74.00	33.16	Vertical
5	17995.5	56.70	43.20	-41.24	58.66	74.00	15.34	Vertical

11ax(HE20)_TX_CH_06_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17993.5	48.82	43.20	-41.27	50.75	54.00	3.25	Horizontal
2	1508.3333	44.95	23.93	-28.08	40.80	74.00	33.20	Horizontal
3	3655.5	66.22	28.72	-53.05	41.89	74.00	32.11	Horizontal
4	4874	61.44	31.45	-50.56	42.33	74.00	31.67	Horizontal
5	17999	55.85	43.20	-41.18	57.87	74.00	16.13	Horizontal

11ax(HE20)_TX_CH_06_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17994	48.90	43.20	-41.26	50.84	54.00	3.16	Vertical
2	1553.6667	45.91	23.86	-28.11	41.66	74.00	32.34	Vertical
3	3655.5	67.58	28.72	-53.05	43.25	74.00	30.75	Vertical
4	4875.5	61.28	31.45	-50.57	42.16	74.00	31.84	Vertical
5	17986	56.27	43.20	-41.40	58.07	74.00	15.93	Vertical

11ax(HE20)_TX_CH_11_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17999.5	48.70	43.20	-41.17	50.73	54.00	3.27	Horizontal
2	1609.5	45.78	23.70	-28.13	41.35	74.00	32.65	Horizontal
3	3693.5	66.30	28.87	-53.08	42.09	74.00	31.91	Horizontal
4	6467	57.38	34.20	-46.70	44.88	74.00	29.12	Horizontal
5	17700.5	56.18	42.80	-41.18	57.80	74.00	16.20	Horizontal

11ax(HE20)_TX_CH_11_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	17992	48.75	43.20	-41.30	50.65	54.00	3.35	Vertical
2	1810	46.34	24.10	-27.64	42.80	74.00	31.20	Vertical
3	3693	66.50	28.87	-53.08	42.29	74.00	31.71	Vertical
4	4924	61.33	31.50	-50.73	42.10	74.00	31.90	Vertical
5	17990.5	56.12	43.20	-41.32	58.00	74.00	16.00	Vertical

7.5 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 52.7 % RH

Atmospheric Pressure: 1010 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 52.7 % RH

Atmospheric Pressure: 1010 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2020) Section 11.10.3 & 11.10.5

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 52.6 % RH

Atmospheric Pressure: 1010 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C


Humidity: 52.6 % RH

Atmospheric Pressure: 1010 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 21.7 °C


Humidity: 52.5 % RH

Atmospheric Pressure: 1010 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40). Only the data of worst case is recorded in the report.

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Report No.: KSCR260100002402

Page: 89 of 164

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for KSCR2601000024AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for KSCR2601000024AT

10 Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1


Ant1									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	/	/	16.770	16.777	99.96	0.00	0.00
		2437	/	/	16.770	16.777	99.96	0.00	0.00
		2462	/	/	16.770	16.777	99.96	0.00	0.00
802.11g	SISO	2412	/	/	1.393	1.399	99.57	0.02	0.08
		2437	/	/	1.392	1.398	99.57	0.02	0.04
		2462	/	/	1.393	1.399	99.57	0.02	0.04
802.11n (HT20)	SISO	2412	/	/	1.301	1.306	99.62	0.02	0.04
		2437	/	/	1.301	1.307	99.54	0.02	0.03
		2462	/	/	1.301	1.307	99.54	0.02	0.08
802.11n (HT40)	SISO	2422	/	/	0.649	0.655	99.08	0.04	0.04
		2437	/	/	0.649	0.655	99.08	0.04	0.04
		2452	/	/	0.648	0.654	99.08	0.04	0.08
802.11ax (HE20)	SISO	2412	SU	/	1.013	1.020	99.31	0.03	0.04
		2437	SU	/	1.013	1.020	99.31	0.03	0.04
		2462	SU	/	1.013	1.019	99.41	0.03	0.08
802.11ax (HE40)	SISO	2422	SU	/	0.537	0.544	98.71	0.06	0.04
		2437	SU	/	0.538	0.544	98.90	0.05	0.04
		2452	SU	/	0.537	0.543	98.90	0.05	0.07

1.2 Test Graph


1.2.1 Ant1




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	14.877	/	Pass
		2437	/	/	1	14.895	/	Pass
		2462	/	/	1	14.866	/	Pass
802.11g	SISO	2412	/	/	1	16.492	/	Pass
		2437	/	/	1	16.459	/	Pass
		2462	/	/	1	16.464	/	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.466	/	Pass
		2437	/	/	1	17.475	/	Pass
		2462	/	/	1	17.452	/	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.405	/	Pass
		2437	/	/	1	35.486	/	Pass
		2452	/	/	1	35.409	/	Pass
802.11ax (HE20)	SISO	2412	SU	/	1	18.806	/	Pass
		2437	SU	/	1	18.816	/	Pass
		2462	SU	/	1	18.809	/	Pass
802.11ax (HE40)	SISO	2422	SU	/	1	37.281	/	Pass
		2437	SU	/	1	37.389	/	Pass
		2452	SU	/	1	37.312	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	10.337	≥ 0.5	Pass
		2437	/	/	1	10.341	≥ 0.5	Pass
		2462	/	/	1	10.338	≥ 0.5	Pass
802.11g	SISO	2412	/	/	1	16.033	≥ 0.5	Pass
		2437	/	/	1	16.105	≥ 0.5	Pass
		2462	/	/	1	16.099	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	16.805	≥ 0.5	Pass
		2437	/	/	1	16.819	≥ 0.5	Pass
		2462	/	/	1	16.761	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	32.984	≥ 0.5	Pass
		2437	/	/	1	33.841	≥ 0.5	Pass
		2452	/	/	1	32.987	≥ 0.5	Pass
802.11ax (HE20)	SISO	2412	SU	/	1	16.168	≥ 0.5	Pass
		2437	SU	/	1	16.310	≥ 0.5	Pass
		2462	SU	/	1	15.942	≥ 0.5	Pass
802.11ax (HE40)	SISO	2422	SU	/	1	29.940	≥ 0.5	Pass
		2437	SU	/	1	33.639	≥ 0.5	Pass
		2452	SU	/	1	29.844	≥ 0.5	Pass


2.2 Test Graph

2.2.1 OBW


802.11b LCH 2412MHz_Ant1 (SISO)_NTNV




802.11b MCH 2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTN



802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV




2.2.2 6dB BW


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH_2452MHz_Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTN



802.11ax(HE40) MCH_2437MHz_SU / Ant1 (SISO) NTN



802.11ax(HE40) HCH_2452MHz_SU / Ant1 (SISO) NTN



3. Maximum Conducted Output Power

3.1 Test Result


3.1.1 Power

Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum Average Conducted Output Power (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	17.10	<=30	Pass
		2437	/	/	17.25	<=30	Pass
		2462	/	/	17.53	<=30	Pass
802.11g	SISO	2412	/	/	13.91	<=30	Pass
		2437	/	/	14.13	<=30	Pass
		2462	/	/	14.49	<=30	Pass
802.11n (HT20)	SISO	2412	/	/	13.75	<=30	Pass
		2437	/	/	13.97	<=30	Pass
		2462	/	/	14.32	<=30	Pass
802.11n (HT40)	SISO	2422	/	/	14.26	<=30	Pass
		2437	/	/	14.38	<=30	Pass
		2452	/	/	14.57	<=30	Pass
802.11ax (HE20)	SISO	2412	SU	/	13.67	<=30	Pass
		2437	SU	/	13.88	<=30	Pass
		2462	SU	/	14.22	<=30	Pass
802.11ax (HE40)	SISO	2422	SU	/	14.21	<=30	Pass
		2437	SU	/	14.34	<=30	Pass
		2452	SU	/	14.52	<=30	Pass


Note1: Antenna Gain: Ant1: 3.94dBi;

3.2 Test Graph


3.2.1 Power




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTN




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTN




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV



4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	RU	RU Pos	Maximum PSD (dBm)		Verdict
					ANT1	Limit	
802.11b	SISO	2412	/	/	-0.90	<=8	Pass
		2437	/	/	-0.82	<=8	Pass
		2462	/	/	-0.34	<=8	Pass
802.11g	SISO	2412	/	/	-4.12	<=8	Pass
		2437	/	/	-4.16	<=8	Pass
		2462	/	/	-3.99	<=8	Pass
802.11n (HT20)	SISO	2412	/	/	-4.76	<=8	Pass
		2437	/	/	-4.74	<=8	Pass
		2462	/	/	-4.28	<=8	Pass
802.11n (HT40)	SISO	2422	/	/	-7.42	<=8	Pass
		2437	/	/	-6.73	<=8	Pass
		2452	/	/	-7.00	<=8	Pass
802.11ax (HE20)	SISO	2412	SU	/	-6.02	<=8	Pass
		2437	SU	/	-5.89	<=8	Pass
		2462	SU	/	-5.43	<=8	Pass
802.11ax (HE40)	SISO	2422	SU	/	-7.95	<=8	Pass
		2437	SU	/	-7.84	<=8	Pass
		2452	SU	/	-7.66	<=8	Pass

Note1: Antenna Gain: Ant1: 3.94dBi;


4.2 Test Graph

4.2.1 PSD


802.11b LCH 2412MHz_Ant1 (SISO)_NTNV




802.11b MCH 2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH 2412MHz Ant1 (SISO) NTN




802.11n(HT20) MCH 2437MHz Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40) HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)
802.11b	SISO	2412	/	/	1	7.73
		2437	/	/	1	7.76
		2462	/	/	1	8.08
802.11g	SISO	2412	/	/	1	4.09
		2437	/	/	1	4.26
		2462	/	/	1	4.56
802.11n (HT20)	SISO	2412	/	/	1	4.02
		2437	/	/	1	4.25
		2462	/	/	1	4.45
802.11n (HT40)	SISO	2422	/	/	1	2.01
		2437	/	/	1	1.75
		2452	/	/	1	2.31
802.11ax (HE20)	SISO	2412	SU	/	1	3.80
		2437	SU	/	1	3.91
		2462	SU	/	1	4.32
802.11ax (HE40)	SISO	2422	SU	/	1	1.64
		2437	SU	/	1	1.64
		2452	SU	/	1	1.90

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.1.2 CSE

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	/	/	1	8.08	-21.92	Pass
		2437	/	/	1	8.08	-21.92	Pass
		2462	/	/	1	8.08	-21.92	Pass
802.11g	SISO	2412	/	/	1	4.56	-25.44	Pass
		2437	/	/	1	4.56	-25.44	Pass
		2462	/	/	1	4.56	-25.44	Pass
802.11n (HT20)	SISO	2412	/	/	1	4.45	-25.55	Pass
		2437	/	/	1	4.45	-25.55	Pass
		2462	/	/	1	4.45	-25.55	Pass
802.11n (HT40)	SISO	2422	/	/	1	2.31	-27.69	Pass
		2437	/	/	1	2.31	-27.69	Pass
		2452	/	/	1	2.31	-27.69	Pass
802.11ax (HE20)	SISO	2412	SU	/	1	4.32	-25.68	Pass
		2437	SU	/	1	4.32	-25.68	Pass
		2462	SU	/	1	4.32	-25.68	Pass




802.11ax (HE40)	SISO	2422	SU	/	1	1.90	-28.10	Pass
		2437	SU	/	1	1.90	-28.10	Pass
		2452	SU	/	1	1.90	-28.10	Pass
Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.								


5.2 Test Graph

5.2.1 Ref


802.11b LCH 2412MHz_Ant1 (SISO)_NTNV




802.11b MCH 2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz Ant1 (SISO) NTN




802.11g LCH 2412MHz Ant1 (SISO) NTN




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO) NTN




802.11n(HT20) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40) HCH_2452MHz_Ant1 (SISO)_NTNV




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTN




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTN



802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV




5.2.2 CSE


802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11b MCH 2437MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz_Ant1 (SISO)_NTNV




802.11b HCH 2462MHz_Ant1 (SISO) NTN




802.11g LCH 2412MHz_Ant1 (SISO) NTN




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT20) HCH_2462MHz_Ant1 (SISO) NTN




802.11n(HT20) HCH 2462MHz Ant1 (SISO) NTN




802.11n(HT40) LCH 2422MHz Ant1 (SISO) NTN




802.11n(HT40) LCH_2422MHz_Ant1 (SISO) NTN




802.11n(HT40) MCH_2437MHz_Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11n(HT40) HCH 2452MHz Ant1 (SISO) NTN




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) LCH 2412MHz SU / Ant1 (SISO) NTNV




802.11ax(HE20) MCH_2437MHz_SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH_2462MHz_SU / Ant1 (SISO) NTNV




802.11ax(HE20) HCH 2462MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) LCH 2422MHz SU / Ant1 (SISO) NTNV




802.11ax(HE40) MCH 2437MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV



802.11ax(HE40) HCH 2452MHz SU / Ant1 (SISO) NTNV



- End of the Report -