



REPORT No.: SZ25040459W03

TEST REPORT

APPLICANT : WALTON DIGI-TECH
INDUSTRIES LIMITED

PRODUCT NAME : Laptop

MODEL NAME : ACC RX513H

BRAND NAME : ACC

FCC ID : 2BLY9-ACCRX513H

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2025-05-23

TEST DATE : 2025-06-03 to 2025-06-27

ISSUE DATE : 2025-12-19

Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	12
3. Test Results	15
3.1. Antenna Requirement	15
3.2. Duty Cycle of Test Signal	16
3.3. Maximum Peak and Average Conducted Output Power	17
3.4. 6 dB Bandwidth	18
3.5. Conducted Spurious Emissions and Band Edge	19
3.6. Power Spectral Density	20
3.7. Conducted Emission	21
3.8. Restricted Frequency Bands	22
3.9. Radiated Emission	23
Annex A Test Data and Result	25



REPORT No.: SZ25040459W03

Change History		
Version	Date	Reason for change
1.0	2025-12-19	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Jun. 08, 2025	Lin Haoyang	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Jun. 08, 2025	Lin Haoyang	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Jun. 08, 2025	Lin Haoyang	PASS	/
5	15.247(a)	Bandwidth	Jun. 08, 2025	Lin Haoyang	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jun. 08, 2025	Lin Haoyang	PASS	/
7	15.247(e)	Power Spectral Density	Jun. 08, 2025	Lin Haoyang	PASS	/
8	15.207	Conducted Emission	Jun. 03, 2025	Fan Shengquan Wang Yapeng	PASS	/
9	15.247(d)	Restricted Frequency Bands	Jun. 19 to 27, 2025	Zhong Xiangyun	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Jun. 19 to 27, 2025	Zhong Xiangyun	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the "Remark".

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.01.15	2026.01.14
Power Sensor	MY54180008	U2021XA	Agilent	2024.09.11	2025.09.10
Attenuator	MTJ6004-20	VAT-10+	MTJ Cooperation	N/A	N/A
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2025.05.15	2026.05.14
LISN	103131	ENV 216	R&S	2025.03.20	2026.03.19
RF Coaxial Cable (DC-100MHz)	EMC-CE-00514	N/A	N/A	2025.05.06	2026.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2025.05.13	2026.05.12
Test Antenna - Bi-Log	01267	VULB 9163	Schwarzbeck	2024.07.26	2025.07.25
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2025.05.16	2026.05.15
Test Antenna – Horn	02634	BBHA 9120D	Schwarzbeck	2024.06.29	2025.06.28
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
				2025.06.20	2026.06.19
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2025.05.13	2026.05.12
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.05.13	2026.05.12
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2024.09.11	2025.09.10
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2024.09.11	2025.09.10
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.11.30	2025.11.29



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174

2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	WALTON DIGI-TECH INDUSTRIES LIMITED
Applicant Address:	Chandra, Kaliakair, Gazipur, Bangladesh.
Manufacturer:	WALTON DIGI-TECH INDUSTRIES LIMITED
Manufacturer Address:	Chandra, Kaliakair, Gazipur, Bangladesh.

2.2. Information of EUT

Product Name:	Laptop		
Sample No.:	1#, 3#, 4#		
Hardware Version:	N156EAL01_MB_V11		
Software Version:	BIOS_N160ARL01_V1.11_WALTON		
Modulation Technology:	DSSS, OFDM		
Modulation Type:	Refer to section 2.4.1		
Wireless Technology:	802.11b, 802.11g, 802.11n (HT20), 802.11n (HT40)		
Operating Frequency Range:	2412MHz–2462MHz		
Antenna Type:	ABS Antenna		
Antenna Gain (dBi):	ANT 1	ANT 2	Directional Gain Note 2
	1.66	1.04	4.37
Accessory Information:	Battery		
	Brand Name:	N/A	
	Model No.:	528282	
	Serial No.:	N/A	
	Capacity:	6460mAh	
	Rated Voltage:	11.61V	
	Charge Limit:	13.35V	
	Manufacturer:	HuiZhou GanFeng LiEnergy Battery Technology CO.,LTD.	

Accessory Information:	AC Adapter	
	Brand Name:	N/A
	Model No.:	TN-050200U3
	Serial No.:	N/A
	Rated Output:	5V $\approx$ 3A; 9V $\approx$ 3A; 12V $\approx$ 3A; 15V $\approx$ 3A; 20V $\approx$ 3.25A;
	Rated Input:	100-240V $\sim$ 50/60Hz, 1.4A
	Manufacturer:	Guangdong Deshen Industrial Co.,Ltd

Note 1: The EUT supports a MIMO function. Physically, the EUT provides two completed transmitters and two receivers for 802.11n modulation mode.

Modulation Mode:	TX Function
802.11b/g	1TX
802.11n	2TX

Note 2: Directional gain is calculated based on KDB 662911 D01

KDB 662911 D01 Directional Gain Calculation			
Clause	Type	Correlation	Calculation formula
F.2.a	Equal G_{ANT} & Power	☐ (i). Correlated	$G_{ANT} + 10\log(N_{ANT})$
		☐ (ii). Uncorrelated	G_{ANT}
F.2.d	Unequal G_{ANT} & Equal Power	☒ (i). Correlated	$10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/N_{ANT}]$
		☐ (ii). Uncorrelated	$10\log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N_{ANT}]$

Where G_{ANT} is the antenna gain in dBi, N_{ANT} is the number of outputs.

Note 3: All radiation test items for 802.11n modulation mode operate at MIMO mode during the test. Other modulation mode operate at SISO mode, both of the two antennas were tested separately, we only recorded the worst test result (ANT 2) in this report.

Note 4: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		
Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
40MHz	3	2422	8	2447
	4	2427	9	2452
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate
802.11b	20	DSSS	DBPSK	1/2/5.5/11Mbps
			DQPSK	
			CCK	
802.11g	20	OFDM	BPSK	6/9/12/18/24/36/48/54Mbps
			QPSK	
			16QAM	
			64QAM	
802.11n	20 (HT20)	OFDM	BPSK	MCS0~MCS7
			QPSK	
			16QAM	
			64QAM	

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.


Note2: The RF signal transmission of EUT is controlled by the build-in engineering mode which is provided by the manufacturer. The recorded power setting value is the maximum that the engineering mode has configuration during testing.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☒ PCB Antenna ☐ PIFA Antenna ☐ ABS Antenna	☒ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout



3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak and Average Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 and A.3 in this report.



3.4.6 dB Bandwidth

3.4.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.4.1.Test Procedures

KDB 558074 Section 8.2 was used in order to prove compliance.

3.4.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.3.Test Result

Refer to Annex A.4 in this report.



3.5. Conducted Spurious Emissions and Band Edge

3.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.5.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.6. Power Spectral Density

3.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 30kHz
- d) Set VBW to 100kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level and recorded as PD
- j) Use below formula to calculate the Conducted PSD value that at specified RBW:

Conducted PSD = PD - 10lg(30k/3k)

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.7 in this report.

3.7. Conducted Emission

3.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.7.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2020.

3.7.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.7.4. Test Result

Refer to Annex A.8 in this report.



3.8. Restricted Frequency Bands

3.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.8.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.8.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.8.4. Test Result

Refer to Annex A.9 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4.Test Result

Refer to Annex A.10 in this report.



Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	99.48	0.02	0.12
NVNT	b	2437	Ant1	99.45	0.02	0.12
NVNT	b	2462	Ant1	99.48	0.02	0.12
NVNT	b	2412	Ant2	99.45	0.02	0.12
NVNT	b	2437	Ant2	99.48	0.02	0.12
NVNT	b	2462	Ant2	99.45	0.02	0.12
NVNT	g	2412	Ant1	76.29	1.18	6.76
NVNT	g	2437	Ant1	76.53	1.16	6.67
NVNT	g	2462	Ant1	76.53	1.16	6.67
NVNT	g	2412	Ant2	76.29	1.18	6.76
NVNT	g	2437	Ant2	75.51	1.22	6.76
NVNT	g	2462	Ant2	76.29	1.18	6.76
NVNT	n20	2412	Ant1	78.76	1.04	5.62
NVNT	n20	2437	Ant1	79.46	1	5.62
NVNT	n20	2462	Ant1	78.57	1.05	5.68
NVNT	n20	2412	Ant2	78.57	1.05	5.68
NVNT	n20	2437	Ant2	78.57	1.05	5.68
NVNT	n20	2462	Ant2	78.57	1.05	5.68
NVNT	n20	2412	Sum	86.19	0.65	3.21
NVNT	n20	2437	Sum	86.67	0.62	3.21
NVNT	n20	2462	Sum	86.19	0.65	3.21
NVNT	n40	2422	Ant1	78.95	1.03	5.56
NVNT	n40	2437	Ant1	78.95	1.03	5.56
NVNT	n40	2452	Ant1	78.95	1.03	5.56
NVNT	n40	2422	Ant2	78.95	1.03	5.56
NVNT	n40	2437	Ant2	78.95	1.03	5.56
NVNT	n40	2452	Ant2	79.13	1.02	5.49
NVNT	n40	2422	Sum	86.49	0.63	3.13
NVNT	n40	2437	Sum	86.49	0.63	3.12
NVNT	n40	2452	Sum	86.56	0.63	3.11

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1




Duty Cycle NVNT b 2412MHz Ant2







Duty Cycle NVNT b 2437MHz Ant2




Duty Cycle NVNT b 2462MHz Ant2




Duty Cycle NVNT g 2412MHz Ant1




Duty Cycle NVNT g 2437MHz Ant1



Duty Cycle NVNT g 2462MHz Ant1




Duty Cycle NVNT g 2412MHz Ant2







Duty Cycle NVNT g 2437MHz Ant2




Duty Cycle NVNT g 2462MHz Ant2




Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2437MHz Ant1




Duty Cycle NVNT n20 2462MHz Ant1




Duty Cycle NVNT n20 2412MHz Ant2




Duty Cycle NVNT n20 2437MHz Ant2




Duty Cycle NVNT n20 2462MHz Ant2




Duty Cycle NVNT n20 2412MHz Sum




Duty Cycle NVNT n20 2437MHz Sum




Duty Cycle NVNT n20 2462MHz Sum




Duty Cycle NVNT n40 2422MHz Ant1




Duty Cycle NVNT n40 2437MHz Ant1




Duty Cycle NVNT n40 2452MHz Ant1




Duty Cycle NVNT n40 2422MHz Ant2




Duty Cycle NVNT n40 2437MHz Ant2



Duty Cycle NVNT n40 2452MHz Ant2




Duty Cycle NVNT n40 2422MHz Sum






Duty Cycle NVNT n40 2437MHz Sum



Duty Cycle NVNT n40 2452MHz Sum



**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	17.18	0	17.18	0.05224	30	Pass
NVNT	b	2437	Ant1	17.35	0	17.35	0.05433	30	Pass
NVNT	b	2462	Ant1	17.44	0	17.44	0.05546	30	Pass
NVNT	b	2412	Ant2	16.82	0	16.82	0.04808	30	Pass
NVNT	b	2437	Ant2	16.75	0	16.75	0.04732	30	Pass
NVNT	b	2462	Ant2	17.17	0	17.17	0.05212	30	Pass
NVNT	g	2412	Ant1	20.38	0	20.38	0.10914	30	Pass
NVNT	g	2437	Ant1	22.49	0	22.49	0.17742	30	Pass
NVNT	g	2462	Ant1	22.58	0	22.58	0.18113	30	Pass
NVNT	g	2412	Ant2	19.83	0	19.83	0.09616	30	Pass
NVNT	g	2437	Ant2	21.87	0	21.87	0.15382	30	Pass
NVNT	g	2462	Ant2	22.31	0	22.31	0.17022	30	Pass
NVNT	n20	2412	Ant1	20.04	0	20.04	0.10093	30	Pass
NVNT	n20	2437	Ant1	22.09	0	22.09	0.16181	30	Pass
NVNT	n20	2462	Ant1	22.24	0	22.24	0.16749	30	Pass
NVNT	n20	2412	Ant2	19.62	0	19.62	0.09162	30	Pass
NVNT	n20	2437	Ant2	21.5	0	21.5	0.14125	30	Pass
NVNT	n20	2462	Ant2	22.01	0	22.01	0.15885	30	Pass
NVNT	n20	2412	Ant1	16.95	0	16.95	0.04955	30	Pass
NVNT	n20	2412	Ant2	16.47	0	16.47	0.04436	30	Pass
NVNT	n20	2412	Sum	NaN	NaN	19.73	0.09391	30	Pass
NVNT	n20	2437	Ant1	19.18	0	19.18	0.08279	30	Pass
NVNT	n20	2437	Ant2	18.38	0	18.38	0.06887	30	Pass
NVNT	n20	2437	Sum	NaN	NaN	21.81	0.15166	30	Pass
NVNT	n20	2462	Ant1	19.34	0	19.34	0.0859	30	Pass
NVNT	n20	2462	Ant2	18.86	0	18.86	0.07691	30	Pass
NVNT	n20	2462	Sum	NaN	NaN	22.12	0.16281	30	Pass
NVNT	n40	2422	Ant1	21.45	0	21.45	0.13964	30	Pass
NVNT	n40	2437	Ant1	22.9	0	22.9	0.19498	30	Pass
NVNT	n40	2452	Ant1	21.93	0	21.93	0.15596	30	Pass
NVNT	n40	2422	Ant2	22.08	0	22.08	0.16144	30	Pass
NVNT	n40	2437	Ant2	22.51	0	22.51	0.17824	30	Pass
NVNT	n40	2452	Ant2	22.85	0	22.85	0.19275	30	Pass




REPORT No.: SZ25040459W03

NVNT	n40	2422	Ant1	20.13	0	20.13	0.10304	30	Pass
NVNT	n40	2422	Ant2	19.4	0	19.4	0.0871	30	Pass
NVNT	n40	2422	Sum	NaN	NaN	22.79	0.19013	30	Pass
NVNT	n40	2437	Ant1	20.24	0	20.24	0.10568	30	Pass
NVNT	n40	2437	Ant2	19.31	0	19.31	0.08531	30	Pass
NVNT	n40	2437	Sum	NaN	NaN	22.81	0.19099	30	Pass
NVNT	n40	2452	Ant1	20.27	0	20.27	0.10641	30	Pass
NVNT	n40	2452	Ant2	19.59	0	19.59	0.09099	30	Pass
NVNT	n40	2452	Sum	NaN	NaN	22.95	0.19741	30	Pass




Test Graphs


Peak Power NVNT b 2412MHz Ant1




Peak Power NVNT b 2437MHz Ant1




Peak Power NVNT b 2462MHz Ant1




Peak Power NVNT b 2412MHz Ant2



Peak Power NVNT b 2437MHz Ant2




Peak Power NVNT b 2462MHz Ant2






Peak Power NVNT g 2412MHz Ant1



Peak Power NVNT g 2437MHz Ant1




Peak Power NVNT g 2462MHz Ant1



Peak Power NVNT g 2412MHz Ant2




Peak Power NVNT g 2437MHz Ant2



Peak Power NVNT g 2462MHz Ant2




Peak Power NVNT n20 2412MHz Ant1



Peak Power NVNT n20 2437MHz Ant1




Peak Power NVNT n20 2462MHz Ant1



Peak Power NVNT n20 2412MHz Ant2




Peak Power NVNT n20 2437MHz Ant2



Peak Power NVNT n20 2462MHz Ant2




Peak Power NVNT n20 2412MHz Ant1



Peak Power NVNT n20 2412MHz Ant2



Peak Power NVNT n20 2437MHz Ant1



Peak Power NVNT n20 2437MHz Ant2






Peak Power NVNT n20 2462MHz Ant1




Peak Power NVNT n20 2462MHz Ant2




Peak Power NVNT n40 2422MHz Ant1




Peak Power NVNT n40 2437MHz Ant1




Peak Power NVNT n40 2452MHz Ant1




Peak Power NVNT n40 2422MHz Ant2




Peak Power NVNT n40 2437MHz Ant2




Peak Power NVNT n40 2452MHz Ant2




Peak Power NVNT n40 2422MHz Ant1




Peak Power NVNT n40 2422MHz Ant2




Peak Power NVNT n40 2437MHz Ant1




Peak Power NVNT n40 2437MHz Ant2



Peak Power NVNT n40 2452MHz Ant1



Peak Power NVNT n40 2452MHz Ant2



**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	14.56	0.02	14.58	0.02871	30	Pass
NVNT	b	2437	Ant1	14.75	0.02	14.77	0.02999	30	Pass
NVNT	b	2462	Ant1	14.83	0.02	14.85	0.03055	30	Pass
NVNT	b	2412	Ant2	14.2	0.02	14.22	0.02642	30	Pass
NVNT	b	2437	Ant2	14.05	0.02	14.07	0.02553	30	Pass
NVNT	b	2462	Ant2	14.45	0.02	14.47	0.02799	30	Pass
NVNT	g	2412	Ant1	11.75	1.18	12.93	0.01963	30	Pass
NVNT	g	2437	Ant1	13.91	1.16	15.07	0.03214	30	Pass
NVNT	g	2462	Ant1	14.05	1.16	15.21	0.03319	30	Pass
NVNT	g	2412	Ant2	11.38	1.18	12.56	0.01803	30	Pass
NVNT	g	2437	Ant2	13.35	1.22	14.57	0.02864	30	Pass
NVNT	g	2462	Ant2	13.78	1.18	14.96	0.03133	30	Pass
NVNT	n20	2412	Ant1	11.89	1.04	12.93	0.01963	30	Pass
NVNT	n20	2437	Ant1	13.98	1	14.98	0.03148	30	Pass
NVNT	n20	2462	Ant1	14.17	1.05	15.22	0.03327	30	Pass
NVNT	n20	2412	Ant2	11.51	1.05	12.56	0.01803	30	Pass
NVNT	n20	2437	Ant2	13.47	1.05	14.52	0.02831	30	Pass
NVNT	n20	2462	Ant2	13.91	1.05	14.96	0.03133	30	Pass
NVNT	n20	2412	Ant1	8.99	0.65	9.64	0.0092	30	Pass
NVNT	n20	2412	Ant2	8.6	0.65	9.25	0.00841	30	Pass
NVNT	n20	2412	Sum	NaN	NaN	12.46	0.01762	30	Pass
NVNT	n20	2437	Ant1	11.35	0.62	11.97	0.01574	30	Pass
NVNT	n20	2437	Ant2	10.57	0.62	11.19	0.01315	30	Pass
NVNT	n20	2437	Sum	NaN	NaN	14.61	0.02889	30	Pass
NVNT	n20	2462	Ant1	11.55	0.65	12.2	0.0166	30	Pass
NVNT	n20	2462	Ant2	10.97	0.65	11.62	0.01452	30	Pass
NVNT	n20	2462	Sum	NaN	NaN	14.93	0.03112	30	Pass
NVNT	n40	2422	Ant1	12.93	1.03	13.96	0.02489	30	Pass
NVNT	n40	2437	Ant1	14.37	1.03	15.4	0.03467	30	Pass
NVNT	n40	2452	Ant1	13.34	1.03	14.37	0.02735	30	Pass
NVNT	n40	2422	Ant2	13.53	1.03	14.56	0.02858	30	Pass
NVNT	n40	2437	Ant2	13.92	1.03	14.95	0.03126	30	Pass
NVNT	n40	2452	Ant2	14.25	1.02	15.27	0.03365	30	Pass



REPORT No.: SZ25040459W03


NVNT	n40	2422	Ant1	11.87	0.63	12.5	0.01778	30	Pass
NVNT	n40	2422	Ant2	11.17	0.63	11.8	0.01514	30	Pass
NVNT	n40	2422	Sum	NaN	NaN	15.17	0.03292	30	Pass
NVNT	n40	2437	Ant1	12	0.63	12.63	0.01832	30	Pass
NVNT	n40	2437	Ant2	11.11	0.63	11.74	0.01493	30	Pass
NVNT	n40	2437	Sum	NaN	NaN	15.22	0.03325	30	Pass
NVNT	n40	2452	Ant1	12.02	0.63	12.65	0.01841	30	Pass
NVNT	n40	2452	Ant2	11.35	0.63	11.98	0.01578	30	Pass
NVNT	n40	2452	Sum	NaN	NaN	15.34	0.03418	30	Pass






Test Graphs


Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1




Average Power NVNT b 2462MHz Ant1




Average Power NVNT b 2412MHz Ant2



Average Power NVNT b 2437MHz Ant2




Average Power NVNT b 2462MHz Ant2






Average Power NVNT g 2412MHz Ant1




Average Power NVNT g 2437MHz Ant1







Average Power NVNT g 2462MHz Ant1



Average Power NVNT g 2412MHz Ant2




Average Power NVNT g 2437MHz Ant2



Average Power NVNT g 2462MHz Ant2




Average Power NVNT n20 2412MHz Ant1




Average Power NVNT n20 2437MHz Ant1




Average Power NVNT n20 2462MHz Ant1




Average Power NVNT n20 2412MHz Ant2




Average Power NVNT n20 2437MHz Ant2




Average Power NVNT n20 2462MHz Ant2




Average Power NVNT n20 2412MHz Ant1




Average Power NVNT n20 2412MHz Ant2




Average Power NVNT n20 2437MHz Ant1




Average Power NVNT n20 2437MHz Ant2



Average Power NVNT n20 2462MHz Ant1




Average Power NVNT n20 2462MHz Ant2







Average Power NVNT n40 2422MHz Ant1




Average Power NVNT n40 2437MHz Ant1




Average Power NVNT n40 2452MHz Ant1




Average Power NVNT n40 2422MHz Ant2



Average Power NVNT n40 2437MHz Ant2




Average Power NVNT n40 2452MHz Ant2







Average Power NVNT n40 2422MHz Ant1




Average Power NVNT n40 2422MHz Ant2




Average Power NVNT n40 2437MHz Ant1




Average Power NVNT n40 2437MHz Ant2



Average Power NVNT n40 2452MHz Ant1



Average Power NVNT n40 2452MHz Ant2



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	10.11	0.5	Pass
NVNT	b	2437	Ant1	10.08	0.5	Pass
NVNT	b	2462	Ant1	10.1	0.5	Pass
NVNT	b	2412	Ant2	10.1	0.5	Pass
NVNT	b	2437	Ant2	10.09	0.5	Pass
NVNT	b	2462	Ant2	10.1	0.5	Pass
NVNT	g	2412	Ant1	15.13	0.5	Pass
NVNT	g	2437	Ant1	15.13	0.5	Pass
NVNT	g	2462	Ant1	15.13	0.5	Pass
NVNT	g	2412	Ant2	15.13	0.5	Pass
NVNT	g	2437	Ant2	15.13	0.5	Pass
NVNT	g	2462	Ant2	15.13	0.5	Pass
NVNT	n20	2412	Ant1	15.12	0.5	Pass
NVNT	n20	2437	Ant1	15.13	0.5	Pass
NVNT	n20	2462	Ant1	15.13	0.5	Pass
NVNT	n20	2412	Ant2	15.13	0.5	Pass
NVNT	n20	2437	Ant2	15.13	0.5	Pass
NVNT	n20	2462	Ant2	15.13	0.5	Pass
NVNT	n20	2412	Ant1	15.13	0.5	Pass
NVNT	n20	2412	Ant2	15.13	0.5	Pass
NVNT	n20	2437	Ant1	15.13	0.5	Pass
NVNT	n20	2437	Ant2	15.12	0.5	Pass
NVNT	n20	2462	Ant1	15.13	0.5	Pass
NVNT	n20	2462	Ant2	15.13	0.5	Pass
NVNT	n40	2422	Ant1	35.09	0.5	Pass
NVNT	n40	2437	Ant1	35.09	0.5	Pass
NVNT	n40	2452	Ant1	35.1	0.5	Pass
NVNT	n40	2422	Ant2	35.09	0.5	Pass
NVNT	n40	2437	Ant2	35.1	0.5	Pass
NVNT	n40	2452	Ant2	35.1	0.5	Pass
NVNT	n40	2422	Ant1	35.1	0.5	Pass
NVNT	n40	2422	Ant2	35.1	0.5	Pass
NVNT	n40	2437	Ant1	35.1	0.5	Pass
NVNT	n40	2437	Ant2	35.08	0.5	Pass
NVNT	n40	2452	Ant1	35.1	0.5	Pass




REPORT No.: SZ25040459W03

NVNT	n40	2452	Ant2	35.1	0.5	Pass
------	-----	------	------	------	-----	------




Test Graphs


-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2437MHz Ant1




-6dB Bandwidth NVNT b 2462MHz Ant1




-6dB Bandwidth NVNT b 2412MHz Ant2




-6dB Bandwidth NVNT b 2437MHz Ant2



-6dB Bandwidth NVNT b 2462MHz Ant2




-6dB Bandwidth NVNT g 2412MHz Ant1




-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant2




-6dB Bandwidth NVNT g 2437MHz Ant2




-6dB Bandwidth NVNT g 2462MHz Ant2




-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant2

