

FCC TEST REPORT

FCC ID:2BLYB-E10

Report No..... : ZHT-251114133W01-2

Product..... : Phone Holder With Wireless Speaker

Trademark..... : /

Model(s)..... : E10
BH009A, BH009B BH009C, BH009D, BH009E

Model Difference..... : E10 is tested model, other models are derivative models .The models are identical in circuit, only different on the model names and colors. So the test data of E10 can represent the remaining models.

Applicant..... : Dongguan Siliang Electronic Technology Co., Ltd

Address..... : Room 1301, Building 2, No. 69 Fengqing Road, Fenggang, Fenggang Town, Dongguan City, Guangdong Province, China

Manufacturer..... : Dongguan Siliang Electronic Technology Co., Ltd

Address..... : Room 1301, Building 2, No. 69 Fengqing Road, Fenggang, Fenggang Town, Dongguan City, Guangdong Province, China

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : Nov. 14, 2025

Date of Test(s)..... : Nov. 14, 2025 to Nov. 30, 2025

Date of Issue..... : Nov. 30, 2025

Standard..... : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Test procedure..... : KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2020

In the configuration tested, the EUT complied with the standards specified above.

Prepared by

Leon Li

Leon Li/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director

Approved by:

Levi Lee

Levi Lee/ Manager

Note: This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report. This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.



	Page
1. TEST SUMMARY	3
2. GENERAL INFORMATION	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 Test Setup Configuration	6
2.3 Support Equipment	6
2.4 Test Mode	6
3. TEST FACILITY AND TEST INSTRUMENT USED	7
3.1 TEST FACILITY	7
3.2 INSTRUMENT LIST FOR ALL TEST ITEMS	7
3.3 Testing software	9
3.4 MEASUREMENT UNCERTAINTY	9
4. EMC EMISSION TEST	10
4.1 Conducted emissions	10
4.2 Radiated emissions	14
5. RADIATED BAND EMISSION MEASUREMENT	22
5.1 Test Requirement:	22
5.2 TEST PROCEDURE	22
5.3 DEVIATION FROM TEST STANDARD	23
5.4 TEST SETUP	23
5.5 EUT OPERATING CONDITIONS	23
5.6 TEST RESULT	24
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	26
6.1 Limit	26
6.2 Test Setup	26
6.3 Test procedure	26
6.4 DEVIATION FROM STANDARD	26
6.5 Test Result	27
7. 20DB&99% BANDWIDTH	51
7.1 Test Setup	51
7.2 Limit	51
7.3 Test procedure	51
7.4 DEVIATION FROM STANDARD	51
7.5 Test Result	51
8. MAXIMUM PEAK OUTPUT POWER	62
8.1 Block Diagram Of Test Setup	62
8.2 Limit	62
8.3 Test procedure	62
8.4 DEVIATION FROM STANDARD	62
8.5 Test Result	62
9. HOPPING CHANNEL SEPARATION	68
9.1 Test Setup	68
9.2 Test procedure	68
9.3 DEVIATION FROM STANDARD	68
9.4 Test Result	68
10. NUMBER OF HOPPING FREQUENCY	74
10.1 Test Setup	74
10.2 Test procedure	74
10.3 DEVIATION FROM STANDARD	74
10.4 Test Result	74
11. DWELL TIME	80
11.1 Test Setup	80
11.2 Test procedure	80
11.3 DEVIATION FROM STANDARD	80
11.4 Test Result	81
12. ANTENNA REQUIREMENT	91
13. TEST SETUP PHOTO	92
14. EUT CONSTRUCTIONAL DETAILS	92



Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.



2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Phone Holder With Wireless Speaker
Test Model No.:	E10
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz-2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	PCB antenna
Antenna gain:	1.68dBi
Power supply:	Input: 5 V  1 A or DC 3.7 V by Battery
Sample Number:	251114133YP001
Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Guangdong Zhonghan Testing Technology Co., Ltd. does not assume any responsibility.	



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz



2.2 Test Setup Configuration


Conducted Emission



Radiated Emission



RF Conducted Emission



2.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	AC Adapter	Huizhou Jinhu Industrial Development Co., Ltd.	VCBAJACH	/	AE
E-2	Laptop	Lenovo (Beijing) Co., Ltd	ThinkPad E480	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) The test software is the FCC_assist_1.0.2.2 which can set the EUT into the individual test modes. TX Power: Default

2.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

**3. TEST FACILITY AND TEST INSTRUMENT USED****3.1 TEST FACILITY**

Guangdong Zhonghan Testing Technology Co., Ltd.
Add.: Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

3.2 INSTRUMENT LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
2	Loop Antenna	TESEQ	HLA6121	58357	Sept. 8, 2025	Sept. 7, 2026
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	May 6, 2025	May 5, 2026
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 7, 2025	May 6, 2026
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	May 15, 2025	May 14, 2026
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	May 15, 2025	May 14, 2026
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	Oct. 20, 2025	Oct. 19, 2026
8	Amplifier	AEROFLEX	100KHz-40GHz	097	Oct. 20, 2025	Oct. 19, 2026
9	Spectrum Analyzer	R&S	FSV40	101413	Oct. 20, 2025	Oct. 19, 2026
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 7, 2025	May 6, 2026
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	May 7, 2025	May 6, 2026
12	Single Generator	Agilent	N5182A	MY48180575	May 7, 2025	May 6, 2026
13	Power Sensor	MWRFTest	MW100-RFCB	/	May 7, 2025	May 6, 2026
14	Power Amplifier Shielding Room	EMToni	2m3m3m	/	Nov. 25, 2021	Nov. 24, 2026
15	CABLE	EMToni	DA800-NM-NM-11000MM	/	May 6, 2025	May 5, 2026



ZHONGHAN

Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	May 6, 2025	May 5, 2026
LISN	R&S	ENV216	102794	May 6, 2025	May 5, 2026
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	May 7, 2025	May 6, 2026
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	May 7, 2025	May 6, 2026
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 8, 2025	May 7, 2026
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 8, 2025	May 7, 2026
CABLE	EMToni	G223-NM-BNCM-2000MM	/	May 7, 2025	May 6, 2026

Conducted Test Instrument

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	Oct. 20, 2025	Oct. 19, 2026
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 7, 2025	May 6, 2026
3	Power Sensor	MWRFTest	MW100-RFCB	/	May 7, 2025	May 6, 2026



Project	Software name	Edition
RF Conducted	MTS 8310	2.0.0.0
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$U=0.92\text{dB}$
2	RF conducted power	$U=0.16\text{dB}$
3	Spurious emissions conducted	$U=0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$U=1.6\text{dB}$
5	All radiated emissions (<1G)	$U=5.1\text{dB}$
6	All radiated emissions (>1G)	$U=4.65\text{dB}$
7	Temperature	$U=0.5^{\circ}\text{C}$
8	Humidity	$U=2\%$
9	Occupied Bandwidth	$U=4.96\%$
10	Power Spectral Density	$U=0.71\text{dB}$

Decision Rule

☒ Uncertainty is not included

☐ Uncertainty is included



4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen 8.8
Test Method:	ANSI C63.10-2020
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 Test result

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3570	30.88	9.97	40.85	58.80	-17.95	QP
2	0.3570	28.61	9.97	38.58	48.80	-10.22	AVG
3	1.0680	30.81	10.06	40.87	56.00	-15.13	QP
4 *	1.0680	28.68	10.06	38.74	46.00	-7.26	AVG
5	1.7790	27.15	10.06	37.21	56.00	-18.79	QP
6	1.7790	23.28	10.06	33.34	46.00	-12.66	AVG
7	2.4900	27.67	10.07	37.74	56.00	-18.26	QP
8	2.4900	20.54	10.07	30.61	46.00	-15.39	AVG
9	3.9165	28.70	10.09	38.79	56.00	-17.21	QP
10	3.9165	24.64	10.09	34.73	46.00	-11.27	AVG
11	4.6275	28.49	10.11	38.60	56.00	-17.40	QP
12	4.6275	24.95	10.11	35.06	46.00	-10.94	AVG


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 8DPSK mode (Low Channel: 2402MHz).



ZHONGHAN

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3570	32.30	9.97	42.27	58.80	-16.53	QP
2	0.3570	29.11	9.97	39.08	48.80	-9.72	AVG
3	1.0680	30.26	10.06	40.32	56.00	-15.68	QP
4 *	1.0680	27.21	10.06	37.27	46.00	-8.73	AVG
5	1.7790	31.07	10.06	41.13	56.00	-14.87	QP
6	1.7790	26.79	10.06	36.85	46.00	-9.15	AVG
7	2.4900	29.27	10.07	39.34	56.00	-16.66	QP
8	2.4900	21.42	10.07	31.49	46.00	-14.51	AVG
9	3.9165	28.62	10.09	38.71	56.00	-17.29	QP
10	3.9165	23.89	10.09	33.98	46.00	-12.02	AVG
11	4.6320	30.37	10.11	40.48	56.00	-15.52	QP
12	4.6320	26.03	10.11	36.14	46.00	-9.86	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 8DPSK mode (Low Channel: 2402MHz).



4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10-2020				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micроволts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


Between 30MHz – 1GHz

Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7 V		





Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Vertical
Test Voltage:	DC 3.7 V		



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case 8DPSK mode(Low Channel:2402MHz).



GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	58.45	30.55	5.77	24.66	58.33	74	-15.67	Pk
V	4804	44.39	30.55	5.77	24.66	44.27	54	-9.73	AV
V	7206	56.23	30.33	6.32	24.55	56.77	74	-17.23	Pk
V	7206	44.81	30.33	6.32	24.55	45.35	54	-8.65	AV
H	4804	58.97	30.55	5.77	24.66	58.85	74	-15.15	Pk
H	4804	41.76	30.55	5.77	24.66	41.64	54	-12.36	AV
H	7206	56.74	30.33	6.32	24.55	57.28	74	-16.72	Pk
H	7206	43.14	30.33	6.32	24.55	43.68	54	-10.32	AV
Middle Channel:2441MHz									
V	4882	56.3	30.55	5.77	24.66	56.18	74	-17.82	Pk
V	4882	41.93	30.55	5.77	24.66	41.81	54	-12.19	AV
V	7323	58.57	30.33	6.32	24.55	59.11	74	-14.89	Pk
V	7323	42.79	30.33	6.32	24.55	43.33	54	-10.67	AV
H	4882	56.91	30.55	5.77	24.66	56.79	74	-17.21	Pk
H	4882	41.55	30.55	5.77	24.66	41.43	54	-12.57	AV
H	7323	56.31	30.33	6.32	24.55	56.85	74	-17.15	Pk
H	7323	41.17	30.33	6.32	24.55	41.71	54	-12.29	AV
High Channel:2480MHz									
V	4960	56.94	30.55	5.77	24.66	56.82	74	-17.18	Pk
V	4960	41.56	30.55	5.77	24.66	41.44	54	-12.56	AV
V	7440	58.78	30.33	6.32	24.55	59.32	74	-14.68	Pk
V	7440	43.32	30.33	6.32	24.55	43.86	54	-10.14	AV
H	4960	58.88	30.55	5.77	24.66	58.76	74	-15.24	Pk
H	4960	44.65	30.55	5.77	24.66	44.53	54	-9.47	AV
H	7440	56.34	30.33	6.32	24.55	56.88	74	-17.12	Pk
H	7440	43.3	30.33	6.32	24.55	43.84	54	-10.16	AV



ZHONGHAN

 $\pi/4$ DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	59.04	30.55	5.77	24.66	58.92	74	-15.08	Pk
V	4804	41.67	30.55	5.77	24.66	41.55	54	-12.45	AV
V	7206	57.62	30.33	6.32	24.55	58.16	74	-15.84	Pk
V	7206	42.55	30.33	6.32	24.55	43.09	54	-10.91	AV
H	4804	57.63	30.55	5.77	24.66	57.51	74	-16.49	Pk
H	4804	41.21	30.55	5.77	24.66	41.09	54	-12.91	AV
H	7206	57.92	30.33	6.32	24.55	58.46	74	-15.54	Pk
H	7206	43.67	30.33	6.32	24.55	44.21	54	-9.79	AV
Middle Channel:2441MHz									
V	4882	57.98	30.55	5.77	24.66	57.86	74	-16.14	Pk
V	4882	41.04	30.55	5.77	24.66	40.92	54	-13.08	AV
V	7323	58.75	30.33	6.32	24.55	59.29	74	-14.71	Pk
V	7323	44.19	30.33	6.32	24.55	44.73	54	-9.27	AV
H	4882	55.41	30.55	5.77	24.66	55.29	74	-18.71	Pk
H	4882	41.94	30.55	5.77	24.66	41.82	54	-12.18	AV
H	7323	59.88	30.33	6.32	24.55	60.42	74	-13.58	Pk
H	7323	41.95	30.33	6.32	24.55	42.49	54	-11.51	AV
High Channel:2480MHz									
V	4960	55.52	30.55	5.77	24.66	55.4	74	-18.6	Pk
V	4960	41.73	30.55	5.77	24.66	41.61	54	-12.39	AV
V	7440	59.41	30.33	6.32	24.55	59.95	74	-14.05	Pk
V	7440	41.89	30.33	6.32	24.55	42.43	54	-11.57	AV
H	4960	55.93	30.55	5.77	24.66	55.81	74	-18.19	Pk
H	4960	44.87	30.55	5.77	24.66	44.75	54	-9.25	AV
H	7440	58.02	30.33	6.32	24.55	58.56	74	-15.44	Pk
H	7440	41.16	30.33	6.32	24.55	41.7	54	-12.3	AV



ZHONGHAN

8DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	59	30.55	5.77	24.66	58.88	74	-15.12	Pk
V	4804	44.61	30.55	5.77	24.66	44.49	54	-9.51	AV
V	7206	58.94	30.33	6.32	24.55	59.48	74	-14.52	Pk
V	7206	43.71	30.33	6.32	24.55	44.25	54	-9.75	AV
H	4804	55.07	30.55	5.77	24.66	54.95	74	-19.05	Pk
H	4804	44.66	30.55	5.77	24.66	44.54	54	-9.46	AV
H	7206	58.44	30.33	6.32	24.55	58.98	74	-15.02	Pk
H	7206	44.48	30.33	6.32	24.55	45.02	54	-8.98	AV
Middle Channel:2441MHz									
V	4882	59.72	30.55	5.77	24.66	59.6	74	-14.4	Pk
V	4882	41.39	30.55	5.77	24.66	41.27	54	-12.73	AV
V	7323	57.28	30.33	6.32	24.55	57.82	74	-16.18	Pk
V	7323	41.9	30.33	6.32	24.55	42.44	54	-11.56	AV
H	4882	56.21	30.55	5.77	24.66	56.09	74	-17.91	Pk
H	4882	41.94	30.55	5.77	24.66	41.82	54	-12.18	AV
H	7323	55	30.33	6.32	24.55	55.54	74	-18.46	Pk
H	7323	41.37	30.33	6.32	24.55	41.91	54	-12.09	AV
High Channel:2480MHz									
V	4960	59.22	30.55	5.77	24.66	59.1	74	-14.9	Pk
V	4960	41.82	30.55	5.77	24.66	41.7	54	-12.3	AV
V	7440	59.78	30.33	6.32	24.55	60.32	74	-13.68	Pk
V	7440	43.21	30.33	6.32	24.55	43.75	54	-10.25	AV
H	4960	56.86	30.55	5.77	24.66	56.74	74	-17.26	Pk
H	4960	41.09	30.55	5.77	24.66	40.97	54	-13.03	AV
H	7440	59.05	30.33	6.32	24.55	59.59	74	-14.41	Pk
H	7440	44.94	30.33	6.32	24.55	45.48	54	-8.52	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported



5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen 8.9, RSS-Gen 8.10				
Test Method:	ANSI C63.10-2020				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



ZHONGHAN
5.6 TEST RESULT

Project No.: ZHT-251114133W01-2
Page 24 of 92

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margi n (dB)	Detec tor Type	Result
GFSK	Low Channel: 2402MHz										
	H	2390.00	59.59	30.22	4.85	23.98	58.20	74.00	-15.80	PK	PASS
	H	2390.00	46.45	30.22	4.85	23.98	45.06	54.00	-8.94	AV	PASS
	H	2400.00	60.68	30.22	4.85	23.98	59.29	74.00	-14.71	PK	PASS
	H	2400.00	48.94	30.22	4.85	23.98	47.55	54.00	-6.45	AV	PASS
	V	2390.00	61.90	30.22	4.85	23.98	60.51	74.00	-13.49	PK	PASS
	V	2390.00	46.28	30.22	4.85	23.98	44.89	54.00	-9.11	AV	PASS
	V	2400.00	61.69	30.22	4.85	23.98	60.30	74.00	-13.70	PK	PASS
	V	2400.00	47.91	30.22	4.85	23.98	46.52	54.00	-7.48	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	62.25	30.22	4.85	23.98	60.86	74.00	-13.14	PK	PASS
	H	2483.50	46.83	30.22	4.85	23.98	45.44	54.00	-8.56	AV	PASS
	H	2500.00	59.08	30.22	4.85	23.98	57.69	74.00	-16.31	PK	PASS
	H	2500.00	48.03	30.22	4.85	23.98	46.64	54.00	-7.36	AV	PASS
	V	2483.50	59.47	30.22	4.85	23.98	58.08	74.00	-15.92	PK	PASS
	V	2483.50	48.19	30.22	4.85	23.98	46.80	54.00	-7.20	AV	PASS
	V	2500.00	61.01	30.22	4.85	23.98	59.62	74.00	-14.38	PK	PASS
	V	2500.00	46.95	30.22	4.85	23.98	45.56	54.00	-8.44	AV	PASS
π/4DQPS K	Low Channel: 2402MHz										
	H	2390.00	60.23	30.22	4.85	23.98	58.84	74.00	-15.16	PK	PASS
	H	2390.00	48.41	30.22	4.85	23.98	47.02	54.00	-6.98	AV	PASS
	H	2400.00	59.81	30.22	4.85	23.98	58.42	74.00	-15.58	PK	PASS
	H	2400.00	48.91	30.22	4.85	23.98	47.52	54.00	-6.48	AV	PASS
	V	2390.00	59.14	30.22	4.85	23.98	57.75	74.00	-16.25	PK	PASS
	V	2390.00	48.87	30.22	4.85	23.98	47.48	54.00	-6.52	AV	PASS
	V	2400.00	59.81	30.22	4.85	23.98	58.42	74.00	-15.58	PK	PASS
	V	2400.00	46.05	30.22	4.85	23.98	44.66	54.00	-9.34	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	59.67	30.22	4.85	23.98	58.28	74.00	-15.72	PK	PASS
	H	2483.50	48.18	30.22	4.85	23.98	46.79	54.00	-7.21	AV	PASS
	H	2500.00	60.64	30.22	4.85	23.98	59.25	74.00	-14.75	PK	PASS
	H	2500.00	47.88	30.22	4.85	23.98	46.49	54.00	-7.51	AV	PASS
	V	2483.50	62.87	30.22	4.85	23.98	61.48	74.00	-12.52	PK	PASS
	V	2483.50	48.35	30.22	4.85	23.98	46.96	54.00	-7.04	AV	PASS
	V	2500.00	60.94	30.22	4.85	23.98	59.55	74.00	-14.45	PK	PASS
	V	2500.00	48.61	30.22	4.85	23.98	47.22	54.00	-6.78	AV	PASS



8DPSK	Low Channel: 2402MHz										
	H	2390.00	61.59	30.22	4.85	23.98	60.20	74.00	-13.80	PK	PASS
	H	2390.00	46.73	30.22	4.85	23.98	45.34	54.00	-8.66	AV	PASS
	H	2400.00	61.19	30.22	4.85	23.98	59.80	74.00	-14.20	PK	PASS
	H	2400.00	46.88	30.22	4.85	23.98	45.49	54.00	-8.51	AV	PASS
	V	2390.00	61.04	30.22	4.85	23.98	59.65	74.00	-14.35	PK	PASS
	V	2390.00	47.10	30.22	4.85	23.98	45.71	54.00	-8.29	AV	PASS
	V	2400.00	61.58	30.22	4.85	23.98	60.19	74.00	-13.81	PK	PASS
	V	2400.00	46.96	30.22	4.85	23.98	45.57	54.00	-8.43	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	59.90	30.22	4.85	23.98	58.51	74.00	-15.49	PK	PASS
	H	2483.50	47.30	30.22	4.85	23.98	45.91	54.00	-8.09	AV	PASS
	H	2500.00	59.15	30.22	4.85	23.98	57.76	74.00	-16.24	PK	PASS
	H	2500.00	48.52	30.22	4.85	23.98	47.13	54.00	-6.87	AV	PASS
	V	2483.50	59.01	30.22	4.85	23.98	57.62	74.00	-16.38	PK	PASS
	V	2483.50	46.57	30.22	4.85	23.98	45.18	54.00	-8.82	AV	PASS
	V	2500.00	62.76	30.22	4.85	23.98	61.37	74.00	-12.63	PK	PASS
	V	2500.00	47.87	30.22	4.85	23.98	46.48	54.00	-7.52	AV	PASS
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 5.5
Test Method:	ANSI C63.10

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

According to RSS-247§5.5 and RSS-Gen§8.9, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) or RSS-Gen is not required.

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD


No deviation.

**Band Edge**


Mode	Frequency (MHz)	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	No-Hopping	-44.84	-20	Pass
1-DH5	2480	No-Hopping	-55.3	-20	Pass
2-DH5	2402	No-Hopping	-47.7	-20	Pass
2-DH5	2480	No-Hopping	-54.79	-20	Pass
3-DH5	2402	No-Hopping	-46.6	-20	Pass
3-DH5	2480	No-Hopping	-53.15	-20	Pass



Test Graphs



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref







Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission


















ZHONGHAN

Band Edge(Hopping)


Mode	Frequency (MHz)	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	Hopping	-44.81	-20	Pass
1-DH5	2480	Hopping	-44.27	-20	Pass
2-DH5	2402	Hopping	-45.56	-20	Pass
2-DH5	2480	Hopping	-44.73	-20	Pass
3-DH5	2402	Hopping	-44.76	-20	Pass
3-DH5	2480	Hopping	-44.02	-20	Pass

Test Graphs


Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission








Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref




Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission








Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission








ZHONGHAN

Conducted RF Spurious Emission


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	-39.98	-20	Pass
1-DH5	2441	-39.93	-20	Pass
1-DH5	2480	-38.51	-20	Pass
2-DH5	2402	-42.37	-20	Pass
2-DH5	2441	-44.85	-20	Pass
2-DH5	2480	-39.26	-20	Pass
3-DH5	2402	-41.55	-20	Pass
3-DH5	2441	-44.6	-20	Pass
3-DH5	2480	-41.18	-20	Pass

Test Graphs


Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref




Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref




Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



**7. 20DB&99% BANDWIDTH**

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1, RSS-Gen 6.7
Test Method:	ANSI C63.10-2020

7.1 Test Setup**7.2 Limit**

According to RSS-247§5.1(a)& §5.1(b), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
8. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 100 KHz VBW record the 99% bandwidth.

7.4 DEVIATION FROM STANDARD


No deviation.

7.5 Test Result


Mode	Test channel	20dB Emission Bandwidth (MHz)	99%Bandwidth (MHz)	Result
GFSK	Lowest	1.027	0.946	Pass
	Middle	1.033	0.956	
	Highest	1.036	0.957	
$\pi/4$ DQPSK	Lowest	1.316	1.234	Pass
	Middle	1.329	1.235	
	Highest	1.356	1.231	
8DPSK	Lowest	1.299	1.221	Pass
	Middle	1.294	1.218	
	Highest	1.282	1.203	

Test Graphs


-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1





-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1

