



TEST REPORT

Applicant Name: Zhuhai Glory Technology Co., Ltd
Address: 8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town,
Zhuhai, Guangdong, 519000 China
Report Number: 2604P33883E-RF-00A
FCC ID: 2BMPT-B301

Test Standard (s)

FCC PART 15.247

Sample Description

Product Name: 4K Battery Wireless Camera
Model No.: B301, GL-228XE-I2V1B
Trade Mark: N/A
Date Received: 2026-01-23
Report Date: 2026-02-10

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:

Amanda Wei

Amanda Wei
EMC Engineer

Approved By:

Bob. Liao

Bob. Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked. This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	6
TEST METHODOLOGY	6
TEST FACILITY	6
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE AND POWER LEVEL [#]	8
SPECIAL ACCESSORIES	8
EQUIPMENT MODIFICATIONS	8
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE	9
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP	15
TEST PROCEDURE	15
CALCULATION	16
TEST DATA	16
RADIATED SPURIOUS EMISSION	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	21
CALCULATION	21
TEST DATA	22
6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	76
APPLICABLE STANDARD	76
TEST PROCEDURE	76
TEST DATA	76
MAXIMUM CONDUCTED OUTPUT POWER	77
APPLICABLE STANDARD	77
TEST PROCEDURE	77
TEST DATA	77
CONDUCTED SPURIOUS EMISSION	78
APPLICABLE STANDARD	78
TEST PROCEDURE	78
TEST DATA	78
POWER SPECTRAL DENSITY	79
APPLICABLE STANDARD	79
TEST PROCEDURE	79

TEST DATA 80

DUTY CYCLE..... 81

TEST PROCEDURE 81

TEST DATA 81

APPENDIX 82

APPENDIX A.1:6dB EMISSION BANDWIDTH..... 83

APPENDIX A.2:99% OCCUPIED BANDWIDTH..... 86

APPENDIX B:MAXIMUM CONDUCTED OUTPUT POWER..... 89

APPENDIX C:CONDUCTED SPURIOUS EMISSION 90

APPENDIX D:POWER SPECTRAL DENSITY..... 96

APPENDIX E:DUTY CYCLE 99

EXHIBIT A-EUT PHOTOGRAPHS 101

EXHIBIT B-TEST SETUP PHOTOGRAPHS 102

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2604P33883E-RF-00A	Original Report	2026-02-10

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Name	4K Battery Wireless Camera
Tested Model	B301
Multiple Model	GL-228XE-I2V1B
Model Difference [#]	The difference between models is model name. Please refer to DOS letter for details. The applicant provided model "B301" for testing.
Voltage Range [#]	DC 3.7V from battery or DC 5V from adapter

Frequency Range	WIFI Halow 1M: 903.5-926.5MHz WIFI Halow 2M: 905-925MHz WIFI Halow 4M: 906-926MHz WIFI Halow 8M: 908-924MHz
Maximum Conducted Peak Output Power (actual test result)	25.12 dBm
Modulation Technique	OFDM
Antenna Specification [#]	External Antenna, Antenna gain: 2.45 dBi (It is provided by the applicant.)
Sample Serial Number	For CE&RE Test: 3GN6-1 For RF Conducted Test: 3GN6-2 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, and KDB 558074 D01 15.247 Meas Guidance v05r02.

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5 %
RF Frequency		0.064×10^{-7}
RF output power, conducted		0.3 dB
Unwanted Emission, conducted		1.2 dB
AC Power Lines Conducted Emissions		2.7 dB
Radiated Emissions	9kHz - 30MHz	2.1 dB
	30MHz - 1GHz	4.3 dB
	1GHz - 18GHz	4.9 dB
	18GHz - 26.5GHz	5.2 dB
Temperature		1 °C
Humidity		7 %
Supply voltages		0.4 %

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For WIFI Halow 1M: 24 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	903.5	7	910.5	14	917.5	21	924.5
1	904.5	8	911.5	15	918.5	22	925.5
2	905.5	9	912.5	16	919.5	23	926.5
3	906.5	10	913.5	17	920.5	/	/
4	907.5	11	914.5	18	921.5	/	/
5	908.5	12	915.5	19	922.5	/	/
6	909.5	13	916.5	20	923.5	/	/

EUT was tested with Channel 0, 12 and 23.

or WIFI Halow 2M: 11 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	905	3	911	6	917	9	923
1	907	4	913	7	919	10	925
2	909	5	915	8	921	/	/

EUT was tested with Channel 0, 5 and 10.

For WIFI Halow 4M: 6 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	906	2	914	4	922
1	910	3	918	5	926

EUT was tested with Channel 0, 2 and 5.

For WIFI Halow 8M: 3 channels are provided to testing:

Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	908	2	924
1	916	/	/

EUT was tested with Channel 0, 1 and 2.

EUT Exercise Software and Power Level[#]

The system was configured for testing in an engineering mode, which was provided by manufacturer.				
Exercise Software:	Secure-CRT			
Mode	Data Rate	Power Level		
		LowChannel	Middle Channel	High Channel
WIFI Halow 1M	MCS0	15	15	15
WIFI Halow 2M	MCS0	15	15	15
WIFI Halow 4M	MCS0	15	15	15
WIFI Halow 8M	MCS0	15	15	15

Note 1: The information in the above table is provided by the applicant.
Note 2: The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Adapter	Unknown	Unknown

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
USB Cable	NO	1.5	Adapter	EUT

Block Diagram of Test Setup


For Conducted Emission:



For Radiated Emission Below 1GHz:



For Radiated Emission Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliance
§15.247(a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	Conducted Spurious Emission	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2025/09/17	2026/09/16
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2025/09/17	2026/09/16
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2025/09/18	2026/09/17
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	100312	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.17	N0350	2025/05/30	2026/05/29
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Below 1GHz)					
Rohde& Schwarz	Test Receiver	ESR	102725	2025/09/18	2026/09/17
SONOMA INSTRUMENT	Amplifier	310N	186131	2025/03/26	2026/03/25
Oulitong	Band Reject Filter	902-928MHz	OE01902501	2025/06/26	2026/06/25
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2024/08/08	2027/08/07
Unknown	RF Coaxial Cable	No.12	N040	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.13	N300	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.14	N800	2025/05/30	2026/05/29
BACL	LOOP ANTENNA	1313-1A	3110711	2024/01/16	2027/01/15
Test Software: e3 191218 (V9)					
Radiated Spurious Emission Test(Above 1GHz)					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2025/09/17	2026/09/16
Decentest	Filter Switch Unit	DT7220FSU	DQ77927	2025/09/18	2026/09/17
Decentest	Multiplex Switch Test Control Set	DT7220CSU	DQ77924	2025/09/18	2026/09/17
Oulitong	Band Reject Filter	902-928MHz	OE01902501	2025/06/26	2026/06/25
A.H. Systems, inc.	Preamplifier	PAM-0118	226	2025/03/20	2026/03/19
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Unknown	RF Coaxial Cable	No.10	N050	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.11	N1000	2025/05/30	2026/05/29
Unknown	RF Coaxial Cable	No.19	N500	2025/05/30	2026/05/29
Test Software: e3 191218 (V9)					

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2025/09/17	2026/09/16
Rohde&Schwarz	Spectrum Analyzer	FSV40	101590	2025/09/17	2026/09/16
Anritsu	Microwave Peak Power Sensor	MA24418A	12619	2025/03/26	2026/03/25
WEINSCHEL	10dB Attenuator	5324	AU 3842	2025/03/26	2026/03/25
/					

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one external antenna arrangement, which used a unique coupling to the EUT. The antenna is 2.45dBi[#]. Fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a).

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss} + 10\text{dB Attenuation(Limiter)}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Test Data


Environmental Conditions

Temperature:	22.5℃
Relative Humidity:	45 %
ATM Pressure:	101.9 kPa
TestEngineer:	Serein Wen
TestDate:	2026-02-04
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note: The maximum output power mode and channel: 2M High Channel was tested.


AC 120V/60Hz, Line:



Site : Shielding Room
 Condition : Line
 Job No. : 2604P33883E-RF
 Test Mode : Transmitting
 Tester : Serein Wen
 Receiver Setting: IF B/W 9kHz PK/AV

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	19.94	1.81	21.75	55.68	-33.93	Average
2	0.156	19.94	7.69	27.63	65.68	-38.05	QP
3	0.247	19.95	-2.05	17.90	51.85	-33.95	Average
4	0.247	19.95	2.78	22.73	61.85	-39.12	QP
5	0.314	19.97	-2.77	17.20	49.87	-32.67	Average
6	0.314	19.97	0.74	20.71	59.87	-39.16	QP
7	0.555	20.08	-2.02	18.06	46.00	-27.94	Average
8	0.555	20.08	2.40	22.48	56.00	-33.52	QP
9	4.936	21.70	-0.84	20.86	46.00	-25.14	Average
10	4.936	21.70	3.55	25.25	56.00	-30.75	QP
11	6.588	21.97	-0.83	21.14	50.00	-28.86	Average
12	6.588	21.97	3.77	25.74	60.00	-34.26	QP

AC 120V/60Hz, Neutral:



Site : Shielding Room
 Condition : Neutral
 Job No. : 2604P33883E-RF
 Test Mode : Transmitting
 Tester : Serein Wen
 Receiver Setting: IF B/W 9kHz PK/AV

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.175	19.81	1.02	20.83	54.71	-33.88	Average
2	0.175	19.81	6.45	26.26	64.71	-38.45	QP
3	0.233	19.93	-1.94	17.99	52.35	-34.36	Average
4	0.233	19.93	2.56	22.49	62.35	-39.86	QP
5	0.311	19.97	-2.67	17.30	49.95	-32.65	Average
6	0.311	19.97	0.94	20.91	59.95	-39.04	QP
7	0.678	20.12	-2.96	17.16	46.00	-28.84	Average
8	0.678	20.12	0.11	20.23	56.00	-35.77	QP
9	2.355	21.02	-4.30	16.72	46.00	-29.28	Average
10	2.355	21.02	0.23	21.25	56.00	-34.75	QP
11	28.984	24.97	-4.34	20.63	50.00	-29.37	Average
12	28.984	24.97	0.12	25.09	60.00	-34.91	QP


RADIATED SPURIOUS EMISSION

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup


9kHz - 30MHz:



30MHz - 1GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver& Spectrum Analyzer Setup

The system was investigated from 9kHz to 10GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz -1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9kHz - 150kHz	PK	0.3kHz	1kHz	/	PK
	QP/AV	/	/	200Hz	QP/AV
150kHz - 30MHz	PK	10kHz	30kHz	/	PK
	QP/AV	/	/	9kHz	QP/AV
30MHz - 1000MHz	PK	100kHz	300kHz	/	PK
	QP	/	/	120kHz	QP

1GHz-10GHz:

Pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	5kHz
		<98%	1MHz	≥1/T, no less than 5kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	Peak	Any	1MHz	3MHz
Ave.	Peak	>98%	1MHz	10Hz
		<98%	1MHz	≥1/T

Note 1: T is minimum transmission duration

Note 2: The 1GHz-1.5GHz testing use the notch filter and the 1.5GHz-10GHz testing use high-pass filter.

Note 3: The band edge testing use 10dB attenuator.

Note 4: The filters and attenuators are all integrated within the filter switch unit.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to FCC §15.209(e), the provisions in §15.31, 15.33, and 15.35 for measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

According to FCC§15.31 measurement standard (f)(2), at frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

For 9kHz-30MHz, test distance is 3m, extrapolation limit shall be calculated using Equation:

$$E_{\text{limit-measure}} = E_{\text{limit-Standard}} + 40 \times \log_{10}\left(\frac{d_{\text{Standard}}}{d_{\text{measure}}}\right)$$

Note 1: If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Note 2: For above 1GHz, the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, so just peak value was recorded.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

After pre-scan in the X, Y and Z axes of orientation, the worst case as setup photos was recorded.

9kHz-1GHz

Environmental Conditions


Temperature:	24.6℃
Relative Humidity:	58%
ATM Pressure:	101.8kPa
Test Engineer:	Jayden Luo
Test Date:	2026-02-03
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: The Loop Antenna were tested in parallel, perpendicular, and ground-parallel. The worst orientation was parallel and the data was recorded in report.


Note 2: The maximum output power mode and channel: 2M High Channel was tested.

9kHz~30MHz:



Site : chamber
Condition : 3m
Job No. : 2604P33883E-RF
Polarization : Parallel Tester: Jayden Luo
Test Mode : Transmitting
Receiver Setting: RBW:300Hz VBW:1kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.012	35.14	31.91	67.05	126.35	-59.30	Peak
2	0.018	32.31	32.70	65.01	122.53	-57.52	Peak
3	0.025	29.05	27.84	56.89	119.55	-62.66	Peak
4	0.039	25.07	27.88	52.95	115.76	-62.81	Peak
5	0.060	21.35	24.18	45.53	112.00	-66.47	Peak
6	0.117	15.68	22.17	37.85	106.26	-68.41	Peak



Site : chamber
Condition : 3m
Job No. : 2604P33883E-RF
Polarization : Parallel Tester: Jayden Luo
Test Mode : Transmitting
Receiver Setting: RBW:10kHz VBW:30kHz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1.216	-2.60	61.77	59.17	65.74	-6.57	Peak
2	2.346	-5.53	61.58	56.05	69.54	-13.49	Peak
3	3.381	-6.01	67.01	61.00	69.54	-8.54	Peak
4	4.672	-6.30	48.97	42.67	69.54	-26.87	Peak
5	6.186	-6.17	41.71	35.54	69.54	-34.00	Peak
6	13.841	-4.33	35.53	31.20	69.54	-38.34	Peak

30MHz~1GHz:



Site : chamber
Condition : 3m HORIZONTAL
Job No. : 2604P33883E-RF Tester: Jayden Luo
Test Mode : Transmitting
Receiver Setting: RBW:100kHz VBW:300kHz

	Freq Factor		Read Level		Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	Line	Limit	
1	36.654	-11.33	34.52	23.19	40.00	-16.81	Peak
2	105.734	-11.13	28.69	17.56	43.50	-25.94	Peak
3	175.037	-13.24	33.06	19.82	43.50	-23.68	Peak
4	233.349	-10.43	38.48	28.05	46.00	-17.95	Peak
5	297.094	-8.91	47.55	38.64	46.00	-7.36	Peak
6	346.505	-6.79	41.30	34.51	46.00	-11.49	Peak



Site : chamber
Condition : 3m VERTICAL
Job No. : 2604P33883E-RF Tester: Jayden Luo
Test Mode : Transmitting
Receiver Setting: RBW:100kHz VBW:300kHz

Freq Factor		Read Level	Limit Level	Over Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.637	-11.33	35.24	23.91	40.00	-16.09 Peak
2	107.322	-11.19	28.63	17.44	43.50	-26.06 Peak
3	199.723	-10.58	30.33	19.75	43.50	-23.75 Peak
4	314.928	-8.62	34.96	26.34	46.00	-19.66 Peak
5	482.639	-4.28	31.56	27.28	46.00	-18.72 Peak
6	594.090	-2.25	33.25	31.00	46.00	-15.00 Peak

1GHz-10GHz


Environmental Conditions

Temperature:	24.3℃
Relative Humidity:	56%
ATM Pressure:	101.8kPa
TestEngineer:	Angel Chen
TestDate:	2026-01-30
EUT Operation Mode:	Transmitting

Test Result: Compliance, please refer to the below data.

Note 1: For 1GHz-1.5GHz, the fundamental with band reject filter.


1M Low Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M Low Channel 903.5MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1402.750	-13.08	59.76	46.68	74.00	-27.32	Peak


1M Low Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M Low Channel 903.5MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1408.563	-13.11	59.68	46.57	74.00	-27.43	Peak

1M Low Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 1M Low Channel 903.5MHz 1.5GHz-10GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1597.750	-13.58	55.51	41.93	74.00	-32.07	Peak
2	1781.563	-12.86	55.49	42.63	74.00	-31.37	Peak
3	1807.063	-12.82	67.10	54.28	74.00	-19.72	Peak
4	1807.063	-12.82	51.23	38.41	54.00	-15.59	Average
5	2710.188	-9.76	54.31	44.55	74.00	-29.45	Peak
6	3613.313	-9.22	56.10	46.88	74.00	-27.12	Peak
7	9674.875	1.90	41.44	43.34	54.00	-10.66	Average
8	9674.875	1.90	53.15	55.05	74.00	-18.95	Peak


1M Low Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M Low Channel 903.5MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1599.875	-13.59	58.07	44.48	74.00	-29.52	Peak
2	1781.563	-12.86	54.72	41.86	74.00	-32.14	Peak
3	1807.063	-12.82	67.51	54.69	74.00	-19.31	Peak
4	1807.063	-12.82	50.94	38.12	54.00	-15.88	Average
5	2709.125	-9.76	53.23	43.47	74.00	-30.53	Peak
6	9977.688	2.19	40.95	43.14	54.00	-10.86	Average
7	9977.688	2.19	53.30	55.49	74.00	-18.51	Peak

1M Middle Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 1M Middle Channel 915.5MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1485.125	-13.25	59.87	46.62	74.00	-27.38	Peak


1M Middle Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M Middle Channel 915.5MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1476.438	-13.28	59.65	46.37	74.00	-27.63	Peak

1M Middle Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 1M Middle Channel 915.5MHz 1.5GHz-10GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1597.750	-13.58	56.53	42.95	74.00	-31.05	Peak
2	1781.563	-12.86	55.16	42.30	74.00	-31.70	Peak
3	1831.500	-12.96	54.44	41.48	54.00	-12.52	Average
4	1831.500	-12.96	69.69	56.73	74.00	-17.27	Peak
5	2746.313	-9.95	59.29	49.34	74.00	-24.66	Peak
6	3661.125	-9.02	60.66	51.64	74.00	-22.36	Peak
7	9773.688	1.90	41.28	43.18	54.00	-10.82	Average
8	9773.688	1.90	53.47	55.37	74.00	-18.63	Peak

1M Middle Channel 1.5GHz-10GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 1M Middle Channel 915.5MHz 1.5GHz-10GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1597.750	-13.58	57.41	43.83	74.00	-30.17	Peak
2	1781.563	-12.86	55.09	42.23	74.00	-31.77	Peak
3	1831.500	-12.96	53.23	40.27	54.00	-13.73	Average
4	1831.500	-12.96	67.94	54.98	74.00	-19.02	Peak
5	2746.313	-9.95	54.52	44.57	74.00	-29.43	Peak
6	3662.188	-9.02	54.23	45.21	74.00	-28.79	Peak
7	9715.250	2.03	41.03	43.06	54.00	-10.94	Average
8	9715.250	2.03	52.68	54.71	74.00	-19.29	Peak


1M High Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M High Channel 926.5MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1427.813	-13.24	59.81	46.57	74.00	-27.43	Peak

1M High Channel 1GHz-1.5GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 1M High Channel 926.5MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1428.875	-13.26	59.82	46.56	74.00	-27.44	Peak


1M High Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M High Channel 926.5MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1853.813	-13.05	68.81	55.76	74.00	-18.24	Peak
2	1853.813	-13.05	54.01	40.96	54.00	-13.04	Average
3	2779.250	-10.13	57.27	47.14	74.00	-26.86	Peak
4	3705.750	-8.93	60.76	51.83	74.00	-22.17	Peak
5	9228.625	1.48	41.41	42.89	54.00	-11.11	Average
6	9228.625	1.48	53.45	54.93	74.00	-19.07	Peak


1M High Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 1M High Channel 926.5MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1851.688	-13.05	51.47	38.42	54.00	-15.58	Average
2	1851.688	-13.05	68.29	55.24	74.00	-18.76	Peak
3	2779.250	-10.13	59.20	49.07	74.00	-24.93	Peak
4	9381.625	1.65	41.34	42.99	54.00	-11.01	Average
5	9381.625	1.65	53.38	55.03	74.00	-18.97	Peak


2M Low Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Low Channel 905MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1434.313	-13.30	59.66	46.36	74.00	-27.64	Peak


2M Low Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Low Channel 905MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1401.188	-13.06	59.43	46.37	74.00	-27.63	Peak


2M Low Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Low Channel 905MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1810.250	-12.83	53.16	40.33	54.00	-13.67	Average
2	1810.250	-12.83	69.61	56.78	74.00	-17.22	Peak
3	2714.438	-9.78	55.15	45.37	74.00	-28.63	Peak


2M Low Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Low Channel 905MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1810.250	-12.83	53.47	40.64	54.00	-13.36	Average
2	1810.250	-12.83	69.97	57.14	74.00	-16.86	Peak
3	2712.313	-9.77	52.56	42.79	74.00	-31.21	Peak


2M Middle Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Middle Channel 915MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1484.563	-13.26	59.79	46.53	74.00	-27.47	Peak


2M Middle Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Middle Channel 915MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1444.625	-13.36	59.67	46.31	74.00	-27.69	Peak


2M Middle Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Middle Channel 915MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1829.375	-12.94	55.07	42.13	54.00	-11.87	Average
2	1829.375	-12.94	70.90	57.96	74.00	-16.04	Peak
3	2744.188	-9.94	61.07	51.13	74.00	-22.87	Peak


2M Middle Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M Middle Channel 915MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1829.375	-12.94	55.13	42.19	54.00	-11.81	Average
2	1829.375	-12.94	68.63	55.69	74.00	-18.31	Peak
3	2744.188	-9.94	56.58	46.64	74.00	-27.36	Peak


2M High Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M High Channel 925MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1387.313	-13.23	59.95	46.72	74.00	-27.28	Peak


2M High Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M High Channel 925MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1336.500	-13.70	60.55	46.85	74.00	-27.15	Peak


2M High Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M High Channel 925MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1850.625	-13.06	65.11	52.05	74.00	-21.95	Peak
2	2776.063	-10.11	56.24	46.13	74.00	-27.87	Peak


2M High Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 2M High Channel 925MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1850.625	-13.06	66.11	53.05	74.00	-20.95	Peak
2	2775.000	-10.10	55.09	44.99	74.00	-29.01	Peak


4M Low Channel 1GHz-1.5GHz_HORTZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Low Channel 906MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1487.938	-13.24	60.16	46.92	74.00	-27.08	Peak

4M Low Channel 1GHz-1.5GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 4M Low Channel 906MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1415.875	-13.16	59.83	46.67	74.00	-27.33	Peak


4M Low Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Low Channel 906MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	55.75	42.89	74.00	-31.11	Peak
2	1812.375	-12.85	66.24	53.39	74.00	-20.61	Peak


4M Low Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Low Channel 906MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.56	41.70	74.00	-32.30	Peak
2	1812.375	-12.85	65.46	52.61	74.00	-21.39	Peak


4M Middle Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Middle Channel 914MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1393.813	-13.14	59.36	46.22	74.00	-27.78	Peak


4M Middle Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Middle Channel 914MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1406.750	-13.11	59.80	46.69	74.00	-27.31	Peak


4M Middle Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Middle Channel 914MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1828.313	-12.93	67.92	54.99	74.00	-19.01	Peak
2	1828.313	-12.93	54.56	41.63	54.00	-12.37	Average
3	2742.063	-9.93	56.79	46.86	74.00	-27.14	Peak


4M Middle Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M Middle Channel 914MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1826.188	-12.92	54.52	41.60	54.00	-12.40	Average
2	1826.188	-12.92	67.43	54.51	74.00	-19.49	Peak
3	2741.000	-9.90	56.74	46.84	74.00	-27.16	Peak


4M High Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M High Channel 926MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1408.250	-13.12	59.93	46.81	74.00	-27.19	Peak


4M High Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M High Channel 926MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1400.125	-13.06	59.39	46.33	74.00	-27.67	Peak

4M High Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 4M High Channel 926MHz 1.5GHz-10GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.92	42.06	74.00	-31.94	Peak
2	1852.750	-13.04	66.70	53.66	74.00	-20.34	Peak


4M High Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 4M High Channel 926MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1851.688	-13.05	66.91	53.86	74.00	-20.14	Peak
2	2778.188	-10.12	52.82	42.70	74.00	-31.30	Peak

8M Low Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 8M Low Channel 908MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1381.063	-13.31	59.49	46.18	74.00	-27.82	Peak

8M Low Channel 1GHz-1.5GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 8M Low Channel 908MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1406.875	-13.11	59.80	46.69	74.00	-27.31	Peak


8M Low Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M Low Channel 908MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	55.36	42.50	74.00	-31.50 Peak
2	1816.625	-12.87	61.02	48.15	74.00	-25.85 Peak


8M Low Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M Low Channel 908MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.34	41.48	74.00	-32.52	Peak
2	1814.500	-12.85	63.26	50.41	74.00	-23.59	Peak

8M Middle Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 8M Middle Channel 916MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1385.063	-13.25	60.60	47.35	74.00	-26.65 Peak


8M Middle Channel 1GHz-1.5GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M Middle Channel 916MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1438.938	-13.33	60.11	46.78	74.00	-27.22	Peak


8M Middle Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M Middle Channel 916MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.70	41.84	74.00	-32.16	Peak
2	1832.563	-12.96	62.57	49.61	74.00	-24.39	Peak


8M Middle Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M Middle Channel 916MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.52	41.66	74.00	-32.34	Peak
2	1834.688	-12.98	65.02	52.04	74.00	-21.96	Peak


8M High Channel 1GHz-1.5GHz_HORIZONTAL



Site : chamber
Condition : 3m HORIZONTAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M High Channel 924MHz 1GHz-1.5GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1381.313	-13.30	59.79	46.49	74.00	-27.51	Peak

8M High Channel 1GHz-1.5GHz_VERTICAL



Site : chamber

Condition : 3m VERTICAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester:Angel Chen

Note : 8M High Channel 924MHz 1GHz-1.5GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz

		Read		Limit	Over	Remark
Freq	Factor	Level	Level	Line	Limit	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1 1474.750	-13.30	60.63	47.33	74.00	-26.67	Peak

8M High Channel 1.5GHz-10GHz_HORIZONTAL



Site : chamber

Condition : 3m HORIZONTAL

Project No.: 2604P33883E-RF

Test Mode : Transmitting


Tester: Angel Chen

Note : 8M High Channel 924MHz 1.5GHz-10GHz

SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.58	41.72	74.00	-32.28	Peak
2	1845.313	-13.03	59.19	46.16	74.00	-27.84	Peak

8M High Channel 1.5GHz-10GHz_VERTICAL



Site : chamber
Condition : 3m VERTICAL
Project No.: 2604P33883E-RF
Test Mode : Transmitting Tester:Angel Chen
Note : 8M High Channel 924MHz 1.5GHz-10GHz
SA setting : Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

	Freq	Factor	Read		Limit	Over	Remark
			Level	Level	Line	Limit	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	1781.563	-12.86	54.59	41.73	74.00	-32.27	Peak
2	1844.250	-13.03	62.28	49.25	74.00	-24.75	Peak

6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

According to FCC §15.247(a)(2), systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020, section 11.8 and section 6.9


The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

According to ANSI C63.10-2020, section 7.8.6 and section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Test Result: Compliance. Please refer to the Appendix A.1 and Appendix A.2.

MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


Test Procedure

According to ANSI C63.10-2020, section 11.9.1.2

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

According to ANSI C63.10-2020, section 11.9.2.3

- Measurement using a power meter (PM)(Method AVGPM)
 - a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent, if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
 - b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
 - c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
 - d) Correct the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.



Test Data

Test Result: Compliance. Please refer to the Appendix B.

CONDUCTED SPURIOUS EMISSION

Applicable Standard


According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020, section 11.11

- Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution. NOTE—the number of points can also be increased for large spans to retain frequency resolution
- Set the RBW: 1MHz(Conducted Spurious), 100 kHz(Band edge)
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.



Test Data

Test Result: Compliance. Please refer to the Appendix C.

POWER SPECTRAL DENSITY

Applicable Standard

According to FCC §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2020, section 11.10.2

- Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max-hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

According to ANSI C63.10-2020, section 11.10.3

- Method AVGPS-1: (for duty cycle $\geq 98\%$)

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to help ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):


- Set instrument center frequency to DTS channel center frequency.
- Set span to > 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq [3 \times \text{RBW}]$.
- Detector = power averaging (rms) or sample detector (when rms not available).
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- Sweep time = auto couple.
- Employ trace averaging (rms) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

According to ANSI C63.10-2020, section 11.10.5

● Method AVGPSD-2: (for duty cycle < 98% and constant duty cycle)

The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than $\pm 2\%$):

- a) Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
- b) Set instrument center frequency to DTS channel center frequency.
- c) Set span to > 1.5 times the OBW.
- d) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- e) Set VBW $\geq [3 \times \text{RBW}]$.
- f) Detector = power averaging (rms) or sample detector (when rms not available).
- g) Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
- h) Sweep time = auto couple.
- i) Do not use sweep triggering; allow sweep to "free run."
- j) Employ trace averaging (rms) mode over a minimum of 100 traces.
- k) Use the peak marker function to determine the maximum amplitude level.
- l) Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
- m) If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this might require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Test Data

Test Result: Compliance. Please refer to the Appendix D.


DUTY CYCLE

Test Procedure

According to ANSI C63.10-2020 Section 11.6

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



Test Data

Test Result: Compliance. Please refer to the Appendix E.

APPENDIX

Test Information:

Sample No.:	3GN6-2	Test Date:	2026.1.30-2026.2.4
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cayde Hou	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	23-25	Relative Humidity: (%)	47-49	ATM Pressure: (kPa)	101.9
----------------------	-------	------------------------------	-------	------------------------	-------


Appendix A.1:6dB Emission Bandwidth

900M SRD:

Mode	Antenna	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
1M	Chain 0	903.5	0.902	≥0.5	Pass
		915.5	0.908	≥0.5	Pass
		926.5	0.908	≥0.5	Pass
2M	Chain 0	905	1.867	≥0.5	Pass
		915	1.852	≥0.5	Pass
		925	1.863	≥0.5	Pass
4M	Chain 0	906	3.675	≥0.5	Pass
		914	3.655	≥0.5	Pass
		926	3.629	≥0.5	Pass
8M	Chain 0	908	7.604	≥0.5	Pass
		916	7.622	≥0.5	Pass
		924	7.557	≥0.5	Pass

Test Graphs:







Appendix A.2:99% Occupied Bandwidth

900M SRD:

Mode	Antenna	Test Frequency (MHz)	Result (MHz)
1M	Chain 0	903.5	0.848
		915.5	0.848
		926.5	0.848
2M	Chain 0	905	1.798
		915	1.798
		925	1.798
4M	Chain 0	906	3.708
		914	3.700
		926	3.700
8M	Chain 0	908	7.560
		916	7.576
		924	7.528

Test Graphs:






Appendix B:Maximum Conducted Output Power

900M SRD:


Mode	Antenna	Test Frequency (MHz)	Peak Power(dBm)	Limit (dBm)	Verdict
1M	Chain 0	903.5	23.35	30	Pass
		915.5	23.81	30	Pass
		926.5	23.64	30	Pass
2M	Chain 0	905	24.36	30	Pass
		915	24.82	30	Pass
		925	25.12	30	Pass
4M	Chain 0	906	23.58	30	Pass
		914	24.03	30	Pass
		926	23.61	30	Pass
8M	Chain 0	908	24.50	30	Pass
		916	24.85	30	Pass
		924	24.67	30	Pass

Appendix C:Conducted Spurious Emission

Test Graphs:




1M_High Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 18:32:06

1M_High Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 4.FEB.2026 10:58:09

2M_Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:11:11

2M_Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 18:37:59

2M_Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:24:53

2M_Middle Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:12:14

2M_Middle_Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:17:09

2M_High_Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:13:20

2M_High_Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 18:50:59

2M_High_Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:19:14

4M_Low_Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:19:36


4M_Low_Channel



ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 18:54:03




8M Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:23:23

8M Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:06:58

8M Low Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:08:20

8M Middle Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:24:13

8M Middle Channel




ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 19:10:00

8M High Channel



ProjectNo.:2604P33883E-RF Tester:Cayde Hou
Date: 3.FEB.2026 17:25:00





Appendix D:Power Spectral Density

900M SRD:

Mode	Antenna	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1M	Chain 0	903.5	1.22	8	Pass
		915.5	1.73	8	Pass
		926.5	1.71	8	Pass
2M	Chain 0	905	-3.69	8	Pass
		915	-3.47	8	Pass
		925	-3.55	8	Pass
4M	Chain 0	906	-6.30	8	Pass
		914	-5.81	8	Pass
		926	-6.16	8	Pass
8M	Chain 0	908	-8.20	8	Pass
		916	-8.82	8	Pass
		924	-8.22	8	Pass

Test Graphs:





Appendix E:Duty Cycle

900M SRD:

Mode	Antenna	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
1M QPSK	Chain 0	915.5	1.4535	8.91	16.31	7.88	688	1
2M QPSK	Chain 0	915	1.1048	7.6161	14.51	8.38	905	1
4M QPSK	Chain 0	914	0.6391	9.6461	6.63	11.78	1565	2
8M QPSK	Chain 0	916	0.5535	6.57	8.42	10.75	1807	2

Note: Test only was performed at Chain 0, Duty Cycle = Ton/(Ton+Toff)*100%.

Test Graphs




EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2604P33883E-RF EUT External Photos and Attachment No.2 2604P33883E-RF EUT Internal Photos.

EXHIBIT B-TEST SETUP PHOTOGRAPHS

Please refer to the Attachment No.3 2604P33883E-RF Test Photos.

******* END OF REPORT *******