

TEST REPORT

Application No.: SZCR2603001102HS
Applicant: Gozney Group Limited
Address of Applicant: Bobby's Third Floor, The Square, 2 -12 Commercial Road, Bournemouth, United Kingdom
Manufacturer: Shenzhen Hypersynes co.,Ltd.
Address of Manufacturer: Floor 3, Workshop No. 13, Xieping Road, Wulian Community, Longgang Street, Longgang District, Shenzhen, Guangdong, China
Factory: Shenzhen Hypersynes co.,Ltd.
Address of Factory: Floor 3, Workshop No. 13, Xieping Road, Wulian Community, Longgang Street, Longgang District, Shenzhen, Guangdong, China
Equipment Under Test (EUT):
EUT Name: Fuel Gauge
Model No.: GOZ-2565
Trade Mark: Gozney
FCC ID: 2BPD7GOZ-2565
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-03-20
Date of Test: 2026-03-24 to 2026-03-31
Date of Issue: 2026-04-05

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 2 of 67

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-04-05		Original

Authorized for issue by:				
				
		Bill Chen/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 11.10.3	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Radiated Emissions which fall in the restricted bands	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	12
7.2 Radiated Spurious Emissions Below 1GHz	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data	18
7.3 Radiated Spurious Emissions Above 1GHz	25
7.3.1 E.U.T. Operation	25
7.3.2 Test Mode Description	25
7.3.3 Test Setup Diagram	26
7.3.4 Measurement Procedure and Data	27
7.4 Maximum Conducted Output Power	35
7.4.1 E.U.T. Operation	35
7.4.2 Test Mode Description	35
7.4.3 Test Setup Diagram	36
7.4.4 Measurement Procedure and Data	36
7.5 Minimum 6dB Bandwidth	37
7.5.1 E.U.T. Operation	37



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 5 of 67

7.5.2	Test Mode Description	37
7.5.3	Test Setup Diagram	37
7.5.4	Measurement Procedure and Data.....	37
7.6	Power Spectral Density	38
7.6.1	E.U.T. Operation	38
7.6.2	Test Mode Description	38
7.6.3	Test Setup Diagram	38
7.6.4	Measurement Procedure and Data.....	38
7.7	Conducted Band Edges Measurement	39
7.7.1	E.U.T. Operation	39
7.7.2	Test Mode Description	39
7.7.3	Test Setup Diagram	40
7.7.4	Measurement Procedure and Data.....	40
7.8	Conducted Spurious Emissions	41
7.8.1	E.U.T. Operation	41
7.8.2	Test Mode Description	41
7.8.3	Test Setup Diagram	42
7.8.4	Measurement Procedure and Data.....	42
8	Test Setup Photo	43
9	EUT Constructional Details (EUT Photos)	43
10	Appendix.....	44



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing and Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	3.0V DC (1.5V x 2 "AA" Size Batteries)
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Emissions (9kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Maximum Conducted Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectral Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2026-02-02	2027-02-01
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	TST PASS	LNA180400G40	SEM005-39	2025-05-22	2026-05-21

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2026-02-02	2027-02-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 9 of 67

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2026-02-02	2027-02-01
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	TST PASS	LNA180400G40	SEM005-39	2025-05-22	2026-05-21

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2026-02-04	2027-02-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2026-02-04	2027-02-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2026-02-03	2027-02-02
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2026-02-02	2027-02-01

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2026-02-14	2027-02-13



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.5dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2365.878	16.10	29.10	32.79	41.10	53.51	74.00	-20.49	Peak	0.00
2 2390.000	16.13	29.10	32.78	39.15	51.60	74.00	-22.40	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	74.55	87.02	74.00	13.02	Peak	0.00


BLE_1M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2372.907	16.11	29.10	32.79	28.07	40.49	54.00	-13.51	Average	0.00
2 2390.000	16.13	29.10	32.78	27.90	40.35	54.00	-13.65	Average	0.00
3 q 2402.000	16.15	29.09	32.77	74.41	86.88	54.00	32.88	Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2385.511	16.13	29.10	32.78	40.95	53.40	74.00	-20.60	Peak	0.00
2 2390.000	16.13	29.10	32.78	39.65	52.10	74.00	-21.90	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	66.71	79.18	74.00	5.18	Peak	0.00

BLE_1M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2369.189	16.10	29.10	32.79	28.29	40.70	54.00	-13.30	Average	0.00
2 2390.000	16.13	29.10	32.78	27.66	40.11	54.00	-13.89	Average	0.00
3 q 2402.000	16.15	29.09	32.77	66.14	78.61	54.00	24.61	Average	0.00




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2480 Band edge
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p 2480.000	16.27	28.90	32.73	74.64	87.08	74.00	13.08 Peak	0.00
2 2483.500	16.28	28.90	32.73	55.64	68.09	74.00	-5.91 Peak	0.00
3 2483.921	16.28	28.90	32.73	54.07	66.52	74.00	-7.48 Peak	0.00


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2480 Band edge
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 q 2480.000	16.27	28.90	32.73	73.62	86.06	54.00	32.06 Average	0.00
2 2483.500	16.28	28.90	32.73	35.48	47.93	54.00	-6.07 Average	0.00
3 2484.221	16.28	28.90	32.73	36.33	48.78	54.00	-5.22 Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2480 Band edge
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 p 2480.000	16.27	28.90	32.73	64.97	77.41	74.00	3.41 Peak	0.00
2 2483.500	16.28	28.90	32.73	43.72	56.17	74.00	-17.83 Peak	0.00
3 2483.846	16.28	28.90	32.73	44.27	56.72	74.00	-17.28 Peak	0.00

BLE_1M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2480 Band edge
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 q 2480.000	16.27	28.90	32.73	63.63	76.07	54.00	22.07 Average	0.00
2 2483.500	16.28	28.90	32.73	28.86	41.31	54.00	-12.69 Average	0.00
3 2483.996	16.28	28.90	32.73	29.28	41.73	54.00	-12.27 Average	0.00




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
	MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2369.290	16.10	29.10	32.79	41.03	53.44	74.00	-20.56 Peak	0.00
2	2390.000	16.13	29.10	32.78	39.09	51.54	74.00	-22.46 Peak	0.00
3 p	2402.000	16.15	29.09	32.77	74.55	87.02	74.00	13.02 Peak	0.00


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
	MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2389.254	16.13	29.10	32.78	28.74	41.19	54.00	-12.81 Average	0.00
2	2390.000	16.13	29.10	32.78	28.47	40.92	54.00	-13.08 Average	0.00
3 q	2402.000	16.15	29.09	32.77	73.22	85.69	54.00	31.69 Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
	MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2349.990	16.07	29.10	32.80	40.88	53.25	74.00	-20.75 Peak	0.00
2	2390.000	16.13	29.10	32.78	39.63	52.08	74.00	-21.92 Peak	0.00
3 p	2402.000	16.15	29.09	32.77	66.67	79.14	74.00	5.14 Peak	0.00

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 Band edge
BLE

	Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
	MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1	2352.880	16.08	29.10	32.80	28.65	41.03	54.00	-12.97 Average	0.00
2	2390.000	16.13	29.10	32.78	28.19	40.64	54.00	-13.36 Average	0.00
3 q	2402.000	16.15	29.09	32.77	64.95	77.42	54.00	23.42 Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 Band edge
BLE

Freq	Cable Loss Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	74.68	87.12	74.00	13.12	Peak	0.00
2 2483.500	16.28	28.90	32.73	49.93	62.38	74.00	-11.62	Peak	0.00
3 2483.821	16.28	28.90	32.73	50.00	62.45	74.00	-11.55	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 Band edge
BLE

Freq	Cable Loss Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	73.11	85.55	74.00	11.55	Average	0.00
2 2483.500	16.28	28.90	32.73	39.50	51.95	74.00	-22.05	Average	0.00
3 2483.971	16.28	28.90	32.73	39.21	51.66	74.00	-22.34	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 Band edge
BLE

Freq	Cable Loss Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	64.99	77.43	74.00	3.43	Peak	0.00
2 2483.500	16.28	28.90	32.73	42.52	54.97	74.00	-19.03	Peak	0.00
3 2484.345	16.28	28.90	32.73	41.87	54.32	74.00	-19.68	Peak	0.00

BLE_2M_TX_CH_39_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 Band edge
BLE

Freq	Cable Loss Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	62.92	75.36	74.00	1.36	Average	0.00
2 2483.500	16.28	28.90	32.73	30.67	43.12	74.00	-30.88	Average	0.00
3 2484.021	16.28	28.90	32.73	30.42	42.87	74.00	-31.13	Average	0.00



7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Mason Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.3 °C Humidity: 45.6 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 19 of 67

Test Mode: 00; Polarity: Coaxial



Condition: 3m

Job No. : 01102HS

Test Mode: 00

: coaxial



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing and Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 20 of 67

Test Mode: 00; Polarity: Coplanar



Condition: 3m

Job No. : 01102HS

Test Mode: 00

: coplanar



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 21 of 67

Test Mode: 00; Polarity: Coaxial



Condition: 3m
Job No. : 01102HS
Test Mode: 00
: coaxial



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 22 of 67

Test Mode: 00; Polarity: Coplanar



Condition: 3m
Job No. : 01102HS
Test Mode: 00
: coplanar




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 00; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 01102HS/01103HS
Test Mode: 00

	Ant Freq	Cable Factor	Preamp Loss	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.180	20.85	0.75	27.65	25.71	19.66	40.00	-20.34	QP
2	53.318	12.38	0.91	27.63	26.31	11.97	40.00	-28.03	QP
3	104.170	12.48	1.25	27.61	31.79	17.91	43.50	-25.59	QP
4	228.490	16.46	1.83	27.70	31.50	22.09	46.00	-23.91	QP
5	699.305	25.89	3.41	27.83	26.18	27.65	46.00	-18.35	QP
6 q	938.833	28.97	4.06	26.74	25.55	31.84	46.00	-14.16	QP



Test Mode: 00; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 01102HS/01103HS
Test Mode: 00

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.211	21.34	0.74	27.65	26.05	20.48	40.00	-19.52 QP
2	52.760	12.49	0.91	27.63	25.36	11.13	40.00	-28.87 QP
3	170.195	14.05	1.59	27.75	26.12	14.01	43.50	-29.49 QP
4	339.589	18.97	2.27	27.61	26.31	19.94	46.00	-26.06 QP
5	689.565	25.70	3.38	27.86	27.34	28.56	46.00	-17.44 QP
6 q	958.794	29.31	4.09	26.63	25.70	32.47	46.00	-13.53 QP



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260300110202

Page: 25 of 67

7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.




SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- b. The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- h. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
2. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
3. For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
4. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	54.04	41.55	74.00	-32.45	Peak	0.00
2 6177.627	8.91	34.79	53.12	53.54	44.12	74.00	-29.88	Peak	0.00
3 7206.000	8.50	35.70	53.18	52.59	45.61	74.00	-30.39	Peak	0.00
4 9608.000	10.74	37.42	53.35	51.13	45.94	74.00	-28.06	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.41	48.09	74.00	-25.91	Peak	0.00
6 p17639.470	11.28	43.68	52.58	50.01	52.39	74.00	-21.61	Peak	0.00


BLE_1M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	46.96	34.47	54.00	-19.53	Average	0.00
2 6358.789	8.89	34.95	53.14	45.87	36.57	54.00	-17.43	Average	0.00
3 7206.000	8.50	35.70	53.18	45.81	36.83	54.00	-17.17	Average	0.00
4 9608.000	10.74	37.42	53.35	44.90	39.71	54.00	-14.29	Average	0.00
5 13957.530	10.97	39.62	52.91	43.31	40.99	54.00	-13.01	Average	0.00
6 q17741.740	11.35	43.84	52.53	41.72	44.38	54.00	-9.62	Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	53.78	41.29	74.00	-32.71	Peak	0.00
2 6934.778	8.60	35.74	53.19	52.83	43.98	74.00	-30.02	Peak	0.00
3 7206.000	8.50	35.70	53.18	53.06	44.08	74.00	-29.92	Peak	0.00
4 9608.000	10.74	37.42	53.35	50.33	45.14	74.00	-28.86	Peak	0.00
5 13957.530	10.97	39.62	52.91	51.17	48.85	74.00	-25.15	Peak	0.00
6 p17844.590	11.41	43.90	52.48	49.97	52.80	74.00	-21.20	Peak	0.00


BLE_1M_TX_CH_00_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4804.000	7.41	34.32	54.22	45.23	32.74	54.00	-21.26	Average	0.00
2 6995.172	8.56	35.71	53.20	45.73	36.08	54.00	-17.90	Average	0.00
3 7206.000	8.50	35.70	53.18	45.04	36.00	54.00	-17.94	Average	0.00
4 9608.000	10.74	37.42	53.35	43.76	38.57	54.00	-15.43	Average	0.00
5 13957.530	10.97	39.62	52.91	43.18	40.86	54.00	-13.14	Average	0.00
6 q17844.590	11.41	43.90	52.48	41.95	44.78	54.00	-9.22	Average	0.00


BLE_1M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	52.64	40.52	74.00	-33.48 Peak	0.00
2 6470.026	8.88	35.54	53.15	52.64	43.91	74.00	-30.09 Peak	0.00
3 7320.000	8.46	35.70	53.17	52.07	43.06	74.00	-30.94 Peak	0.00
4 9760.000	10.69	37.38	53.29	51.71	46.49	74.00	-27.51 Peak	0.00
5 13957.530	10.97	39.62	52.91	49.90	47.58	74.00	-26.42 Peak	0.00
6 17436.710	11.17	43.40	52.68	50.39	52.28	74.00	-21.72 Peak	0.00


BLE_1M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	47.19	35.07	54.00	-18.93 Average	0.00
2 6470.026	8.88	35.54	53.15	45.69	36.96	54.00	-17.04 Average	0.00
3 7320.000	8.46	35.70	53.17	44.66	35.65	54.00	-18.35 Average	0.00
4 9760.000	10.69	37.38	53.29	44.26	39.04	54.00	-14.96 Average	0.00
5 13957.530	10.97	39.62	52.91	43.50	41.18	54.00	-12.82 Average	0.00
6 17436.710	11.35	43.84	52.53	41.57	44.23	54.00	-9.77 Average	0.00


BLE_1M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	52.83	40.71	74.00	-33.29 Peak	0.00
2 6470.026	8.90	34.92	53.14	53.00	44.48	74.00	-29.52 Peak	0.00
3 7320.000	8.46	35.70	53.17	52.04	43.03	74.00	-30.97 Peak	0.00
4 9760.000	10.69	37.38	53.29	51.94	46.72	74.00	-27.28 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.07	49.55	74.00	-24.45 Peak	0.00
6 17436.710	11.41	43.90	52.48	49.45	52.28	74.00	-21.72 Peak	0.00

BLE_1M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	45.96	33.84	54.00	-20.16 Average	0.00
2 6470.026	8.73	35.20	53.18	46.58	37.33	54.00	-16.67 Average	0.00
3 7320.000	8.46	35.70	53.17	44.90	35.89	54.00	-18.11 Average	0.00
4 9760.000	10.69	37.38	53.29	45.06	39.84	54.00	-14.16 Average	0.00
5 13957.530	10.97	39.62	52.91	44.16	41.84	54.00	-12.16 Average	0.00
6 17436.710	11.38	43.89	52.50	41.80	44.57	54.00	-9.43 Average	0.00




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB	dB
1 4960.000	7.53	34.56	54.20	52.87	40.76	74.00	-33.24 Peak	0.00
2 6414.167	8.89	35.29	53.14	52.71	43.75	74.00	-30.25 Peak	0.00
3 7440.000	8.43	35.96	53.15	53.34	44.58	74.00	-29.42 Peak	0.00
4 9920.000	10.64	37.30	53.23	51.13	45.84	74.00	-28.16 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.06	48.74	74.00	-25.26 Peak	0.00
6 p17639.470	11.28	43.68	52.58	49.92	52.30	74.00	-21.70 Peak	0.00


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB	dB
1 4960.000	7.53	34.56	54.20	46.02	33.91	54.00	-20.09 Average	0.00
2 6322.136	8.90	34.96	53.13	45.86	36.59	54.00	-17.41 Average	0.00
3 7440.000	8.43	35.96	53.15	46.08	37.32	54.00	-16.68 Average	0.00
4 9920.000	10.64	37.30	53.23	44.19	38.90	54.00	-15.10 Average	0.00
5 13957.530	10.97	39.62	52.91	43.67	41.35	54.00	-12.65 Average	0.00
6 q17793.890	11.38	43.89	52.58	41.61	44.38	54.00	-9.62 Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB	dB
1 4960.000	7.53	34.56	54.20	52.97	40.86	74.00	-33.14 Peak	0.00
2 6358.789	8.89	34.95	53.14	53.55	44.25	74.00	-29.75 Peak	0.00
3 7440.000	8.43	35.96	53.15	54.17	45.41	74.00	-28.59 Peak	0.00
4 9920.000	10.64	37.30	53.23	52.59	47.30	74.00	-26.70 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.57	49.25	74.00	-24.75 Peak	0.00
6 p17741.740	11.35	43.84	52.53	49.65	52.31	74.00	-21.69 Peak	0.00

BLE_1M_TX_CH_39_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE


Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dB	dB	dB
1 4960.000	7.53	34.56	54.20	45.90	33.79	54.00	-20.21 Average	0.00
2 5949.811	8.86	34.70	53.15	45.63	36.04	54.00	-17.96 Average	0.00
3 7440.000	8.43	35.96	53.15	45.81	37.05	54.00	-16.95 Average	0.00
4 9920.000	10.64	37.30	53.23	44.81	39.52	54.00	-14.48 Average	0.00
5 13957.530	10.97	39.62	52.91	43.77	41.45	54.00	-12.55 Average	0.00
6 q17844.590	11.41	43.90	52.48	41.40	44.23	54.00	-9.77 Average	0.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	54.45	41.96	74.00	-32.04 Peak	0.00
2 6995.172	8.56	35.71	53.20	52.93	44.00	74.00	-30.00 Peak	0.00
3 7206.000	8.50	35.70	53.18	53.18	44.20	74.00	-29.80 Peak	0.00
4 9608.000	10.74	37.42	53.35	50.15	44.96	74.00	-29.04 Peak	0.00
5 13957.530	10.97	39.62	52.91	50.80	48.48	74.00	-25.52 Peak	0.00
6 p17741.740	11.35	43.84	52.53	49.34	52.00	74.00	-22.00 Peak	0.00


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	46.20	33.71	54.00	-20.29 Average	0.00
2 6995.172	8.92	35.08	53.11	45.62	36.51	54.00	-17.49 Average	0.00
3 7206.000	8.50	35.70	53.18	45.28	36.30	54.00	-17.70 Average	0.00
4 9608.000	10.74	37.42	53.35	44.33	39.14	54.00	-14.86 Average	0.00
5 13957.530	10.97	39.62	52.91	43.86	41.54	54.00	-12.46 Average	0.00
6 q17793.890	11.38	43.89	52.50	42.23	45.00	54.00	-9.00 Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	52.58	40.09	74.00	-33.91 Peak	0.00
2 6432.732	8.89	35.40	53.15	52.74	43.88	74.00	-30.12 Peak	0.00
3 7206.000	8.50	35.70	53.18	52.72	43.74	74.00	-30.26 Peak	0.00
4 9608.000	10.74	37.42	53.35	50.65	45.46	74.00	-28.54 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.23	48.91	74.00	-25.09 Peak	0.00
6 p17793.890	11.38	43.89	52.50	49.66	52.43	74.00	-21.57 Peak	0.00

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4804.000	7.41	34.32	54.22	46.14	33.65	54.00	-20.35 Average	0.00
2 6995.172	8.56	35.71	53.20	46.25	37.32	54.00	-16.68 Average	0.00
3 7206.000	8.50	35.70	53.18	44.91	35.93	54.00	-18.07 Average	0.00
4 9608.000	10.74	37.42	53.35	44.82	39.63	54.00	-14.37 Average	0.00
5 13957.530	10.97	39.62	52.91	44.87	41.75	54.00	-12.25 Average	0.00
6 q17844.590	11.41	43.90	52.48	41.52	44.35	54.00	-9.65 Average	0.00




BLE_2M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	52.71	48.59	74.00	-33.41 Peak	0.00
2 5932.638	8.83	34.67	53.17	54.69	45.02	74.00	-28.98 Peak	0.00
3 7320.000	8.46	35.70	53.17	51.45	42.44	74.00	-31.56 Peak	0.00
4 9760.000	10.69	37.38	53.29	51.95	46.73	74.00	-27.27 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.24	48.92	74.00	-25.08 Peak	0.00
6 p17741.740	11.35	43.84	52.53	49.24	51.90	74.00	-22.10 Peak	0.00


BLE_2M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	45.41	33.29	54.00	-20.71 Average	0.00
2 5932.638	8.56	35.71	53.20	45.12	36.19	54.00	-17.81 Average	0.00
3 7320.000	8.46	35.70	53.17	44.73	35.72	54.00	-18.28 Average	0.00
4 9760.000	10.69	37.38	53.29	44.40	39.18	54.00	-14.82 Average	0.00
5 13957.530	10.97	39.62	52.91	43.85	41.53	54.00	-12.47 Average	0.00
6 q17639.470	11.28	43.68	52.58	42.57	44.95	54.00	-9.05 Average	0.00


BLE_2M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	53.47	41.35	74.00	-32.65 Peak	0.00
2 6071.417	8.92	35.04	53.11	53.31	44.16	74.00	-29.84 Peak	0.00
3 7320.000	8.46	35.70	53.17	52.46	43.45	74.00	-30.55 Peak	0.00
4 9760.000	10.69	37.38	53.29	52.53	47.31	74.00	-26.69 Peak	0.00
5 13957.530	10.97	39.62	52.91	51.09	48.77	74.00	-25.23 Peak	0.00
6 p17639.470	11.28	43.68	52.58	49.70	52.00	74.00	-21.92 Peak	0.00

BLE_2M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 4880.000	7.47	34.62	54.21	45.42	33.30	54.00	-20.70 Average	0.00
2 5967.033	8.88	34.77	53.13	46.43	36.95	54.00	-17.05 Average	0.00
3 7320.000	8.46	35.70	53.17	44.14	35.13	54.00	-18.87 Average	0.00
4 9760.000	10.69	37.38	53.29	44.13	38.91	54.00	-15.09 Average	0.00
5 13957.530	10.97	39.62	52.91	42.87	40.55	54.00	-13.45 Average	0.00
6 q17644.590	11.41	43.90	52.48	41.40	44.31	54.00	-9.69 Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Remark	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	53.30	41.19	74.00	-32.81	Peak	0.00
2 6071.417	8.92	35.04	53.11	52.69	43.54	74.00	-30.46	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.35	44.59	74.00	-29.41	Peak	0.00
4 9920.000	10.64	37.30	53.23	52.04	46.75	74.00	-27.25	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.82	48.50	74.00	-25.50	Peak	0.00
6 p17639.470	11.28	43.68	52.58	49.91	52.29	74.00	-21.71	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Remark	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	45.37	33.26	54.00	-20.74	Average	0.00
2 6071.417	8.92	35.04	53.11	46.37	37.22	54.00	-16.78	Average	0.00
3 7440.000	8.43	35.96	53.15	45.82	37.06	54.00	-16.94	Average	0.00
4 9920.000	10.64	37.30	53.23	44.66	39.37	54.00	-14.63	Average	0.00
5 13957.530	10.97	39.62	52.91	43.62	41.30	54.00	-12.70	Average	0.00
6 q17793.090	11.38	43.89	52.58	41.84	44.61	54.00	-9.39	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Remark	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	52.70	40.59	74.00	-33.41	Peak	0.00
2 6071.906	8.64	35.55	53.19	52.90	43.90	74.00	-30.10	Peak	0.00
3 7440.000	8.43	35.96	53.15	53.34	44.58	74.00	-29.42	Peak	0.00
4 9920.000	10.64	37.30	53.23	52.67	47.38	74.00	-26.62	Peak	0.00
5 13957.530	10.97	39.62	52.91	50.22	47.90	74.00	-26.10	Peak	0.00
6 p17844.500	11.41	43.90	52.48	49.05	52.68	74.00	-21.32	Peak	0.00

BLE_2M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2400 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Remark	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4960.000	7.53	34.56	54.20	45.92	33.81	54.00	-20.19	Average	0.00
2 6018.999	8.93	34.94	53.10	45.41	36.18	54.00	-17.82	Average	0.00
3 7440.000	8.43	35.96	53.15	46.68	37.92	54.00	-16.08	Average	0.00
4 9920.000	10.64	37.30	53.23	44.67	39.38	54.00	-14.62	Average	0.00
5 13957.530	10.97	39.62	52.91	43.53	41.21	54.00	-12.79	Average	0.00
6 q17741.740	11.35	43.84	52.53	42.01	44.67	54.00	-9.33	Average	0.00




BLE_TX_CH_M_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23868.430	6.77	38.95	50.37	51.38	37.19	74.00	-36.81	Peak	-9.54

BLE_TX_CH_M_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 01102HS\01103HS
Mode : 2440 TX RSE
BLE

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p23719.920	6.77	38.86	50.34	51.25	37.00	74.00	-37.00	Peak	-9.54



7.4 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.1
 Test Engineer: Mingli Hu

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 23.7 °C Humidity: 43.8 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Mingli Hu

Limit:
 ≥500 kHz


7.5.1 E.U.T. Operation

Operating Environment:
 Temperature: 23.6 °C Humidity: 43.3 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.6 Power Spectral Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.3

Test Engineer: Mingli Hu

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C


Humidity: 43.3 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 23.4 °C Humidity: 43.3 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.8 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 23.4 °C Humidity: 42.8 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2603001102HS

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for SZCR2603001102HS



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.239	0.625	38.24	4.17	0.00
		2440	0.239	0.625	38.24	4.17	0.00
		2480	0.239	0.625	38.24	4.17	0.00
2M	SISO	2402	0.143	0.625	22.88	6.41	0.00
		2440	0.143	0.625	22.88	6.41	0.00
		2480	0.144	0.625	23.04	6.38	0.00




1.2 Test Graph


1.2.1 Ant1




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.996	/	Pass
		2440	1	0.998	/	Pass
		2480	1	0.999	/	Pass
2M	SISO	2402	1	1.994	/	Pass
		2440	1	1.995	/	Pass
		2480	1	1.992	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.665	≥ 0.5	Pass
		2440	1	0.666	≥ 0.5	Pass
		2480	1	0.676	≥ 0.5	Pass
2M	SISO	2402	1	1.156	≥ 0.5	Pass
		2440	1	1.149	≥ 0.5	Pass
		2480	1	1.161	≥ 0.5	Pass



2.2 Test Graph


2.2.1 OBW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-6.72	<=30	Pass
		2440	-7.02	<=30	Pass
		2480	-6.92	<=30	Pass
2M	SISO	2402	-6.72	<=30	Pass
		2440	-7.00	<=30	Pass
		2480	-6.89	<=30	Pass

Note1: Antenna Gain: Ant1: 2.50dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-22.33	<=8	Pass
		2440	-22.45	<=8	Pass
		2480	-22.49	<=8	Pass
2M	SISO	2402	-24.08	<=8	Pass
		2440	-24.07	<=8	Pass
		2480	-23.98	<=8	Pass

Note1: Antenna Gain: Ant1: 2.50dBi;

4.2 Test Graph


4.2.1 PSD




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	-6.76
		2440	1	-7.05
		2480	1	-6.94
2M	SISO	2402	1	-6.73
		2440	1	-7.02
		2480	1	-6.94

5.1.2 CSE


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	-6.76	-26.76	Pass
		2440	1	-6.76	-26.76	Pass
		2480	1	-6.76	-26.76	Pass
2M	SISO	2402	1	-6.73	-26.73	Pass
		2440	1	-6.73	-26.73	Pass
		2480	1	-6.73	-26.73	Pass

5.2 Test Graph


5.2.1 Ref




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




5.2.2 CSE




1M_MCH_2440MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



- End of the Report -

