

TEST REPORT

Applicant: HANSHOW PTE.LTD.

Address of Applicant: 138 ROBINSON ROAD#02-33OXLEY TOWER
SINGAPORE(068906)

Manufacturer: HANSHOW PTE.LTD.

Address of Manufacturer: 138 ROBINSON ROAD#02-33OXLEY TOWER
SINGAPORE(068906)

Equipment Under Test (EUT)

Product Name: electronic shelf label

Model No.: Nebular Ultra-437WQ-N

FCC ID: 2BPF3-NU-437W

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.225

Date of sample receipt: August 25, 2026

Date of Test: August 25, 2026-September 04, 2026

Date of report issued: September 04, 2026

Test Result : PASS

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	September 04, 2026	Original

Tested By:

Jaosh. Gai

Date:

September 04, 2026

Test Engineer

Prepared By:

Jessie Lu

Date:

September 04, 2026

Project Engineer

Check By:

Robinson Lu

Date:

September 04, 2026

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	6
5.3 TEST FACILITY	6
5.4 TEST LOCATION.....	6
5.5 DESCRIPTION OF SUPPORT UNITS	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA.....	9
7.1 ANTENNA REQUIREMENT:	9
7.2 FIELD STRENGTH OF FUNDAMENTAL EMISSIONS AND MASK MEASUREMENT	10
7.3 RADIATED EMISSION	12
7.4 CHANNEL BANDWIDTH AND 99% OCCUPIED BANDWIDTH	17
7.5 FREQUENCY STABILITY MEASUREMENT	19
8 TEST SETUP PHOTO	21
9 EUT CONSTRUCTIONAL DETAILS	21

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field Strength of Fundamental Emissions and Mask Measurement	15.225(a)(b)(c)	Pass
Radiated Emission	15.225(d)&15.209	Pass
20dB Emission Bandwidth	15.225&15.215	Pass
Frequency Stability Measurement	15.225(e)	Pass

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: Not applicable.

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	electronic shelf label
Model No.:	Nebular Ultra-437WQ-N
Test sample(s) ID:	GTS2026080415-1
Sample(s) Status	Engineered sample
S/N:	N/A
Operation Frequency:	13.56MHz
Channel Number:	1
Modulation:	ASK
Antenna type:	PCB Antenna
Antenna gain:	0dBi(Declared by applicant)
Power supply:	DC 3.0V(Size"CR2450" Lithium Battery) *2 parallel

Disclaimer statement:

1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

5.2 Test mode

Transmitter mode	Keep the EUT in continuously transmitting. New battery used in test		
Pre-test mode.			
GTS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report (Only show the worst case:Y axis) and defined as follows:			
Axis	X	Y	Z
Field Strength(dBuV/m)	59.98	60.40	60.13
Final Test Mode:			
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”: Y axis (see the test setup photo)			

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● ISED —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.4 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.5 Description of Support Units

None

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 10, 2026	Apr. 09, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 10, 2026	Apr. 09, 2027
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 11, 2026	Apr. 10, 2027
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2026	Apr. 10, 2027
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul 17, 2026	Jul 16, 2027
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.22, 2025	Nov.21, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 10, 2026	Apr. 09, 2027
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 10, 2026	Apr. 09, 2027
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2026	Apr. 10, 2027
11	Spectrum analyzer (9kHz-40GHz)	Rohde & Schwarz	FSV40-N	GTS666	Mar. 10, 2026	Mar. 09, 2027
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 10, 2026	Apr. 09, 2027
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 24, 2025	Nov. 23, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 10, 2026	Apr. 09, 2027
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 13, 2026	Apr. 12, 2027
16	RE cable 1	GTS	N/A	GTS675	Jul. 17, 2026	Jul. 16, 2027
17	RE cable 2	GTS	N/A	GTS676	Jul. 17, 2026	Jul. 16, 2027
18	RE cable 3	GTS	N/A	GTS677	Jul. 17, 2026	Jul. 16, 2027
19	RE cable 4	GTS	N/A	GTS678	Jul. 17, 2026	Jul. 16, 2027
20	RE cable 5	GTS	N/A	GTS679	Jul. 17, 2026	Jul. 16, 2027
21	RE cable 6	GTS	N/A	GTS680	Jul. 17, 2026	Jul. 16, 2027
22	RE cable 7	GTS	N/A	GTS681	Jul. 22, 2026	Jul. 21, 2027
23	RE cable 8	GTS	N/A	GTS682	Jul. 22, 2026	Jul. 21, 2027
24	CE cable 9	GTS	N/A	GTS683	Jul. 23, 2026	Jul. 22, 2027
25	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 10, 2026	Apr. 09, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Jun. 03, 2026	Jun. 02, 2027
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 10, 2026	Apr. 09, 2027
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 10, 2026	Apr. 09, 2027
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 10, 2026	Apr. 09, 2027
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 10, 2026	Apr. 09, 2027
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 10, 2026	Apr. 09, 2027
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 10, 2026	Apr. 09, 2027
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 10, 2026	Apr. 09, 2027
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 14, 2026	Apr. 13, 2027


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 21, 2026	Jul. 20, 2027

7 Test results and Measurement Data


7.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is PCB antenna, reference to the appendix II for details	

7.2 Field Strength of Fundamental Emissions and Mask Measurement

Test Requirement:	FCC Part15 C Section 15.225(a)(b)(c)																				
Test Method:	ANSI C63.10:2020 & ANSI C63.4: 2014																				
Test site:	Measurement Distance: 3m																				
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=Auto																				
limit:	FCC Part 15.225 <table><tr><th>Frequencies(MHz)</th><th>Limit at 30m(dBuV/m)</th><th>Limit at 3m(dBuV/m)</th></tr><tr><td>13.110-13.410</td><td>40.50</td><td>80.50</td></tr><tr><td>13.410-13.553</td><td>50.50</td><td>90.50</td></tr><tr><td>13.553-13.567</td><td>84.00</td><td>124.00</td></tr><tr><td>13.567-13.710</td><td>50.50</td><td>90.50</td></tr><tr><td>13.710-14.010</td><td>40.50</td><td>80.50</td></tr></table>			Frequencies(MHz)	Limit at 30m(dBuV/m)	Limit at 3m(dBuV/m)	13.110-13.410	40.50	80.50	13.410-13.553	50.50	90.50	13.553-13.567	84.00	124.00	13.567-13.710	50.50	90.50	13.710-14.010	40.50	80.50
Frequencies(MHz)	Limit at 30m(dBuV/m)	Limit at 3m(dBuV/m)																			
13.110-13.410	40.50	80.50																			
13.410-13.553	50.50	90.50																			
13.553-13.567	84.00	124.00																			
13.567-13.710	50.50	90.50																			
13.710-14.010	40.50	80.50																			
Test setup:																					
Test Instruments:	Refer to section 6.0 for details																				
Test mode:	Refer to section 5.2 for details																				
Test results:	Pass																				


Measurement data:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
13.562	39.32	20.57	0.51	0.00	60.40	124.00	-63.60	Peak

Remarks: level = Reading level + Antenna factor + Cable loss - Preamp Factor

7.3 Radiated Emission


Test Requirement:	FCC Part15 C Section 15.225(d) and 15.209																												
Test Method:	ANSI C63.10: 2020 & ANSI C63.4: 2014																												
Test Frequency Range:	9KHz to 1000MHz																												
Test site:	Measurement Distance: 3m																												
Receiver setup:	Frequency	Detector	RBW	VBW	Remark																								
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value																								
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value																								
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value																								
FCC Limit:	<table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100**</td><td>3</td></tr><tr><td>88-216</td><td>150**</td><td>3</td></tr><tr><td>216-960</td><td>200**</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table> The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.					Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100**	3	88-216	150**	3	216-960	200**	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																											
0.009-0.490	2400/F(kHz)	300																											
0.490-1.705	24000/F(kHz)	30																											
1.705-30.0	30	30																											
30-88	100**	3																											
88-216	150**	3																											
216-960	200**	3																											
Above 960	500	3																											
Test setup:	Below 30MHz  Above 30MHz																												

						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	DC 3V					
Test results:	Pass					

Measurement data:

■ 9kHz~30MHz

Test data combines x, y, z-axis; the radiation emission more than 20dB below the limit




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
0.015	19.47	21.30	0.04	0.00	40.81	123.80	-82.99	Peak
0.047	20.07	21.00	0.11	0.00	41.18	114.14	-72.96	Peak
0.215	15.05	20.26	0.22	0.00	35.53	100.97	-65.44	Peak
1.342	12.78	20.61	0.35	0.00	33.74	65.05	-31.31	QP
3.303	13.89	20.94	0.41	0.00	35.24	69.54	-34.30	QP
13.560	39.32	20.57	0.51	0.00	60.40	69.54	-9.14	QP
19.203	10.28	20.81	0.53	0.00	31.62	69.54	-37.92	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

■ 30MHz~1GHz


Horizontal:



Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
36.254	27.29	13.23	1.28	33.40	8.40	40.00	-31.60	QP
65.114	29.00	11.39	1.61	33.36	8.64	40.00	-31.36	QP
102.001	35.59	10.10	2.06	33.29	14.46	43.50	-29.04	QP
167.824	32.99	12.92	2.47	33.15	15.23	43.50	-28.27	QP
255.623	32.35	11.71	3.19	32.98	14.27	46.00	-31.73	QP
547.098	24.89	18.08	4.92	32.57	15.32	46.00	-30.68	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)


7.4 Channel Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC Part15 C Section 15.225 and 15.215
Test Method:	ANSI C63.10:2020
Limit:	N/A
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth & 99%bandwidth.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test frequency(MHz)	20dB bandwidth(KHz)	99% bandwidth(KHz)	Result
13.56	124.384	279.7750	Pass

Test plot as follows:



7.5 Frequency Stability Measurement

Test Requirement:	FCC Part15 C Section 15.225 (e)
Test Method:	ANSI C63.10: 2020
Receiver setup:	RBW=1KHz, VBW=1KHz, Sweep time=Auto
Limit:	The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.
Test setup:	 The diagram illustrates the test setup. On the left is a green Spectrum Analyzer. A cable connects it to a yellow Equipment Under Test (EUT) which is placed inside a blue Oven. The labels 'Spectrum Analyzer', 'EUT', and 'OVEN' are present below their respective components.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Reference Frequency: 13.56MHz						
Power supplied (Vdc)	Temperature (°C)	Frequency error			Limit	Result
		Frequency(Hz)	Hz	%		
3	-20	13.560005	05	0.00004	+/- 0.01%	Pass
	-10	13.560009	09	0.00007		
	0	13.560008	08	0.00006		
	10	13.560009	09	0.00007		
	20	13.560008	08	0.00006		
	30	13.560005	05	0.00004		
	40	13.560009	09	0.00007		
	50	13.560009	09	0.00007		

Reference Frequency: 13.56MHz						
Temperature (°C)	Power supplied (Vac)	Frequency error			Limit	Result
		Frequency(Hz)	Hz	Ppm		
20	2.55	13.560012	12	0.00009	+/- 0.01%	Pass
	3.45	13.560008	08	0.00006		

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

----- End -----