

# RF EXPOSURE Test Report

**Product:** NEXUS 3IN1 MAGNETIC WIRELESS  
CHARGING PORTFOLIO

**Trade Mark:** SPECTOR&CO

**Model Number:** T151

**FCC ID:** 2BQNL-T151

**Prepared for**

DONGGUAN COHESION LEATHER GOODS CO.,LTD  
ROOM 301, BUILDING 1, NO. 30 WEIXING ROAD, CHASHAN TOWN,  
DONGGUAN CITY, GUANGDONG PROVINCE, CHINA

**Prepared by**

Shenzhen HongBiao Certification& Testing Co., Ltd  
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan  
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,  
China  
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110  
Website: <http://www.sz-hongbiao.com>

**Table of Contents**

**1 GENERAL DESCRIPTION ..... 5**

1.1 DESCRIPTION OF EUT ..... 5

1.2 TEST MODE..... 5

1.3 TEST SETUP ..... 6

1.4 ANCILLARY EQUIPMENT ..... 6

**2 TEST FACILITIES AND ACCREDITATIONS ..... 7**

2.1 TEST LABORATORY ..... 7

2.2 ENVIRONMENTAL CONDITIONS ..... 7

2.3 MEASUREMENT UNCERTAINTY ..... 7

2.4 TEST SOFTWARE ..... 7

**3 LIST OF TEST EQUIPMENT ..... 8**

**4 RF EXPOSURE..... 9**

4.1 MAXIMUM PERMISSIBLE EXPOSURE ..... 9

4.1.1. *Limit* ..... 9

4.1.2. *Test Procedures* ..... 9

4.1.3. *Test Setup*..... 9

4.1.4. *Test Result* ..... 10

**5 PHOTOGRAPHS OF THE TEST SETUP..... 13**

## TEST RESULT CERTIFICATION

**Applicant's Name** ..... : DONGGUAN COHESION LEATHER GOODS CO.,LTD  
**Address** ..... : ROOM 301, BUILDING 1, NO. 30 WEIXING ROAD, CHASHAN  
TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA  
**Manufacturer's Name** ..... : DONGGUAN COHESION LEATHER GOODS CO.,LTD  
**Address** ..... : ROOM 301, BUILDING 1, NO. 30 WEIXING ROAD, CHASHAN  
TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA

### Product description

**Product name** ..... : NEXUS 3IN1 MAGNETIC WIRELESS CHARGING  
PORTFOLIO  
**Model Number** ..... : T151

**Standards** ..... : FCC CFR 47 PART 1 , 1.1310

**Test procedure** ..... : KDB 680106 D01 Wireless Power Transfer v04

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

**Date of Test** ..... :

**Date (s) of performance of tests** ..... : Oct. 11, 2025~Nov. 03, 2025


**Test Result**..... : **Pass**

**Testing Engineer** :




( Z o e S u )

**Technical Manager** :



( M i n g L i u )

**Authorized Signatory** :



( L e o S u )

[illegible]

# 1 General Description

## 1.1 Description of EUT

|                            |                                                                                                                                                                                                          |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product name:              | NEXUS 3IN1 MAGNETIC WIRELESS CHARGING PORTFOLIO                                                                                                                                                          |
| Model name:                | T151                                                                                                                                                                                                     |
| Series Model:              | N/A                                                                                                                                                                                                      |
| Different of series model: | N/A                                                                                                                                                                                                      |
| Operation frequency:       | Phone: 115-205kHz<br>Earbuds: 115-205kHz<br>Watch: 320-340kHz                                                                                                                                            |
| Operational mode:          | Wireless charging                                                                                                                                                                                        |
| Modulation type:           | ASK                                                                                                                                                                                                      |
| Antenna type:              | Coil Antenna                                                                                                                                                                                             |
| Hardware version:          | V1.0                                                                                                                                                                                                     |
| Software version:          | V1.0                                                                                                                                                                                                     |
| Battery:                   | DC 3.7V, 5000mAh, 18.5Wh                                                                                                                                                                                 |
| Power supply:              | Type-C Input: 5V=3A, 9V=3A, 12V=3A<br>Type-C Output: 5V=3A, 9V=2A<br>Wireless Output For Phone: 5W/7.5W/10W/ 15W Max<br>Wireless Output For TWS Earbuds: 5W Max<br>Wireless Output For iWatch : 2.5W Max |
| Adapter information:       | N/A                                                                                                                                                                                                      |

## 1.2 Test Mode

| Pretest Test Mode | Description of Mode                       |
|-------------------|-------------------------------------------|
| 1                 | Wireless Output Phone: 5W                 |
| 2                 | Wireless Output Earbuds: 5W               |
| 3                 | Wireless Output iWatch: 2.5W              |
| 4                 | Wireless Output Phone: 15W                |
| 5                 | Wireless Output Phone: 7.5W               |
| 6                 | Wireless Output Phone: 10W                |
| 7                 | Wireless Output Phone: 15W                |
| 8                 | AC/DC adapter + Wireless Output Phone: 5W |

|    |                                              |
|----|----------------------------------------------|
| 9  | AC/DC adapter + Wireless Output Earbuds: 5W  |
| 10 | AC/DC adapter + Wireless Output iWatch: 2.5W |

### 1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

### 1.4 Ancillary Equipment

| Equipment | Model  | S/N            | Manufacturer                         |
|-----------|--------|----------------|--------------------------------------|
| Phone     | LE2120 | 98d9b780       | Shenzhen Oneplus Technology Co., Ltd |
| Earbuds   | /      | /              | Apple Inc.                           |
| Watch     | A2859  | M69PQQ7J2<br>T | Apple Inc.                           |
| Adapter   | CD289  | 35810          | Ugreen Group Limited                 |

## 2 Test Facilities and Accreditations

### 2.1 Test Laboratory

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site             | Shenzhen HongBiao Certification& Testing Co., Ltd                                                                                                 |
| Test Site Location    | Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China |
| Telephone:            | (86-755) 2998 9321                                                                                                                                |
| Fax:                  | (86-755) 2998 5110                                                                                                                                |
| FCC Registration No.: | CN1341                                                                                                                                            |
| A2LA Certificate No.: | 6765.01                                                                                                                                           |

### 2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

|                    |              |
|--------------------|--------------|
| Temperature:       | 15°C~35°C    |
| Relative Humidity: | 20%~75%      |
| Air Pressure:      | 98kPa~101kPa |

### 2.3 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

| Measurement Frequency Range | U, (dB)            | Note |
|-----------------------------|--------------------|------|
| RF frequency                | $2 \times 10^{-5}$ |      |
| E-field                     | $\pm 2.5$ dB       |      |
| H-field                     | $\pm 4.2$ dB       |      |
| Temperature                 | $\pm 1$ degree     |      |
| Humidity                    | $\pm 5$ %          |      |

### 2.4 Test Software

| Software name | Manufacturer                    | Model      | Version |
|---------------|---------------------------------|------------|---------|
| MAGPy V2.6    | Schmid & Partner Engineering AG | MAGPy V2.6 | V2.6    |

3 List of Test Equipment

| Item | Equipment No. | Equipment name                               | Manufacturer                    | Model           | Serial No. | Calibration date | Due date   |
|------|---------------|----------------------------------------------|---------------------------------|-----------------|------------|------------------|------------|
| 1    | HB-E077       | Magnetic Amplitude and Gradient Probe System | Schmid & Partner Engineering AG | MAGPy -8H3D+E3D | 3107       | 2024-03-15       | 2026-03-14 |
| 2    | HB-E078       | Magnetic Amplitude and Gradient Probe System | Schmid & Partner Engineering AG | MAGPy-DAS       | 3097       | 2024-03-15       | 2026-03-14 |

Note: the calibration interval of the above test instruments is 24 months and the calibrations are traceable to international system unit (SI).

## 4 RF Exposure

### 4.1 Maximum Permissible Exposure

#### 4.1.1. Limit


| Frequency range(MHz)                                    | Electric field strength(V/m) | Magnetic field strength(A/m) | Power density(mW/cm <sup>2</sup> ) | Averaging time(minutes) |
|---------------------------------------------------------|------------------------------|------------------------------|------------------------------------|-------------------------|
| (A) Limits for Occupational/Controlled Exposure         |                              |                              |                                    |                         |
| 0.3-3.0                                                 | 614                          | 1.63                         | *100                               | 6                       |
| 3.0-30                                                  | 1842/f                       | 4.89/f                       | *900/f <sup>2</sup>                | 6                       |
| 30-300                                                  | 61.4                         | 0.163                        | 1.0 6                              | 6                       |
| 300-1500                                                |                              |                              | f/300                              | 6                       |
| 1500-100000                                             |                              |                              | 5                                  | 6                       |
| (B) Limits for General Population/Uncontrolled Exposure |                              |                              |                                    |                         |
| 0.3-1.34                                                | 614                          | 1.63                         | *100                               | 30                      |
| 1.34-30                                                 | 824/f                        | 2.19/f                       | *180/f <sup>2</sup>                | 30                      |
| 30-300                                                  | 27.5                         | 0.073                        | 0.2                                | 30                      |
| 300-1500                                                |                              |                              | f/1500                             | 30                      |
| 1500-100000                                             |                              |                              | 1                                  | 30                      |

f = frequency in MHz \* = Plane-wave equivalent power density

#### 4.1.2. Test Procedures

- The RF exposure test was performed in anechoic chamber.
- Perform H-field measurements for each edge/top surface of the host/client pair at every 2 cm, starting from as close as possible out to 20 cm.
- The highest emission level was recorded and compared with limit.

#### 4.1.3. Test Setup



#### 4.1.4. Test Result

For portable exposure condition:

Operating modes with client device (1 %, 50%, 99% battery status of client device) have been test, only show the data of worst case of 1% battery status of client device.

H-field measurements taken every 2 cm (starting as close to 20 cm as possible) on each edge/top surface of the host/client pair were also evaluated for portable use conditions. The report reflects data for the worst 0 cm test distance mode only.

Test condition 1: Mode 1 operating mode with client device (1 % battery status of client device).

Measurement results directly tested using MAGPy.

| Maximum permissible Exposure(Phone: 115-205kHz) |            |                   |               |              |
|-------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                  | Test sides | Test distance(cm) | E –field(V/m) | H–field(A/m) |
| <1%                                             | Top        | 0                 | 79.7          | 0.3          |
| <1%                                             | Left       | 0                 | 13            | 0.06         |
| <1%                                             | Right      | 0                 | 16.9          | 0.09         |
| <1%                                             | Front      | 0                 | 52.5          | 1.31         |
| <1%                                             | Back       | 0                 | 12.3          | 0.03         |
| <1%                                             | Bottom     | 0                 | 46            | 1.45         |
| Limit                                           |            |                   | 614           | 1.63         |
| Margin Limit (%)                                |            |                   | 12.98%        | 88.96%       |

When setting MAGPy to select compliance location as probe tip, the measured value is extrapolated to 0mm as the result.

| Maximum permissible Exposure(Phone: 115-205kHz) |            |                   |               |              |
|-------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                  | Test sides | Test distance(cm) | E –field(V/m) | H–field(A/m) |
| <1%                                             | Top        | 0                 | 180           | 1.27         |
| <1%                                             | Left       | 0                 | 7.4           | 0.11         |
| <1%                                             | Right      | 0                 | 18.7          | 0.23         |
| <1%                                             | Front      | 0                 | 57.3          | 1.46         |
| <1%                                             | Back       | 0                 | 9.43          | 0.05         |
| <1%                                             | Bottom     | 0                 | 68            | 1.54         |
| Limit                                           |            |                   | 614           | 1.63         |
| Margin Limit (%)                                |            |                   | 29.32%        | 94.48%       |

Test condition 2: Mode 2 operating mode with client device (1 % battery status of client device).  
Measurement results directly tested using MAGPy.

| Maximum permissible Exposure(Earbuds: 115-205kHz) |            |                   |               |              |
|---------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                    | Test sides | Test distance(cm) | E –field(V/m) | H–field(A/m) |
| <1%                                               | Top        | 0                 | 27.1          | 0.95         |
| <1%                                               | Left       | 0                 | 3.11          | 0.18         |
| <1%                                               | Right      | 0                 | 1.78          | 0.15         |
| <1%                                               | Front      | 0                 | 14.6          | 1.14         |
| <1%                                               | Back       | 0                 | 5.25          | 0.03         |
| <1%                                               | Bottom     | 0                 | 49            | 1.26         |
| Limit                                             |            |                   | 614           | 1.63         |
| Margin Limit (%)                                  |            |                   | 7.98%         | 77.3%        |

When setting MAGPy to select compliance location as probe tip, the measured value is extrapolated to 0mm as the result.

| Maximum permissible Exposure(Earbuds: 115-205kHz) |            |                   |               |              |
|---------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                    | Test sides | Test distance(cm) | E –field(V/m) | H–field(A/m) |
| <1%                                               | Top        | 0                 | 24.9          | 1.23         |
| <1%                                               | Left       | 0                 | 2.55          | 0.31         |
| <1%                                               | Right      | 0                 | 3.29          | 0.26         |
| <1%                                               | Front      | 0                 | 13.1          | 1.35         |
| <1%                                               | Back       | 0                 | 5.15          | 0.09         |
| <1%                                               | Bottom     | 0                 | 46.1          | 1.43         |
| Limit                                             |            |                   | 614           | 1.63         |
| Margin Limit (%)                                  |            |                   | 7.5%          | 87.73%       |

Test condition 3: Mode 3 operating mode with client device (1 % battery status of client device).  
Measurement results directly tested using MAGPy.

| Maximum permissible Exposure(iWatch: 326.5kHz) |            |                   |               |              |
|------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                 | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <1%                                            | Top        | 0                 | 189           | 0.79         |
| <1%                                            | Left       | 0                 | 3.77          | 0.05         |
| <1%                                            | Right      | 0                 | 3.39          | 0.05         |
| <1%                                            | Front      | 0                 | 53.4          | 0.71         |
| <1%                                            | Back       | 0                 | 7.05          | 0.02         |
| <1%                                            | Bottom     | 0                 | 110           | 0.92         |
| Limit                                          |            |                   | 614           | 1.63         |
| Margin Limit (%)                               |            |                   | 30.78%        | 56.44%       |

When setting MAGPy to select compliance location as probe tip, the measured value is extrapolated to 0mm as the result.

| Maximum permissible Exposure(iWatch: 326.5kHz) |            |                   |               |              |
|------------------------------------------------|------------|-------------------|---------------|--------------|
| Battery levels                                 | Test sides | Test distance(cm) | E -field(V/m) | H-field(A/m) |
| <1%                                            | Top        | 0                 | 187           | 1.16         |
| <1%                                            | Left       | 0                 | 3.82          | 0.09         |
| <1%                                            | Right      | 0                 | 3.05          | 0.08         |
| <1%                                            | Front      | 0                 | 35            | 0.81         |
| <1%                                            | Back       | 0                 | 7.83          | 0.03         |
| <1%                                            | Bottom     | 0                 | 99.3          | 1.37         |
| Limit                                          |            |                   | 614           | 1.63         |
| Margin Limit (%)                               |            |                   | 30.46%        | 84.05%       |

## 5 Photographs of the Test Setup

Phone

Photo 1



Photo 2



Photo 3




Photo 4




Photo 5





Photo 6



Earbuds

Photo 7




Photo 8




Photo 9




Photo 10





Photo 11



Photo 12



Watch

Photo 13




Photo 14



Photo 15




Photo 16




Photo 17





Photo 18



\*\*\*\*\* END OF REPORT \*\*\*\*\*