

SAR TEST REPORT

Reference No. : WTD25D08233044W007
FCC ID : 2BSNE-M55
Applicant : Shenzhen Telemiles Co., Ltd
Address : 24F, Block B of Block A.B, Haiwang Building, Nanhai Blvd No.2221,
Nanshan Street, Nanshan District, Shenzhen, China
Manufacturer : Shenzhen Telemiles Co., Ltd
Address : 24F, Block B of Block A.B, Haiwang Building, Nanhai Blvd No.2221,
Nanshan Street, Nanshan District, Shenzhen, China
Product : ONE
Model(s) : M55
Standards : FCC 47 CFR Part2(2.1093)
IEEE Std C95.1: 2019
IEC/IEEE 62209-1528:2020
Date of Receipt sample : 2025-09-22
Date of Test : 2025-10-10 to 2025-11-06
Date of Issue : 2025-12-19
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:

Deval Qin


Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	4
4 GENERAL INFORMATION	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.	5
4.3 TEST FACILITY	8
5 SUMMARY OF TEST RESULTS	9
6 EQUIPMENT USED DURING TEST	10
6.1 EQUIPMENT LIST	10
7 SAR INTRODUCTION	11
7.1 INTRODUCTION	11
7.2 SAR DEFINITION	11
8 SAR MEASUREMENT SETUP	12
9 EXPOSURE LIMIT	21
10 SYSTEM AND LIQUID VALIDATION	22
10.1 SYSTEM VALIDATION	22
10.2 LIQUID VALIDATION	25
11 TYPE A MEASUREMENT UNCERTAINTY	34
12 OUTPUT POWER VERIFICATION	37
12.1 TEST CONDITION	37
12.2 TEST PROCEDURES	37
12.3 TEST RESULT	38
13 EXPOSURE CONDITIONS CONSIDERATION	101
13.1 EUT ANTENNA LOCATION	101
13.2 TEST POSITION CONSIDERATION	101
14 SAR TEST RESULTS	102
14.1 TEST CONDITION	102
14.2 GENERALLY TEST PROCEDURES	102
14.3 SAR SUMMARY TEST RESULT	103
15 SAR MEASUREMENT REFERENCE	128
15.1 REFERENCES	128
15.2 MAXIMUM SAR MEASUREMENT PLOTS	129
16 CALIBRATION REPORTS-PROBE AND DIPOLE	145
17 SAR SYSTEM PHOTOS	239
18 SETUP PHOTOS	240

19 EUT PHOTOS241

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD25D08233044W007	2025-09-22	2025-10-10 to 2025-11-06	2025-12-19	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	ONE
Model(s):	M55
Model Description:	N/A
Test Sample No.:	1-1/1
Wi-Fi Specification:	2.4G-802.11b/g/n(HT20/40)/ax(HE20/40) 5G-802.11a/ n(HT20/40)/ac(VHT20/40/80)/ax(HE20/40/80)
WCDMA Band(s):	FDD Band II
LTE Band(s):	FDD/TDD Band 2/4/5/7/12/13/14/17/25/26/41/66/71
Hardware Version:	Mobile.Router.H01
Software Version:	Mobile.Router.B03

4.2 Details of E.U.T.

Operation Frequency:	2.4G Wi-Fi: 802.11b/g/n HT20/ax HE20: 2412~2462MHz 802.11n HT40/ax HE40: 2422~2452MHz 5G Wi-Fi: 802.11a/n(HT20)/ac(VHT20)/ax (HE20): U-NII-1: 5180-5240MHz, U-NII-2A: 5260-5320MHz(DFS), U-NII-2C: 5500-5720MHz(DFS), U-NII-3: 5745-5825MHz 802.11n(HT40)/ac(VHT40)/ax (HE40): U-NII-1: 5190-5230MHz, U-NII-2A: 5270-5310MHz(DFS), U-NII-2C: 5510-5710MHz(DFS), U-NII-3: 5755-5795MHz 802.11ac(VHT80)/ax(HE80): U-NII-1: 5210MHz, U-NII-2A: 5290MHz(DFS), U-NII-2C: 5530-5690MHz(DFS), U-NII-3: 5775MHz WCDMA Band II: 1850~1910MHz LTE Band 2: 1850~1910MHz LTE Band 4: 1710~1755MHz LTE Band 5: 824~849MHz LTE Band 7: 2500~2570MHz LTE Band 12: 699~716MHz LTE Band 13: 777~787MHz LTE Band 14: 788~798MHz LTE Band 17: 704~716MHz LTE Band 25 1850~1915MHz LTE Band 26(Part 90): 814~824MHz LTE Band 26(Part 22): 824~849MHz LTE Band 41: 2496~2690MHz LTE Band 66: 1710~1780MHz LTE Band 71: 663~698MHz
Max. RF output power:	2.4G Wi-Fi: 20.00dBm 5G Wi-Fi:

	U-NII-1: 18.89dBm
	U-NII-2A: 19.13dBm
	U-NII-2C: 19.09dBm
	U-NII-3: 17.48dBm
	WCDMA Band II: 22.57dBm
	LTE Band 2: 23.60dBm
	LTE Band 4: 23.18dBm
	LTE Band 5: 23.78dBm
	LTE Band 7: 22.53dBm
	LTE Band 12: 23.27dBm
	LTE Band 13: 23.27dBm
	LTE Band 14: 23.11dBm
	LTE Band 17: 23.13dBm
	LTE Band 25: 23.36dBm
	LTE Band 26(Part 90): 23.50dBm
	LTE Band 26(Part 22): 23.63dBm
	LTE Band 41: 23.11dBm
	LTE Band 66: 23.17dBm
	LTE Band 71: 23.95dBm
Max.SAR:	1.180W/kg 1g Body Tissue
Max Simultaneous SAR	1.334W/kg
Type of Modulation:	2.4G Wi-Fi: DSSS, OFDM 5G Wi-Fi: OFDM WCDMA: BPSK, QPSK, 16QAM, 64QAM LTE: QPSK, 16QAM, 64QAM
Antenna installation	2.4G Wi-Fi/5G Wi-Fi: FPC Antenna WCDMA/LTE: FPC Antenna
Antenna Gain:	2.4G Wi-Fi: 2.4dBi 5G Wi-Fi: 2.8dBi WCDMA Band II: 2.4dBi LTE Band 2: 2.4dBi LTE Band 4: 2.2dBi LTE Band 5: 1.6dBi LTE Band 7: 2.8dBi LTE Band 12: 0.9dBi LTE Band 13: 0.9dBi LTE Band 14: 0.9dBi LTE Band 17: 0.9dBi LTE Band 25: 2.4dBi LTE Band 26(Part 90): 1.6dBi LTE Band 26(Part 22): 1.6dBi LTE Band 41: 2.8dBi LTE Band 66: 2.2dBi LTE Band 71: -0.5dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings:

TYPE-C Input: DC 5V/3A, DC 9V/2A, DC 12V/1.5A
TYPE-C output: DC 5V/3A, DC 9V/2.22A, DC 12V/1.67A
CC line Input: DC 5V/3A, DC 9V/2A, DC 12V/1.5A

	CC line output: DC 5V/3A, DC 9V/2.22A, DC 12V/1.67A
	USB-A output: DC 5V/3A, DC 9V/2A, DC 12V/1.5A, DC 10V/2.25A
	Lighting Output: DC 5V/2.4A
Battery:	DC 3.85V, 10000mAh

4.3 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Body-worn (5mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	
WCDMA	1.141	1.6
LTE	1.180	1.6
WLAN 2.4GHz	0.118	1.6
WLAN 5GHz	0.332	1.6
Simultaneous Transmission	1.334	1.6

Remark:

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and IEEE Std C95.1: 2019, and had been tested in accordance with the measurement methods and procedure specified in KDB 865664 D01 v01r04, KDB 865664 D02 v01r02 and KDB 941225 D06.

6 Equipment Used during Test

6.1 Equipment List

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Calibration Due
6 AXIS ROBOT	KUKA	KR6 R900 SIXX	502635	N/A	N/A
SATIMO Test Software	MVG	OPENSAR	OPENSAR V_4_02_27	N/A	N/A
PHANTOM TABLE	MVG	N/A	SAR_1215_01	N/A	N/A
SAM PHANTOM	MVG	SAM118	SN 11/15 SAM118	N/A	N/A
MultiMeter	Keithley	MiltiMeter 2000	4073942	2025-02-25	2026-02-24
S-Parameter Network Analyzer	Agilent	8753E	JP38160684	2025-09-15	2026-09-14
Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	114798	2025-07-04	2026-07-03
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	127818	2025-04-19	2026-04-18
E-Field Probe	MVG	SSE2	2523-EPGO-417	2025-07-25	2026-07-24
DIPOLE 750	MVG	SID750	SN 09/15 DIP 0G750-357	2023-08-08	2026-08-07
DIPOLE 835	MVG	SID835	SN 09/15 DIP 0G835-358	2023-08-08	2026-08-07
DIPOLE 1800	MVG	SID1800	SN 09/15 DIP 1G800-360	2023-08-08	2026-08-07
DIPOLE 1900	MVG	SID1900	SN 09/15 DIP 1G900-361	2023-08-08	2026-08-07
DIPOLE 2450	MVG	SID2450	SN 09/15 DIP 2G450-363	2023-08-08	2026-08-07
DIPOLE 2600	MVG	SID2600	SN 16/15 DIP 2G600-376	2023-08-08	2026-08-07
Limesar Dielectric Probe	MVG	SCLMP	SN 11/15 OCPG 69	2025-02-24	2026-02-23
Power Amplifier	BONN	BLWA 0830 -160/100/40D	128740	2025-07-04	2026-07-03
Signal Generator	R&S	SMB100A	105942	2025-07-04	2026-07-03
Power Meter	R&S	NRP2	102031	2025-07-04	2026-07-03
Power Meter	R&S	NRVD	102284	2025-07-04	2026-07-03
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340009	2025-07-04	2026-07-03
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340010	2025-07-04	2026-07-03

7 SAR Introduction

7.1 Introduction

This measurement report shows compliance of the EUT with IEEE Std C95.1: 2019 and FCC 47 CFR Part2 (2.1093). The test procedures, as described in IEC/IEEE 62209-1528: 2020 Standard for Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –Part 1528: Human models, instrumentation, and procedures(Frequency range of 4 MHz to 10 GHz)

7.2 SAR Definition

- ✧ SAR : Specific Absorption Rate
- ✧ The SAR characterize the absorption of energy by a quantity of tissue
- ✧ This is related to a increase of the temperature of these tissues during a time period.

$$DAS = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

$$DAS = \frac{\sigma E^2}{\rho}$$

$$DAS = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

SAR definition

$$SAR = \frac{\sigma E^2}{\rho}$$

- ✧ SAR : Specific Absorption Rate

- σ : Liquid conductivity

$$\circ \epsilon_r = \epsilon' - j\epsilon'' \text{ (complex permittivity of liquid)}$$

$$\circ \sigma = \frac{\epsilon'' \omega}{\epsilon_0}$$

- ρ : Liquid density


$$\circ \rho = 1000 \text{ g/L} = 1000 \text{ Kg/m}^3$$

where:

σ = conductivity of the tissue (S/m)
 ρ = mass density of the tissue (kg/m³)
 E = rms electric field strength (V/m)

8 SAR Measurement Setup

SAR bench sub-systems





Scanning System (robot)

- ✎ It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- ✎ Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- ✎ Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.




SAM Phantom (Specific Anthropomorphic Mannequin)

- ✎ The probe scanning of the E-Field is done in the 2 half of the normalized head.
- ✎ The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size.
- ✎ The materials for the phantom should not affect the radiation of the device under test (DUT)
 - Permittivity < 5
- ✎ The head is filled with tissue simulating liquid.
- ✎ The hand holding the DUT does not have to be modeled.



Bi-section sagittale du fantôme avec périmètre étendu (montrée sur le côté comme lors des essais de DAS de l'appareil)



The OPENSAR system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (KUKA) with controller and software.
2. KUKA Control Panel (KCP).
3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
4. The functions of the PC plug-in card are to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
5. A computer operating Windows 7.
6. OPENSAR software.
7. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
8. The SAM phantom enabling testing left-hand right-hand and body usage.
9. The Position device for handheld EUT.
10. Tissue simulating liquid mixed according to the given recipes (see Application Note).
11. System validation dipoles to validate the proper functioning of the system.

Data Evaluation

The OPENSAR software automatically executes the following procedure to calculate the field units from the microvolt readings at the probe connector. The parameters used in the valuation are stored in the configuration modules of the software:

Probe Parameters	- Sensitivity	Norm _i
	- Conversion factor	ConvFi
	- Diode compression point Dcpi	
Device Parameter	- Frequency	f
	- Crest factor	cf
Media Parametrs	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the OPENSAR components.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

U_i = Input signal of channel i ($i = x, y, z$)

cf = Crest factor of exciting field (DASY parameter)

dcp_i = Diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

Norm_i = Sensor sensitivity of channel i ($i = x, y, z$)
μV/(V/m)² for E0field Probes

ConvF = Sensitivity enhancement in solution

a_{ij} = Sensor sensitivity factors for H-field probes

$$\begin{aligned}
 f &= \text{Carrier frequency (GHz)} \\
 E_i &= \text{Electric field strength of channel } i \text{ in V/m} \\
 H_i &= \text{Magnetic field strength of channel } i \text{ in A/m}
 \end{aligned}$$

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

$$\begin{aligned}
 \text{where } SAR &= \text{local specific absorption rate in mW/g} \\
 E_{\text{tot}} &= \text{total field strength in V/m} \\
 \sigma &= \text{conductivity in [mho/m] or [siemens/m]} \\
 \rho &= \text{equivalent tissue density in g/cm}^3
 \end{aligned}$$

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{\text{pwe}} = \frac{E_{\text{tot}}^2}{3770} \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

$$\begin{aligned}
 \text{where } P_{\text{pwe}} &= \text{Equivalent power density of a plane wave in mW/cm}^2 \\
 E_{\text{tot}} &= \text{total electric field strength in V/m} \\
 H_{\text{tot}} &= \text{total magnetic field strength in A/m}
 \end{aligned}$$

SAR Evaluation – Peak Spatial - Average

The procedure for assessing the peak spatial-average SAR value consists of the following steps

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in OPENSAR software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

SAR Evaluation – Peak SAR

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1528 standard. It can be conducted for 1 g and 10 g. The OPENSAR system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the fourth order least square polynomial method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

Definition of Reference Points

Ear Reference Point

Figure 6.2 shows the front, back and side views of the SAM Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 6.1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 6.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 6.1 Close-up side view of ERP's



Figure 6.2 Front, back and side view of SAM

Device Reference Points

Two imaginary lines on the device need to be established: the vertical centerline and the horizontal line. The test device is placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 6.3). The “test device reference point” is then located at the same level as the center of the ear reference point. The test device is positioned so that the “vertical centerline” is bisecting the front surface of the device at its top and bottom edges, positioning the “ear reference point” on the outer surface of both the left and right head phantoms on the ear reference point [5].




Figure 6.3 Handset Vertical Center & Horizontal Line Reference Points

Test Configuration – Positioning for Cheek / Touch

1. Position the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure below), such that the plane defined by the vertical center line and the horizontal line of the device is approximately parallel to the sagittal plane of the phantom




Figure 7.1 Front, Side and Top View of Cheek/Touch Position

2. Translate the device towards the phantom along the line passing through RE and LE until the device touches the ear.
3. While maintaining the device in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
4. Rotate the device around the vertical centerline until the device (horizontal line) is symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the device contact with the ear, rotate the device about the line NF until any point on the device is in contact with a phantom point below the ear (cheek). See Figure below.




Figure 7.2 Side view w/ relevant markings

Test Configuration – Positioning for Ear / 15° Tilt

With the test device aligned in the Cheek/Touch Position”:

1. While maintaining the orientation of the device, retract the device parallel to the reference plane far enough to enable a rotation of the device by 15 degrees.
2. Rotate the device around the horizontal line by 15 degrees.
3. While maintaining the orientation of the device, move the device parallel to the reference plane until any part of the device touches the head. (In this position, point A is located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, the angle of the device shall be reduced. The tilted position is obtained when any part of the device is in contact with the ear as well as a second part of the device is in contact with the head (see Figure below).





Figure 7.3 Front, Side and Top View of Ear/15° Tilt Position

Test Position – Body Configurations

Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.0 cm or holster surface and the flat phantom to 0 cm.



9 Exposure limit

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 8.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00


¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

10 System and liquid validation

10.1 System validation



Verification Setup Block Diagram



Dipole Antenna Setup Photo

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 30 dBm (1000 mW) before dipole is connected.

Numerical reference SAR values (W/kg) for reference dipole and flat phantom

Frequency (MHz)	1g SAR	10g SAR	Local SAR at surface(above feed-point)	Local SAR at surface(y = 2 cm offset from feedpoint)
300	3.02	2.04	4.40	2.10
450	4.92	3.28	7.20	3.20
750	8.49	5.55	12.6	4.59
835	9.56	6.22	14.1	4.90
900	10.9	6.99	16.4	5.40
1450	29.0	16.0	50.2	6.50
1800	38.4	20.1	69.5	6.80
1900	39.7	20.5	72.1	6.60
2000	41.1	21.1	74.6	6.50
2450	52.4	24.0	104	7.70
2600	55.3	24.6	113	8.29
3000	63.8	25.7	140	9.50

Table 1: system validation (1g)

Measurement Date	Frequency (MHz)	Liquid Type (head/body)	1W Target SAR1g (W/kg)	Measured SAR1g (W/kg)	1W Normalized SAR1g (W/kg)	Desired Tolerance (%)	Actual Tolerance (%)
2025-10-24	750	head	8.78	0.915	9.15	±10	4.21
2025-10-23	835	head	9.57	0.962	9.62	±10	0.52
2025-10-28	1800	head	38.73	4.104	41.04	±10	5.96
2025-10-28	1900	head	39.51	4.117	41.17	±10	4.20
2025-10-18	2450	head	54.33	5.549	55.49	±10	2.14
2025-10-20	2600	head	56.23	5.486	54.86	±10	-2.44

Remark: 1. system check input power: 100mW.

2. Referring to IEEE 1528:2013, Section 8.2, The system check shall be performed at a test frequency that is within ±10% or ±100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

10.2 liquid validation

The dielectric parameters were checked prior to assessment using the HP85070C dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

KDB 865664 recommended Tissue Dielectric Parameters

The head and body tissue parameters given in this below table should be used to measure the SAR of transmitters operating in 100 MHz to 6 GHz frequency range. The tissue dielectric parameters of the tissue medium at the test frequency should be within the tolerance required in this document. The dielectric parameters should be linearly interpolated between the closest pair of target frequencies to determine the applicable dielectric parameters corresponding to the device test frequency.

The head tissue dielectric parameters recommended by IEEE Std 1528-2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in 1528 are derived from tissue dielectric parameters computed from the 4-Cole-Cole equations described above and extrapolated according to the head parameters specified in 1528.

Target Frequency	Head Tissue		Body Tissue	
MHz	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
750	41.9	0.89	55.5	0.96
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness Power drifts in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Table 2: Recommended Dielectric Performance of Tissue

Recommended Dielectric Performance of Tissue						
Head/Body						
Ingredients (% by weight)	Frequency (MHz)					
	750	835	1800	1900	2450	2600
Water	40.52	41.45	55.2	54.9	62.7	54.8
Salt (Nacl)	1.61	1.45	0.3	0.18	0.5	0.1
Sugar	57.67	56.0	0.0	0.0	0.0	0.0
HEC	0.1	1.0	0.0	0.0	0.0	0.0
Bactericide	0.1	0.1	0.0	0.0	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	44.5	44.92	0.0	45.1

Table 3: Dielectric Performance of Head Tissue Simulating Liquid


Temperature: 22.9°C , Relative humidity: 51.4%				
Frequency(MHz)	Measured Date	Description	Dielectric Parameters	
			ϵ_r	$\sigma(\text{s/m})$
750	2025-10-24	Target Value $\pm 5\%$ window	41.90 39.81 — 44.00	0.89 0.85 — 0.93
		Measurement Value	42.13	0.91
835	2025-10-23	Target Value $\pm 5\%$ window	41.50 39.43 — 43.58	0.90 0.86 — 0.95
		Measurement Value	41.50	0.90
1800	2025-10-28	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	38.61	1.34
1900	2025-10-28	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	38.96	1.35
2450	2025-10-18	Target Value $\pm 5\%$ window	39.2 37.24 — 41.16	1.80 1.71 — 1.89
		Measurement Value	39.23	1.79
2600	2025-10-20	Target Value $\pm 5\%$ window	39.0 37.05 — 40.95	1.96 1.87 — 2.05
		Measurement Value	39.09	1.89

System Verification Plots




Product Description: Dipole

Model: SID750


Test Date: 2025-10-24




Product Description: Dipole
Model: SID835
Test Date: 2025-10-23

Medium(liquid type)	HL850
Frequency (MHz)	835.000
Relative permittivity (real part)	41.50
Conductivity (S/m)	0.90
Input power	100mW
Crest factor	1.0
E-Field Probe	2523-EPGO-417
Conversion Factor	2.47
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-2.25
SAR 10g (W/kg)	0.611823
SAR 1g (W/kg)	0.961766
SURFACE SAR	VOLUME SAR
	
	




Product Description: Dipole
Model: SID1800
Test Date: 2025-10-28




Product Description: Dipole
Model: SID1900
Test Date: 2025-10-28



Product Description: Dipole
Model: SID2450
Test Date: 2025-10-18

Medium(liquid type)	HL2450
Frequency (MHz)	2450.000
Relative permittivity (real part)	39.23
Conductivity (S/m)	1.79
Input power	100mW
Crest factor	1.0
E-Field Probe	2523-EPGO-417
Conversion Factor	3.02
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Variation (%)	-1.86
SAR 10g (W/kg)	2.711062
SAR 1g (W/kg)	5.548538
SURFACE SAR	VOLUME SAR
	
	

Product Description: Dipole
Model: SID2600
Test Date: 2025-10-20



11 Type a Measurement Uncertainty

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table below :

Uncertainty Distribution	Normal	Rectangle	Triangular	U Shape
Multi-plying Factor(a)	$1/k(b)$	$1 / \sqrt{3}$	$1 / \sqrt{6}$	$1 / \sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type -sum- by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %.

The COMOSAR Uncertainty Budget is show in below table:

UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0.00	N	1	1	1	0.00	0.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	4.00	N	1	1	1	4.00	4.00	∞
Input power and SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid Distance	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.21	10.12	
Expanded Uncertainty (95% Confidence interval)		k				19.91	19.73	

UNCERTAINTY EVALUATION FOR HANDSET SAR TEST								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{Cp})^{\wedge 1/2}$	$(1_{Cp})^{\wedge 1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{\wedge 1/2}$	$(Cp)^{\wedge 1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.00	N	1	1	1	3.00	3.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.60	N	1	1	1	2.60	2.60	N-1
Device Holder Uncertainty	3.00	N	1	1	1	3.00	3.00	N-1
Output power Variation - SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.63	10.54	
Expanded Uncertainty (95% Confidence interval)		k				20.73	20.56	

12 Output Power Verification

12.1 Test Condition

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The base station simulator was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is $\pm 1.5\text{dB}$.
3. Environmental Conditions

Temperature	23.2°C
Relative Humidity	52.9%
Atmospheric Pressure	1014mbar

12.2 Test Procedures

ONE radio output power measurement

1. The transmitter output port was connected to base station emulator.
2. Establish communication link between emulator and EUT and set EUT to operate at maximum output power all the time.
3. Select lowest, middle, and highest channels for each band and different possible test mode.
4. Measure the conducted peak burst power and conducted average burst power from EUT antenna port.

Other radio output power measurement:

The output power was measured using power meter at low, mid, and hi channels.

Source-based Time Averaged Burst Power Calculation:

For TDMA, the following duty cycle factor was used to calculate the source-based time average power

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Duty cycle factor	-9.03 dB	-6.02 dB	-4.26 dB	-3.01 dB
Crest Factor	8	4	2.66	2

Remark: Time slot duty cycle factor = $10 * \log(\text{Time Slot Duty Cycle})$

Source based time averaged power = Maximum burst averaged power (1 Uplink) – 9.03 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) – 6.02 dB

Source based time averaged power = Maximum burst averaged power (3 Uplink) – 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Uplink) – 3.01 dB

12.3 Test Result

WCDMA - Average Power (dBm)				
Band	WCDMA Band II			
Channel	9262	9400	9538	Tune up Power tolerant
Frequency (MHz)	1852.4	1880	1907.6	/
RMC 12.2k	22.54	22.57	22.44	22±1
HSDPA Subtest-1	21.72	21.77	21.62	21±1
HSDPA Subtest-2	21.29	21.32	21.20	21±1
HSDPA Subtest-3	20.94	21.03	20.93	21±1
HSDPA Subtest-4	20.63	20.67	20.56	20±1
HSUPA Subtest-1	22.13	22.19	22.05	21±1
HSUPA Subtest-2	21.63	21.78	21.60	21±1
HSUPA Subtest-3	21.37	21.57	21.25	21±1
HSUPA Subtest-4	21.08	21.29	21.03	20±1
HSUPA Subtest-5	20.80	20.94	20.64	20±1

LTE Power Reduction

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-
Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.					

LTE Band 2:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	18607	1850.7	QPSK	1	0	23.6	23.0±1	/
				1	2	23.37	23.0±1	/
				1	5	23.46	23.0±1	/
				3	0	23.27	23.0±1	/
				3	1	23.24	23.0±1	/
				3	2	23.2	23.0±1	/
				6	0	22.14	23.0±1	1.0
			16QAM	1	0	22.41	22.0±1	1.0
				1	2	22.28	22.0±1	1.0
				1	5	22.35	22.0±1	1.0
				3	0	22.18	22.0±1	1.0
				3	1	22.17	22.0±1	1.0
				3	2	22.13	22.0±1	1.0
				6	0	21.32	22.0±1	1.0
	18900	1880	QPSK	1	0	23.19	23.0±1	/
				1	2	23.08	23.0±1	/
				1	5	23.16	23.0±1	/
				3	0	22.99	23.0±1	/
				3	1	22.99	23.0±1	/
				3	2	22.97	23.0±1	/
				6	0	22.03	23.0±1	1.0
			16QAM	1	0	22.52	22.0±1	1.0
				1	2	22.45	22.0±1	1.0
				1	5	22.55	22.0±1	1.0
				3	0	22.24	22.0±1	1.0
				3	1	22.25	22.0±1	1.0
				3	2	22.23	22.0±1	1.0
				6	0	21	22.0±1	1.0
	19193	1909.3	QPSK	1	0	23.36	23.0±1	/
				1	2	23.25	23.0±1	/
				1	5	23.35	23.0±1	/
				3	0	23.16	23.0±1	/
				3	1	23.24	23.0±1	/
				3	2	23.24	23.0±1	/
				6	0	22.16	23.0±1	1.0
			16QAM	1	0	22.29	22.0±1	1.0
				1	2	22.27	22.0±1	1.0
				1	5	22.29	22.0±1	1.0
				3	0	22.33	22.0±1	1.0
				3	1	22.41	22.0±1	1.0
				3	2	22.38	22.0±1	1.0
				6	0	21.48	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	18615	1851.5	QPSK	1	0	23.23	22.5±1	/
				1	8	23.18	22.5±1	/
				1	14	23.03	22.5±1	/
				6	0	22.03	22.5±1	1.0
				6	4	22.02	22.5±1	1.0
				6	9	21.9	22.5±1	1.0
				15	0	21.96	22.5±1	1.0
			16QAM	1	0	21.99	21.0±1	1.0
				1	8	21.93	21.0±1	1.0
				1	14	21.79	21.0±1	1.0
				6	0	21.17	21.0±1	1.0
				6	4	21.17	21.0±1	1.0
				6	9	21.06	21.0±1	1.0
				15	0	21.05	21.0±1	1.0
	18900	1880	QPSK	1	0	22.92	22.5±1	/
				1	8	23.05	22.5±1	/
				1	14	22.9	22.5±1	/
				6	0	22.03	22.5±1	1.0
				6	4	22.04	22.5±1	1.0
				6	9	22	22.5±1	1.0
				15	0	21.98	22.5±1	1.0
			16QAM	1	0	22.37	22.0±1	1.0
				1	8	22.44	22.0±1	1.0
				1	14	22.31	22.0±1	1.0
				6	0	21.13	22.0±1	1.0
				6	4	21.16	22.0±1	1.0
				6	9	21.12	22.0±1	1.0
				15	0	21.04	22.0±1	1.0
	19185	1908.5	QPSK	1	0	23.02	22.5±1	/
				1	8	23.15	22.5±1	/
				1	14	23.22	22.5±1	/
				6	0	22.08	22.5±1	1.0
				6	4	22.11	22.5±1	1.0
				6	9	22.18	22.5±1	1.0
				15	0	22.07	22.5±1	1.0
			16QAM	1	0	22.02	22.0±1	1.0
				1	8	22.13	22.0±1	1.0
				1	14	22.13	22.0±1	1.0
				6	0	21.21	22.0±1	1.0
				6	4	21.24	22.0±1	1.0
				6	9	21.31	22.0±1	1.0
				15	0	21.13	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	18625	1852.5	QPSK	1	0	23.22	22.5±1	/
				1	12	23.12	22.5±1	/
				1	24	23.04	22.5±1	/
				12	0	21.9	22.5±1	1.0
				12	6	21.89	22.5±1	1.0
				12	11	21.83	22.5±1	1.0
				25	0	21.82	22.5±1	1.0
			16QAM	1	0	22.13	21.5±1	1.0
				1	12	22.07	21.5±1	1.0
				1	24	22.07	21.5±1	1.0
				12	0	21.01	21.5±1	1.0
				12	6	21.01	21.5±1	1.0
				12	11	20.96	21.5±1	1.0
				25	0	20.9	21.5±1	1.0
	18900	1880	QPSK	1	0	22.85	22.0±1	/
				1	12	22.98	22.0±1	/
				1	24	22.75	22.0±1	/
				12	0	21.86	22.0±1	1.0
				12	6	22	22.0±1	1.0
				12	11	21.9	22.0±1	1.0
				25	0	21.92	22.0±1	1.0
			16QAM	1	0	22.36	22.0±1	1.0
				1	12	22.53	22.0±1	1.0
				1	24	22.26	22.0±1	1.0
				12	0	21.06	22.0±1	1.0
				12	6	21.16	22.0±1	1.0
				12	11	21.07	22.0±1	1.0
				25	0	21.01	22.0±1	1.0
	19175	1907.5	QPSK	1	0	23.09	22.5±1	/
				1	12	23.09	22.5±1	/
				1	24	23.26	22.5±1	/
				12	0	22.05	22.5±1	1.0
				12	6	22.1	22.5±1	1.0
				12	11	22.06	22.5±1	1.0
				25	0	22.05	22.5±1	1.0
			16QAM	1	0	22.16	22.0±1	1.0
				1	12	22.16	22.0±1	1.0
				1	24	22.24	22.0±1	1.0
				12	0	21.18	22.0±1	1.0
				12	6	21.23	22.0±1	1.0
				12	11	21.2	22.0±1	1.0
				25	0	21.09	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	18650	1855	QPSK	1	0	23.04	22.5±1	/
				1	24	23.08	22.5±1	/
				1	49	22.85	22.5±1	/
				25	0	21.69	22.5±1	1.0
				25	12	21.92	22.5±1	1.0
				25	24	21.79	22.5±1	1.0
				50	0	21.9	22.5±1	1.0
			16QAM	1	0	21.73	21.0±1	1.0
				1	24	21.91	21.0±1	1.0
				1	49	21.77	21.0±1	1.0
				25	0	20.77	21.0±1	1.0
				25	12	21.03	21.0±1	1.0
				25	24	20.92	21.0±1	1.0
				50	0	20.95	21.0±1	1.0
	18900	1880	QPSK	1	0	22.55	22.0±1	/
				1	24	22.93	22.0±1	/
				1	49	22.67	22.0±1	/
				25	0	21.68	22.0±1	1.0
				25	12	21.93	22.0±1	1.0
				25	24	21.73	22.0±1	1.0
				50	0	21.83	22.0±1	1.0
			16QAM	1	0	21.95	21.5±1	1.0
				1	24	22.38	21.5±1	1.0
				1	49	22.04	21.5±1	1.0
				25	0	20.72	21.5±1	1.0
				25	12	21.02	21.5±1	1.0
				25	24	20.8	21.5±1	1.0
				50	0	20.93	21.5±1	1.0
	19150	1905	QPSK	1	0	22.58	22.5±1	/
				1	24	23.01	22.5±1	/
				1	49	23.06	22.5±1	/
				25	0	21.91	22.5±1	1.0
				25	12	22.06	22.5±1	1.0
				25	24	21.88	22.5±1	1.0
				50	0	21.99	22.5±1	1.0
			16QAM	1	0	21.77	22.0±1	1.0
				1	24	22.12	22.0±1	1.0
				1	49	22.03	22.0±1	1.0
				25	0	21.03	22.0±1	1.0
				25	12	21.23	22.0±1	1.0
				25	24	21.05	22.0±1	1.0
				50	0	21.11	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	18675	1857.5	QPSK	1	0	23.1	22.5±1	/
				1	37	23.08	22.5±1	/
				1	74	23.05	22.5±1	/
				36	0	21.96	22.5±1	1.0
				36	16	22.03	22.5±1	1.0
				36	35	22.09	22.5±1	1.0
				75	0	22.03	22.5±1	1.0
			16QAM	1	0	21.83	21.5±1	1.0
				1	37	21.96	21.5±1	1.0
				1	74	22.09	21.5±1	1.0
				36	0	20.98	21.5±1	1.0
				36	16	21.07	21.5±1	1.0
				36	35	21.15	21.5±1	1.0
				75	0	21.1	21.5±1	1.0
	18900	1880	QPSK	1	0	22.69	22.0±1	/
				1	37	22.99	22.0±1	/
				1	74	22.78	22.0±1	/
				36	0	21.78	22.0±1	1.0
				36	16	21.94	22.0±1	1.0
				36	35	21.82	22.0±1	1.0
				75	0	21.93	22.0±1	1.0
			16QAM	1	0	22.1	21.5±1	1.0
				1	37	22.37	21.5±1	1.0
				1	74	22.21	21.5±1	1.0
				36	0	20.85	21.5±1	1.0
				36	16	21.08	21.5±1	1.0
				36	35	20.91	21.5±1	1.0
				75	0	21.06	21.5±1	1.0
	19125	1902.5	QPSK	1	0	23.03	22.5±1	/
				1	37	22.91	22.5±1	/
				1	74	23.18	22.5±1	/
				36	0	22.01	22.5±1	1.0
				36	16	22.12	22.5±1	1.0
				36	35	21.98	22.5±1	1.0
				75	0	21.97	22.5±1	1.0
			16QAM	1	0	22.54	22.0±1	1.0
				1	37	22.43	22.0±1	1.0
				1	74	22.44	22.0±1	1.0
				36	0	21.03	22.0±1	1.0
				36	16	21.14	22.0±1	1.0
				36	35	21.08	22.0±1	1.0
				75	0	21.07	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	18700	1860	QPSK	1	0	23	22.5±1	/
				1	49	23.01	22.5±1	/
				1	99	22.59	22.5±1	/
				50	0	21.95	22.5±1	1.0
				50	24	22.13	22.5±1	1.0
				50	49	22.08	22.5±1	1.0
				100	0	21.98	22.5±1	1.0
			16QAM	1	0	22.31	22.0±1	1.0
				1	49	22.59	22.0±1	1.0
				1	99	22.26	22.0±1	1.0
				50	0	21.01	22.0±1	1.0
				50	24	21.21	22.0±1	1.0
				50	49	21.12	22.0±1	1.0
				100	0	21.09	22.0±1	1.0
	18900	1880	QPSK	1	0	22.47	22.0±1	/
				1	49	22.91	22.0±1	/
				1	99	22.66	22.0±1	/
				50	0	21.65	22.0±1	1.0
				50	24	21.95	22.0±1	1.0
				50	49	21.81	22.0±1	1.0
				100	0	21.93	22.0±1	1.0
			16QAM	1	0	22.1	21.5±1	1.0
				1	49	22.44	21.5±1	1.0
				1	99	22.2	21.5±1	1.0
				50	0	20.74	21.5±1	1.0
				50	24	21.06	21.5±1	1.0
				50	49	20.87	21.5±1	1.0
				100	0	21.05	21.5±1	1.0
	19100	1900	QPSK	1	0	22.99	22.5±1	/
				1	49	22.86	22.5±1	/
				1	99	23.02	22.5±1	/
				50	0	22.23	22.5±1	1.0
				50	24	21.85	22.5±1	1.0
				50	49	22.07	22.5±1	1.0
				100	0	21.57	22.5±1	1.0
			16QAM	1	0	22.46	21.5±1	1.0
				1	49	22.32	21.5±1	1.0
				1	99	22.35	21.5±1	1.0
				50	0	21.26	21.5±1	1.0
				50	24	20.92	21.5±1	1.0
				50	49	21.11	21.5±1	1.0
				100	0	20.68	21.5±1	1.0

LTE Band 4:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	19957	1710.7	QPSK	1	0	23.17	22.5±1	/
				1	2	23.02	22.5±1	/
				1	5	23.18	22.5±1	/
				3	0	22.97	22.5±1	/
				3	1	22.97	22.5±1	/
				3	2	22.93	22.5±1	/
				6	0	21.83	22.5±1	1.0
			16QAM	1	0	22.06	22.0±1	1.0
				1	2	21.92	22.0±1	1.0
				1	5	22.08	22.0±1	1.0
				3	0	21.82	22.0±1	1.0
				3	1	21.84	22.0±1	1.0
				3	2	21.81	22.0±1	1.0
				6	0	21	22.0±1	1.0
	20175	1732.5	QPSK	1	0	23.16	22.5±1	/
				1	2	22.96	22.5±1	/
				1	5	23.08	22.5±1	/
				3	0	22.89	22.5±1	/
				3	1	22.88	22.5±1	/
				3	2	22.86	22.5±1	/
				6	0	21.76	22.5±1	1.0
			16QAM	1	0	22.31	21.5±1	1.0
				1	2	22.17	21.5±1	1.0
				1	5	22.28	21.5±1	1.0
				3	0	21.97	21.5±1	1.0
				3	1	21.97	21.5±1	1.0
				3	2	21.96	21.5±1	1.0
				6	0	20.75	21.5±1	1.0
	20393	1754.3	QPSK	1	0	23.03	22.5±1	/
				1	2	22.86	22.5±1	/
				1	5	22.99	22.5±1	/
				3	0	22.85	22.5±1	/
				3	1	22.86	22.5±1	/
				3	2	22.86	22.5±1	/
				6	0	21.68	22.5±1	1.0
			16QAM	1	0	21.85	21.0±1	1.0
				1	2	21.72	21.0±1	1.0
				1	5	21.9	21.0±1	1.0
				3	0	21.86	21.0±1	1.0
				3	1	21.87	21.0±1	1.0
				3	2	21.88	21.0±1	1.0
				6	0	21.03	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	19965	1711.5	QPSK	1	0	22.95	22.5±1	/
				1	8	23.01	22.5±1	/
				1	14	22.92	22.5±1	/
				6	0	21.77	22.5±1	1.0
				6	4	21.82	22.5±1	1.0
				6	9	21.78	22.5±1	1.0
				15	0	21.77	22.5±1	1.0
			16QAM	1	0	21.62	21.0±1	1.0
				1	8	21.7	21.0±1	1.0
				1	14	21.65	21.0±1	1.0
				8	0	20.92	21.0±1	1.0
				8	4	20.98	21.0±1	1.0
				8	9	20.95	21.0±1	1.0
				15	0	20.87	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.99	22.0±1	/
				1	8	22.94	22.0±1	/
				1	14	22.88	22.0±1	/
				6	0	21.76	22.0±1	1.0
				6	4	21.78	22.0±1	1.0
				6	9	21.73	22.0±1	1.0
				15	0	21.72	22.0±1	1.0
			16QAM	1	0	22.12	21.5±1	1.0
				1	8	22.15	21.5±1	1.0
				1	14	22.06	21.5±1	1.0
				6	0	20.92	21.5±1	1.0
				6	4	20.94	21.5±1	1.0
				6	9	20.9	21.5±1	1.0
				15	0	20.83	21.5±1	1.0
	20385	1753.5	QPSK	1	0	22.93	22.0±1	/
				1	8	22.86	22.0±1	/
				1	14	22.88	22.0±1	/
				6	0	21.76	22.0±1	1.0
				6	4	21.79	22.0±1	1.0
				6	9	21.67	22.0±1	1.0
				15	0	21.75	22.0±1	1.0
			16QAM	1	0	21.77	21.0±1	1.0
				1	8	21.82	21.0±1	1.0
				1	14	21.75	21.0±1	1.0
				8	0	20.94	21.0±1	1.0
				8	4	20.98	21.0±1	1.0
				8	9	20.9	21.0±1	1.0
				15	0	20.86	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	19975	1712.5	QPSK	1	0	22.88	22.0±1	/
				1	49	22.91	22.0±1	/
				1	99	22.72	22.0±1	/
				12	0	21.75	22.0±1	1.0
				12	24	21.82	22.0±1	1.0
				12	49	21.75	22.0±1	1.0
				25	0	21.72	22.0±1	1.0
			16QAM	1	0	21.92	21.0±1	1.0
				1	49	21.96	21.0±1	1.0
				1	99	21.75	21.0±1	1.0
				12	0	20.87	21.0±1	1.0
				12	24	20.96	21.0±1	1.0
				12	49	20.9	21.0±1	1.0
				25	0	20.81	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.91	22.0±1	/
				1	49	22.92	22.0±1	/
				1	99	22.82	22.0±1	/
				12	0	21.73	22.0±1	1.0
				12	24	21.78	22.0±1	1.0
				12	49	21.68	22.0±1	1.0
				25	0	21.69	22.0±1	1.0
			16QAM	1	0	22.19	21.5±1	1.0
				1	49	22.29	21.5±1	1.0
				1	99	22.18	21.5±1	1.0
				12	0	20.94	21.5±1	1.0
				12	24	20.99	21.5±1	1.0
				12	49	20.89	21.5±1	1.0
				25	0	20.83	21.5±1	1.0
	20375	1752.5	QPSK	1	0	22.94	22.5±1	/
				1	49	23.03	22.5±1	/
				1	99	22.88	22.5±1	/
				12	0	21.77	22.5±1	1.0
				12	24	21.82	22.5±1	1.0
				12	49	21.72	22.5±1	1.0
				25	0	21.73	22.5±1	1.0
			16QAM	1	0	21.85	21.0±1	1.0
				1	49	21.95	21.0±1	1.0
				1	99	21.89	21.0±1	1.0
				12	0	20.98	21.0±1	1.0
				12	24	21	21.0±1	1.0
				12	49	20.94	21.0±1	1.0
				25	0	20.77	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20000	1715	QPSK	1	0	22.76	22.0±1	/
				1	49	22.79	22.0±1	/
				1	99	22.75	22.0±1	/
				25	0	21.55	22.0±1	1.0
				25	24	21.58	22.0±1	1.0
				25	49	21.5	22.0±1	1.0
				50	0	21.5	22.0±1	1.0
			16QAM	1	0	21.47	21.0±1	1.0
				1	49	21.5	21.0±1	1.0
				1	99	21.52	21.0±1	1.0
				25	0	20.63	21.0±1	1.0
				25	24	20.67	21.0±1	1.0
				25	49	20.58	21.0±1	1.0
				50	0	20.55	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.79	22.0±1	/
				1	49	22.88	22.0±1	/
				1	99	22.73	22.0±1	/
				25	0	21.63	22.0±1	1.0
				25	24	21.71	22.0±1	1.0
				25	49	21.52	22.0±1	1.0
				50	0	21.59	22.0±1	1.0
			16QAM	1	0	22.02	21.5±1	1.0
				1	49	22.14	21.5±1	1.0
				1	99	21.96	21.5±1	1.0
				25	0	20.72	21.5±1	1.0
				25	24	20.81	21.5±1	1.0
				25	49	20.63	21.5±1	1.0
				50	0	20.68	21.5±1	1.0
	20350	1750	QPSK	1	0	22.58	22.0±1	/
				1	49	22.85	22.0±1	/
				1	99	22.66	22.0±1	/
				25	0	21.53	22.0±1	1.0
				25	24	21.62	22.0±1	1.0
				25	49	21.53	22.0±1	1.0
				50	0	21.49	22.0±1	1.0
			16QAM	1	0	21.49	21.0±1	1.0
				1	49	21.71	21.0±1	1.0
				1	99	21.55	21.0±1	1.0
				25	0	20.68	21.0±1	1.0
				25	24	20.87	21.0±1	1.0
				25	49	20.74	21.0±1	1.0
				50	0	20.7	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20025	1717.5	QPSK	1	0	22.75	22.0±1	/
				1	49	22.83	22.0±1	/
				1	99	22.81	22.0±1	/
				36	0	21.63	22.0±1	1.0
				36	24	21.75	22.0±1	1.0
				36	49	21.79	22.0±1	1.0
				75	0	21.68	22.0±1	1.0
			16QAM	1	0	21.53	21.0±1	1.0
				1	49	21.66	21.0±1	1.0
				1	99	21.61	21.0±1	1.0
				36	0	20.67	21.0±1	1.0
				36	24	20.82	21.0±1	1.0
				36	49	20.87	21.0±1	1.0
				75	0	20.77	21.0±1	1.0
	20175	1732.5	QPSK	1	0	22.82	22.0±1	/
				1	49	22.98	22.0±1	/
				1	99	22.74	22.0±1	/
				36	0	21.71	22.0±1	1.0
				36	24	21.73	22.0±1	1.0
				36	49	21.57	22.0±1	1.0
				75	0	21.63	22.0±1	1.0
			16QAM	1	0	21.98	21.5±1	1.0
				1	49	22.16	21.5±1	1.0
				1	99	21.95	21.5±1	1.0
				36	0	20.8	21.5±1	1.0
				36	24	20.83	21.5±1	1.0
				36	49	20.77	21.5±1	1.0
				75	0	20.82	21.5±1	1.0
	20325	1747.5	QPSK	1	0	22.77	22.0±1	/
				1	49	22.9	22.0±1	/
				1	99	22.77	22.0±1	/
				36	0	21.6	22.0±1	1.0
				36	24	21.65	22.0±1	1.0
				36	49	21.63	22.0±1	1.0
				75	0	21.59	22.0±1	1.0
			16QAM	1	0	22.06	21.5±1	1.0
				1	49	22.19	21.5±1	1.0
				1	99	22.02	21.5±1	1.0
				36	0	20.67	21.5±1	1.0
				36	24	20.76	21.5±1	1.0
				36	49	20.79	21.5±1	1.0
				75	0	20.71	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20050	1720	QPSK	1	0	22.63	22.0±1	/
				1	49	22.97	22.0±1	/
				1	99	22.78	22.0±1	/
				50	0	21.55	22.0±1	1.0
				50	24	21.8	22.0±1	1.0
				50	49	21.78	22.0±1	1.0
				100	0	21.64	22.0±1	1.0
			16QAM	1	0	22.1	21.5±1	1.0
				1	49	22.37	21.5±1	1.0
				1	99	22.29	21.5±1	1.0
				50	0	20.62	21.5±1	1.0
				50	24	20.89	21.5±1	1.0
				50	49	20.91	21.5±1	1.0
				100	0	20.74	21.5±1	1.0
	20175	1732.5	QPSK	1	0	22.7	22.0±1	/
				1	49	22.91	22.0±1	/
				1	99	22.65	22.0±1	/
				50	0	21.68	22.0±1	1.0
				50	24	21.76	22.0±1	1.0
				50	49	21.55	22.0±1	1.0
				100	0	21.61	22.0±1	1.0
			16QAM	1	0	22.06	21.5±1	1.0
				1	49	22.2	21.5±1	1.0
				1	99	22.1	21.5±1	1.0
				50	0	20.78	21.5±1	1.0
				50	24	20.86	21.5±1	1.0
				50	49	20.65	21.5±1	1.0
				100	0	20.73	21.5±1	1.0
	20300	1745	QPSK	1	0	22.7	22.0±1	/
				1	49	22.86	22.0±1	/
				1	99	22.63	22.0±1	/
				50	0	21.55	22.0±1	1.0
				50	24	21.72	22.0±1	1.0
				50	49	21.56	22.0±1	1.0
				100	0	21.62	22.0±1	1.0
			16QAM	1	0	21.99	21.5±1	1.0
				1	49	22.09	21.5±1	1.0
				1	99	21.91	21.5±1	1.0
				50	0	20.61	21.5±1	1.0
				50	24	20.76	21.5±1	1.0
				50	49	20.62	21.5±1	1.0
				100	0	20.7	21.5±1	1.0

LTE Band 5:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	20407	824.7	QPSK	1	0	23.57	23.0±1	/
				1	2	23.4	23.0±1	/
				1	5	23.6	23.0±1	/
				3	0	23.31	23.0±1	/
				3	1	23.39	23.0±1	/
				3	2	23.35	23.0±1	/
				6	0	22.36	23.0±1	1.0
			16QAM	1	0	22.57	22.0±1	1.0
				1	2	22.5	22.0±1	1.0
				1	5	22.52	22.0±1	1.0
				3	0	22.4	22.0±1	1.0
				3	1	22.4	22.0±1	1.0
				3	2	22.36	22.0±1	1.0
				6	0	21.39	22.0±1	1.0
	20525	836.5	QPSK	1	0	23.39	23.0±1	/
				1	2	23.25	23.0±1	/
				1	5	23.26	23.0±1	/
				3	0	23.23	23.0±1	/
				3	1	23.19	23.0±1	/
				3	2	23.1	23.0±1	/
				6	0	22.24	23.0±1	1.0
			16QAM	1	0	22.71	22.0±1	1.0
				1	2	22.62	22.0±1	1.0
				1	5	22.6	22.0±1	1.0
				3	0	22.46	22.0±1	1.0
				3	1	22.43	22.0±1	1.0
				3	2	22.35	22.0±1	1.0
				6	0	21.12	22.0±1	1.0
	20634	848.3	QPSK	1	0	23.3	22.5±1	/
				1	2	23.02	22.5±1	/
				1	5	22.79	22.5±1	/
				3	0	23.16	22.5±1	/
				3	1	23.02	22.5±1	/
				3	2	22.79	22.5±1	/
				6	0	21.85	22.5±1	1.0
			16QAM	1	0	22.19	22.0±1	1.0
				1	2	21.84	22.0±1	1.0
				1	5	21.64	22.0±1	1.0
				3	0	22.13	22.0±1	1.0
				3	1	22	22.0±1	1.0
				3	2	21.78	22.0±1	1.0
				6	0	21.06	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	20415	825.5	QPSK	1	0	23.28	23.0±1	/
				1	8	23.31	23.0±1	/
				1	14	23.28	23.0±1	/
				6	0	22.26	23.0±1	1.0
				6	4	22.26	23.0±1	1.0
				6	9	22.24	23.0±1	1.0
				15	0	22.22	23.0±1	1.0
			16QAM	1	0	22.12	22.0±1	1.0
				1	8	22.17	22.0±1	1.0
				1	14	22.07	22.0±1	1.0
				8	0	21.31	22.0±1	1.0
				8	4	21.31	22.0±1	1.0
				8	9	21.3	22.0±1	1.0
				15	0	21.21	22.0±1	1.0
	20525	836.5	QPSK	1	0	23.24	23.0±1	/
				1	8	23.18	23.0±1	/
				1	14	23.01	23.0±1	/
				6	0	22.31	23.0±1	1.0
				6	4	22.24	23.0±1	1.0
				6	9	22.15	23.0±1	1.0
				15	0	22.16	23.0±1	1.0
			16QAM	1	0	22.6	22.0±1	1.0
				1	8	22.57	22.0±1	1.0
				1	14	22.36	22.0±1	1.0
				6	0	21.35	22.0±1	1.0
				6	4	21.29	22.0±1	1.0
				6	9	21.16	22.0±1	1.0
				15	0	21.17	22.0±1	1.0
	20635	847.5	QPSK	1	0	23.66	22.7±1	/
				1	8	23.33	22.7±1	/
				1	14	22.55	22.7±1	/
				6	0	22.38	22.7±1	1.0
				6	4	22.26	22.7±1	1.0
				6	9	21.87	22.7±1	1.0
				15	0	22.14	22.7±1	1.0
			16QAM	1	0	22.4	22.0±1	1.0
				1	8	22.19	22.0±1	1.0
				1	14	21.4	22.0±1	1.0
				8	0	21.51	22.0±1	1.0
				8	4	21.41	22.0±1	1.0
				8	9	21	22.0±1	1.0
				15	0	21.19	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20425	826.5	QPSK	1	0	23.24	23.0±1	/
				1	49	23.28	23.0±1	/
				1	99	23.27	23.0±1	/
				12	0	22.14	23.0±1	1.0
				12	24	22.23	23.0±1	1.0
				12	49	22.12	23.0±1	1.0
				25	0	22.14	23.0±1	1.0
			16QAM	1	0	22.33	22.0±1	1.0
				1	49	22.41	22.0±1	1.0
				1	99	22.32	22.0±1	1.0
				12	0	21.16	22.0±1	1.0
				12	24	21.25	22.0±1	1.0
				12	49	21.2	22.0±1	1.0
				25	0	21.12	22.0±1	1.0
	20525	836.5	QPSK	1	0	23.1	23.0±1	/
				1	49	23.13	23.0±1	/
				1	99	22.92	23.0±1	/
				12	0	22.24	23.0±1	1.0
				12	24	22.21	23.0±1	1.0
				12	49	22.01	23.0±1	1.0
				25	0	22.08	23.0±1	1.0
			16QAM	1	0	22.67	22.0±1	1.0
				1	49	22.69	22.0±1	1.0
				1	99	22.4	22.0±1	1.0
				12	0	21.34	22.0±1	1.0
				12	24	21.32	22.0±1	1.0
				12	49	21.13	22.0±1	1.0
				25	0	21.11	22.0±1	1.0
	20625	846.5	QPSK	1	0	23.36	23.0±1	/
				1	49	23.78	23.0±1	/
				1	99	22.71	23.0±1	/
				12	0	22.31	23.0±1	1.0
				12	24	22.44	23.0±1	1.0
				12	49	22.1	23.0±1	1.0
				25	0	22.17	23.0±1	1.0
			16QAM	1	0	22.21	22.0±1	1.0
				1	49	22.57	22.0±1	1.0
				1	99	21.59	22.0±1	1.0
				12	0	21.39	22.0±1	1.0
				12	24	21.59	22.0±1	1.0
				12	49	21.28	22.0±1	1.0
				25	0	21.24	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20450	829	QPSK	1	0	23.1	22.5±1	/
				1	49	23.25	22.5±1	/
				1	99	22.92	22.5±1	/
				25	0	21.97	22.5±1	1.0
				25	24	22.2	22.5±1	1.0
				25	49	22.03	22.5±1	1.0
				50	0	22.13	22.5±1	1.0
			16QAM	1	0	21.81	21.5±1	1.0
				1	49	22.13	21.5±1	1.0
				1	99	21.82	21.5±1	1.0
				25	0	20.9	21.5±1	1.0
				25	24	21.18	21.5±1	1.0
				25	49	21.02	21.5±1	1.0
				50	0	21.09	21.5±1	1.0
	20525	836.5	QPSK	1	0	23.11	22.5±1	/
				1	49	23.04	22.5±1	/
				1	99	22.54	22.5±1	/
				25	0	21.92	22.5±1	1.0
				25	24	22.04	22.5±1	1.0
				25	49	21.63	22.5±1	1.0
				50	0	21.78	22.5±1	1.0
			16QAM	1	0	22.32	21.5±1	1.0
				1	49	22.48	21.5±1	1.0
				1	99	21.58	21.5±1	1.0
				25	0	20.88	21.5±1	1.0
				25	24	21.01	21.5±1	1.0
				25	49	20.71	21.5±1	1.0
				50	0	20.73	21.5±1	1.0
	20600	844	QPSK	1	0	22.64	22.5±1	/
				1	49	23.08	22.5±1	/
				1	99	22.56	22.5±1	/
				25	0	21.34	22.5±1	1.0
				25	24	21.87	22.5±1	1.0
				25	49	21.97	22.5±1	1.0
				50	0	21.88	22.5±1	1.0
			16QAM	1	0	21.37	21.0±1	1.0
				1	49	21.89	21.0±1	1.0
				1	99	21.42	21.0±1	1.0
				25	0	20.47	21.0±1	1.0
				25	24	21.01	21.0±1	1.0
				25	49	21.08	21.0±1	1.0
				50	0	20.93	21.0±1	1.0

LTE Band 7:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20775	2502.5	QPSK	1	0	22.04	22.0±1	/
				1	49	22.13	22.0±1	/
				1	99	21.99	22.0±1	/
				12	0	21.08	22.0±1	1.0
				12	24	21.13	22.0±1	1.0
				12	49	21.05	22.0±1	1.0
				25	0	21.05	22.0±1	1.0
			16QAM	1	0	21.54	21.0±1	1.0
				1	49	21.61	21.0±1	1.0
				1	99	21.48	21.0±1	1.0
				12	0	20.17	21.0±1	1.0
				12	24	20.27	21.0±1	1.0
				12	49	20.14	21.0±1	1.0
				25	0	20.11	21.0±1	1.0
	21100	2535	QPSK	1	0	22.33	22.0±1	/
				1	49	22.33	22.0±1	/
				1	99	22.11	22.0±1	/
				12	0	21.25	22.0±1	1.0
				12	24	21.32	22.0±1	1.0
				12	49	21.24	22.0±1	1.0
				25	0	21.22	22.0±1	1.0
			16QAM	1	0	21.37	21.0±1	1.0
				1	49	21.41	21.0±1	1.0
				1	99	21.21	21.0±1	1.0
				12	0	20.26	21.0±1	1.0
				12	24	20.33	21.0±1	1.0
				12	49	20.27	21.0±1	1.0
				25	0	20.15	21.0±1	1.0
	21425	2567.5	QPSK	1	0	22.53	21.6±1	/
				1	49	22.52	21.6±1	/
				1	99	22.29	21.6±1	/
				12	0	21.45	21.6±1	1.0
				12	24	21.57	21.6±1	1.0
				12	49	21.37	21.6±1	1.0
				25	0	21.47	21.6±1	1.0
			16QAM	1	0	21.66	21.0±1	1.0
				1	49	21.7	21.0±1	1.0
				1	99	21.39	21.0±1	1.0
				12	0	20.55	21.0±1	1.0
				12	24	20.63	21.0±1	1.0
				12	49	20.43	21.0±1	1.0
				25	0	20.48	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20800	2505	QPSK	1	0	21.95	21.5±1	/
				1	49	22.09	21.5±1	/
				1	99	21.78	21.5±1	/
				25	0	20.97	21.5±1	1.0
				25	24	21.04	21.5±1	1.0
				25	49	20.96	21.5±1	1.0
				50	0	20.91	21.5±1	1.0
			16QAM	1	0	20.81	20.0±1	1.0
				1	49	20.98	20.0±1	1.0
				1	99	20.69	20.0±1	1.0
				25	0	19.94	20.0±1	1.0
				25	24	20.02	20.0±1	1.0
				25	49	19.95	20.0±1	1.0
				50	0	19.86	20.0±1	1.0
	21100	2535	QPSK	1	0	22.12	22.0±1	/
				1	49	22.2	22.0±1	/
				1	99	21.83	22.0±1	/
				25	0	21.13	22.0±1	1.0
				25	24	21.18	22.0±1	1.0
				25	49	21.03	22.0±1	1.0
				50	0	21.06	22.0±1	1.0
			16QAM	1	0	21.47	21.0±1	1.0
				1	49	21.58	21.0±1	1.0
				1	99	21.2	21.0±1	1.0
				25	0	20.14	21.0±1	1.0
				25	24	20.24	21.0±1	1.0
				25	49	20.05	21.0±1	1.0
				50	0	20.12	21.0±1	1.0
	21400	2565	QPSK	1	0	22.07	22.0±1	/
				1	49	22.38	22.0±1	/
				1	99	22	22.0±1	/
				25	0	21.25	22.0±1	1.0
				25	24	21.42	22.0±1	1.0
				25	49	21.23	22.0±1	1.0
				50	0	21.28	22.0±1	1.0
			16QAM	1	0	21.12	21.0±1	1.0
				1	49	21.47	21.0±1	1.0
				1	99	21.01	21.0±1	1.0
				25	0	20.37	21.0±1	1.0
				25	24	20.55	21.0±1	1.0
				25	49	20.32	21.0±1	1.0
				50	0	20.36	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20825	2507.5	QPSK	1	0	21.95	21.5±1	/
				1	49	22.01	21.5±1	/
				1	99	21.94	21.5±1	/
				36	0	20.95	21.5±1	1.0
				36	24	21.05	21.5±1	1.0
				36	49	20.93	21.5±1	1.0
				75	0	20.89	21.5±1	1.0
			16QAM	1	0	20.8	20.0±1	1.0
				1	49	20.94	20.0±1	1.0
				1	99	20.9	20.0±1	1.0
				36	0	19.91	20.0±1	1.0
				36	24	20.04	20.0±1	1.0
				36	49	20.01	20.0±1	1.0
				75	0	19.93	20.0±1	1.0
	21100	2535	QPSK	1	0	22.15	22.0±1	/
				1	49	22.22	22.0±1	/
				1	99	21.83	22.0±1	/
				36	0	21.15	22.0±1	1.0
				36	24	21.21	22.0±1	1.0
				36	49	21.03	22.0±1	1.0
				75	0	21.13	22.0±1	1.0
			16QAM	1	0	21.49	21.0±1	1.0
				1	49	21.6	21.0±1	1.0
				1	99	21.22	21.0±1	1.0
				36	0	20.2	21.0±1	1.0
				36	24	20.26	21.0±1	1.0
				36	49	20.08	21.0±1	1.0
				75	0	20.17	21.0±1	1.0
	21375	2562.5	QPSK	1	0	22.09	22.0±1	/
				1	49	22.43	22.0±1	/
				1	99	22.09	22.0±1	/
				36	0	21.23	22.0±1	1.0
				36	24	21.43	22.0±1	1.0
				36	49	21.31	22.0±1	1.0
				75	0	21.29	22.0±1	1.0
			16QAM	1	0	21.6	21.0±1	1.0
				1	49	21.85	21.0±1	1.0
				1	99	21.46	21.0±1	1.0
				36	0	20.24	21.0±1	1.0
				36	24	20.41	21.0±1	1.0
				36	49	20.3	21.0±1	1.0
				75	0	20.31	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20850	2510	QPSK	1	0	21.81	21.0±1	/
				1	49	21.88	21.0±1	/
				1	99	21.83	21.0±1	/
				50	0	20.91	21.0±1	1.0
				50	24	21.03	21.0±1	1.0
				50	49	20.99	21.0±1	1.0
				100	0	20.83	21.0±1	1.0
			16QAM	1	0	21.3	20.7±1	1.0
				1	49	21.54	20.7±1	1.0
				1	99	21.4	20.7±1	1.0
				50	0	19.91	20.7±1	1.0
				50	24	20.03	20.7±1	1.0
				50	49	20.01	20.7±1	1.0
				100	0	19.86	20.7±1	1.0
	21100	2535	QPSK	1	0	21.91	21.5±1	/
				1	49	22.11	21.5±1	/
				1	99	21.6	21.5±1	/
				50	0	21.1	21.5±1	1.0
				50	24	21.18	21.5±1	1.0
				50	49	20.9	21.5±1	1.0
				100	0	21.04	21.5±1	1.0
			16QAM	1	0	21.41	20.7±1	1.0
				1	49	21.64	20.7±1	1.0
				1	99	21.16	20.7±1	1.0
				50	0	20.16	20.7±1	1.0
				50	24	20.21	20.7±1	1.0
				50	49	19.92	20.7±1	1.0
				100	0	20.07	20.7±1	1.0
	21350	2560	QPSK	1	0	21.72	21.5±1	/
				1	49	22.2	21.5±1	/
				1	99	21.98	21.5±1	/
				50	0	20.97	21.5±1	1.0
				50	24	21.21	21.5±1	1.0
				50	49	21.19	21.5±1	1.0
				100	0	20.96	21.5±1	1.0
			16QAM	1	0	21.14	20.7±1	1.0
				1	49	21.64	20.7±1	1.0
				1	99	21.38	20.7±1	1.0
				50	0	19.98	20.7±1	1.0
				50	24	20.24	20.7±1	1.0
				50	49	20.23	20.7±1	1.0
				100	0	20.03	20.7±1	1.0

LTE Band 12:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	23017	699.7	QPSK	1	0	23.19	22.5±1	/
				1	2	23.09	22.5±1	/
				1	5	23.27	22.5±1	/
				3	0	22.96	22.5±1	/
				3	1	22.99	22.5±1	/
				3	2	22.99	22.5±1	/
				6	0	21.81	22.5±1	1.0
			16QAM	1	0	21.92	21.5±1	1.0
				1	2	21.86	21.5±1	1.0
				1	5	22.1	21.5±1	1.0
				3	0	21.73	21.5±1	1.0
				3	1	21.77	21.5±1	1.0
				3	2	21.9	21.5±1	1.0
				6	0	20.95	21.5±1	1.0
	23095	707.5	QPSK	1	0	23.24	22.5±1	/
				1	2	23.05	22.5±1	/
				1	5	23.27	22.5±1	/
				3	0	23.02	22.5±1	/
				3	1	22.98	22.5±1	/
				3	2	23.03	22.5±1	/
				6	0	21.99	22.5±1	1.0
			16QAM	1	0	22.47	21.5±1	1.0
				1	2	22.34	21.5±1	1.0
				1	5	22.48	21.5±1	1.0
				3	0	22.13	21.5±1	1.0
				3	1	22.15	21.5±1	1.0
				3	2	22.2	21.5±1	1.0
				6	0	20.92	21.5±1	1.0
	23173	715.3	QPSK	1	0	22.85	22.0±1	/
				1	2	22.77	22.0±1	/
				1	5	22.93	22.0±1	/
				3	0	22.71	22.0±1	/
				3	1	22.71	22.0±1	/
				3	2	22.8	22.0±1	/
				6	0	21.83	22.0±1	1.0
			16QAM	1	0	21.84	22.0±1	1.0
				1	2	21.73	22.0±1	1.0
				1	5	21.91	22.0±1	1.0
				3	0	21.99	22.0±1	1.0
				3	1	21.98	22.0±1	1.0
				3	2	22	22.0±1	1.0
				6	0	21.11	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	23025	700.5	QPSK	1	0	22.95	22.5±1	/
				1	8	23.16	22.5±1	/
				1	14	23.09	22.5±1	/
				8	0	21.86	22.5±1	1.0
				8	4	21.91	22.5±1	1.0
				8	9	21.94	22.5±1	1.0
				15	0	21.86	22.5±1	1.0
			16QAM	1	0	21.52	21.0±1	1.0
				1	8	21.81	21.0±1	1.0
				1	14	21.76	21.0±1	1.0
				8	0	20.93	21.0±1	1.0
				8	4	20.98	21.0±1	1.0
				8	9	21.02	21.0±1	1.0
				15	0	20.86	21.0±1	1.0
	23095	707.5	QPSK	1	0	23	22.5±1	/
				1	8	23.01	22.5±1	/
				1	14	22.96	22.5±1	/
				8	0	21.93	22.5±1	1.0
				8	4	21.97	22.5±1	1.0
				8	9	21.99	22.5±1	1.0
				15	0	21.91	22.5±1	1.0
			16QAM	1	0	22.26	21.5±1	1.0
				1	8	22.33	21.5±1	1.0
				1	14	22.25	21.5±1	1.0
				8	0	21.03	21.5±1	1.0
				8	4	21.07	21.5±1	1.0
				8	9	21.09	21.5±1	1.0
				15	0	20.97	21.5±1	1.0
	23165	714.5	QPSK	1	0	22.83	22.0±1	/
				1	8	22.76	22.0±1	/
				1	14	22.74	22.0±1	/
				8	0	21.85	22.0±1	1.0
				8	4	21.83	22.0±1	1.0
				8	9	21.85	22.0±1	1.0
				15	0	21.81	22.0±1	1.0
			16QAM	1	0	21.78	21.0±1	1.0
				1	8	21.74	21.0±1	1.0
				1	14	21.76	21.0±1	1.0
				8	0	20.95	21.0±1	1.0
				8	4	20.93	21.0±1	1.0
				8	9	20.95	21.0±1	1.0
				15	0	20.83	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	23035	701.5	QPSK	1	0	22.87	22.5±1	/
				1	49	23.07	22.5±1	/
				1	99	22.72	22.5±1	/
				12	0	21.81	22.5±1	1.0
				12	24	21.95	22.5±1	1.0
				12	49	21.82	22.5±1	1.0
				25	0	21.81	22.5±1	1.0
			16QAM	1	0	21.72	21.5±1	1.0
				1	49	22.1	21.5±1	1.0
				1	99	21.78	21.5±1	1.0
				12	0	20.85	21.5±1	1.0
				12	24	21	21.5±1	1.0
				12	49	20.88	21.5±1	1.0
				25	0	20.82	21.5±1	1.0
	23095	707.5	QPSK	1	0	22.93	22.0±1	/
				1	49	22.96	22.0±1	/
				1	99	22.89	22.0±1	/
				12	0	21.9	22.0±1	1.0
				12	24	21.95	22.0±1	1.0
				12	49	21.92	22.0±1	1.0
				25	0	21.84	22.0±1	1.0
			16QAM	1	0	22.33	21.5±1	1.0
				1	49	22.45	21.5±1	1.0
				1	99	22.39	21.5±1	1.0
				12	0	21.06	21.5±1	1.0
				12	24	21.1	21.5±1	1.0
				12	49	21.08	21.5±1	1.0
				25	0	20.93	21.5±1	1.0
	23155	713.5	QPSK	1	0	22.95	22.0±1	/
				1	49	22.86	22.0±1	/
				1	99	22.8	22.0±1	/
				12	0	21.83	22.0±1	1.0
				12	24	21.89	22.0±1	1.0
				12	49	21.76	22.0±1	1.0
				25	0	21.81	22.0±1	1.0
			16QAM	1	0	21.89	21.0±1	1.0
				1	49	21.94	21.0±1	1.0
				1	99	21.78	21.0±1	1.0
				12	0	20.9	21.0±1	1.0
				12	24	20.97	21.0±1	1.0
				12	49	20.86	21.0±1	1.0
				25	0	20.81	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	23060	704	QPSK	1	0	22.77	22.0±1	/
				1	49	22.79	22.0±1	/
				1	99	22.76	22.0±1	/
				25	0	21.59	22.0±1	1.0
				25	24	21.78	22.0±1	1.0
				25	49	21.62	22.0±1	1.0
				50	0	21.67	22.0±1	1.0
			16QAM	1	0	21.33	21.0±1	1.0
				1	49	21.45	21.0±1	1.0
				1	99	21.53	21.0±1	1.0
				25	0	20.58	21.0±1	1.0
				25	24	20.79	21.0±1	1.0
				25	49	20.67	21.0±1	1.0
				50	0	20.63	21.0±1	1.0
	23095	707.5	QPSK	1	0	22.69	22.0±1	/
				1	49	22.81	22.0±1	/
				1	99	22.61	22.0±1	/
				25	0	21.61	22.0±1	1.0
				25	24	21.71	22.0±1	1.0
				25	49	21.66	22.0±1	1.0
				50	0	21.47	22.0±1	1.0
			16QAM	1	0	21.79	21.5±1	1.0
				1	49	22.12	21.5±1	1.0
				1	99	21.88	21.5±1	1.0
				25	0	20.66	21.5±1	1.0
				25	24	20.76	21.5±1	1.0
				25	49	20.72	21.5±1	1.0
				50	0	20.54	21.5±1	1.0
	23130	711	QPSK	1	0	22.74	22.0±1	/
				1	49	22.83	22.0±1	/
				1	99	22.5	22.0±1	/
				25	0	21.64	22.0±1	1.0
				25	24	21.76	22.0±1	1.0
				25	49	21.53	22.0±1	1.0
				50	0	21.59	22.0±1	1.0
			16QAM	1	0	21.64	21.0±1	1.0
				1	49	21.87	21.0±1	1.0
				1	99	21.44	21.0±1	1.0
				25	0	20.75	21.0±1	1.0
				25	24	20.88	21.0±1	1.0
				25	49	20.66	21.0±1	1.0
				50	0	20.67	21.0±1	1.0

LTE Band 13:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	23205	779.5	QPSK	1	0	22.84	22.5±1	/
				1	49	23.16	22.5±1	/
				1	99	23.21	22.5±1	/
				12	0	21.85	22.5±1	1.0
				12	24	22.06	22.5±1	1.0
				12	49	22.16	22.5±1	1.0
				25	0	21.99	22.5±1	1.0
			16QAM	1	0	22.18	22.0±1	1.0
				1	49	22.54	22.0±1	1.0
				1	99	22.63	22.0±1	1.0
				12	0	21.07	22.0±1	1.0
				12	24	21.2	22.0±1	1.0
				12	49	21.3	22.0±1	1.0
				25	0	21.06	22.0±1	1.0
	23230	782.0	QPSK	1	0	23.06	23.0±1	/
				1	49	23.19	23.0±1	/
				1	99	23.16	23.0±1	/
				12	0	22.17	23.0±1	1.0
				12	24	22.22	23.0±1	1.0
				12	49	22.14	23.0±1	1.0
				25	0	22.05	23.0±1	1.0
			16QAM	1	0	22.08	22.0±1	1.0
				1	49	22.26	22.0±1	1.0
				1	99	22.11	22.0±1	1.0
				12	0	21.23	22.0±1	1.0
				12	24	21.29	22.0±1	1.0
				12	49	21.21	22.0±1	1.0
				25	0	21.04	22.0±1	1.0
	23255	784.5	QPSK	1	0	23.19	23.0±1	/
				1	49	23.27	23.0±1	/
				1	99	23.12	23.0±1	/
				12	0	22.05	23.0±1	1.0
				12	24	22.22	23.0±1	1.0
				12	49	22	23.0±1	1.0
				25	0	22.19	23.0±1	1.0
			16QAM	1	0	22.17	22.0±1	1.0
				1	49	22.22	22.0±1	1.0
				1	99	22.05	22.0±1	1.0
				12	0	21.18	22.0±1	1.0
				12	24	21.33	22.0±1	1.0
				12	49	21.1	22.0±1	1.0
				25	0	21.24	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	23230	782.0	QPSK	1	0	22.59	22.5±1	/
				1	49	23.03	22.5±1	/
				1	99	22.85	22.5±1	/
				25	0	21.68	22.5±1	1.0
				25	24	21.82	22.5±1	1.0
				25	49	21.87	22.5±1	1.0
				50	0	21.53	22.5±1	1.0
			16QAM	1	0	21.23	21.0±1	1.0
				1	49	21.83	21.0±1	1.0
				1	99	21.49	21.0±1	1.0
				25	0	20.77	21.0±1	1.0
				25	24	20.94	21.0±1	1.0
				25	49	20.93	21.0±1	1.0
				50	0	20.61	21.0±1	1.0

LTE Band 14:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	23305	790.5	QPSK	1	0	22.82	22.5±1	/
				1	49	23.01	22.5±1	/
				1	99	23.04	22.5±1	/
				12	0	21.82	22.5±1	1.0
				12	24	21.94	22.5±1	1.0
				12	49	21.9	22.5±1	1.0
				25	0	21.87	22.5±1	1.0
			16QAM	1	0	21.89	21.5±1	1.0
				1	49	22.02	21.5±1	1.0
				1	99	22	21.5±1	1.0
				12	0	20.85	21.5±1	1.0
				12	24	20.97	21.5±1	1.0
				12	49	20.97	21.5±1	1.0
				25	0	20.82	21.5±1	1.0
	23330	793.0	QPSK	1	0	22.94	22.5±1	/
				1	49	23.08	22.5±1	/
				1	99	22.96	22.5±1	/
				12	0	21.87	22.5±1	1.0
				12	24	21.88	22.5±1	1.0
				12	49	21.88	22.5±1	1.0
				25	0	21.8	22.5±1	1.0
			16QAM	1	0	22.22	21.5±1	1.0
				1	49	22.35	21.5±1	1.0
				1	99	22.31	21.5±1	1.0
				12	0	20.92	21.5±1	1.0
				12	24	21.03	21.5±1	1.0
				12	49	21.04	21.5±1	1.0
				25	0	20.88	21.5±1	1.0
	23355	795.5	QPSK	1	0	23.01	22.5±1	/
				1	49	23.10	22.5±1	/
				1	99	22.63	22.5±1	/
				12	0	21.96	22.5±1	1.0
				12	24	22.01	22.5±1	1.0
				12	49	21.79	22.5±1	1.0
				25	0	21.87	22.5±1	1.0
			16QAM	1	0	21.85	21.5±1	1.0
				1	49	22.03	21.5±1	1.0
				1	99	21.62	21.5±1	1.0
				12	0	20.99	21.5±1	1.0
				12	24	21.05	21.5±1	1.0
				12	49	20.84	21.5±1	1.0
				25	0	20.83	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	23330	793.0	QPSK	1	0	22.76	22.5±1	/
				1	49	23.11	22.5±1	/
				1	99	22.63	22.5±1	/
				25	0	21.74	22.5±1	1.0
				25	24	21.84	22.5±1	1.0
				25	49	21.73	22.5±1	1.0
				50	0	21.64	22.5±1	1.0
			16QAM	1	0	21.52	21.0±1	1.0
				1	49	21.77	21.0±1	1.0
				1	99	21.32	21.0±1	1.0
				25	0	20.68	21.0±1	1.0
				25	24	20.84	21.0±1	1.0
				25	49	20.74	21.0±1	1.0
				50	0	20.6	21.0±1	1.0

LTE Band 17:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	23755	706.5	QPSK	1	0	22.7	22.5±1	/
				1	49	23.08	22.5±1	/
				1	99	22.99	22.5±1	/
				12	0	21.81	22.5±1	1.0
				12	24	22.02	22.5±1	1.0
				12	49	22.03	22.5±1	1.0
				25	0	21.9	22.5±1	1.0
			16QAM	1	0	21.62	21.5±1	1.0
				1	49	22.11	21.5±1	1.0
				1	99	21.99	21.5±1	1.0
				12	0	20.86	21.5±1	1.0
				12	24	21.07	21.5±1	1.0
				12	49	21.09	21.5±1	1.0
				25	0	20.86	21.5±1	1.0
	23790	710	QPSK	1	0	23.13	22.5±1	/
				1	49	23.08	22.5±1	/
				1	99	22.83	22.5±1	/
				12	0	21.94	22.5±1	1.0
				12	24	22.01	22.5±1	1.0
				12	49	21.92	22.5±1	1.0
				25	0	21.94	22.5±1	1.0
			16QAM	1	0	22.11	21.5±1	1.0
				1	49	22.13	21.5±1	1.0
				1	99	21.83	21.5±1	1.0
				12	0	21.02	21.5±1	1.0
				12	24	21.1	21.5±1	1.0
				12	49	21.02	21.5±1	1.0
				25	0	20.97	21.5±1	1.0
	23825	713.5	QPSK	1	0	22.93	22.0±1	/
				1	49	22.87	22.0±1	/
				1	99	22.74	22.0±1	/
				12	0	21.86	22.0±1	1.0
				12	24	21.91	22.0±1	1.0
				12	49	21.81	22.0±1	1.0
				25	0	21.83	22.0±1	1.0
			16QAM	1	0	22.32	21.5±1	1.0
				1	49	22.38	21.5±1	1.0
				1	99	22.25	21.5±1	1.0
				12	0	21.01	21.5±1	1.0
				12	24	21.07	21.5±1	1.0
				12	49	20.97	21.5±1	1.0
				25	0	20.93	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	23780	709	QPSK	1	0	22.46	22.0±1	/
				1	49	22.86	22.0±1	/
				1	99	22.68	22.0±1	/
				25	0	21.59	22.0±1	1.0
				25	24	21.78	22.0±1	1.0
				25	49	21.61	22.0±1	1.0
				50	0	21.59	22.0±1	1.0
			16QAM	1	0	21.19	21.0±1	1.0
				1	49	21.74	21.0±1	1.0
				1	99	21.43	21.0±1	1.0
				25	0	20.67	21.0±1	1.0
				25	24	20.87	21.0±1	1.0
				25	49	20.71	21.0±1	1.0
				50	0	20.65	21.0±1	1.0
	23790	710	QPSK	1	0	22.73	22.0±1	/
				1	49	22.86	22.0±1	/
				1	99	22.58	22.0±1	/
				25	0	21.63	22.0±1	1.0
				25	24	21.81	22.0±1	1.0
				25	49	21.62	22.0±1	1.0
				50	0	21.63	22.0±1	1.0
			16QAM	1	0	21.89	21.5±1	1.0
				1	49	22.18	21.5±1	1.0
				1	99	21.79	21.5±1	1.0
				25	0	20.68	21.5±1	1.0
				25	24	20.87	21.5±1	1.0
				25	49	20.69	21.5±1	1.0
				50	0	20.69	21.5±1	1.0
	23800	711	QPSK	1	0	22.7	22.0±1	/
				1	49	22.81	22.0±1	/
				1	99	22.49	22.0±1	/
				25	0	21.66	22.0±1	1.0
				25	24	21.77	22.0±1	1.0
				25	49	21.58	22.0±1	1.0
				50	0	21.63	22.0±1	1.0
			16QAM	1	0	21.65	21.0±1	1.0
				1	49	21.85	21.0±1	1.0
				1	99	21.41	21.0±1	1.0
				25	0	20.77	21.0±1	1.0
				25	24	20.9	21.0±1	1.0
				25	49	20.71	21.0±1	1.0
				50	0	20.7	21.0±1	1.0

LTE Band 25:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	26047	1850.7	QPSK	1	0	23.34	23.0±1	/
				1	2	23.15	23.0±1	/
				1	5	23.2	23.0±1	/
				3	0	23.05	23.0±1	/
				3	1	23.12	23.0±1	/
				3	2	23.07	23.0±1	/
				6	0	22.05	23.0±1	1.0
			16QAM	1	0	22.28	22.0±1	1.0
				1	2	22.19	22.0±1	1.0
				1	5	22.21	22.0±1	1.0
				3	0	22.1	22.0±1	1.0
				3	1	22.09	22.0±1	1.0
				3	2	22.05	22.0±1	1.0
				6	0	21.13	22.0±1	1.0
	26365	1882.5	QPSK	1	0	23.36	23.0±1	/
				1	2	23.21	23.0±1	/
				1	5	23.3	23.0±1	/
				3	0	23.13	23.0±1	/
				3	1	23.12	23.0±1	/
				3	2	23.11	23.0±1	/
				6	0	22.03	23.0±1	1.0
			16QAM	1	0	22.6	22.0±1	1.0
				1	2	22.44	22.0±1	1.0
				1	5	22.6	22.0±1	1.0
				3	0	22.24	22.0±1	1.0
				3	1	22.33	22.0±1	1.0
				3	2	22.33	22.0±1	1.0
				6	0	21.04	22.0±1	1.0
	26683	1914.3	QPSK	1	0	22.61	22.0±1	/
				1	2	22.53	22.0±1	/
				1	5	22.62	22.0±1	/
				3	0	22.51	22.0±1	/
				3	1	22.52	22.0±1	/
				3	2	22.44	22.0±1	/
				6	0	21.49	22.0±1	1.0
			16QAM	1	0	21.64	21.0±1	1.0
				1	2	21.51	21.0±1	1.0
				1	5	21.66	21.0±1	1.0
				3	0	21.65	21.0±1	1.0
				3	1	21.66	21.0±1	1.0
				3	2	21.64	21.0±1	1.0
				6	0	20.68	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	26055	1851.5	QPSK	1	0	23.05	22.5±1	/
				1	8	23.03	22.5±1	/
				1	14	22.85	22.5±1	/
				6	0	21.95	22.5±1	1.0
				6	4	21.94	22.5±1	1.0
				6	9	21.86	22.5±1	1.0
				15	0	21.88	22.5±1	1.0
			16QAM	1	0	21.87	21.0±1	1.0
				1	8	21.87	21.0±1	1.0
				1	14	21.71	21.0±1	1.0
				8	0	21.05	21.0±1	1.0
				8	4	21.05	21.0±1	1.0
				8	9	20.98	21.0±1	1.0
				15	0	20.93	21.0±1	1.0
	26365	1882.5	QPSK	1	0	23.2	23.0±1	/
				1	8	23.14	23.0±1	/
				1	14	23.1	23.0±1	/
				6	0	22.04	23.0±1	1.0
				6	4	22.06	23.0±1	1.0
				6	9	22.05	23.0±1	1.0
				15	0	22.02	23.0±1	1.0
			16QAM	1	0	22.42	22.0±1	1.0
				1	8	22.48	22.0±1	1.0
				1	14	22.47	22.0±1	1.0
				6	0	21.19	22.0±1	1.0
				6	4	21.22	22.0±1	1.0
				6	9	21.22	22.0±1	1.0
				15	0	21.12	22.0±1	1.0
	26675	1913.5	QPSK	1	0	22.63	22.0±1	/
				1	8	22.55	22.0±1	/
				1	14	22.46	22.0±1	/
				6	0	21.58	22.0±1	1.0
				6	4	21.58	22.0±1	1.0
				6	9	21.46	22.0±1	1.0
				15	0	21.5	22.0±1	1.0
			16QAM	1	0	21.66	21.0±1	1.0
				1	8	21.58	21.0±1	1.0
				1	14	21.46	21.0±1	1.0
				8	0	20.59	21.0±1	1.0
				8	4	20.61	21.0±1	1.0
				8	9	20.59	21.0±1	1.0
				15	0	20.5	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	26065	1852.5	QPSK	1	0	23.02	22.5±1	/
				1	49	22.95	22.5±1	/
				1	99	22.92	22.5±1	/
				12	0	21.88	22.5±1	1.0
				12	24	21.91	22.5±1	1.0
				12	49	21.8	22.5±1	1.0
				25	0	21.84	22.5±1	1.0
			16QAM	1	0	22.12	21.5±1	1.0
				1	49	22.09	21.5±1	1.0
				1	99	22.08	21.5±1	1.0
				12	0	20.95	21.5±1	1.0
				12	24	20.94	21.5±1	1.0
				12	49	20.88	21.5±1	1.0
				25	0	20.83	21.5±1	1.0
	26365	1882.5	QPSK	1	0	23.13	23.0±1	/
				1	49	23.19	23.0±1	/
				1	99	23.08	23.0±1	/
				12	0	22.03	23.0±1	1.0
				12	24	22.09	23.0±1	1.0
				12	49	22.07	23.0±1	1.0
				25	0	22.04	23.0±1	1.0
			16QAM	1	0	22.55	22.0±1	1.0
				1	49	22.6	22.0±1	1.0
				1	99	22.51	22.0±1	1.0
				12	0	21.18	22.0±1	1.0
				12	24	21.25	22.0±1	1.0
				12	49	21.23	22.0±1	1.0
				25	0	21.12	22.0±1	1.0
	26665	1912.5	QPSK	1	0	23.02	22.5±1	/
				1	49	22.71	22.5±1	/
				1	99	22.53	22.5±1	/
				12	0	21.79	22.5±1	1.0
				12	24	21.67	22.5±1	1.0
				12	49	21.47	22.5±1	1.0
				25	0	21.62	22.5±1	1.0
			16QAM	1	0	22.08	21.5±1	1.0
				1	49	21.81	21.5±1	1.0
				1	99	21.55	21.5±1	1.0
				12	0	20.81	21.5±1	1.0
				12	24	20.7	21.5±1	1.0
				12	49	20.56	21.5±1	1.0
				25	0	20.56	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	26090	1855	QPSK	1	0	22.82	22.0±1	/
				1	49	22.97	22.0±1	/
				1	99	22.77	22.0±1	/
				25	0	21.67	22.0±1	1.0
				25	24	21.85	22.0±1	1.0
				25	49	21.74	22.0±1	1.0
				50	0	21.81	22.0±1	1.0
			16QAM	1	0	21.71	21.0±1	1.0
				1	49	21.81	21.0±1	1.0
				1	99	21.63	21.0±1	1.0
				25	0	20.63	21.0±1	1.0
				25	24	20.88	21.0±1	1.0
				25	49	20.72	21.0±1	1.0
				50	0	20.81	21.0±1	1.0
	26365	1882.5	QPSK	1	0	22.87	22.5±1	/
				1	49	23.13	22.5±1	/
				1	99	22.83	22.5±1	/
				25	0	21.85	22.5±1	1.0
				25	24	21.99	22.5±1	1.0
				25	49	21.89	22.5±1	1.0
				50	0	21.91	22.5±1	1.0
			16QAM	1	0	22.08	21.5±1	1.0
				1	49	22.4	21.5±1	1.0
				1	99	22.11	21.5±1	1.0
				25	0	20.9	21.5±1	1.0
				25	24	21.04	21.5±1	1.0
				25	49	20.96	21.5±1	1.0
				50	0	20.97	21.5±1	1.0
	26640	1910	QPSK	1	0	22.66	22.0±1	/
				1	49	22.95	22.0±1	/
				1	99	22.18	22.0±1	/
				25	0	21.64	22.0±1	1.0
				25	24	21.9	22.0±1	1.0
				25	49	21.49	22.0±1	1.0
				50	0	21.96	22.0±1	1.0
			16QAM	1	0	21.61	21.5±1	1.0
				1	49	22.07	21.5±1	1.0
				1	99	21.22	21.5±1	1.0
				25	0	20.71	21.5±1	1.0
				25	24	21.03	21.5±1	1.0
				25	49	20.56	21.5±1	1.0
				50	0	20.95	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	26115	1857.5	QPSK	1	0	22.94	22.0±1	/
				1	49	22.99	22.0±1	/
				1	99	23.16	22.0±1	/
				36	0	21.82	22.0±1	1.0
				36	24	21.89	22.0±1	1.0
				36	49	21.93	22.0±1	1.0
				75	0	21.91	22.0±1	1.0
			16QAM	1	0	21.73	21.0±1	1.0
				1	49	21.84	21.0±1	1.0
				1	99	21.93	21.0±1	1.0
				36	0	20.8	21.0±1	1.0
				36	24	20.93	21.0±1	1.0
				36	49	20.98	21.0±1	1.0
				75	0	20.88	21.0±1	1.0
	26365	1882.5	QPSK	1	0	22.96	22.5±1	/
				1	49	23.16	22.5±1	/
				1	99	22.98	22.5±1	/
				36	0	21.96	22.5±1	1.0
				36	24	22.05	22.5±1	1.0
				36	49	21.94	22.5±1	1.0
				75	0	22.06	22.5±1	1.0
			16QAM	1	0	22.18	22.0±1	1.0
				1	49	22.43	22.0±1	1.0
				1	99	22.22	22.0±1	1.0
				36	0	21.03	22.0±1	1.0
				36	24	21.13	22.0±1	1.0
				36	49	21.02	22.0±1	1.0
				75	0	21.12	22.0±1	1.0
	26615	1907.5	QPSK	1	0	22.98	22.0±1	/
				1	49	22.88	22.0±1	/
				1	99	22.38	22.0±1	/
				36	0	21.82	22.0±1	1.0
				36	24	21.88	22.0±1	1.0
				36	49	21.82	22.0±1	1.0
				75	0	21.97	22.0±1	1.0
			16QAM	1	0	22.1	21.5±1	1.0
				1	49	22.23	21.5±1	1.0
				1	99	21.71	21.5±1	1.0
				36	0	20.91	21.5±1	1.0
				36	24	20.89	21.5±1	1.0
				36	49	20.83	21.5±1	1.0
				75	0	20.97	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	26140	1860	QPSK	1	0	22.73	22.5±1	/
				1	49	23	22.5±1	/
				1	99	22.72	22.5±1	/
				50	0	21.84	22.5±1	1.0
				50	24	21.99	22.5±1	1.0
				50	49	21.91	22.5±1	1.0
				100	0	21.87	22.5±1	1.0
			16QAM	1	0	22.27	21.5±1	1.0
				1	49	22.46	21.5±1	1.0
				1	99	22.14	21.5±1	1.0
				50	0	20.82	21.5±1	1.0
				50	24	21.02	21.5±1	1.0
				50	49	20.99	21.5±1	1.0
				100	0	20.92	21.5±1	1.0
	26365	1882.5	QPSK	1	0	22.74	22.5±1	/
				1	49	23.09	22.5±1	/
				1	99	22.98	22.5±1	/
				50	0	21.8	22.5±1	1.0
				50	24	22.07	22.5±1	1.0
				50	49	21.8	22.5±1	1.0
				100	0	22.06	22.5±1	1.0
			16QAM	1	0	22.1	21.5±1	1.0
				1	49	22.5	21.5±1	1.0
				1	99	22.39	21.5±1	1.0
				50	0	20.93	21.5±1	1.0
				50	24	21.11	21.5±1	1.0
				50	49	20.96	21.5±1	1.0
				100	0	21.11	21.5±1	1.0
	26590	1905.0	QPSK	1	0	23.07	22.5±1	/
				1	49	22.95	22.5±1	/
				1	99	22.28	22.5±1	/
				50	0	21.66	22.5±1	1.0
				50	24	21.93	22.5±1	1.0
				50	49	21.91	22.5±1	1.0
				100	0	21.86	22.5±1	1.0
			16QAM	1	0	22.32	21.5±1	1.0
				1	49	22.27	21.5±1	1.0
				1	99	21.73	21.5±1	1.0
				50	0	20.77	21.5±1	1.0
				50	24	20.94	21.5±1	1.0
				50	49	20.93	21.5±1	1.0
				100	0	20.92	21.5±1	1.0

LTE Band 26(Part 90):

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	26697	814.7	QPSK	1	0	23.5	23.0±1	/
				1	2	23.36	23.0±1	/
				1	5	23.49	23.0±1	/
				3	0	23.26	23.0±1	/
				3	1	23.27	23.0±1	/
				3	2	23.28	23.0±1	/
				6	0	22.22	23.0±1	1.0
			16QAM	1	0	22.46	22.0±1	1.0
				1	2	22.33	22.0±1	1.0
				1	5	22.45	22.0±1	1.0
				3	0	22.23	22.0±1	1.0
				3	1	22.25	22.0±1	1.0
				3	2	22.17	22.0±1	1.0
				6	0	21.27	22.0±1	1.0
	26740	819.0	QPSK	1	0	23.35	23.0±1	/
				1	2	23.23	23.0±1	/
				1	5	23.35	23.0±1	/
				3	0	23.16	23.0±1	/
				3	1	23.16	23.0±1	/
				3	2	23.17	23.0±1	/
				6	0	22	23.0±1	1.0
			16QAM	1	0	22.54	21.6±1	1.0
				1	2	22.4	21.6±1	1.0
				1	5	22.53	21.6±1	1.0
				3	0	22.19	21.6±1	1.0
				3	1	22.21	21.6±1	1.0
				3	2	22.22	21.6±1	1.0
				6	0	20.96	21.6±1	1.0
	26783	823.3	QPSK	1	0	23.37	23.0±1	/
				1	2	23.26	23.0±1	/
				1	5	23.36	23.0±1	/
				3	0	23.24	23.0±1	/
				3	1	23.23	23.0±1	/
				3	2	23.25	23.0±1	/
				6	0	22.14	23.0±1	1.0
			16QAM	1	0	22.29	22.0±1	1.0
				1	2	22.17	22.0±1	1.0
				1	5	22.32	22.0±1	1.0
				3	0	22.33	22.0±1	1.0
				3	1	22.34	22.0±1	1.0
				3	2	22.31	22.0±1	1.0
				6	0	21.31	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	26705	815.5	QPSK	1	0	23.22	23.0±1	/
				1	8	23.33	23.0±1	/
				1	14	23.18	23.0±1	/
				6	0	22.1	23.0±1	1.0
				6	4	22.12	23.0±1	1.0
				6	9	22.04	23.0±1	1.0
				15	0	22.07	23.0±1	1.0
			16QAM	1	0	21.99	22.0±1	1.0
				1	8	22.02	22.0±1	1.0
				1	14	21.9	22.0±1	1.0
				8	0	21.18	22.0±1	1.0
				8	4	21.15	22.0±1	1.0
				8	9	21.13	22.0±1	1.0
				15	0	21.05	22.0±1	1.0
	26740	819.0	QPSK	1	0	23.18	22.5±1	/
				1	8	23.19	22.5±1	/
				1	14	23.19	22.5±1	/
				6	0	21.98	22.5±1	1.0
				6	4	22.02	22.5±1	1.0
				6	9	22.02	22.5±1	1.0
				15	0	21.97	22.5±1	1.0
			16QAM	1	0	22.38	22.0±1	1.0
				1	8	22.41	22.0±1	1.0
				1	14	22.42	22.0±1	1.0
				6	0	21.1	22.0±1	1.0
				6	4	21.15	22.0±1	1.0
				6	9	21.15	22.0±1	1.0
				15	0	21.04	22.0±1	1.0
	26775	822.5	QPSK	1	0	23.19	23.0±1	/
				1	8	23.27	23.0±1	/
				1	14	23.25	23.0±1	/
				6	0	22.15	23.0±1	1.0
				6	4	22.16	23.0±1	1.0
				6	9	22.14	23.0±1	1.0
				15	0	22.1	23.0±1	1.0
			16QAM	1	0	22.12	22.0±1	1.0
				1	8	22.19	22.0±1	1.0
				1	14	22.16	22.0±1	1.0
				8	0	21.2	22.0±1	1.0
				8	4	21.25	22.0±1	1.0
				8	9	21.19	22.0±1	1.0
				15	0	21.13	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	26715	816.5	QPSK	1	0	23.21	22.5±1	/
				1	49	23.26	22.5±1	/
				1	99	23.1	22.5±1	/
				12	0	22.04	22.5±1	1.0
				12	24	22.09	22.5±1	1.0
				12	49	21.99	22.5±1	1.0
				25	0	21.96	22.5±1	1.0
			16QAM	1	0	22.24	22.0±1	1.0
				1	49	22.28	22.0±1	1.0
				1	99	22.14	22.0±1	1.0
				12	0	21.14	22.0±1	1.0
				12	24	21.19	22.0±1	1.0
				12	49	21.1	22.0±1	1.0
				25	0	21.06	22.0±1	1.0
	26740	819.0	QPSK	1	0	23.15	22.5±1	/
				1	49	23.23	22.5±1	/
				1	99	23.25	22.5±1	/
				12	0	21.99	22.5±1	1.0
				12	24	22.03	22.5±1	1.0
				12	49	21.98	22.5±1	1.0
				25	0	21.94	22.5±1	1.0
			16QAM	1	0	22.5	22.0±1	1.0
				1	49	22.56	22.0±1	1.0
				1	99	22.6	22.0±1	1.0
				12	0	21.17	22.0±1	1.0
				12	24	21.2	22.0±1	1.0
				12	49	21.16	22.0±1	1.0
				25	0	21.04	22.0±1	1.0
	26765	821.5	QPSK	1	0	23.15	23.0±1	/
				1	49	23.38	23.0±1	/
				1	99	23.25	23.0±1	/
				12	0	22.1	23.0±1	1.0
				12	24	22.16	23.0±1	1.0
				12	49	22.07	23.0±1	1.0
				25	0	22.06	23.0±1	1.0
			16QAM	1	0	22.13	22.0±1	1.0
				1	49	22.27	22.0±1	1.0
				1	99	22.21	22.0±1	1.0
				12	0	21.09	22.0±1	1.0
				12	24	21.25	22.0±1	1.0
				12	49	21.17	22.0±1	1.0
				25	0	21.06	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	26740	819.0	QPSK	1	0	22.96	22.5±1	/
				1	49	23.06	22.5±1	/
				1	99	22.92	22.5±1	/
				25	0	21.74	22.5±1	1.0
				25	24	21.79	22.5±1	1.0
				25	49	21.76	22.5±1	1.0
				50	0	21.62	22.5±1	1.0
			16QAM	1	0	21.78	21.0±1	1.0
				1	49	21.79	21.0±1	1.0
				1	99	21.75	21.0±1	1.0
				25	0	20.78	21.0±1	1.0
				25	24	20.85	21.0±1	1.0
				25	49	20.82	21.0±1	1.0
				50	0	20.64	21.0±1	1.0

LTE Band 26(Part 22):

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	26797	824.7	QPSK	1	0	23.49	23.0±1	/
				1	2	23.29	23.0±1	/
				1	5	23.38	23.0±1	/
				3	0	23.22	23.0±1	/
				3	1	23.21	23.0±1	/
				3	2	23.16	23.0±1	/
			6	0	22.12	23.0±1	1.0	
			16QAM	1	0	22.43	22.0±1	1.0
				1	2	22.26	22.0±1	1.0
				1	5	22.38	22.0±1	1.0
				3	0	22.18	22.0±1	1.0
				3	1	22.17	22.0±1	1.0
	3	2		22.14	22.0±1	1.0		
	26915	836.5	QPSK	6	0	21.3	22.0±1	1.0
				1	0	23.42	23.0±1	/
				1	2	23.33	23.0±1	/
				1	5	23.36	23.0±1	/
				3	0	23.27	23.0±1	/
				3	1	23.24	23.0±1	/
			3	2	23.2	23.0±1	/	
			16QAM	6	0	22.22	23.0±1	1.0
				1	0	22.72	22.0±1	1.0
				1	2	22.59	22.0±1	1.0
				1	5	22.68	22.0±1	1.0
				3	0	22.34	22.0±1	1.0
				3	1	22.41	22.0±1	1.0
3				2	22.39	22.0±1	1.0	
6	0	21.11		22.0±1	1.0			
27033	848.3	QPSK	1	0	23.37	23.0±1	/	
			1	2	23.07	23.0±1	/	
			1	5	22.82	23.0±1	/	
			3	0	23.16	23.0±1	/	
			3	1	23.08	23.0±1	/	
			3	2	22.85	23.0±1	/	
		6	0	22.11	23.0±1	1.0		
		16QAM	1	0	22.35	22.0±1	1.0	
			1	2	22.08	22.0±1	1.0	
			1	5	21.81	22.0±1	1.0	
3	0		22.33	22.0±1	1.0			
3	1	22.26	22.0±1	1.0				
3	2	22.05	22.0±1	1.0				
6	0	21.15	22.0±1	1.0				

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	26805	825.5	QPSK	1	0	23.27	22.5±1	/
				1	8	23.23	22.5±1	/
				1	14	23.08	22.5±1	/
				6	0	22.04	22.5±1	1.0
				6	4	22.04	22.5±1	1.0
				6	9	21.99	22.5±1	1.0
				15	0	22	22.5±1	1.0
			16QAM	1	0	21.95	21.0±1	1.0
				1	8	21.95	21.0±1	1.0
				1	14	21.87	21.0±1	1.0
				8	0	21.19	21.0±1	1.0
				8	4	21.18	21.0±1	1.0
				8	9	21.03	21.0±1	1.0
				15	0	21.08	21.0±1	1.0
	26915	836.5	QPSK	1	0	23.31	23.0±1	/
				1	8	23.28	23.0±1	/
				1	14	23.16	23.0±1	/
				6	0	22.2	23.0±1	1.0
				6	4	22.23	23.0±1	1.0
				6	9	22.16	23.0±1	1.0
				15	0	22.21	23.0±1	1.0
			16QAM	1	0	22.49	22.0±1	1.0
				1	8	22.6	22.0±1	1.0
				1	14	22.45	22.0±1	1.0
				6	0	21.29	22.0±1	1.0
				6	4	21.28	22.0±1	1.0
				6	9	21.26	22.0±1	1.0
				15	0	21.17	22.0±1	1.0
	27025	847.5	QPSK	1	0	23.5	23.0±1	/
				1	8	23.32	23.0±1	/
				1	14	22.61	23.0±1	/
				6	0	22.45	23.0±1	1.0
				6	4	22.42	23.0±1	1.0
				6	9	22.14	23.0±1	1.0
				15	0	22.29	23.0±1	1.0
			16QAM	1	0	22.45	22.0±1	1.0
				1	8	22.36	22.0±1	1.0
				1	14	21.68	22.0±1	1.0
				8	0	21.46	22.0±1	1.0
				8	4	21.36	22.0±1	1.0
				8	9	21.09	22.0±1	1.0
				15	0	21.17	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	26815	826.5	QPSK	1	0	23.19	22.5±1	/
				1	49	23.22	22.5±1	/
				1	99	22.99	22.5±1	/
				12	0	21.97	22.5±1	1.0
				12	24	22.01	22.5±1	1.0
				12	49	21.91	22.5±1	1.0
				25	0	21.93	22.5±1	1.0
			16QAM	1	0	22.21	21.5±1	1.0
				1	49	22.19	21.5±1	1.0
				1	99	22	21.5±1	1.0
				12	0	21.07	21.5±1	1.0
				12	24	21.02	21.5±1	1.0
				12	49	20.93	21.5±1	1.0
				25	0	20.89	21.5±1	1.0
	26915	836.5	QPSK	1	0	23.17	23.0±1	/
				1	49	23.26	23.0±1	/
				1	99	23.03	23.0±1	/
				12	0	22.11	23.0±1	1.0
				12	24	22.22	23.0±1	1.0
				12	49	22.1	23.0±1	1.0
				25	0	22.15	23.0±1	1.0
			16QAM	1	0	22.5	22.0±1	1.0
				1	49	22.74	22.0±1	1.0
				1	99	22.52	22.0±1	1.0
				12	0	21.29	22.0±1	1.0
				12	24	21.33	22.0±1	1.0
				12	49	21.19	22.0±1	1.0
				25	0	21.13	22.0±1	1.0
	27015	846.5	QPSK	1	0	23.22	23.0±1	/
				1	49	23.63	23.0±1	/
				1	99	22.74	23.0±1	/
				12	0	22.3	23.0±1	1.0
				12	24	22.46	23.0±1	1.0
				12	49	22.25	23.0±1	1.0
				25	0	22.25	23.0±1	1.0
			16QAM	1	0	22.2	22.0±1	1.0
				1	49	22.56	22.0±1	1.0
				1	99	21.76	22.0±1	1.0
				12	0	21.24	22.0±1	1.0
				12	24	21.48	22.0±1	1.0
				12	49	21.2	22.0±1	1.0
				25	0	21.14	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	26840	829.0	QPSK	1	0	22.9	22.0±1	/
				1	49	22.92	22.0±1	/
				1	99	22.85	22.0±1	/
				25	0	21.65	22.0±1	1.0
				25	24	21.71	22.0±1	1.0
				25	49	21.69	22.0±1	1.0
				50	0	21.63	22.0±1	1.0
			16QAM	1	0	21.67	21.0±1	1.0
				1	49	21.75	21.0±1	1.0
				1	99	21.68	21.0±1	1.0
				25	0	20.69	21.0±1	1.0
				25	24	20.85	21.0±1	1.0
				25	49	20.74	21.0±1	1.0
				50	0	20.75	21.0±1	1.0
	26915	836..5	QPSK	1	0	22.18	21.5±1	/
				1	49	22.46	21.5±1	/
				1	99	21.88	21.5±1	/
				25	0	20.81	21.5±1	1.0
				25	24	21.07	21.5±1	1.0
				25	49	20.74	21.5±1	1.0
				50	0	20.8	21.5±1	1.0
			16QAM	1	0	22.92	22.5±1	1.0
				1	49	23.16	22.5±1	1.0
				1	99	22.54	22.5±1	1.0
				25	0	21.69	22.5±1	1.0
				25	24	21.99	22.5±1	1.0
				25	49	21.75	22.5±1	1.0
				50	0	21.75	22.5±1	1.0
	26990	844.0	QPSK	1	0	22.68	22.5±1	/
				1	49	23	22.5±1	/
				1	99	22.58	22.5±1	/
				25	0	21.55	22.5±1	1.0
				25	24	21.97	22.5±1	1.0
				25	49	22.01	22.5±1	1.0
				50	0	22.06	22.5±1	1.0
			16QAM	1	0	21.64	21.0±1	1.0
				1	49	21.99	21.0±1	1.0
				1	99	21.62	21.0±1	1.0
				25	0	20.52	21.0±1	1.0
				25	24	21.02	21.0±1	1.0
				25	49	21.03	21.0±1	1.0
				50	0	20.99	21.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	26865	831.5	QPSK	1	0	23.21	22.5±1	/
				1	49	23.29	22.5±1	/
				1	99	23.1	22.5±1	/
				36	0	21.99	22.5±1	1.0
				36	24	22.14	22.5±1	1.0
				36	49	22.02	22.5±1	1.0
				75	0	21.88	22.5±1	1.0
			16QAM	1	0	21.95	21.5±1	1.0
				1	49	22.03	21.5±1	1.0
				1	99	21.99	21.5±1	1.0
				36	0	20.96	21.5±1	1.0
				36	24	21.08	21.5±1	1.0
				36	49	21.07	21.5±1	1.0
				75	0	20.93	21.5±1	1.0
	26915	836.5	QPSK	1	0	23.07	22.5±1	/
				1	49	23.36	22.5±1	/
				1	99	22.94	22.5±1	/
				36	0	21.95	22.5±1	1.0
				36	24	22.18	22.5±1	1.0
				36	49	21.98	22.5±1	1.0
				75	0	21.94	22.5±1	1.0
			16QAM	1	0	22.32	21.7±1	1.0
				1	49	22.63	21.7±1	1.0
				1	99	22.24	21.7±1	1.0
				36	0	21.04	21.7±1	1.0
				36	24	21.21	21.7±1	1.0
				36	49	20.87	21.7±1	1.0
				75	0	20.9	21.7±1	1.0
	26965	841.5	QPSK	1	0	23.16	23.0±1	/
				1	49	22.91	23.0±1	/
				1	99	23.05	23.0±1	/
				36	0	22.09	23.0±1	1.0
				36	24	22.05	23.0±1	1.0
				36	49	22.26	23.0±1	1.0
				75	0	22.25	23.0±1	1.0
			16QAM	1	0	22.44	21.5±1	1.0
				1	49	22.22	21.5±1	1.0
				1	99	22.33	21.5±1	1.0
				36	0	20.96	21.5±1	1.0
				36	24	20.88	21.5±1	1.0
				36	49	21.17	21.5±1	1.0
				75	0	21.13	21.5±1	1.0

LTE Band 41:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	40265	2557.5	QPSK	1	0	22.3	22.0±1	/
				1	12	22.34	22.0±1	/
				1	24	22.23	22.0±1	/
				12	0	21.24	22.0±1	1.0
				12	6	21.25	22.0±1	1.0
				12	11	21.17	22.0±1	1.0
				25	0	21.16	22.0±1	1.0
			16QAM	1	0	21.55	20.6±1	1.0
				1	12	21.53	20.6±1	1.0
				1	24	21.47	20.6±1	1.0
				12	0	19.97	20.6±1	1.0
				12	6	20.03	20.6±1	1.0
				12	11	19.96	20.6±1	1.0
				25	0	19.98	20.6±1	1.0
	40740	2605.0	QPSK	1	0	22.32	22.0±1	/
				1	12	22.38	22.0±1	/
				1	24	22.21	22.0±1	/
				12	0	21.18	22.0±1	1.0
				12	6	21.23	22.0±1	1.0
				12	11	21.14	22.0±1	1.0
				25	0	21.13	22.0±1	1.0
			16QAM	1	0	21.52	21.0±1	1.0
				1	12	21.58	21.0±1	1.0
				1	24	21.47	21.0±1	1.0
				12	0	20.23	21.0±1	1.0
				12	6	20.29	21.0±1	1.0
				12	11	20.21	21.0±1	1.0
				25	0	20.12	21.0±1	1.0
	41215	2652.5	QPSK	1	0	22.93	22.0±1	/
				1	12	22.83	22.0±1	/
				1	24	22.96	22.0±1	/
				12	0	21.91	22.0±1	1.0
				12	6	21.98	22.0±1	1.0
				12	11	21.98	22.0±1	1.0
				25	0	21.91	22.0±1	1.0
			16QAM	1	0	22.14	21.5±1	1.0
				1	12	22.19	21.5±1	1.0
				1	24	22.18	21.5±1	1.0
				12	0	21	21.5±1	1.0
				12	6	21.07	21.5±1	1.0
				12	11	21.07	21.5±1	1.0
				25	0	20.95	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	40290	2560.0	QPSK	1	0	22.12	22.0±1	/
				1	24	22.18	22.0±1	/
				1	49	21.93	22.0±1	/
				25	0	21.12	22.0±1	1.0
				25	12	21.21	22.0±1	1.0
				25	24	21.03	22.0±1	1.0
				50	0	21.08	22.0±1	1.0
			16QAM	1	0	21.47	20.6±1	1.0
				1	24	21.51	20.6±1	1.0
				1	49	21.27	20.6±1	1.0
				25	0	19.97	20.6±1	1.0
				25	12	20.03	20.6±1	1.0
				25	24	19.9	20.6±1	1.0
				50	0	19.9	20.6±1	1.0
	40740	2605.0	QPSK	1	0	22.35	22.0±1	/
				1	24	22.5	22.0±1	/
				1	49	22.23	22.0±1	/
				25	0	21.13	22.0±1	1.0
				25	12	21.23	22.0±1	1.0
				25	24	21.07	22.0±1	1.0
				50	0	21.11	22.0±1	1.0
			16QAM	1	0	21.58	21.0±1	1.0
				1	24	21.7	21.0±1	1.0
				1	49	21.48	21.0±1	1.0
				25	0	20.06	21.0±1	1.0
				25	12	20.17	21.0±1	1.0
				25	24	20.01	21.0±1	1.0
				50	0	20.08	21.0±1	1.0
	41190	2650.0	QPSK	1	0	22.97	22.5±1	/
				1	24	22.99	22.5±1	/
				1	49	23.09	22.5±1	/
				25	0	21.89	22.5±1	1.0
				25	12	22.04	22.5±1	1.0
				25	24	21.89	22.5±1	1.0
				50	0	21.92	22.5±1	1.0
			16QAM	1	0	22.04	21.5±1	1.0
				1	24	22.46	21.5±1	1.0
				1	49	22.19	21.5±1	1.0
				25	0	20.95	21.5±1	1.0
				25	12	21.12	21.5±1	1.0
				25	24	20.96	21.5±1	1.0
				50	0	21.01	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	40315	2562.5	QPSK	1	0	22.25	21.5±1	/
				1	37	22.15	21.5±1	/
				1	74	21.87	21.5±1	/
				36	0	21.18	21.5±1	1.0
				36	16	21.14	21.5±1	1.0
				36	35	20.97	21.5±1	1.0
				75	0	21.06	21.5±1	1.0
			16QAM	1	0	21.44	20.5±1	1.0
				1	37	21.42	20.5±1	1.0
				1	74	21.15	20.5±1	1.0
				36	0	19.92	20.5±1	1.0
				36	16	19.89	20.5±1	1.0
				36	35	19.79	20.5±1	1.0
				75	0	19.84	20.5±1	1.0
	40740	2605.0	QPSK	1	0	22.42	22.0±1	/
				1	37	22.48	22.0±1	/
				1	74	22.24	22.0±1	/
				36	0	21.24	22.0±1	1.0
				36	16	21.28	22.0±1	1.0
				36	35	21.12	22.0±1	1.0
				75	0	21.16	22.0±1	1.0
			16QAM	1	0	21.56	21.0±1	1.0
				1	37	21.74	21.0±1	1.0
				1	74	21.42	21.0±1	1.0
				36	0	20.21	21.0±1	1.0
				36	16	20.26	21.0±1	1.0
				36	35	20.1	21.0±1	1.0
				75	0	20.12	21.0±1	1.0
	41165	2647.5	QPSK	1	0	22.93	22.5±1	/
				1	37	23.05	22.5±1	/
				1	74	23.05	22.5±1	/
				36	0	21.72	22.5±1	1.0
				36	16	22.06	22.5±1	1.0
				36	35	21.96	22.5±1	1.0
				75	0	21.99	22.5±1	1.0
			16QAM	1	0	22	21.5±1	1.0
				1	37	22.4	21.5±1	1.0
				1	74	22.31	21.5±1	1.0
				36	0	20.89	21.5±1	1.0
				36	16	21.1	21.5±1	1.0
				36	35	21.02	21.5±1	1.0
				75	0	21.01	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	40340	2565.0	QPSK	1	0	22.14	21.5±1	/
				1	49	22.16	21.5±1	/
				1	99	21.89	21.5±1	/
				50	0	21	21.5±1	1.0
				50	24	21.04	21.5±1	1.0
				50	49	20.86	21.5±1	1.0
				100	0	20.93	21.5±1	1.0
			16QAM	1	0	21.43	20.5±1	1.0
				1	49	21.34	20.5±1	1.0
				1	99	21.15	20.5±1	1.0
				50	0	19.84	20.5±1	1.0
				50	24	19.84	20.5±1	1.0
				50	49	19.65	20.5±1	1.0
				100	0	19.74	20.5±1	1.0
	40740	2605.0	QPSK	1	0	22.34	22.0±1	/
				1	49	22.46	22.0±1	/
				1	99	22.14	22.0±1	/
				50	0	21.17	22.0±1	1.0
				50	24	21.27	22.0±1	1.0
				50	49	21.08	22.0±1	1.0
				100	0	21.13	22.0±1	1.0
			16QAM	1	0	21.35	21.0±1	1.0
				1	49	21.46	21.0±1	1.0
				1	99	21.2	21.0±1	1.0
				50	0	20.17	21.0±1	1.0
				50	24	20.28	21.0±1	1.0
				50	49	20.09	21.0±1	1.0
				100	0	20.15	21.0±1	1.0
	41140	2645.0	QPSK	1	0	22.66	22.5±1	/
				1	49	22.97	22.5±1	/
				1	99	23.11	22.5±1	/
				50	0	21.59	22.5±1	1.0
				50	24	21.92	22.5±1	1.0
				50	49	21.86	22.5±1	1.0
				100	0	21.8	22.5±1	1.0
			16QAM	1	0	21.84	21.5±1	1.0
				1	49	22.39	21.5±1	1.0
				1	99	22.2	21.5±1	1.0
				50	0	20.78	21.5±1	1.0
				50	24	21.07	21.5±1	1.0
				50	49	20.96	21.5±1	1.0
				100	0	20.85	21.5±1	1.0

LTE Band 66:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	131979	1710.7	QPSK	1	0	23.09	22.5±1	/
				1	2	22.95	22.5±1	/
				1	5	23.03	22.5±1	/
				3	0	22.89	22.5±1	/
				3	1	22.89	22.5±1	/
				3	2	22.86	22.5±1	/
				6	0	21.85	22.5±1	1.0
			16QAM	1	0	22.03	22.0±1	1.0
				1	2	21.92	22.0±1	1.0
				1	5	22.1	22.0±1	1.0
				3	0	21.85	22.0±1	1.0
				3	1	21.88	22.0±1	1.0
				3	2	21.85	22.0±1	1.0
				6	0	21.08	22.0±1	1.0
	132321	1744.9	QPSK	1	0	23.03	22.5±1	/
				1	2	22.92	22.5±1	/
				1	5	23	22.5±1	/
				3	0	22.83	22.5±1	/
				3	1	22.82	22.5±1	/
				3	2	22.81	22.5±1	/
				6	0	21.79	22.5±1	1.0
			16QAM	1	0	22.31	21.5±1	1.0
				1	2	22.2	21.5±1	1.0
				1	5	22.29	21.5±1	1.0
				3	0	21.99	21.5±1	1.0
				3	1	21.99	21.5±1	1.0
				3	2	21.98	21.5±1	1.0
				6	0	20.77	21.5±1	1.0
	132664	1779.2	QPSK	1	0	23.11	23.0±1	/
				1	2	23	23.0±1	/
				1	5	23.12	23.0±1	/
				3	0	22.99	23.0±1	/
				3	1	23.04	23.0±1	/
				3	2	23.05	23.0±1	/
				6	0	22.06	23.0±1	1.0
			16QAM	1	0	22.18	22.0±1	1.0
				1	2	22.03	22.0±1	1.0
				1	5	22.24	22.0±1	1.0
				3	0	22.23	22.0±1	1.0
				3	1	22.23	22.0±1	1.0
				3	2	22.19	22.0±1	1.0
				6	0	21.23	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	131987	1711.5	QPSK	1	0	22.74	22.0±1	/
				1	8	22.9	22.0±1	/
				1	14	22.83	22.0±1	/
				6	0	21.8	22.0±1	1.0
				6	4	21.85	22.0±1	1.0
				6	9	21.86	22.0±1	1.0
				15	0	21.8	22.0±1	1.0
			16QAM	1	0	21.61	21.0±1	1.0
				1	8	21.73	21.0±1	1.0
				1	14	21.69	21.0±1	1.0
				8	0	20.95	21.0±1	1.0
				8	4	21.01	21.0±1	1.0
				8	9	21.03	21.0±1	1.0
				15	0	20.9	21.0±1	1.0
	132321	1744.9	QPSK	1	0	22.85	22.0±1	/
				1	8	22.88	22.0±1	/
				1	14	22.8	22.0±1	/
				6	0	21.78	22.0±1	1.0
				6	4	21.8	22.0±1	1.0
				6	9	21.78	22.0±1	1.0
				15	0	21.74	22.0±1	1.0
			16QAM	1	0	22.11	21.5±1	1.0
				1	8	22.18	21.5±1	1.0
				1	14	22.11	21.5±1	1.0
				6	0	20.93	21.5±1	1.0
				6	4	20.97	21.5±1	1.0
				6	9	20.95	21.5±1	1.0
				15	0	20.85	21.5±1	1.0
	132656	1778.4	QPSK	1	0	22.95	22.5±1	/
				1	8	23.05	22.5±1	/
				1	14	23.01	22.5±1	/
				6	0	21.99	22.5±1	1.0
				6	4	22.02	22.5±1	1.0
				6	9	22.03	22.5±1	1.0
				15	0	21.98	22.5±1	1.0
			16QAM	1	0	22.03	22.0±1	1.0
				1	8	22.03	22.0±1	1.0
				1	14	22.01	22.0±1	1.0
				8	0	21.09	22.0±1	1.0
				8	4	21.12	22.0±1	1.0
				8	9	21.03	22.0±1	1.0
				15	0	21.01	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	131997	1712.5	QPSK	1	0	22.66	22.0±1	/
				1	49	22.81	22.0±1	/
				1	99	22.54	22.0±1	/
				12	0	21.69	22.0±1	1.0
				12	24	21.81	22.0±1	1.0
				12	49	21.71	22.0±1	1.0
				25	0	21.71	22.0±1	1.0
			16QAM	1	0	21.79	21.0±1	1.0
				1	49	21.97	21.0±1	1.0
				1	99	21.73	21.0±1	1.0
				12	0	20.83	21.0±1	1.0
				12	24	20.97	21.0±1	1.0
				12	49	20.88	21.0±1	1.0
				25	0	20.83	21.0±1	1.0
	132321	1744.9	QPSK	1	0	22.67	22.0±1	/
				1	49	22.8	22.0±1	/
				1	99	22.7	22.0±1	/
				12	0	21.72	22.0±1	1.0
				12	24	21.75	22.0±1	1.0
				12	49	21.61	22.0±1	1.0
				25	0	21.67	22.0±1	1.0
			16QAM	1	0	22.09	21.5±1	1.0
				1	49	22.27	21.5±1	1.0
				1	99	22.17	21.5±1	1.0
				12	0	20.93	21.5±1	1.0
				12	24	20.97	21.5±1	1.0
				12	49	20.83	21.5±1	1.0
				25	0	20.82	21.5±1	1.0
	132646	1777.4	QPSK	1	0	23	22.5±1	/
				1	49	23.06	22.5±1	/
				1	99	22.98	22.5±1	/
				12	0	22.01	22.5±1	1.0
				12	24	22.05	22.5±1	1.0
				12	49	21.93	22.5±1	1.0
				25	0	21.97	22.5±1	1.0
			16QAM	1	0	22.09	21.5±1	1.0
				1	49	22.21	21.5±1	1.0
				1	99	22.13	21.5±1	1.0
				12	0	21.06	21.5±1	1.0
				12	24	21.11	21.5±1	1.0
				12	49	21.09	21.5±1	1.0
				25	0	20.94	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	132022	1715	QPSK	1	0	22.56	22.0±1	/
				1	49	22.64	22.0±1	/
				1	99	22.52	22.0±1	/
				25	0	21.63	22.0±1	1.0
				25	24	21.61	22.0±1	1.0
				25	49	21.52	22.0±1	1.0
				50	0	21.53	22.0±1	1.0
			16QAM	1	0	21.45	21.0±1	1.0
				1	49	21.55	21.0±1	1.0
				1	99	21.54	21.0±1	1.0
				25	0	20.73	21.0±1	1.0
				25	24	20.73	21.0±1	1.0
				25	49	20.63	21.0±1	1.0
				50	0	20.6	21.0±1	1.0
	132321	1744.9	QPSK	1	0	22.52	22.0±1	/
				1	49	22.8	22.0±1	/
				1	99	22.59	22.0±1	/
				25	0	21.55	22.0±1	1.0
				25	24	21.68	22.0±1	1.0
				25	49	21.57	22.0±1	1.0
				50	0	21.57	22.0±1	1.0
			16QAM	1	0	21.9	21.5±1	1.0
				1	49	22.11	21.5±1	1.0
				1	99	21.91	21.5±1	1.0
				25	0	20.63	21.5±1	1.0
				25	24	20.74	21.5±1	1.0
				25	49	20.59	21.5±1	1.0
				50	0	20.63	21.5±1	1.0
	132621	1774.9	QPSK	1	0	22.79	22.0±1	/
				1	49	23.01	22.0±1	/
				1	99	22.81	22.0±1	/
				25	0	21.87	22.0±1	1.0
				25	24	21.98	22.0±1	1.0
				25	49	21.84	22.0±1	1.0
				50	0	21.89	22.0±1	1.0
			16QAM	1	0	21.88	21.5±1	1.0
				1	49	22.02	21.5±1	1.0
				1	99	21.85	21.5±1	1.0
				25	0	21.02	21.5±1	1.0
				25	24	21.13	21.5±1	1.0
				25	49	20.94	21.5±1	1.0
				50	0	20.99	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	132097	1722.5	QPSK	1	0	22.59	22.0±1	/
				1	49	22.74	22.0±1	/
				1	99	22.71	22.0±1	/
				36	0	21.6	22.0±1	1.0
				36	24	21.71	22.0±1	1.0
				36	49	21.76	22.0±1	1.0
				75	0	21.66	22.0±1	1.0
			16QAM	1	0	21.5	21.0±1	1.0
				1	49	21.62	21.0±1	1.0
				1	99	21.63	21.0±1	1.0
				36	0	20.67	21.0±1	1.0
				36	24	20.79	21.0±1	1.0
				36	49	20.85	21.0±1	1.0
				75	0	20.76	21.0±1	1.0
	132321	1744.9	QPSK	1	0	22.67	22.0±1	/
				1	49	22.82	22.0±1	/
				1	99	22.81	22.0±1	/
				36	0	21.7	22.0±1	1.0
				36	24	21.72	22.0±1	1.0
				36	49	21.63	22.0±1	1.0
				75	0	21.66	22.0±1	1.0
			16QAM	1	0	21.94	21.5±1	1.0
				1	49	22.13	21.5±1	1.0
				1	99	22.13	21.5±1	1.0
				36	0	20.82	21.5±1	1.0
				36	24	20.85	21.5±1	1.0
				36	49	20.77	21.5±1	1.0
				75	0	20.78	21.5±1	1.0
	132546	1767.4	QPSK	1	0	22.96	22.5±1	/
				1	49	23.07	22.5±1	/
				1	99	22.99	22.5±1	/
				36	0	21.96	22.5±1	1.0
				36	24	22.05	22.5±1	1.0
				36	49	21.97	22.5±1	1.0
				75	0	22	22.5±1	1.0
			16QAM	1	0	22.24	21.5±1	1.0
				1	49	22.48	21.5±1	1.0
				1	99	22.26	21.5±1	1.0
				36	0	20.97	21.5±1	1.0
				36	24	21.1	21.5±1	1.0
				36	49	20.92	21.5±1	1.0
				75	0	21.09	21.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	132072	1720	QPSK	1	0	22.4	22.0±1	/
				1	49	22.74	22.0±1	/
				1	99	22.56	22.0±1	/
				50	0	21.45	22.0±1	1.0
				50	24	21.7	22.0±1	1.0
				50	49	21.67	22.0±1	1.0
				100	0	21.54	22.0±1	1.0
			16QAM	1	0	22.02	21.5±1	1.0
				1	49	22.31	21.5±1	1.0
				1	99	22.26	21.5±1	1.0
				50	0	20.57	21.5±1	1.0
				50	24	20.82	21.5±1	1.0
				50	49	20.79	21.5±1	1.0
				100	0	20.68	21.5±1	1.0
	132321	1744.9	QPSK	1	0	22.5	22.0±1	/
				1	49	22.69	22.0±1	/
				1	99	22.58	22.0±1	/
				50	0	21.57	22.0±1	1.0
				50	24	21.66	22.0±1	1.0
				50	49	21.55	22.0±1	1.0
				100	0	21.56	22.0±1	1.0
			16QAM	1	0	21.91	21.5±1	1.0
				1	49	22.13	21.5±1	1.0
				1	99	22.05	21.5±1	1.0
				50	0	20.66	21.5±1	1.0
				50	24	20.76	21.5±1	1.0
				50	49	20.66	21.5±1	1.0
				100	0	20.66	21.5±1	1.0
	132471	1759.9	QPSK	1	0	22.96	22.5±1	/
				1	49	23.17	22.5±1	/
				1	99	22.98	22.5±1	/
				50	0	21.76	22.5±1	1.0
				50	24	22.07	22.5±1	1.0
				50	49	21.94	22.5±1	1.0
				100	0	21.95	22.5±1	1.0
			16QAM	1	0	21.96	21.5±1	1.0
				1	49	22.44	21.5±1	1.0
				1	99	22.21	21.5±1	1.0
				50	0	20.83	21.5±1	1.0
				50	24	21.13	21.5±1	1.0
				50	49	20.96	21.5±1	1.0
				100	0	21.06	21.5±1	1.0

LTE Band 71:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	133147	665.5	QPSK	1	0	23.51	23.0±1	/
				1	12	23.74	23.0±1	/
				1	24	23.56	23.0±1	/
				12	0	22.75	23.0±1	1.0
				12	6	22.8	23.0±1	1.0
				12	11	22.73	23.0±1	1.0
				25	0	22.69	23.0±1	1.0
			16QAM	1	0	22.58	22.0±1	1.0
				1	12	22.68	22.0±1	1.0
				1	24	22.51	22.0±1	1.0
				12	0	21.84	22.0±1	1.0
				12	6	21.85	22.0±1	1.0
				12	11	21.79	22.0±1	1.0
				25	0	21.68	22.0±1	1.0
	133297	680.5	QPSK	1	0	23.56	23.0±1	/
				1	12	23.64	23.0±1	/
				1	24	23.68	23.0±1	/
				12	0	22.84	23.0±1	1.0
				12	6	22.88	23.0±1	1.0
				12	11	22.88	23.0±1	1.0
				25	0	22.75	23.0±1	1.0
			16QAM	1	0	22.45	22.0±1	1.0
				1	12	22.45	22.0±1	1.0
				1	24	22.28	22.0±1	1.0
				12	0	21.95	22.0±1	1.0
				12	6	21.9	22.0±1	1.0
				12	11	21.88	22.0±1	1.0
				25	0	21.91	22.0±1	1.0
	133447	695.5	QPSK	1	0	23.67	23.0±1	/
				1	12	23.93	23.0±1	/
				1	24	23.75	23.0±1	/
				12	0	22.92	23.0±1	1.0
				12	6	22.97	23.0±1	1.0
				12	11	22.82	23.0±1	1.0
				25	0	22.82	23.0±1	1.0
			16QAM	1	0	22.79	22.0±1	1.0
				1	12	22.91	22.0±1	1.0
				1	24	22.35	22.0±1	1.0
				12	0	21.71	22.0±1	1.0
				12	6	21.75	22.0±1	1.0
				12	11	22.01	22.0±1	1.0
				25	0	21.94	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	133172	668	QPSK	1	0	23.94	23.0±1	/
				1	24	23.82	23.0±1	/
				1	49	23.52	23.0±1	/
				25	0	22.74	23.0±1	1.0
				25	12	22.73	23.0±1	1.0
				25	24	22.64	23.0±1	1.0
				50	0	22.73	23.0±1	1.0
			16QAM	1	0	22.69	22.5±1	1.0
				1	24	23.13	22.5±1	1.0
				1	49	22.48	22.5±1	1.0
				25	0	21.71	22.5±1	1.0
				25	12	21.63	22.5±1	1.0
				25	24	21.61	22.5±1	1.0
				50	0	21.54	22.5±1	1.0
	133297	680.5	QPSK	1	0	23.47	23.0±1	/
				1	24	23.84	23.0±1	/
				1	49	23.51	23.0±1	/
				25	0	22.6	23.0±1	1.0
				25	12	22.75	23.0±1	1.0
				25	24	22.64	23.0±1	1.0
				50	0	22.61	23.0±1	1.0
			16QAM	1	0	22.41	22.0±1	1.0
				1	24	22.56	22.0±1	1.0
				1	49	22.12	22.0±1	1.0
				25	0	21.7	22.0±1	1.0
				25	12	21.75	22.0±1	1.0
				25	24	21.71	22.0±1	1.0
				50	0	21.68	22.0±1	1.0
	133422	693	QPSK	1	0	23.54	23.0±1	/
				1	24	23.86	23.0±1	/
				1	49	23.72	23.0±1	/
				25	0	22.62	23.0±1	1.0
				25	12	22.77	23.0±1	1.0
				25	24	22.69	23.0±1	1.0
				50	0	22.66	23.0±1	1.0
			16QAM	1	0	22.58	22.0±1	1.0
				1	24	22.65	22.0±1	1.0
				1	49	22.08	22.0±1	1.0
				25	0	21.79	22.0±1	1.0
				25	12	22	22.0±1	1.0
				25	24	21.91	22.0±1	1.0
				50	0	21.66	22.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	133197	670.5	QPSK	1	0	23.62	23.0±1	/
				1	37	23.46	23.0±1	/
				1	74	23.6	23.0±1	/
				36	0	22.59	23.0±1	1.0
				36	16	22.59	23.0±1	1.0
				36	35	22.63	23.0±1	1.0
				75	0	22.59	23.0±1	1.0
			16QAM	1	0	22.67	22.0±1	1.0
				1	37	22.97	22.0±1	1.0
				1	74	22.38	22.0±1	1.0
				36	0	21.56	22.0±1	1.0
				36	16	21.56	22.0±1	1.0
				36	35	21.68	22.0±1	1.0
				75	0	21.57	22.0±1	1.0
	133297	680.5	QPSK	1	0	23.4	23.0±1	/
				1	37	23.49	23.0±1	/
				1	74	23.43	23.0±1	/
				36	0	22.51	23.0±1	1.0
				36	16	22.59	23.0±1	1.0
				36	35	22.41	23.0±1	1.0
				75	0	22.47	23.0±1	1.0
			16QAM	1	0	22.46	22.0±1	1.0
				1	37	22.55	22.0±1	1.0
				1	74	21.88	22.0±1	1.0
				36	0	21.55	22.0±1	1.0
				36	16	21.7	22.0±1	1.0
				36	35	21.51	22.0±1	1.0
				75	0	21.47	22.0±1	1.0
	133397	690.5	QPSK	1	0	23.44	23.0±1	/
				1	37	23.42	23.0±1	/
				1	74	23.48	23.0±1	/
				36	0	22.52	23.0±1	1.0
				36	16	22.64	23.0±1	1.0
				36	35	22.7	23.0±1	1.0
				75	0	22.66	23.0±1	1.0
			16QAM	1	0	23.14	22.5±1	1.0
				1	37	22.5	22.5±1	1.0
				1	74	22.63	22.5±1	1.0
				36	0	21.57	22.5±1	1.0
				36	16	21.68	22.5±1	1.0
				36	35	21.67	22.5±1	1.0
				75	0	21.65	22.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	133222	673	QPSK	1	0	23.28	23.0±1	/
				1	49	23.58	23.0±1	/
				1	99	23.31	23.0±1	/
				50	0	22.5	23.0±1	1.0
				50	24	22.59	23.0±1	1.0
				50	49	22.7	23.0±1	1.0
				100	0	22.59	23.0±1	1.0
			16QAM	1	0	22.82	22.0±1	1.0
				1	49	22.68	22.0±1	1.0
				1	99	22.13	22.0±1	1.0
				50	0	21.47	22.0±1	1.0
				50	24	21.77	22.0±1	1.0
				50	49	21.54	22.0±1	1.0
				100	0	21.6	22.0±1	1.0
	133322	683	QPSK	1	0	23.43	23.0±1	/
				1	49	23.88	23.0±1	/
				1	99	23.52	23.0±1	/
				50	0	22.63	23.0±1	1.0
				50	24	22.63	23.0±1	1.0
				50	49	22.72	23.0±1	1.0
				100	0	22.47	23.0±1	1.0
			16QAM	1	0	22.25	22.0±1	1.0
				1	49	23.04	22.0±1	1.0
				1	99	21.99	22.0±1	1.0
				50	0	21.59	22.0±1	1.0
				50	24	21.71	22.0±1	1.0
				50	49	21.55	22.0±1	1.0
				100	0	21.56	22.0±1	1.0
	133372	688	QPSK	1	0	23.29	23.0±1	/
				1	49	23.95	23.0±1	/
				1	99	23.39	23.0±1	/
				50	0	22.42	23.0±1	1.0
				50	24	22.57	23.0±1	1.0
				50	49	22.64	23.0±1	1.0
				100	0	22.57	23.0±1	1.0
			16QAM	1	0	22.5	22.0±1	1.0
				1	49	22.42	22.0±1	1.0
				1	99	22.12	22.0±1	1.0
				50	0	21.48	22.0±1	1.0
				50	24	21.52	22.0±1	1.0
				50	49	21.61	22.0±1	1.0
				100	0	21.57	22.0±1	1.0


2.4G Wi-Fi Measurement Result

Channel number	Frequency (MHz)	Output Power(dBm)	Tune up limited(dBm)
TX 11b	2412	18.14	18.0±1
	2437	17.94	18.0±1
	2462	17.63	18.0±1
TX 11g	2412	19.78	20.0±1
	2437	20.00	20.0±1
	2462	19.44	20.0±1
TX 11n HT20	2412	17.97	18.0±1
	2437	18.60	18.0±1
	2462	17.87	18.0±1
TX 11n HT40	2422	15.50	15.0±1
	2437	14.80	15.0±1
	2452	14.38	15.0±1
TX 11ax HE20	2412	18.15	18.0±1
	2437	18.77	18.0±1
	2462	18.05	18.0±1
TX 11ax HE40	2422	15.16	15.0±1
	2437	15.53	15.0±1
	2452	15.02	15.0±1

Note: 5G WiFi power please refer to the test report WTX25X10277821W.

13 Exposure Conditions Consideration

13.1 EUT antenna location



13.2 Test position consideration

Distance of EUT antenna-to-edge/surface(mm)						
Antennas	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	<25	<25	83	<25	32	<25
WLAN	<25	<25	58	<25	80	<25
Test distance:5mm						
Antennas	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	YES	YES	NO	YES	NO	YES
WLAN	YES	YES	NO	YES	NO	YES

Note:

1. Body SAR mode assessments are required.
2. Per KDB 447498 D01v06, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user, which is 10 mm for body SAR.

14 SAR Test Results

14.1 Test Condition

1. SAR Measurement
The distance between the EUT and the antenna of the emulator is more than 50 cm and the output power radiated from the emulator antenna is at least 30 dB less than the output power of EUT.
2. Environmental Conditions

Temperature	22.9°C
Relative Humidity	51.4%
Atmospheric Pressure	1021mbar

14.2 Generally Test Procedures

1. Establish communication link between EUT and base station emulation by air link.
2. Place the EUT in the selected test position. (Cheek, tilt or flat)
3. Perform SAR testing at middle or highest output power channel under the selected test mode. If the measured 1-g SAR is ≤ 0.8 W/kg, then testing for the other channel will not be performed.
4. When SAR is < 0.8 W/kg, no repeated SAR measurement is required

For WCDMA test:

1. KDB941225 D01-Body SAR is not required for HSDPA when the average output of each RF channel with HSDPA active is less than 0.25dB higher than measured without HSDPA using 12.2kbps RMC or the maximum SAR for 12.2kbps RMC $< 75\%$ of the SAR limit.
2. KDB941225 D01-Body SAR is not required for handset with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25dB higher than that measure without HSUPA/HSDPA using 12.2kbps RMC AND THE maximum SAR for 12.2kbps RMC is $< 75\%$ of the SAR limit

For LTE test:

1. According to FCC KDB 941225 D05v02r05:
 - a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
 - b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
 - c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
 - d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.
 - e. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

14.3 SAR Summary Test Result

Table 4: SAR Values of WCDMA BAND II

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Body-worn (5mm Separation)	Front Side	9400	1880	RMC 12.2kbps	23	22.57	1.104	0.619	0.683	--
	Back Side	9400	1880	RMC 12.2kbps	23	22.57	1.104	0.754	0.832	--
	Right Edge	9400	1880	RMC 12.2kbps	23	22.57	1.104	1.033	1.141	1
	Bottom Edge	9400	1880	RMC 12.2kbps	23	22.57	1.104	0.746	0.824	--
	Back Side	9262	1852.4	RMC 12.2kbps	23	22.54	1.112	0.729	0.810	--
	Back Side	9538	1907.6	RMC 12.2kbps	23	22.44	1.138	0.711	0.809	--
	Right Edge	9262	1852.4	RMC 12.2kbps	23	22.54	1.112	1.023	1.137	--
	Right Edge	9538	1907.6	RMC 12.2kbps	23	22.44	1.138	1.001	1.139	--
	Bottom Edge	9262	1852.4	RMC 12.2kbps	23	22.54	1.112	0.725	0.806	--
	Bottom Edge	9538	1907.6	RMC 12.2kbps	23	22.44	1.138	0.713	0.811	--

Table 5: SAR Values of LTE BAND 2, 1.4MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	18607	1850.7	24	23.6	0	1.096	0.446	0.489	--
		Back Side	18607	1850.7	24	23.6	0	1.096	0.435	0.477	--
		Right Edge	18607	1850.7	24	23.6	0	1.096	0.917	1.005	2
		Bottom Edge	18607	1850.7	24	23.6	0	1.096	0.340	0.373	--
		Right Edge	18900	1880	24	23.19	0	1.205	0.829	0.999	--
		Right Edge	19193	1909.3	24	23.36	0	1.159	0.864	1.001	--
50%RB	Body-worn (5mm Separation)	Front Side	18607	1850.7	24	23.6	1	1.096	0.422	0.463	--
		Back Side	18607	1850.7	24	23.6	1	1.096	0.407	0.446	--
		Right Edge	18607	1850.7	24	23.6	1	1.096	0.886	0.971	--
		Bottom Edge	18607	1850.7	24	23.6	1	1.096	0.323	0.354	--
		Right Edge	18900	1880	24	23.19	1	1.205	0.806	0.971	--
		Right Edge	19193	1909.3	24	23.36	1	1.159	0.835	0.968	--

Table 6: SAR Values of LTE BAND 2, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	19100	1900	23.5	23.02	0	1.117	0.387	0.432	--
		Back Side	19100	1900	23.5	23.02	0	1.117	0.352	0.393	--
		Right Edge	19100	1900	23.5	23.02	0	1.117	0.856	0.956	--
		Bottom Edge	19100	1900	23.5	23.02	0	1.117	0.271	0.303	--
		Right Edge	18700	1860	23.5	23.01	0	1.119	0.843	0.944	--
		Right Edge	18900	1880	23	22.91	0	1.021	0.829	0.846	--
50%RB	Body-worn (5mm Separation)	Front Side	19100	1900	23.5	23.02	1	1.117	0.355	0.396	--
		Back Side	19100	1900	23.5	23.02	1	1.117	0.327	0.365	--
		Right Edge	19100	1900	23.5	23.02	1	1.117	0.832	0.929	--
		Bottom Edge	19100	1900	23.5	23.02	1	1.117	0.249	0.278	--
		Right Edge	18700	1860	23.5	23.01	1	1.119	0.818	0.916	--
		Right Edge	18900	1880	23	22.91	1	1.021	0.803	0.820	--

Table 7: SAR Values of LTE BAND 4, 1.4MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	19957	1710.7	23.5	23.18	0	1.076	0.200	0.215	
		Back Side	19957	1710.7	23.5	23.18	0	1.076	0.302	0.325	--
		Right Edge	19957	1710.7	23.5	23.18	0	1.076	0.423	0.455	3
		Bottom Edge	19957	1710.7	23.5	23.18	0	1.076	0.368	0.396	--
50%RB	Body-worn (5mm Separation)	Front Side	19957	1710.7	23.5	23.18	1	1.076	0.175	0.188	--
		Back Side	19957	1710.7	23.5	23.18	1	1.076	0.282	0.304	--
		Right Edge	19957	1710.7	23.5	23.18	1	1.076	0.404	0.435	--
		Bottom Edge	19957	1710.7	23.5	23.18	1	1.076	0.339	0.365	--

Table 8: SAR Values of LTE BAND 4, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	20050	1720	23	22.97	0	1.007	0.168	0.169	--
		Back Side	20050	1720	23	22.97	0	1.007	0.291	0.293	--
		Right Edge	20050	1720	23	22.97	0	1.007	0.395	0.398	--
		Bottom Edge	20050	1720	23	22.97	0	1.007	0.343	0.345	--
50%RB	Body-worn (5mm Separation)	Front Side	20050	1720	23	22.97	1	1.007	0.142	0.143	--
		Back Side	20050	1720	23	22.97	1	1.007	0.269	0.271	--
		Right Edge	20050	1720	23	22.97	1	1.007	0.377	0.380	--
		Bottom Edge	20050	1720	23	22.97	1	1.007	0.326	0.328	--

Table 9: SAR Values of LTE BAND 5, 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	20625	846.5	24	23.78	0	1.052	0.273	0.287	4
		Back Side	20625	846.5	24	23.78	0	1.052	0.070	0.074	--
		Right Edge	20625	846.5	24	23.78	0	1.052	0.096	0.101	--
		Bottom Edge	20625	846.5	24	23.78	0	1.052	0.080	0.084	--
50%RB	Body-worn (5mm Separation)	Front Side	20625	846.5	24	23.78	1	1.052	0.253	0.266	--
		Back Side	20625	846.5	24	23.78	1	1.052	0.058	0.061	--
		Right Edge	20625	846.5	24	23.78	1	1.052	0.078	0.082	--
		Bottom Edge	20625	846.5	24	23.78	1	1.052	0.064	0.067	--

Table 10: SAR Values of LTE BAND 5, 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	20450	829	23.5	23.25	0	1.059	0.241	0.255	--
		Back Side	20450	829	23.5	23.25	0	1.059	0.053	0.056	--
		Right Edge	20450	829	23.5	23.25	0	1.059	0.067	0.071	--
		Bottom Edge	20450	829	23.5	23.25	0	1.059	0.056	0.059	--
50%RB	Body-worn (5mm Separation)	Front Side	20450	829	23.5	23.25	1	1.059	0.229	0.243	--
		Back Side	20450	829	23.5	23.25	1	1.059	0.046	0.049	--
		Right Edge	20450	829	23.5	23.25	1	1.059	0.060	0.064	--
		Bottom Edge	20450	829	23.5	23.25	1	1.059	0.048	0.051	--

Table 11: SAR Values of LTE BAND 7, 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	21425	2567.5	22.6	22.53	0	1.016	0.826	0.839	--
		Back Side	21425	2567.5	22.6	22.53	0	1.016	0.274	0.278	--
		Right Edge	21425	2567.5	22.6	22.53	0	1.016	1.099	1.117	5
		Bottom Edge	21425	2567.5	22.6	22.53	0	1.016	0.216	0.220	--
		Front Side	20775	2502.5	22.6	22.13	0	1.114	0.774	0.862	--
		Front Side	21100	2535	22.6	22.33	0	1.064	0.795	0.846	--
		Right Edge	20775	2502.5	22.6	22.13	0	1.114	0.950	1.059	--
		Right Edge	21100	2535	22.6	22.33	0	1.064	0.986	1.049	--
50%RB	Body-worn (5mm Separation)	Front Side	21425	2567.5	22.6	22.53	1	1.016	0.792	0.805	--
		Back Side	21425	2567.5	22.6	22.53	1	1.016	0.239	0.243	--
		Right Edge	21425	2567.5	22.6	22.53	1	1.016	1.055	1.072	--
		Bottom Edge	21425	2567.5	22.6	22.53	1	1.016	0.188	0.191	--
		Front Side	20775	2502.5	22.6	22.13	1	1.114	0.736	0.820	--
		Front Side	21100	2535	22.6	22.33	1	1.064	0.755	0.803	--
		Right Edge	20775	2502.5	22.6	22.13	1	1.114	0.937	1.044	--
		Right Edge	21100	2535	22.6	22.33	1	1.064	0.962	1.024	--

Table 12: SAR Values of LTE BAND 7, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	21350	2560	22.5	22.2	0	1.072	0.705	0.755	--
		Back Side	21350	2560	22.5	22.2	0	1.072	0.187	0.200	--
		Right Edge	21100	2535	22.5	22.2	0	1.072	0.933	1.000	--
		Bottom Edge	21350	2560	22.5	22.2	0	1.072	0.119	0.128	--
		Right Edge	20850	2510	22	21.88	0	1.028	0.886	0.911	--
		Right Edge	21100	2535	22.5	22.11	0	1.094	0.903	0.988	--
50%RB	Body-worn (5mm Separation)	Front Side	21350	2560	22.5	22.2	1	1.072	0.683	0.732	--
		Back Side	21350	2560	22.5	22.2	1	1.072	0.158	0.169	--
		Right Edge	21100	2535	22.5	22.2	1	1.072	0.897	0.961	--
		Bottom Edge	21350	2560	22.5	22.2	1	1.072	0.102	0.109	--
		Right Edge	20850	2510	22	21.88	1	1.028	0.836	0.859	--
		Right Edge	21100	2535	22.5	22.11	1	1.094	0.858	0.939	--

Table 13: SAR Values of LTE BAND 12, 1.4MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23095	707.5	23.5	23.27	0	1.054	0.274	0.289	6
		Back Side	23095	707.5	23.5	23.27	0	1.054	0.096	0.101	--
		Right Edge	23095	707.5	23.5	23.27	0	1.054	0.120	0.127	--
		Bottom Edge	23095	707.5	23.5	23.27	0	1.054	0.067	0.071	--
50%RB	Body-worn (5mm Separation)	Front Side	23095	707.5	23.5	23.27	1	1.054	0.236	0.249	--
		Back Side	23095	707.5	23.5	23.27	1	1.054	0.068	0.072	--
		Right Edge	23095	707.5	23.5	23.27	1	1.054	0.095	0.100	--
		Bottom Edge	23095	707.5	23.5	23.27	1	1.054	0.053	0.056	--

Table 14: SAR Values of LTE BAND 12, 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23130	711	23	22.83	0	1.040	0.202	0.210	--
		Back Side	23130	711	23	22.83	0	1.040	0.049	0.051	--
		Right Edge	23130	711	23	22.83	0	1.040	0.077	0.080	--
		Bottom Edge	23130	711	23	22.83	0	1.040	0.043	0.045	--
50%RB	Body-worn (5mm Separation)	Front Side	23130	711	23	22.83	1	1.040	0.176	0.183	--
		Back Side	23130	711	23	22.83	1	1.040	0.035	0.036	--
		Right Edge	23130	711	23	22.83	1	1.040	0.058	0.060	--
		Bottom Edge	23130	711	23	22.83	1	1.040	0.036	0.037	--

Table 15: SAR Values of LTE BAND 13, 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23255	784.5	24	23.27	0	1.183	0.343	0.406	7
		Back Side	23255	784.5	24	23.27	0	1.183	0.110	0.130	--
		Right Edge	23255	784.5	24	23.27	0	1.183	0.065	0.077	--
		Bottom Edge	23255	784.5	24	23.27	0	1.183	0.080	0.095	--
50%RB	Body-worn (5mm Separation)	Front Side	23255	784.5	24	23.27	1	1.183	0.315	0.373	--
		Back Side	23255	784.5	24	23.27	1	1.183	0.098	0.116	--
		Right Edge	23255	784.5	24	23.27	1	1.183	0.052	0.062	--
		Bottom Edge	23255	784.5	24	23.27	1	1.183	0.069	0.082	--

Table 16: SAR Values of LTE BAND 13, 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23230	782.0	23.5	23.03	0	1.114	0.321	0.358	--
		Back Side	23230	782.0	23.5	23.03	0	1.114	0.094	0.105	--
		Right Edge	23230	782.0	23.5	23.03	0	1.114	0.056	0.062	--
		Bottom Edge	23230	782.0	23.5	23.03	0	1.114	0.073	0.081	--
50%RB	Body-worn (5mm Separation)	Front Side	23230	782.0	23.5	23.03	1	1.114	0.287	0.320	--
		Back Side	23230	782.0	23.5	23.03	1	1.114	0.079	0.088	--
		Right Edge	23230	782.0	23.5	23.03	1	1.114	0.042	0.047	--
		Bottom Edge	23230	782.0	23.5	23.03	1	1.114	0.058	0.065	--

Table 17: SAR Values of LTE BAND 14, 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23330	793.0	23.5	23.11	0	1.094	0.341	0.373	8
		Back Side	23330	793.0	23.5	23.11	0	1.094	0.109	0.119	--
		Right Edge	23330	793.0	23.5	23.11	0	1.094	0.082	0.090	--
		Bottom Edge	23330	793.0	23.5	23.11	0	1.094	0.119	0.130	--
50%RB	Body-worn (5mm Separation)	Front Side	23330	793.0	23.5	23.11	1	1.094	0.318	0.348	--
		Back Side	23330	793.0	23.5	23.11	1	1.094	0.083	0.091	--
		Right Edge	23330	793.0	23.5	23.11	1	1.094	0.065	0.071	--
		Bottom Edge	23330	793.0	23.5	23.11	1	1.094	0.099	0.108	--

Table 18: SAR Values of LTE BAND 17, 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23790	710	23.5	23.13	0	1.089	0.278	0.303	9
		Back Side	23790	710	23.5	23.13	0	1.089	0.099	0.108	--
		Right Edge	23790	710	23.5	23.13	0	1.089	0.111	0.121	--
		Bottom Edge	23790	710	23.5	23.13	0	1.089	0.095	0.103	--
50%RB	Body-worn (5mm Separation)	Front Side	23790	710	23.5	23.13	1	1.089	0.254	0.277	--
		Back Side	23790	710	23.5	23.13	1	1.089	0.079	0.086	--
		Right Edge	23790	710	23.5	23.13	1	1.089	0.102	0.111	--
		Bottom Edge	23790	710	23.5	23.13	1	1.089	0.077	0.084	--

Table 19: SAR Values of LTE BAND 17, 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	23790	710	23	22.86	0	1.033	0.224	0.231	--
		Back Side	23790	710	23	22.86	0	1.033	0.056	0.058	--
		Right Edge	23790	710	23	22.86	0	1.033	0.081	0.084	--
		Bottom Edge	23790	710	23	22.86	0	1.033	0.066	0.068	--
50%RB	Body-worn (5mm Separation)	Front Side	23790	710	23	22.86	1	1.033	0.194	0.200	--
		Back Side	23790	710	23	22.86	1	1.033	0.047	0.049	--
		Right Edge	23790	710	23	22.86	1	1.033	0.069	0.071	--
		Bottom Edge	23790	710	23	22.86	1	1.033	0.052	0.054	--

Table 20: SAR Values of LTE BAND 25, 1.4MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	26365	1882.5	24	23.36	0	1.159	0.456	0.528	--
		Back Side	26365	1882.5	24	23.36	0	1.159	0.306	0.355	--
		Right Edge	26365	1882.5	24	23.36	0	1.159	1.018	1.180	10
		Bottom Edge	26365	1882.5	24	23.36	0	1.159	0.364	0.422	--
		Right Edge	26047	1850.7	24	23.34	0	1.164	0.995	1.158	--
		Right Edge	26683	1914.3	23	22.62	0	1.091	0.918	1.002	--
50%RB	Body-worn (5mm Separation)	Front Side	26365	1882.5	24	23.36	1	1.159	0.427	0.495	--
		Back Side	26365	1882.5	24	23.36	1	1.159	0.274	0.318	--
		Right Edge	26365	1882.5	24	23.36	1	1.159	0.986	1.143	--
		Bottom Edge	26365	1882.5	24	23.36	1	1.159	0.351	0.407	--
		Right Edge	26047	1850.7	24	23.34	1	1.164	0.964	1.122	--
		Right Edge	26683	1914.3	23	22.62	1	1.091	0.907	0.990	--

Table 21: SAR Values of LTE BAND 25, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	26365	1882.5	23.5	23.09	0	1.099	0.417	0.458	--
		Back Side	26365	1882.5	23.5	23.09	0	1.099	0.266	0.292	--
		Right Edge	26365	1882.5	23.5	23.09	0	1.099	0.958	1.053	--
		Bottom Edge	26365	1882.5	23.5	23.09	0	1.099	0.335	0.368	--
		Right Edge	26140	1860	23.5	23	0	1.122	0.917	1.029	--
		Right Edge	26590	1905.0	23.5	23.07	0	1.104	0.933	1.030	--
50%RB	Body-worn (5mm Separation)	Front Side	26365	1882.5	23.5	23.09	1	1.099	0.386	0.424	--
		Back Side	26365	1882.5	23.5	23.09	1	1.099	0.241	0.265	--
		Right Edge	26365	1882.5	23.5	23.09	1	1.099	0.929	1.021	--
		Bottom Edge	26365	1882.5	23.5	23.09	1	1.099	0.312	0.343	--
		Right Edge	26140	1860	23.5	23	1	1.122	0.895	1.004	--
		Right Edge	26590	1905.0	23.5	23.07	1	1.104	0.902	0.996	--

Table 22: SAR Values of LTE BAND 26(Part 90), 1.4MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	26697	814.7	24	23.5	0	1.122	0.358	0.402	11
		Back Side	26697	814.7	24	23.5	0	1.122	0.128	0.144	--
		Right Edge	26697	814.7	24	23.5	0	1.122	0.090	0.101	--
		Bottom Edge	26697	814.7	24	23.5	0	1.122	0.200	0.224	--
50%RB	Body-worn (5mm Separation)	Front Side	26697	814.7	24	23.5	1	1.122	0.332	0.373	--
		Back Side	26697	814.7	24	23.5	1	1.122	0.111	0.125	--
		Right Edge	26697	814.7	24	23.5	1	1.122	0.076	0.085	--
		Bottom Edge	26697	814.7	24	23.5	1	1.122	0.185	0.208	--

Table 23: SAR Values of LTE BAND 26(Part 90), 10MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	26740	819.0	23.5	23.06	0	1.107	0.314	0.347	--
		Back Side	26740	819.0	23.5	23.06	0	1.107	0.097	0.107	--
		Right Edge	26740	819.0	23.5	23.06	0	1.107	0.065	0.072	--
		Bottom Edge	26740	819.0	23.5	23.06	0	1.107	0.168	0.186	--
50%RB	Body-worn (5mm Separation)	Front Side	26740	819.0	23.5	23.06	1	1.107	0.302	0.334	--
		Back Side	26740	819.0	23.5	23.06	1	1.107	0.078	0.086	--
		Right Edge	26740	819.0	23.5	23.06	1	1.107	0.046	0.051	--
		Bottom Edge	26740	819.0	23.5	23.06	1	1.107	0.159	0.176	--

Table 24: SAR Values of LTE BAND 26(Part 22), 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	27015	846.5	24	23.63	0	1.089	0.342	0.372	12
		Back Side	27015	846.5	24	23.63	0	1.089	0.145	0.158	--
		Right Edge	27015	846.5	24	23.63	0	1.089	0.101	0.110	--
		Bottom Edge	27015	846.5	24	23.63	0	1.089	0.228	0.248	--
50%RB	Body-worn (5mm Separation)	Front Side	27015	846.5	24	23.63	1	1.089	0.323	0.352	--
		Back Side	27015	846.5	24	23.63	1	1.089	0.118	0.128	--
		Right Edge	27015	846.5	24	23.63	1	1.089	0.093	0.101	--
		Bottom Edge	27015	846.5	24	23.63	1	1.089	0.214	0.233	--

Table 25: SAR Values of LTE BAND 26(Part 22), 15MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	26915	836.5	23.5	23.36	0	1.033	0.315	0.325	--
		Back Side	26915	836.5	23.5	23.36	0	1.033	0.103	0.106	--
		Right Edge	26915	836.5	23.5	23.36	0	1.033	0.088	0.091	--
		Bottom Edge	26915	836.5	23.5	23.36	0	1.033	0.206	0.213	--
50%RB	Body-worn (5mm Separation)	Front Side	26915	836.5	23.5	23.36	1	1.033	0.293	0.303	--
		Back Side	26915	836.5	23.5	23.36	1	1.033	0.086	0.089	--
		Right Edge	26915	836.5	23.5	23.36	1	1.033	0.079	0.082	--
		Bottom Edge	26915	836.5	23.5	23.36	1	1.033	0.194	0.200	--

Table 26: SAR Values of LTE BAND 41, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	41140	2645.0	23.5	23.11	0	1.094	0.467	0.511	--
		Back Side	41140	2645.0	23.5	23.11	0	1.094	0.144	0.158	--
		Right Edge	41140	2645.0	23.5	23.11	0	1.094	0.803	0.878	13
		Bottom Edge	41140	2645.0	23.5	23.11	0	1.094	0.080	0.088	--
		Right Edge	40340	2565.0	22.5	22.16	0	1.081	0.711	0.769	--
		Right Edge	40740	2605.0	23	22.46	0	1.132	0.735	0.832	--
50%RB	Body-worn (5mm Separation)	Front Side	41140	2645.0	23.5	23.11	1	1.094	0.452	0.494	--
		Back Side	41140	2645.0	23.5	23.11	1	1.094	0.126	0.138	--
		Right Edge	41140	2645.0	23.5	23.11	1	1.094	0.781	0.854	--
		Bottom Edge	41140	2645.0	23.5	23.11	1	1.094	0.067	0.073	--
		Right Edge	40340	2565.0	22.5	22.16	1	1.081	0.704	0.761	--
		Right Edge	40740	2605.0	23	22.46	1	1.132	0.729	0.826	--

Table 27: SAR Values of LTE BAND 66, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	132471	1759.9	23.5	23.17	0	1.079	0.423	0.456	--
		Back Side	132471	1759.9	23.5	23.17	0	1.079	0.542	0.585	--
		Right Edge	132471	1759.9	23.5	23.17	0	1.079	0.717	0.774	14
		Bottom Edge	132471	1759.9	23.5	23.17	0	1.079	0.556	0.600	--
50%RB	Body-worn (5mm Separation)	Front Side	132471	1759.9	23.5	23.17	1	1.079	0.404	0.436	--
		Back Side	132471	1759.9	23.5	23.17	1	1.079	0.525	0.566	--
		Right Edge	132471	1759.9	23.5	23.17	1	1.079	0.688	0.742	--
		Bottom Edge	132471	1759.9	23.5	23.17	1	1.079	0.526	0.568	--

Table 28: SAR Values of LTE BAND 71, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB	Body-worn (5mm Separation)	Front Side	133372	688	24	23.95	0	1.012	0.237	0.240	15
		Back Side	133372	688	24	23.95	0	1.012	0.086	0.087	--
		Right Edge	133372	688	24	23.95	0	1.012	0.153	0.155	--
		Bottom Edge	133372	688	24	23.95	0	1.012	0.086	0.087	--
50%RB	Body-worn (5mm Separation)	Front Side	133372	688	24	23.95	1	1.012	0.215	0.217	--
		Back Side	133372	688	24	23.95	1	1.012	0.072	0.073	--
		Right Edge	133372	688	24	23.95	1	1.012	0.128	0.129	--
		Bottom Edge	133372	688	24	23.95	1	1.012	0.076	0.077	--

Table 31: SAR Values of 2.4G Wi-Fi

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power (dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Body-worn (5mm Separation)	Front Side	6	2437	802.11g	21	20	1.259	0.075	0.094	--
	Back Side	6	2437	802.11g	21	20	1.259	0.037	0.047	--
	Right Edge	6	2437	802.11g	21	20	1.259	0.051	0.064	--
	Bottom Edge	6	2437	802.11g	21	20	1.259	0.094	0.118	16

Note:

1. According to KDB 648474-D04 Handset SAR v01r03 section 1.5,the diagonal dimension of this device is > 16.0 cm,but the hotspot mode 1-g reported SAR is 1.180 W/kg <1.2 W/kg ,so the 10-g extremity SAR is required.
2. 5G WiFi power please refer to the test report WTX25X10277821W.

Measurement variability consideration

According to KDB 865664 D01v01r04 section 2.8.1, repeated measurements are required following the procedures as below:

Repeated measurement is not required when the original highest measured SAR is $< 0.80 \text{ W/kg}$; steps 2) through 4) do not apply.

When the original highest measured SAR is $\geq 0.80 \text{ W/kg}$, repeat that measurement once.

Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45 \text{ W/kg}$ (~ 10% from the 1-g SAR limit).

Perform a third repeated measurement only if the original, first or second repeated measurement is $\geq 1.5 \text{ W/kg}$ and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Repeated SAR

Body SAR Test								
Band	Mode	Test Position Body	Frequency	SAR1g (W/kg)	Repeated SAR		Ratio	
			MHz		1	2	1	2
WCDMA BAND II	RMC 12.2kbps	Right Edge	1880	1.033	1.018	/	1.015	/
WCDMA BAND II	RMC 12.2kbps	Right Edge	1852.4	1.023	1.011	/	1.012	/
WCDMA BAND II	RMC 12.2kbps	Right Edge	1907.6	1.001	0.996	/	1.005	/
LTE BAND 2	QPSK 1RB 1.4MHz	Right Edge	1850.7	0.917	0.909	/	1.009	/
LTE BAND 2	QPSK 1RB 1.4MHz	Right Edge	1880	0.829	0.823	/	1.007	/
LTE BAND 2	QPSK 1RB 1.4MHz	Right Edge	1909.3	0.864	0.858	/	1.007	/
LTE BAND 2	QPSK 50%RB 1.4MHz	Right Edge	1850.7	0.886	0.868	/	1.021	/
LTE BAND 2	QPSK 50%RB 1.4MHz	Right Edge	1880	0.806	0.795	/	1.014	/
LTE BAND 2	QPSK 50%RB 1.4MHz	Right Edge	1909.3	0.835	0.831	/	1.005	/
LTE BAND 2	QPSK 1RB 20MHz	Right Edge	1900	0.856	0.847	/	1.011	/
LTE BAND 2	QPSK 1RB 20MHz	Right Edge	1860	0.843	0.836	/	1.008	/
LTE BAND 2	QPSK 1RB 20MHz	Right Edge	1880	0.829	0.824	/	1.006	/

LTE BAND 2	QPSK 50%RB 20MHz	Right Edge	1900	0.832	0.819	/	1.016	/
LTE BAND 2	QPSK 50%RB 20MHz	Right Edge	1860	0.818	0.812	/	1.007	/
LTE BAND 2	QPSK 50%RB 20MHz	Right Edge	1880	0.803	0.797	/	1.008	/
LTE BAND 7	QPSK 1RB 5MHz	Front Side	2567.5	0.826	0.818	/	1.010	/
LTE BAND 7	QPSK 1RB 5MHz	Right Edge	2567.5	1.099	1.093	/	1.005	/
LTE BAND 7	QPSK 1RB 5MHz	Right Edge	2502.5	0.950	0.945	/	1.005	/
LTE BAND 7	QPSK 1RB 5MHz	Right Edge	2535	0.986	0.982	/	1.004	/
LTE BAND 7	QPSK 50%RB 5MHz	Right Edge	2567.5	1.055	1.049	/	1.006	/
LTE BAND 7	QPSK 50%RB 5MHz	Right Edge	2502.5	0.937	0.933	/	1.004	/
LTE BAND 7	QPSK 50%RB 5MHz	Right Edge	2535	0.962	0.956	/	1.006	/
LTE BAND 7	QPSK 1RB 20MHz	Right Edge	2560	0.933	0.922	/	1.012	/
LTE BAND 7	QPSK 1RB 20MHz	Right Edge	2510	0.886	0.881	/	1.006	/
LTE BAND 7	QPSK 1RB 20MHz	Right Edge	2535	0.903	0.896	/	1.008	/
LTE BAND 7	QPSK 50%RB 20MHz	Right Edge	2560	0.897	0.893	/	1.004	/
LTE BAND 7	QPSK 50%RB 20MHz	Right Edge	2510	0.836	0.825	/	1.013	/
LTE BAND 7	QPSK 50%RB 20MHz	Right Edge	2535	0.858	0.855	/	1.004	/
LTE BAND 25	QPSK 1RB 1.4MHz	Right Edge	1882.5	1.018	1.011	/	1.007	/

LTE BAND 25	QPSK 1RB 1.4MHz	Right Edge	1850.7	0.995	0.988	/	1.007	/
LTE BAND 25	QPSK 1RB 1.4MHz	Right Edge	1914.3	0.918	0.914	/	1.004	/
LTE BAND 25	QPSK 50%RB 1.4MHz	Right Edge	1882.5	0.986	0.984	/	1.002	/
LTE BAND 25	QPSK 50%RB 1.4MHz	Right Edge	1850.7	0.964	0.953	/	1.012	/
LTE BAND 25	QPSK 50%RB 1.4MHz	Right Edge	1914.3	0.907	0.902	/	1.006	/
LTE BAND 25	QPSK 1RB 20MHz	Right Edge	1882.5	0.958	0.947	/	1.012	/
LTE BAND 25	QPSK 1RB 20MHz	Right Edge	1860	0.917	0.913	/	1.004	/
LTE BAND 25	QPSK 1RB 20MHz	Right Edge	1905.0	0.933	0.926	/	1.008	/
LTE BAND 25	QPSK 50%RB 20MHz	Right Edge	1882.5	0.929	0.922	/	1.008	/
LTE BAND 25	QPSK 50%RB 20MHz	Right Edge	1860	0.895	0.886	/	1.010	/
LTE BAND 25	QPSK 50%RB 20MHz	Right Edge	1905.0	0.902	0.892	/	1.011	/
LTE BAND 41	QPSK 1RB 20MHz	Right Edge	2645.0	0.803	0.801	/	1.002	/

Simultaneous Transmission SAR Analysis.**List of Mode for Simultaneous Multi-band Transmission:**

No.	Configurations	Body-worn SAR
1	WCDMA (Data) + WLAN 2.4GHz(Data)	Yes
2	LTE (Data) + WLAN 2.4GHz(Data)	Yes
1	WCDMA (Data) + WLAN 5GHz(Data)	Yes
2	LTE (Data) + WLAN 5GHz(Data)	Yes

Remark:

1. WCDMA/LTE share the same antenna, and cannot transmit simultaneously.
2. The maximum SAR summation is calculated based on the same configuration and test position

WWAN and 2.4G Wi-Fi

Position	WWAN (maximum)		2.4G Wi-Fi (5mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front Side	WCDMA	0.683	0.094	0.777
Back Side		0.832	0.047	0.879
Right Edge		1.141	0.064	1.205
Bottom Edge		0.824	0.118	0.942
Front Side	LTE	0.839	0.094	0.933
Back Side		0.585	0.047	0.632
Right Edge		1.180	0.064	1.244
Bottom Edge		0.600	0.118	0.718

WWAN and 5G Wi-Fi

Position	WWAN (maximum)		5G Wi-Fi (5mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front Side	WCDMA	0.683	0.327	1.010
Back Side		0.832	0.203	1.035
Right Edge		1.141	0.154	1.295
Bottom Edge		0.824	0.332	1.156
Front Side	LTE	0.839	0.327	1.166
Back Side		0.585	0.203	0.788
Right Edge		1.180	0.154	1.334
Bottom Edge		0.600	0.332	0.932


15 SAR Measurement Reference

15.1 References


1. FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
2. IEEE Std. C95.1:2019, “IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz”, 2019
3. IEC/IEEE 62209-1528:2020, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
4. FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 23th, 2015
5. FCC KDB 941225 D01 v03r01, “3G SAR Measurement Procedures”, Oct 23th, 2015
6. FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 16th, 2015
7. FCC KDB 941225 D06 v02r01, “SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities”, Oct 23th, 2015
8. FCC KDB865664 D01 v01r04, “SAR Measurement Requirements 100MHz to 6GHz”, Aug 7th, 2015
9. FCC KDB865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations ”, Oct 23th, 2015
10. FCC KDB648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 23th, 2015
11. FCC KDB 248227 D01 v02r02, SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters, Oct 23th, 2015.

15.2Maximum SAR measurement Plots

Plot 1: WCDMA BAND II, Middle channel (Body-worn, Right Edge)
Product Description: ONE
Test Date: 2025-10-28




Plot 2:LTE BAND 2, Low channel (Body-worn, Right Edge)
Product Description:ONE
Test Date: 2025-10-28




Plot 3: LTE BAND 4, Low channel (Body-worn, Right Edge)


Product Description: ONE
Test Date: 2025-10-28




Plot 4: LTE BAND 5, High channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-23




Plot 5: LTE BAND 7, High channel (Body-worn, Right Edge)
Product Description: ONE
Test Date: 2025-10-20




Plot 6: LTE BAND 12, Middle channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-24




Plot 7: LTE BAND 13, High channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-24




Plot 8: LTE BAND 14, Low channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-24




Plot 9: LTE BAND 17, Middle channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-24




Plot 10: LTE BAND 25, Middle channel (Body-worn, Right Edge)
Product Description: ONE
Test Date: 2025-10-28




Plot 11: LTE BAND 26(Part 90), Low channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-23



Plot 12: LTE BAND 26(Part 22), High channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-23




Plot 13: LTE BAND 41, High channel (Body-worn, Right Edge)
Product Description: ONE
Test Date: 2025-10-20




Plot 14: LTE BAND 66, High channel (Body-worn, Right Edge)

Product Description: ONE


Test Date: 2025-10-28



Plot 15: LTE BAND 71, High channel (Body-worn, Front Side)
Product Description: ONE
Test Date: 2025-10-24



Plot 16: 2.4G Wi-Fi, Middle channel (Body-worn, Bottom Edge)
Product Description: ONE
Test Date: 2025-10-18



16 Calibration Reports-Probe and Dipole



COMOSAR E-Field Probe Calibration Report

Ref : ACR.304.21.27.BES.B

WALTEK TESTING GROUP CO., LTD
NO,77, HOUJIE SECTION, GUANTAI ROAD, HOUJIE TOWN
DONGGUAN GUANGDONG 518105, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: 2523-EPGO-417

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 07/25/2025



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.304.21.27.BES.B

	<i>Name</i>	<i>Function</i>	<i>Date</i>	<i>Signature</i>
<i>Prepared by :</i>	Cyrille ONNEE	Measurement Responsible	7/25/2025	
<i>Checked & approved by:</i>	Jérôme Luc	Technical Manager	7/25/2025	
<i>Authorized by:</i>	Yann Toutain	Laboratory Director	7/25/2025	

Yann
Toutain ID

Signature
numérique de
Yann Toutain ID
Date : 2025.07.25
09:52:33 +01'00'

	<i>Customer Name</i>
<i>Distribution :</i>	WALTEK TESTING GROUP CO., LTD

<i>Issue</i>	<i>Name</i>	<i>Date</i>	<i>Modifications</i>
A	Cyrille ONNEE	7/25/2025	Initial release

Page: 2/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR Probe vL

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



TABLE OF CONTENTS

1 Device Under Test 4

2 Product Description 4

2.1 General Information 4

3 Measurement Method 4

3.1 Sensitivity 4

3.2 Linearity 5

3.3 Isotropy 5

3.4 Boundary Effect 5

4 Measurement Uncertainty 6

5 Calibration Results..... 6

5.1 Calibration in air 6

5.2 Calibration in liquid 7

6 Verification Results 8

7 List of Equipment 9



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.304.21.27.BES.B

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	2523-EPGO-417
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-7.5GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.232 MΩ Dipole 2: R2=0.224 MΩ Dipole 3: R3=0.209 MΩ

2 PRODUCT DESCRIPTION**2.1 GENERAL INFORMATION**

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

Probe Length	330 mm
Length of Individual Dipoles	24.5 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.55 mm
Distance between dipoles / probe extremity	12.7 mm

3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their effect. All calibrations / measurements performed meet the fore-mentioned standards.

3.1 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards for frequency range 600-7500MHz and using the calorimeter cell method (transfer method) as outlined in the standards for frequency 150-450 MHz.

Page: 4/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR Probe vL

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.304.21.27.BES.B

3.2 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

3.3 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.4 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta})}{\delta/2} \text{ for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14 \text{ mm}$ at 3 GHz;
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).

Page: 5/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR Probe vL

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with a SAR probe calibration using the waveguide or calorimetric cell technique depending on the frequency.


The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-11% for the frequency range 150-450MHz.
The estimated expanded uncertainty (k=2) in calibration for SAR (W/kg) is +/-14% for the frequency range 600-7500MHz.

5 CALIBRATION RESULTS

Ambient condition	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 CALIBRATION IN AIR

The following curve represents the measurement in waveguide of the voltage picked up by the probe toward the E-field generated inside the waveguide.



From this curve, the sensitivity in air is calculated using the below formula.

$$E^2 = \sum_{i=1}^3 \frac{V_i (1 + V_i / DCP_i)}{Norm_i}$$

where
Vi=voltage readings on the 3 channels of the probe
DCPi=diode compression point given below for the 3 channels of the probe
Normi=dipole sensitivity given below for the 3 channels of the probe