

4K Wireless Display Dongle

RX & TX User Manual

Rev 1.0



The product specifications and information mentioned in this manual are for reference only. Changes may be made without prior notice.

About the 4K Wireless Display Dongle

Transmitter (H-1)

The transmitter allows you to easily mirror or extend your screen display by connecting to a computer or a mobile phone that supports DisplayPort signals. It is ideal for watching videos or sharing your screen.



Receiver (4KR-1)

Connect to a 4K TV or monitor to display the content transmitted from the transmitter.



Product Specifications

Transmitter:

Antenna: 1T1R (built-in)
Wireless Network: 5GHz/2.4GHz
Port: HDMI

Receiver:

Antenna: 1T1R (built-in)
Wireless Network: 5GHz/2.4GHz
Port: HDMI

How to Mirror


1. Installing the Receiver

Insert the receiver into the HDMI port of your TV or monitor.
Connect the Type-C power supply port to a 5V/1A power source.

2. Connecting the Transmitter for Screen Mirroring

Connect the transmitter to your computer or a mobile phone that supports DisplayPort. Plug the transmitter into the HDMI port of your device. Wait a few seconds until the blinking light on the transmitter stops, and screen mirroring will begin automatically.

1. The transmitter (HDMI connector), you need to connect the Type-C power port to an independent power source (5V1A) to provide power.



3. Stopping/Restarting Mirroring

Press the Screen Mirroring/Pairing Button on the transmitter



Note:

The transmitter supports Windows/macOS computers as well as iPhones or Android phones that support DisplayPort output.

How to Pair the Receiver

*Note: The product has been pre-paired before leaving the factory.
If you need to re-pair, please follow the steps below.*

1. Activating the Receiver's Pairing Mode

- (1) Connect the receiver's power supply port to a power source using the Type-C connector.
- (2) Connect the receiver's HDMI end to your TV or monitor.
- (3) Press and hold the wireless display receiver button for about 3 seconds. Release the button when the screen displays the message: **"Release the button to pair with Transmitter."**



2. Press the Screen Mirroring/Pairing Button on the Transmitter

Connect the transmitter to your computer or mobile phone. ensure that the Type-C power supply is connected. When the screen displays "Ready to pair", press and hold the Screen Mirroring/Pairing Button on the transmitter for more than 5 seconds. Release the button after the indicator light turns off, and wait for the light to flash rapidly and then stay on, indicating that pairing is complete.



Note: The reset button on the wireless display receiver has two setting modes depending on the duration of the press:

- (1) Press and hold for 3 seconds: Activates the receiver's pairing mode to pair with the transmitter.
- (2) Single click: Allows screen rotation when mirroring from an iPhone or Android phone.

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Note: The Grantee is not responsible for any changes or modifications not expressly approved by the party responsible for compliance. such modifications could void the user's authority to operate the equipment.

The device has been evaluated to meet general RF exposure requirement.

This equipment complies with FCC's RF radiation exposure limits set forth for an uncontrolled environment. This device and its antenna(s) must not be co-located or conjunction with any other antenna or transmitter.

The device can be used in portable exposure conditions without restriction.

4K 无线投屏器 RX & TX 使用手册

Rev 1.0



本手册所提到的产品规格和资讯仅供参考，如有变更，恕不另行通知。

关于4K无线投屏器

发射器 (H-1)

连接电脑或支持DisplayPort 信号的手机，
轻松镜像或扩展屏幕的显示内容，适合用于观看视频或分享屏幕。



接收器 (4KR-1)

连接于 4K TV 或显示器来显示您从发射器传递的内容



产品参数

发射器: 天线: 1T1R (已装载) 无线网络: 5Ghz/2.4Ghz 端口: HDMI

接收器: 天线: 1T1R (已装载) 无线网络: 5Ghz/2.4Ghz 端口: HDMI

如何镜像

1 安装接收器

将接收器插到电视或显示器 HDMI 接口,并将 TypeC 供电接口接上 (5V1A) 的电源进行供电。

2 发射器接上电脑或支持DisplayPort的手机即可开始投屏

将发射器接上电脑或手机的 HDMI 接口, 等待数秒至发射器上的闪灯停止, 即开始自动投屏。

1.使用H-1 型号的发射器(HDMI) 接头, 需以TYPE-C接头连接至独立电源 (5V1A) 供电。



3 停止/重新镜像

点击发射器上投屏/配对按钮, 可停止或重新镜像。



注意:

发射器支持Windows/macOS 电脑,
以及支持DisplayPort输出的iPhone 或Android 手机。

如何配对接收器

注意:产品在出厂时已完成配对,如需重新配对请按以下步骤操作。

1 开启接收器配对模式

- (1) 将接收器的供电接口以 Type-C 接头连接至电源。
- (2) 将接收器 HDMI 端接上电视或显示器。
- (3) 长按无线显示接收器按钮3秒左右,待屏幕显示文字
“Release the button to pair with Transmitter” 时松开按钮。



2 按下发射器上的投影 / 配对按钮

将发射器接上电脑或手机,请确保已连接 Type-C 供电并在屏幕显示“Ready to pair”时长按发射器上的投屏配对按钮 5 秒以上待指示灯熄灭后松开按钮等待指示灯快速闪烁至常亮即完成配对。



注意:无线显示接收器上的重置按钮,根据按压时间不同,有两种设定模式。

- (1) 长按 3秒:开启接收器的配对模式与发射器进行配对。
- (2) 单击:可在iPhone 或 Android手机投屏时屏幕旋转。