



Antenna Specification

SPECIFICATIONS	
Frequency (MHz)	2400-2480
Peak Gain (dBi)	2.50
Average Gain (dBi)	>-4
VSWR	<3.2
Impedance (Ω)	50 Ω
Antenna Type	Plannar Inverted F Antenna on board
Polarization	Linear

Testing environment: Zhongke Guoji darkroom testing system




Physical antenna and dimensions:



Passive S-parameters of antenna:


Standing Wave Ratio (VSWR), Return Loss, and Smith Chart




Antenna efficiency and gain:

Frequency (MHz)	Gain (dBi)	Efficiency (%)	AverageGain (dBi)	Efficiency (dB)
2400	1.43	59.329%	-2.717	-2.267
2410	0.93	51.861%	-3.416	-2.852
2420	0.83	52.112%	-3.166	-2.831
2430	0.88	49.299%	-3.258	-3.072
2440	1.19	50.672%	-3.144	-2.952
2450	1.69	53.067%	-2.735	-2.752
2460	2.19	59.423%	-2.276	-2.260
2470	2.12	56.680%	-2.438	-2.466
2480	2.50	61.727%	-2.112	-2.095
Average	1.53	54.908%	-2.806	-2.616
Peak	2.50	61.727%	-2.112	-2.095


2440MHz 2D-Theta Pattern




2440MHz 2D-Phi Pattern



2440MHz 3D-Horizontal Pattern



2440MHz 3D-Vertical Pattern



2440MHz 3D-Total Pattern

