



RF EXPOSURE EVALUATION

FCC ID: 2BWJ2-JL-106

Product	:	Cassette Player
Model Name	:	JL-106, F-01
Brand	:	Burtowic, Famehouse, OR
Report No.	:	PTC26051305601E-FC02
Prepared for		
SHENZHEN CHAOBOTAO ELECTRONICS TECHNOLOGY CO.,LTD		
B17I,Binfen Century,#99 Chenguang Road,Longcheng Street,Longgang District,Shenzhen,China		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



Report No.: PTC26051305601E-FC02

General Information

Product Name	:	Cassette Player
Model Name	:	JL-106, F-01
Test Model	:	JL-106
Specification	:	Bluetooth BDR+EDR
Operation Frequency	:	2400-2480MHz for BT
Number of Channel	:	79 channels for BDR+EDR
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK For DSS
Antenna installation	:	PCB Antenna
Antenna Gain	:	-0.58 dBi
Power supply	:	Input: DC 5V, 0.12A
Hardware Version	:	N/A
Software Version	:	N/A
Test sample No.	:	PTC26051305601E-1/2, PTC26051305601E-2/2.
Test Date	:	May 22, 2026 to June 19, 2026
Model difference	:	all models are different in color only. the function is same.



Report No.: PTC26051305601E-FC02

TEST FACILITY

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong,
China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq 50\text{mm}$ are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g SAR extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is $\leq 50\text{mm}$ and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is $< 5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality for TCB approval.



Report No.: PTC26051305601E-FC02

RF Output power

Mode	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2441MHz	1.11	1.11 ± 1	1.526	5	0.508	3	Bluetooth

Conclusion:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.