



FCC TEST REPORT

FCC ID: 2BWLW-YH629-BC

Report Number.....: ZKT-260826L1729E

Date of Test..... June. 11, 2026 - Aug. 11, 2026

Date of issue.....: Aug. 11, 2026

Test Result: PASS

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: YAOKUNBIAO TECHNOLOGY EQUIPMENT (JIANGSU) CO., LTD

Address: Industrial Park, No. 318, Kexing Road, Yuelai Town, Haimen District, Nantong City, Jiangsu Province

Manufacturer's name: YAOKUNBIAO TECHNOLOGY EQUIPMENT (JIANGSU) CO., LTD

Address: Industrial Park, No. 318, Kexing Road, Yuelai Town, Haimen District, Nantong City, Jiangsu Province

Test specification:

Standard.....: FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024

Test procedure.....: /

Non-standard test method: N/A

Test Report Form No.....: TRF-EL-120_V0

Test Report Form(s) Originator.....: ZKT Testing

Master TRF: Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....: Four-button Bluetooth controller

Trademark: /

Model/Type reference.....: YH629-BC

Ratings.....: Input: DC 5-12V



Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Jim Liu

Reviewer (name + signature).....: Jackson Fang

Approved (name + signature).....: Lake Xie





Table of Contents

Page

1.VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.2 RADIATED EMISSION LIMITS	17
4.2.1 TEST PROCEDURE	18
4.2.2 DEVIATION FROM TEST STANDARD	18
4.2.3 TEST SETUP	18
4.2.4 EUT OPERATING CONDITIONS	19
5.RADIATED BAND EMISSION MEASUREMENT	24
5.1 TEST REQUIREMENT:	24
5.2 TEST PROCEDURE	24
5.3 DEVIATION FROM TEST STANDARD	24
5.4 TEST SETUP	25
5.5 EUT OPERATING CONDITIONS	25
5.6 TEST RESULT	26
6.POWER SPECTRAL DENSITY TEST	27
6.1 APPLIED PROCEDURES / LIMIT	27
6.2 TEST PROCEDURE	27
6.3 DEVIATION FROM STANDARD	27
6.4 TEST SETUP	27
6.5 EUT OPERATION CONDITIONS	27



Table of Contents	Page
6.6 TEST RESULT	28
7. CHANNEL BANDWIDTH	32
7.1 APPLIED PROCEDURES / LIMIT	32
7.2 TEST PROCEDURE	32
7.3 DEVIATION FROM STANDARD	32
7.4 TEST SETUP	32
7.5 EUT OPERATION CONDITIONS	32
7.6 TEST RESULT	33
8. PEAK OUTPUT POWER TEST	37
8.1 APPLIED PROCEDURES / LIMIT	37
8.2 TEST PROCEDURE	37
8.3 DEVIATION FROM STANDARD	37
8.4 TEST SETUP	37
8.5 EUT OPERATION CONDITIONS	37
8.6 TEST RESULT	38
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	39
9.1 APPLICABLE STANDARD	39
9.2 TEST PROCEDURE	39
9.3 DEVIATION FROM STANDARD	39
9.4 TEST SETUP	39
9.5 EUT OPERATION CONDITIONS	39
11. ANTENNA REQUIREMENT	52
12. TEST SETUP PHOTO	53
13. EUT CONSTRUCTIONAL DETAILS	53



1.VERSION

Report No.	Version	Description	Approved
ZKT-260826L1729E	Rev.01	Initial issue of report	Aug. 11, 2026



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	-6dB OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Conducted Spurious and Band edge Emission	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)“N/A” denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 927491
Designation Number: CN1431
IC Registered No.: 27033
CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9KHz-30MHz)	4.5dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	5.0dB
5	Conducted disturbance	3.2dB
6	RF Band Edge	1.68dB
7	RF power conducted	1.86dB
8	RF conducted Spurious Emission	2.2dB
9	RF Occupied Bandwidth	1.8MHz
10	RF Power Spectral Density	1.75dB
11	humidity uncertainty	5.3%
12	Temperature uncertainty	0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Four-button Bluetooth controller
Model No.:	YH629-BC
Model Different.:	/
Serial No.:	/
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	Input: DC 5V-12V
Sample ID	260826L1729E-1



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Charging mode	Keep the EUT in Charging mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT_tool_v1.1.4
Power level setup	default



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission




Radiated Emission(30MHz-1GHz)



Radiated Emission(above 1GHz)



RF Conducted test



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo (Beijing) Co., Ltd	ThinkPad E480	/	AE
E-2	USB serial port board	/	/	/	AE
E-3	POWER ADAPTER	Guangdong Sangu Technology Co., Ltd	SG-0502000AU	/	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Emissions & Radiation Spurious Emissions Test

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 20, 2025	Sep. 19, 2026
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 20, 2025	Sep. 19, 2026
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	100969	4.32	Oct. 24, 2025	Oct. 23, 2026
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	00877	N/A	Sep. 20, 2025	Sep. 19, 2026
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Sep. 20, 2025	Sep. 19, 2026
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Sep. 30, 2025	Sep. 29, 2026
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Sep. 20, 2025	Sep. 19, 2026
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	60747	N/A	Sep. 19, 2025	Sep. 18, 2026
9	Amplifier (1GHz-26.5GHz)	HuiPu	8449B	3008A00315	N/A	Sep. 19, 2025	Sep. 18, 2026
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Oct. 24, 2025	Oct. 23, 2026
11	Test Cable	N/A	R-01	N/A	N/A	May. 25, 2026	May. 24, 2027
12	Test Cable	N/A	R-02	N/A	N/A	May. 25, 2026	May. 24, 2027
13	Test Cable	N/A	R-03	N/A	N/A	May. 25, 2026	May. 24, 2027
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



Conducted emissions Test

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Sep. 23, 2025	Sep. 22, 2026
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Sep. 19, 2025	Sep. 18, 2026
3	Test Cable	N/A	C-01	N/A	N/A	May. 25, 2026	May. 24, 2027
4	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Oct. 24, 2025	Oct. 23, 2026
5	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

RF Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	N9020A	MY55370835	A.17.05	Sep. 20, 2025	Sep. 19, 2026
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Sep. 20, 2025	Sep. 19, 2026
3	Test Cable	N/A	RF-01	N/A	N/A	May. 25, 2026	May. 24, 2027
4	Test Cable	N/A	RF-02	N/A	N/A	May. 25, 2026	May. 24, 2027
5	Test Cable	N/A	RF-03	N/A	N/A	May. 25, 2026	May. 24, 2027
6	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Sep. 19, 2025	Sep. 18, 2026
7	Signal Generator	Agilent	N5182A	N/A	A.01.87	Sep. 20, 2025	Sep. 19, 2026
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344/M-17 52	N/A	Sep. 25, 2025	Sep. 24, 2026
9	SHIELD BOX	TESCOM	TC-5970C	5970C01555 3	N/A	Dec. 18, 2024	Dec. 17, 2025
10	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Sep. 28, 2025	Sep. 27, 2026
11	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Sep. 19, 2025	Sep. 18, 2026
12	D.C. Power Supply	LongWei	TPR-6405 D	N/A	N/A	\	\
13	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



- Note:** 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to Charging during test. This operating condition was tested and used to collect the included data.



4.1.6 Test Result

Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	0.1524	49.95	9.89	59.84	65.87	-6.03	QP
2	0.1524	29.59	9.89	39.48	55.87	-16.39	AVG
3	0.1893	47.61	9.91	57.52	64.07	-6.55	QP
4	0.1893	27.64	9.91	37.55	54.07	-16.52	AVG
5	0.2231	44.48	9.92	54.40	62.70	-8.30	QP
6	0.2231	26.50	9.92	36.42	52.70	-16.28	AVG
7	0.2847	40.75	9.94	50.69	60.68	-9.99	QP
8	0.2847	21.76	9.94	31.70	50.68	-18.98	AVG
9	0.4237	38.10	9.99	48.09	57.38	-9.29	QP
10	0.4237	25.21	9.99	35.20	47.38	-12.18	AVG
11	0.5324	37.07	10.02	47.09	56.00	-8.91	QP
12	0.5324	23.69	10.02	33.71	46.00	-12.29	AVG

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case GFSK 2480MHz mode.



Temperature :	26℃	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	51.13	9.89	61.02	66.00	-4.98	QP
2	0.1500	34.84	9.89	44.73	56.00	-11.27	AVG
3	0.1680	49.91	9.90	59.81	65.06	-5.25	QP
4	0.1680	29.24	9.90	39.14	55.06	-15.92	AVG
5 *	0.1860	49.47	9.90	59.37	64.21	-4.84	QP
6	0.1860	33.61	9.90	43.51	54.21	-10.70	AVG
7	0.2243	47.15	9.92	57.07	62.66	-5.59	QP
8	0.2243	30.75	9.92	40.67	52.66	-11.99	AVG
9	0.2670	44.27	9.94	54.21	61.21	-7.00	QP
10	0.2670	27.91	9.94	37.85	51.21	-13.36	AVG
11	0.3390	42.23	9.96	52.19	59.23	-7.04	QP
12	0.3390	24.75	9.96	34.71	49.23	-14.52	AVG

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor
- 4.The test data shows only the worst case GFSK 2480MHz mode.



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



4.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	193.7726	38.67	-10.88	27.79	43.50	-15.71	QP
2	203.5226	35.98	-10.21	25.77	43.50	-17.73	QP
3	227.6905	36.71	-9.42	27.29	46.00	-18.71	QP
4	245.9510	35.81	-8.82	26.99	46.00	-19.01	QP
5	300.3672	38.73	-7.93	30.80	46.00	-15.20	QP
6 *	360.4476	37.77	-6.52	31.25	46.00	-14.75	QP



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.8541	37.77	-9.07	28.70	40.00	-11.30	QP
2 *	55.2207	39.04	-8.85	30.19	40.00	-9.81	QP
3	61.9950	38.10	-10.10	28.00	40.00	-12.00	QP
4	71.0802	41.40	-13.07	28.33	40.00	-11.67	QP
5	75.4462	43.07	-13.85	29.22	40.00	-10.78	QP
6	87.7246	40.49	-12.71	27.78	40.00	-12.22	QP

Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case GFSK 2480MHz mode.
8. '*'Means the test Degree and Height are not recorded by the test software and only show the worstcase in the test report.



1GHz~25GHz

GFSK-1M									
Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	59.39	30.55	5.77	24.66	59.27	74.00	-14.73	Pk
V	4804.00	48.06	30.55	5.77	24.66	47.94	54.00	-6.06	AV
V	7206.00	62.43	30.33	6.32	24.55	62.97	74.00	-11.03	Pk
V	7206.00	47.65	30.33	6.32	24.55	48.19	54.00	-5.81	AV
H	4804.00	60.23	30.55	5.77	24.66	60.11	74.00	-13.89	Pk
H	4804.00	46.35	30.55	5.77	24.66	46.23	54.00	-7.77	AV
H	7206.00	60.29	30.33	6.32	24.55	60.83	74.00	-13.17	Pk
H	7206.00	47.30	30.33	6.32	24.55	47.84	54.00	-6.16	AV
Middle Channel:2440MHz									
V	4880.00	60.15	30.55	5.77	24.66	60.03	74.00	-13.97	Pk
V	4880.00	47.20	30.55	5.77	24.66	47.08	54.00	-6.92	AV
V	7320.00	61.60	30.33	6.32	24.55	62.14	74.00	-11.86	Pk
V	7320.00	47.16	30.33	6.32	24.55	47.70	54.00	-6.30	AV
H	4880.00	61.10	30.55	5.77	24.66	60.98	74.00	-13.02	Pk
H	4880.00	46.33	30.55	5.77	24.66	46.21	54.00	-7.79	AV
H	7320.00	61.08	30.33	6.32	24.55	61.62	74.00	-12.38	Pk
H	7320.00	48.20	30.33	6.32	24.55	48.74	54.00	-5.26	AV
High Channel:2480MHz									
V	4960.00	60.62	30.55	5.77	24.66	60.50	74.00	-13.50	Pk
V	4960.00	48.88	30.55	5.77	24.66	48.76	54.00	-5.24	AV
V	7440.00	62.40	30.33	6.32	24.55	62.94	74.00	-11.06	Pk
V	7440.00	47.39	30.33	6.32	24.55	47.93	54.00	-6.07	AV
H	4960.00	62.10	30.55	5.77	24.66	61.98	74.00	-12.02	Pk
H	4960.00	46.86	30.55	5.77	24.66	46.74	54.00	-7.26	AV
H	7440.00	60.38	30.33	6.32	24.55	60.92	74.00	-13.08	Pk
H	7440.00	46.45	30.33	6.32	24.55	46.99	54.00	-7.01	AV



GFSK-2M									
Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	60.00	30.85	7.45	24.69	61.29	74.00	-12.71	Pk
V	4804.00	47.62	30.85	7.45	24.69	48.91	54.00	-5.09	AV
V	7206.00	61.05	31.02	8.99	25.57	64.59	74.00	-9.41	Pk
V	7206.00	46.34	31.02	8.99	25.57	49.88	54.00	-4.12	AV
H	4804.00	59.78	30.85	7.45	24.69	61.07	74.00	-12.93	Pk
H	4804.00	47.45	30.85	7.45	24.69	48.74	54.00	-5.26	AV
H	7206.00	59.20	31.02	8.99	25.57	62.74	74.00	-11.26	Pk
H	7206.00	47.46	31.02	8.99	25.57	51.00	54.00	-3.00	AV
Middle Channel:2440MHz									
V	4880.00	61.60	30.85	7.45	24.69	62.89	74.00	-11.11	Pk
V	4880.00	48.33	30.85	7.45	24.69	49.62	54.00	-4.38	AV
V	7320.00	59.39	31.02	8.99	25.57	62.93	74.00	-11.07	Pk
V	7320.00	48.62	31.02	8.99	25.57	52.16	54.00	-1.84	AV
H	4880.00	61.89	30.85	7.45	24.69	63.18	74.00	-10.82	Pk
H	4880.00	47.76	30.85	7.45	24.69	49.05	54.00	-4.95	AV
H	7320.00	59.70	31.02	8.99	25.57	63.24	74.00	-10.76	Pk
H	7320.00	47.33	31.02	8.99	25.57	50.87	54.00	-3.13	AV
High Channel:2480MHz									
V	4960.00	62.62	30.85	7.45	24.69	63.91	74.00	-10.09	Pk
V	4960.00	47.19	30.85	7.45	24.69	48.48	54.00	-5.52	AV
V	7440.00	62.67	31.02	8.99	25.57	66.21	74.00	-7.79	Pk
V	7440.00	46.78	31.02	8.99	25.57	50.32	54.00	-3.68	AV
H	4960.00	62.75	30.85	7.45	24.69	64.04	74.00	-9.96	Pk
H	4960.00	48.33	30.85	7.45	24.69	49.62	54.00	-4.38	AV
H	7440.00	59.81	31.02	8.99	25.57	63.35	74.00	-10.65	Pk
H	7440.00	48.38	31.02	8.99	25.57	51.92	54.00	-2.08	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5.RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


5.3 DEVIATION FROM TEST STANDARD

No deviation



5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 5.4 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Margi n (dB)	Detec tor Type	Result
GFSK 1M	Low Channel: 2402MHz										
	H	2390.00	61.57	30.22	4.85	23.98	60.18	74.00	-13.82	PK	PASS
	H	2390.00	46.71	30.22	4.85	23.98	45.32	54.00	-8.68	AV	PASS
	H	2400.00	61.59	30.22	4.85	23.98	60.20	74.00	-13.8	PK	PASS
	H	2400.00	47.67	30.22	4.85	23.98	46.28	54.00	-7.72	AV	PASS
	V	2390.00	59.96	30.22	4.85	23.98	58.57	74.00	-15.43	PK	PASS
	V	2390.00	48.23	30.22	4.85	23.98	46.84	54.00	-7.16	AV	PASS
	V	2400.00	62.41	30.22	4.85	23.98	61.02	74.00	-12.98	PK	PASS
	V	2400.00	46.90	30.22	4.85	23.98	45.51	54.00	-8.49	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	57.72	30.55	5.77	24.66	57.6	74.00	-16.4	AV	PASS
	H	2483.50	47.52	30.22	4.85	23.98	46.13	54.00	-7.87	PK	PASS
	H	2500.00	60.65	30.22	4.85	23.98	59.26	74.00	-14.74	AV	PASS
	H	2500.00	46.79	30.22	4.85	23.98	45.40	54.00	-8.6	PK	PASS
	V	2483.50	60.92	30.22	4.85	23.98	59.53	74.00	-14.47	AV	PASS
	V	2483.50	46.83	30.22	4.85	23.98	45.44	54.00	-8.56	PK	PASS
	V	2500.00	60.38	30.22	4.85	23.98	58.99	74.00	-15.01	AV	PASS
	V	2500.00	48.75	30.22	4.85	23.98	47.36	54.00	-6.64	AV	PASS
GFSK 2M	Low Channel: 2402MHz										
	H	2390.00	62.65	30.22	4.85	23.98	61.26	74.00	-12.74	PK	PASS
	H	2390.00	47.89	30.22	4.85	23.98	46.50	54.00	-7.5	AV	PASS
	H	2400.00	62.99	30.22	4.85	23.98	61.60	74.00	-12.4	PK	PASS
	H	2400.00	46.72	30.22	4.85	23.98	45.33	54.00	-8.67	AV	PASS
	V	2390.00	61.00	30.22	4.85	23.98	59.61	74.00	-14.39	PK	PASS
	V	2390.00	47.83	30.22	4.85	23.98	46.44	54.00	-7.56	AV	PASS
	V	2400.00	60.71	30.22	4.85	23.98	59.32	74.00	-14.68	PK	PASS
	V	2400.00	46.84	30.22	4.85	23.98	45.45	54.00	-8.55	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	60.64	30.22	4.85	23.98	59.25	74.00	-14.75	PK	PASS
	H	2483.50	46.96	30.22	4.85	23.98	45.57	54.00	-8.43	AV	PASS
	H	2500.00	63.00	30.22	4.85	23.98	61.61	74.00	-12.39	PK	PASS
	H	2500.00	48.19	30.22	4.85	23.98	46.80	54.00	-7.2	AV	PASS
	V	2483.50	61.71	30.22	4.85	23.98	60.32	74.00	-13.68	PK	PASS
	V	2483.50	47.68	30.22	4.85	23.98	46.29	54.00	-7.71	AV	PASS
	V	2500.00	60.38	30.22	4.85	23.98	58.99	74.00	-15.01	PK	PASS
	V	2500.00	48.38	30.22	4.85	23.98	46.99	54.00	-7.01	AV	PASS
Remark:											
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit											



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span ≥ 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 6.4 Unless otherwise a special operating condition is specified in the follows during the testing.







6.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Test Mode :	GFSK	Test Voltage :	AC 120V/60Hz

Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402	-22.06	8	PASS
2440	-22.73	8	PASS
2480	-24.27	8	PASS
2402	-24.68	8	PASS
2440	-25.25	8	PASS
2480	-26.77	8	PASS









7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width with SA automatic 6dB bandwidth down setting, Record the final DTS bandwidth result.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 7.4 Unless otherwise a special operating condition is specified in the follows during the testing.







7.6 TEST RESULT


Temperature:	24.2℃	Relative Humidity:	54.2%
Test Mode:	GFSK	Test Voltage:	AC 120V/60Hz

Test channel	-6dB bandwidth (MHz)	Limit(KHz)	Result
Lowest	0.504	>500	Pass
Middle	0.509		
Highest	0.512		
Lowest	0.869		
Middle	0.889		
Highest	0.864		











8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



8.6 TEST RESULT

Temperature:	24.2℃	Relative Humidity:	54.2%
Test Mode:	GFSK	Test Voltage:	AC 120V/60Hz

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	-8.74	30.00	Pass
Middle	-9.46		
Highest	-11.02		
Lowest	-8.7		
Middle	-9.36		
Highest	-10.99		



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

9.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP




9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.






9.6 TEST RESULTS
Band Edge

Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	Ant1	-36.5	-20	Pass
BLE 1M	2480	Ant1	-45.78	-20	Pass
BLE 2M	2402	Ant1	-36.68	-20	Pass
BLE 2M	2480	Ant1	-46.3	-20	Pass












Conducted RF Spurious Emission

Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	Ant1	-37.48	-20	Pass
BLE 1M	2440	Ant1	-38.15	-20	Pass
BLE 1M	2480	Ant1	-34.56	-20	Pass
BLE 2M	2402	Ant1	-41.38	-20	Pass
BLE 2M	2440	Ant1	-38.96	-20	Pass
BLE 2M	2480	Ant1	-34.66	-20	Pass






Test Graphs


Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission











Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission






Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission






Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission





11.ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details.	



12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****