



FCC Test Report

Report No.: DCHU-ESH-P26050206B-2

FCC ID: 2BWM2-ASTY01

Product: Ultimate Game Show

Model: 10027

Received Date: May.12, 2026

Test Date: May.12 to Jun.22, 2026

Issued Date: Jul.05, 2026

Applicant: ARTISKILLS INC.

Address: 3935 Rabold Circle South, Bethlehem, PA 18020, United States

Manufacturer: ARTISKILLS INC.

Address: 3935 Rabold Circle South, Bethlehem, PA 18020, United States

Issued By: BUREAU VERITAS LCIE CHINA COMPANY LIMITED

Lab Address: No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Release Control Record.....	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Test Instruments	7
2.2 Measurement Uncertainty	8
2.3 Modification Record	8
3 General Information.....	9
3.1 General Description of EUT.....	9
3.2 Description of Test Modes	10
3.2.1 Test Mode Applicability:	11
3.2.2 Test Condition:	12
3.3 Description of Support Units.....	16
3.4 General Description of Applied Standards	16
4 Test Procedure and Results.....	17
4.1 AC Power Conducted Emission.....	17
4.1.1 Limits	17
4.1.2 Test Procedures	17
4.1.3 Deviation from Test Standard.....	17
4.1.4 Test Setup.....	18
4.1.5 EUT Operating Conditions.....	18
4.1.6 Test Results	19
4.2 Minimum 6dB Bandwidth.....	20
4.2.1 Limit.....	20
4.2.2 Test Setup.....	20
4.2.3 Test Procedures	20
4.2.4 Deviation of Test Standard.....	20
4.2.5 Test Results	21
4.3 Conducted Output Power	24
4.3.1 Limit.....	24
4.3.2 Test Setup.....	24
4.3.3 Test Procedures	24
4.3.4 Deviation of Test Standard.....	24



4.3.5	Test Results	25
4.4	Power Spectral Density	28
4.4.1	Limit	28
4.4.2	Test Setup	28
4.4.3	Test Procedures	28
4.4.4	Deviation of Test Standard	28
4.4.5	Test Results	29
4.5	Conducted Band Edges Measurement	32
4.5.1	Limit	32
4.5.2	Test Setup	32
4.5.3	Test Procedures	32
4.5.4	Deviation of Test Standard	32
4.5.5	Test Results	33
4.6	Conducted Spurious Emissions	36
4.6.1	Limit	36
4.6.2	Test Setup	36
4.6.3	Test Procedures	36
4.6.4	Deviation of Test Standard	36
4.6.5	Test Results	37
4.7	Emissions in restricted frequency bands	44
4.7.1	Test Limit	44
4.7.2	Test Procedure Reference	45
4.7.3	Test Procedures	45
4.7.4	Test Setup	46
4.7.5	Test Results	47
4.8	Radiated Emission Measurement	51
4.8.1	Limits	51
4.8.2	Test Procedures	51
4.8.3	Deviation from Test Standard	52
4.8.4	Test Setup	53
4.8.5	EUT Operating Conditions	54
4.8.6	Test Results	54
5	Pictures of Test Arrangements	69



Release Control Record

Issue No.	Description	Date Issued
DCHU-ESH-P26050206B-2	Original release	Jul.05, 2026

1 Certificate of Conformity

Product: Ultimate Game Show

Brand: 

Model: 10027

Applicant: ARTISKILLS INC.

Test Date: May.12 to Jun.22, 2026

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024

The above equipment has been tested by **BUREAU VERITAS LCIE CHINA COMPANY LIMITED**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Jul.05, 2026

Yuan ZHANG
Project Engineer

Approved by :  , **Date:** Jul.05, 2026

Sean YU
RF Supervisor

2 Summary of Test Results

The EUT has been tested according to the following specifications:

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.203	Antenna Requirement	PASS	No antenna connector is used.
15.207	AC Power Conducted Emission	N/A	EUT is powered by battery.
15.247(a)(2)	Minimum 6dB Bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.247(d)	Conducted Band Edges Measurement	PASS	Meet the requirement of limit.
15.247(d)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
15.247(d)	Emissions in restricted frequency bands	PASS	Meet the requirement of limit.
15.205 / 15.209 / 15.247(d)	Radiated Emissions Measurement	PASS	Meet the requirement of limit.

Note: None.

2.1 Test Facility

Laboratory Name: BUREAU VERITAS LCIE CHINA COMPANY LIMITED

Laboratory Address: No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China

Test Location: No.829,Xin Zhuan Road,Song Jiang District,Shanghai,China

A2LA Lab Code: 2343.01

FCC-Recognized Accredited Testing Lab: CN1213

ISED Recognized Lab: 6392A

FCC Accredited Test Site Number: 176467

CAB identifier: CN0070

2.2 Test Instruments

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Loop Antenna	ETS-LINDGREN	6502	E1A1039	Jul.29,26
Hybrid Antenna(25MHz-1.5GHz)	Schwarzbeck	VULB9168	E1A1001	Mar.29,28
Horn Antenna(1GHz -18GHz)	Schwarzbeck	BBHA9120D	E1A1017	Jul.30,26
Double Ridge Horn Antenna(18G-40G)	COM-POWER	AH-840	E1A1040	Jul.30,26
Pre-Amplifier(100kHz-1.3GHz)	Agilent	8447D	E1A2001	Feb.01,27
Pre-Amplifier(0.5GHz-18GHz)	EMCI	EMC184045SE	E1A2009	Jun.11,27
Pre-Amplifier(18GHz-40GHz)	Tonscend	TAP18040048	E1A2014	Jun.07,27
EMI test receiver	R&S	ESR26	E1R1009	Aug.11,26
Spectrum Analyzer	Keysight	N9030B	E1S1003	May.20,27
Spectrum Analyzer	Keysight	N9020A	E1S1004	Feb.09,27
EMI test receiver	R&S	ESR3	E1R1008	Aug.11,26
LISN	R&S	ENV216	E1L1013	Aug.17, 26
RF cable(30MHz~26.5GHz)	--	--	--	Mar.30,27
RF cable(9kHz~1GHz)	--	--	E3T4104/05/ 06/07	Mar.18,27
RF cable(1GHz~40GHz)	--	--	E3T4108/09/ 10/11	Mar.30,27
Humidity&Temp Tester	ESPEC	SE TH-Z-042U	C1TH002	Jun.02,27
RF Control Unit	Toscend	JS0806-2	E1C5003	Jun.23,27
Test Software	Toscend	JS32-CE	N/A	N/A
Test Software	Toscend	JS32-RE	N/A	N/A
Test Software	Toscend	JS1120	N/A	N/A
Test Software	Toscend	JS1120-3	N/A	N/A

Note: The RF Control Unit (Path: CH to SPA) includes one splitter, one attenuator, two RF switches, and several cables. All correction factors have already been compensated for by the instrument.

2.3 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.56 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.08 dB
Radiated Emissions above 1 GHz	Above 1GHz	5.12 dB

2.4 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Ultimate Game Show
Brand	
Test Model	10027
Power Rating	The EUT is powered by battery.
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 5.0
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Gain	-0.68dBi

Note:

1. For more details, please refer to the User's manual of the EUT.

3.2 Description of Test Modes

40 channels are provided for Bluetooth LE.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
0	2402 MHz	20	2442 MHz
1	2404 MHz	21	2444 MHz
2	2406 MHz	22	2446 MHz
3	2408 MHz	23	2448 MHz
4	2410 MHz	24	2450 MHz
5	2412 MHz	25	2452 MHz
6	2414 MHz	26	2454 MHz
7	2416 MHz	27	2456 MHz
8	2418 MHz	28	2458 MHz
9	2420 MHz	29	2460 MHz
10	2422 MHz	30	2462 MHz
11	2424 MHz	31	2464 MHz
12	2426 MHz	32	2466 MHz
13	2428 MHz	33	2468 MHz
14	2430 MHz	34	2470 MHz
15	2432 MHz	35	2472 MHz
16	2434 MHz	36	2474 MHz
17	2436 MHz	37	2476 MHz
18	2438 MHz	38	2478 MHz
19	2440 MHz	39	2480 MHz

3.2.1 Test Mode Applicability:

EUT Configure Mode	Applicable to				Description
	RE ≥ 1G	RE < 1G	PLC	APCM	
-	√	√	--	√	-

Where **RE ≥ 1G**: Radiated Emission above 1GHz **RE < 1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.
- ☒ For different antenna gain, select high gain antenna for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Power Line Conducted Emission Test:

- ☐ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☐ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0	GFSK

Antenna Port Conducted Measurement

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
-	BLE	0 to 39	0, 19, 39	GFSK

3.2.2 Test Condition:


Applicable to	Normal Environmental Conditions	Normal Input Power
RE $\geq$ 1G	23deg. C, 58%RH	Powered by USB
RE < 1G	23deg. C, 58%RH	Powered by BATTERY
PLC	23deg. C, 58%RH	--
APCM	25deg. C, 60%RH	Powered by USB

3.3 Duty Cycle of Test Signal

Test Mode	Antenna	Channel [MHz]	Duty Cycle [%]	10log(1/x) Factor[dB]
BLE 1M	Ant1	2402	85.60	0.68
		2440	85.60	0.68
		2480	85.60	0.68
BLE 2M	Ant1	2402	43.20	3.65
		2440	43.20	3.65
		2480	43.20	3.65

Note: Duty Cycle Factor=10* Log[1/Duty Cycle(%)*100], Duty Cycle= $T_{on}/T_{period} * 100\%$

BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480





3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

NO.	PRODUCT	BRAND/ Manufacturer	MODEL NO.
1	Laptop	Lenovo	L470

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standard:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024

All relaxed test items have been performed and recorded as per the above standard.

4 Test Procedure and Results

4.1 AC Power Conducted Emission

4.1.1 Limits

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.1.2 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.1.3 Deviation from Test Standard

No deviation.

4.1.4 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 EUT Operating Conditions

Same as 4.1.6.

4.1.6 Test Results


Not applicable. The EUT is powered by battery.

4.2 Minimum 6dB Bandwidth

4.2.1 Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.2.2 Test Setup



4.2.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 8.2).

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 · RBW, peak detector with maximum hold) is implemented by the instrumentation function.


4.2.4 Deviation of Test Standard

No deviation.


4.2.5 Test Results

Test Mode	Antenna	Channel [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.704	2401.672	2402.376	≥ 0.5	PASS
		2440	0.740	2439.652	2440.392	≥ 0.5	PASS
		2480	0.660	2479.688	2480.348	≥ 0.5	PASS
BLE_2M	Ant1	2402	1.224	2401.364	2402.588	≥ 0.5	PASS
		2440	1.096	2439.460	2440.556	≥ 0.5	PASS
		2480	1.064	2479.480	2480.544	≥ 0.5	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480




4.3 Conducted Output Power

4.3.1 Limit

For systems using digital modulation in the 2400 – 2483.5 MHz bands: 1 Watt (30 dBm)

4.3.2 Test Setup



4.3.3 Test Procedures

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” for compliance to FCC 47CFR 15.247 requirements (clause 9.2.2.4).

- a) Set RBW $\geq$ DTS bandwidth
- b) Set VBW $\geq$ 3 RBW.
- c) Set Span $\geq$ 3 RBW.
- d) Sweep time = No faster than coupled (auto) time.
- e) Detector = peak
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.


4.3.4 Deviation of Test Standard

No deviation.


4.3.5 Test Results

Test Mode	Antenna	Channel [MHz]	Power [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
BLE_1M	Ant1	2402	2.72	≤30	-0.68	2.04	≤36	PASS
		2440	2.26	≤30	-0.68	1.58	≤36	PASS
		2480	2.67	≤30	-0.68	1.99	≤36	PASS
BLE_2M	Ant1	2402	2.93	≤30	-0.68	2.25	≤36	PASS
		2440	2.43	≤30	-0.68	1.75	≤36	PASS
		2480	2.90	≤30	-0.68	2.22	≤36	PASS


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480




4.4 Power Spectral Density

4.4.1 Limit

The Maximum of Power Spectral Density Measurement is 8 dBm.

4.4.2 Test Setup



4.4.3 Test Procedures

The power output per FCC § 15.247(e) was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 10.5) for compliance to FCC 47CFR 15.247 requirements.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = No faster than coupled (auto) time.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


4.4.4 Deviation of Test Standard

No deviation.


4.4.5 Test Results

Test Mode	Antenna	Channel [MHz]	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-13.64	<=8	PASS
		2440	-14.23	<=8	PASS
		2480	-13.96	<=8	PASS
BLE_2M	Ant1	2402	-15.45	<=8	PASS
		2440	-16.30	<=8	PASS
		2480	-15.27	<=8	PASS


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480



BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480

