

TEST REPORT

RF Exposure Evaluation

Report No.	CISRR26062325102
Project No.	CISR260623251
FCC ID	2BWSV-PD511
Applicant	Shenzhen PaiPai Industries Co., Ltd.
Address	Room 309, Building A15, Taizhong Industrial Zone, No. 6 Xinfeng Road, Ailian Community, Longcheng Street, Longgang District, Shenzhen
Manufacturer	Shenzhen PaiPai Industries Co., Ltd.
Address	Room 309, Building A15, Taizhong Industrial Zone, No. 6 Xinfeng Road, Ailian Community, Longcheng Street, Longgang District, Shenzhen
Product Name	Dog training collar
Trade mark	-
Model/Type reference	PD 511
Listed Model(s)	PD509,PD509-TIO,PD509V,PD510, PD510-TIO,PD510V,PD511 PD511-Tio,PD511V,PD512,PD512-TIO,PD512V, PD513,PD513-TIO PD513V,PD517,PD517-TIO,PD517V,PD518,PD518-TIO,PD518V
Standard	47 CFR Part 2.1093
Date of sample receipt	June 24, 2026
Test date	June 26, 2026 to July 13, 2026
Issue date	July 14, 2026
Test result	Complied

Lucas Huang

Reviewed by: Lucas Huang



Approved by: Hans Hu

The test results relate only to the tested samples.

The test report should not be reproduced except in full without the written approval of Shenzhen Bangce Testing Technology Co., Ltd.

1. APPLICABLE STANDARD

[47 CFR Part2.1093](#): Radio frequency radiation exposure evaluation: portable devices

[ANSI C95.1–2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01](#) General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[47 CFR Part1.1307](#): Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.

2. REPORT VERSION

Version No.	Issue date	Description
00	July 14, 2026	Original

3. RADIO SPECIFICATION DESCRIPTION

433M

Supported type:

☒ ASK

Note: Please refer to RF report for detailed technical specifications

4. SIMULTANEOUS TRANSMISSION ANALYSIS

These devices use a single transmitter module and antenna for both 433M.

5. TEST RESULT

5.1. Standalone transmission

Limit:

KDB447498 D01 v06, Clause 4.3.1 a)

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation³¹
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

Result:

Passed

Test Data

Radio type	Frequency (MHz)	Maximum EIRP ^{#1} (dBm)	Maximum tune-up ^{#2} EIRP (dBm)	Minimum distance (mm)	Evaluated value	Limit	Result
433M	433.92	-29.38	-27	5.00	0.0003	3.00	PASS

Note

#1: This value comes from the RF test report

Max. Field Strength: 65.88dBuV/m @3m

Maximum EIRP=Max. Field Strength-104.8+20logD

=65.88-104.8+20log3

=-29.38dBm

#2: This value is declared by the applicant.

5.2. Simultaneous transmission

Limit:

KDB447498 D01 v06, Clause 4.3.2, 47 CFR Part1.1307

In the case of xed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the speci ed minimum distance including existing evaluated transmitters.

P_j = the available maximum time-averaged power or the ERP, whichever is greater, for xed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (P) according to paragraph (b)(3)(i)(B) of this section for xed, mobile, or portable RF source i.

ERP_j = the ERP of fixed, mobile, or portable RF source j.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or speci c absorption rate (SAR) limit for each xed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

Result:

Not Applicable

-----End of Report-----