







Plot 7-230 PSD CDD Diversity Antenna WF7b (20MHz BW 802.11be(RU) RU26 Index8 - Ch.149)




Plot 7-233 PSD CDD Diversity Antenna WF2a (20MHz BW 802.11be(RU) RU26 Index0 - Ch.149)




Plot 7-231 PSD CDD Diversity Antenna WF7b (40MHz BW 802.11be(RU) RU26 Index0 - Ch.151)



Plot 7-234 PSD CDD Diversity Antenna WF2a (40MHz BW 802.11be(RU) RU26 Index0 - Ch.151)



Plot 7-232 PSD CDD Diversity Antenna WF7b (80MHz BW 802.11be(RU) RU26 Index0 - Ch.155)




Plot 7-235 PSD CDD Diversity Antenna WF2a (80MHz BW 802.11be(RU) RU26 Index0 - Ch.155)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 141 of 384




Plot 7-236 PSD CDD Diversity Antenna WF7b (20MHz BW 802.11be(RU) RU52+26 Index71 - Ch.165)



Plot 7-238 PSD CDD Diversity Antenna WF2a (20MHz BW 802.11be(RU) RU52+26 Index71 - Ch.165)




Plot 7-237 PSD CDD Diversity Antenna WF7b (80MHz BW 802.11be(RU) RU484+242 Index91 - Ch.155)




Plot 7-239 PSD CDD Diversity Antenna WF2a (80MHz BW 802.11be(RU) RU484+242 Index91 - Ch.155)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG			Page 142 of 384




Plot 7-240 PSD CDD Primary Antenna WF7b (20MHz BW 802.11be(RU) RU242 Index61 - Ch.149)




Plot 7-243 PSD CDD Primary Antenna WF2a (20MHz BW 802.11be(RU) RU242 Index61 - Ch.149)




Plot 7-241 PSD CDD Primary Antenna WF7b (40MHz BW 802.11be(RU) RU484 Index65 - Ch.151)



Plot 7-244 PSD CDD Primary Antenna WF2a (40MHz BW 802.11be(RU) RU484 Index65 - Ch.151)



Plot 7-242 PSD CDD Primary Antenna WF7b (80MHz BW 802.11be(RU) RU996 Index67 - Ch.155)



Plot 7-245 PSD CDD Primary Antenna WF2a (80MHz BW 802.11be(RU) RU996 Index67 - Ch.155)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 143 of 384

	Frequency [MHz]	Channel	802.11 MODE	Mode	RU Size	RU Index	Data Rate	Antenna WF2a Power Density [dBm/MHz]	Antenna WF7b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directoinal Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
Band 1	5180	36	be (20MHz)	SDM	26	0	MCSS	2.19	3.39	5.84	0.45	6.29	10.0	-3.71
	5200	40	be (20MHz)	SDM	26	8	MCSS	2.48	3.30	5.92	0.45	6.37	10.0	-3.63
	5240	48	be (20MHz)	SDM	26	0	MCSS	2.42	3.26	5.87	0.45	6.32	10.0	-3.68
	5190	38	be (40MHz)	SDM	26	17	MCSS	2.59	3.44	6.05	0.45	6.50	10.0	-3.50
	5230	46	be (40MHz)	SDM	26	8	MCSS	2.53	3.27	5.93	0.45	6.38	10.0	-3.62
	5210	42	be (80MHz)	SDM	26	36	MCSS	2.15	3.44	5.85	0.45	6.30	10.0	-3.70
Band 1/2A	5250	50	be (160MHz)	SDM	52	52	MCSS	0.96	1.83	4.43	0.45	4.88	10.0	-5.12

Table 7-191. ISED Band 1 e.i.r.p. Power Spectral Density Measurements SDM Diversity (RU26)


	Frequency [MHz]	Channel No.	802.11 MODE	Mode	RU Size	RU Index	Data Rate	Antenna WF2a Power Density [dBm/MHz]	Antenna WF7b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directoinal Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
Band 1	5180	36	be (20MHz)	SDM	52+26	72	MCSS	3.07	2.71	5.90	0.45	6.35	10	-3.65
	5200	40	be (20MHz)	SDM	52+26	71	MCSS	3.70	3.53	6.63	0.45	7.08	10	-2.92
	5240	48	be (20MHz)	SDM	52+26	71	MCSS	3.81	3.79	6.81	0.45	7.26	10	-2.74
	5180	36	be (20MHz)	SDM	106+26	82	MCSS	2.92	2.61	5.77	0.45	6.23	10	-3.77
	5200	40	be (20MHz)	SDM	106+26	82	MCSS	3.44	3.56	6.51	0.45	6.96	10	-3.04
	5240	48	be (20MHz)	SDM	106+26	82	MCSS	3.56	3.80	6.69	0.45	7.14	10	-2.86
	5210	42	be (80MHz)	CDD	484+242	90	MCSS	-4.85	-4.87	-1.85	3.46	1.61	10	-8.39
	5250	50 (L)	be (160MHz)	CDD	996+484	95	MCSS	-8.14	-9.80	-5.88	3.46	-2.42	10	-12.42
Band 1/2A	5250	50 (L)	be (160MHz)	CDD	996+484+242	96	MCSS	-8.66	-10.83	-6.60	3.46	-3.14	10	-13.14
	5250	50 (U)	be (160MHz)	CDD	996+484	94	MCSS	-8.05	-9.74	-5.80	3.46	-2.34	10	-12.34
	5250	50 (U)	be (160MHz)	CDD	996+484+242	96	MCSS	-8.65	-10.43	-6.44	3.46	-2.98	10	-12.98

Table 7-192. ISED Band 1 e.i.r.p. Power Spectral Density Measurements CDD/SDM Diversity (MRU)


	Frequency [MHz]	Channel	802.11 MODE	Mode	RU Size	RU Index	Data Rate	Antenna WF2a Power Density [dBm/MHz]	Antenna WF7b Power Density [dBm/MHz]	Summed Power Density [dBm/MHz]	Directoinal Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
Band 1	5180	36	be (20MHz)	SDM	242	61	MCSS	1.01	2.48	4.82	0.45	5.27	10.0	-4.73
	5200	40	be (20MHz)	SDM	242	61	MCSS	2.18	3.43	5.86	0.45	6.31	10.0	-3.69
	5240	48	be (20MHz)	SDM	242	61	MCSS	2.55	4.00	6.35	0.45	6.80	10.0	-3.20
	5190	38	be (40MHz)	CDD	484	65	MCSS	-3.15	-2.27	0.33	3.46	3.79	10.0	-6.21
	5230	46	be (40MHz)	SDM	484	65	MCSS	1.15	2.23	4.73	0.45	5.19	10.0	-4.81
	5210	42	be (80MHz)	CDD	996	67	MCSS	-7.20	-6.57	-3.86	3.46	-0.40	10.0	-10.40
	5250	50	be (160MHz)	CDD	996	68	MCSS	-10.60	-9.92	-7.23	3.46	-3.77	10.0	-13.77

Table 7-193. ISED Band 1 e.i.r.p. Power Spectral Density Measurements CDD/SDM Diversity (Fully-loaded RU)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 144 of 384	




Plot 7-246 PSD CDD Diversity Antenna WF7b (20MHz BW 802.11be(RU) RU26 Index8 - Ch.40)




Plot 7-250 PSD CDD Diversity Antenna WF2a (20MHz BW 802.11be(RU) RU26 Index8 - Ch.40)




Plot 7-247 PSD CDD Diversity Antenna WF7b (40MHz BW 802.11be(RU) RU26 Index17 - Ch.38)




Plot 7-251 PSD CDD Diversity Antenna WF2a (40MHz BW 802.11be(RU) RU26 Index17 - Ch.38)




Plot 7-248 PSD CDD Diversity Antenna WF7b (80MHz BW 802.11be(RU) RU26 Index36 - Ch.42)



Plot 7-252 PSD CDD Diversity Antenna WF2a (80MHz BW 802.11be(RU) RU26 Index36 - Ch.42)



Plot 7-249 PSD CDD Diversity Antenna WF7b (160MHz BW 802.11be(RU) RU52 Index52 - Ch.50)



Plot 7-253 PSD SDM Diversity Antenna WF2a (160MHz BW 802.11be(RU) RU52 Index52 - Ch.50)


FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 145 of 384




Plot 7-254 PSD CDD Diversity Antenna WF7b (20MHz BW 802.11be(RU) RU52+26 Index71 - Ch.48)




Plot 7-257 PSD CDD Diversity Antenna WF2a (20MHz BW 802.11be(RU) RU52+26 Index71 - Ch.48)




Plot 7-255 PSD CDD Diversity Antenna WF7b (80MHz BW 802.11be(RU) RU484+242 Index91 - Ch.42)



Plot 7-258 PSD CDD Diversity Antenna WF2a (80MHz BW 802.11be(RU) RU484+242 Index91 - Ch.42)




Plot 7-256 PSD CDD Diversity Antenna WF7b (160MHz BW 802.11be(RU) RU996+484 Index94 - Ch.50)



Plot 7-259 PSD CDD Diversity Antenna WF2a (160MHz BW 802.11be(RU) RU996+484 Index94 - Ch.50)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 146 of 384



Plot 7-260 PSD SDM Diversity Antenna WF7b (20MHz BW 802.11be(RU) RU242 Index61 - Ch.48)




Plot 7-264 PSD CDD Diversity Antenna WF2a (20MHz BW 802.11be(RU) RU242 Index61 - Ch.48)




Plot 7-261 PSD CDD Diversity Antenna WF7b (40MHz BW 802.11be(RU) RU484 Index65 - Ch.46)




Plot 7-265 PSD CDD Diversity Antenna WF2a (40MHz BW 802.11be(RU) RU484 Index65 - Ch.46)



Plot 7-262 PSD CDD Diversity Antenna WF7b (80MHz BW 802.11be(RU) RU996 Index67 - Ch.42)



Plot 7-266 PSD CDD Diversity Antenna WF2a (80MHz BW 802.11be(RU) RU996 Index67 - Ch.42)



Plot 7-263 PSD CDD Diversity Antenna WF7b (160MHz BW 802.11be(RU) RU996X2 Index68 - Ch.50)



Plot 7-267 PSD CDD Diversity Antenna WF2a (160MHz BW 802.11be(RU) RU996X2 Index68 - Ch.50)

FCC ID: BCGA3461
IC: 579C-A3461

MEASUREMENT REPORT (CERTIFICATION)

Approved by:
Technical Manager

Test Report S/N:
1C2509100081-14-R3.BCG

Test Dates:
09/15/2025 - 12/31/2025

EUT Type:
Tablet Device

Page 147 of 384

V 10.6 10/27/2023

Note:

Per ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 662911 v02r01 Section E1), the conducted powers at Antenna WF7a and Antenna WF2a were first measured separately during CDD/SDM transmission as shown in the section above. The measured values were then summed in linear power units then converted back to dBm.

Per ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 Section 14.6.3, the directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}] \text{ dBi}$$

Per ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 Section 14.6.3, the uncorrelated directional gain is calculated using the following formula, where G_N is the gain of the nth antenna and N_{ANT} , the total number of antennas used.

$$\text{Directional gain} = 10 \log[(10^{G_1/10} + 10^{G_2/10} + \dots + 10^{G_N/10}) / N_{ANT}] \text{ dBi}$$

Sample CDD/SDM Calculation:

At 5180MHz in 802.11be(RU) (20MHz BW) mode, the power spectral density was measured to be 3.67 dBm for Antenna WF7a and 2.19 dBm for Antenna WF2a.

$$\text{Antenna WF7a} + \text{Antenna WF2a} = \text{CDD/SDM}$$

$$(3.67 \text{ dBm} + 2.19 \text{ dBm}) = (2.328 \text{ mW} + 1.656 \text{ mW}) = 3.984 \text{ mW} = 6.00 \text{ dBm}$$

Sample e.i.r.p. Calculation:

At 5180MHz in 802.11be(RU) (20MHz BW) mode, the average MIMO power spectral density was calculated to be 6.00 dBm with directional gain of 0.88 dBi.

$$\begin{aligned} \text{e.i.r.p. (dBm)} &= \text{Power Density (dBm)} + \text{Ant gain (dBi)} \\ 6.00 \text{ dBm} + 0.88 \text{ dBi} &= 6.88 \text{ dBm} \end{aligned}$$

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 148 of 384

V 10.6 10/27/2023

7.6 Radiated Spurious Emission – Above 1GHz

\$15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. RU26, 52 Tones, RU106, RU242, RU484, RU996 and RU996x2), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-194 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-194. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024 – Subclauses 12.7.7, 12.7.6
KDB 789033 D02 v02r01 – Section G

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 149 of 384

V 10.6 10/27/2023

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 150 of 384

V 10.6 10/27/2023

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-194.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-194. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dB μ V/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. This device operates under these frequencies only under the control of a certified master device and does not support active scanning on these channels. This device does not transmit any beacons or initiate any transmissions in UNII Bands 2A or 2C.
10. For radiated measurements, emissions were investigated for the fully-loaded RU configuration and for all of the partially-loaded RU configurations. Among all of the available partially-loaded RU configurations, only the configuration with the worst case emissions is reported.

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 151 of 384

V 10.6 10/27/2023

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.6.3 to 7.6.22 was calculated using the formula:


$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: BCGA3461 IC: 579C-A3461	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 152 of 384

V 10.6 10/27/2023

7.6.1 CDD Primary Radiated Spurious Emissions

RU26



Plot 7-268. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.36 – RU26)


Mode:	802.11be (20MHz BW)
Data Rate:	MCS0
RU Index:	4
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10360.00	Peak	H	-	-	-72.95	17.05	51.10	68.23	-17.13
* 15540.00	Average	V	-	-	-85.20	24.96	46.76	53.98	-7.22
* 15540.00	Peak	V	-	-	-73.78	24.96	58.19	73.98	-15.79


Table 7-195. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 153 of 384

V 10.6 10/27/2023



Plot 7-269. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.40 – RU26)



Plot 7-270. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.40 — RU26)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5200MHz
Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	V	-	-	-72.57	17.27	0.00	51.70	68.23	-16.53
* 15600.00	Average	V	-	-	-85.20	24.98	0.00	46.78	53.98	-7.20
* 15600.00	Peak	V	-	-	-74.26	24.98	0.00	57.72	73.98	-16.26
* 20800.00	Average	V	-	-	-61.49	-7.75	-9.54	28.22	53.98	-25.76
* 20800.00	Peak	V	-	-	-50.36	-7.75	-9.54	39.35	73.98	-34.62
26000.00	Peak	V	-	-	-49.11	-5.94	-9.54	42.41	68.23	-25.82
* 31200.00	Average	H	-	-	-63.77	-3.75	-9.54	29.94	53.98	-24.04
* 31200.00	Peak	H	-	-	-52.28	-3.75	-9.54	41.43	73.98	-32.55

Table 7-196. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 154 of 384

V 10.6 10/27/2023




Plot 7-271. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.48 – RU26)

Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	H	-	-	-73.23	17.66	51.43	68.23	-16.80
* 15720.00	Average	V	-	-	-85.88	25.61	46.73	53.98	-7.25
* 15720.00	Peak	V	-	-	-74.18	25.61	58.43	73.98	-15.55

Table 7-197. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 155 of 384



Plot 7-272. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.52 – RU26)


Mode: 802.11be (20MHz BW)
 Data Rate: MCS0
 RU Index: 4
 Distance of Measurements: 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	-	-	-68.32	9.34	48.02	68.23	-20.21
* 15780.00	Average	V	-	-	-79.18	13.13	40.95	53.98	-13.03
* 15780.00	Peak	V	-	-	-68.66	13.13	51.48	73.98	-22.50


Table 7-198. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 156 of 384

V 10.6 10/27/2023



Plot 7-273. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.56 – RU26)



Plot 7-274. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.56 — RU26)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10560.00	Peak	V	-	-	-68.85	9.61	0.00	47.76	68.23	-20.47
* 15840.00	Average	V	-	-	-79.23	13.37	0.00	41.13	53.98	-12.85
* 15840.00	Peak	V	-	-	-68.70	13.37	0.00	51.66	73.98	-22.32
* 21120.00	Average	V	-	-	-60.93	-7.64	-9.54	28.89	53.98	-25.09
* 21120.00	Peak	V	-	-	-49.21	-7.64	-9.54	40.61	73.98	-33.37
26400.00	Peak	H	-	-	-50.45	-5.42	-9.54	41.59	68.23	-26.64
* 31680.00	Average	H	-	-	-63.30	-4.09	-9.54	30.07	53.98	-23.91
* 31680.00	Peak	H	-	-	-51.90	-4.09	-9.54	41.47	73.98	-32.51

Table 7-199. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 157 of 384

V 10.6 10/27/2023




Plot 7-275. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.64 – RU26)

Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
*	10640.00	Average	H	-	-	-79.05	9.30	37.25	53.98	-16.73
*	10640.00	Peak	H	-	-	-68.60	9.30	47.70	73.98	-26.28
*	15960.00	Average	V	-	-	-79.50	13.50	41.00	53.98	-12.98
*	15960.00	Peak	V	-	-	-68.78	13.50	51.72	73.98	-22.26

Table 7-200. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 158 of 384



Plot 7-276. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.100 – RU26)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	V	-	-	-79.29	9.77	37.47	53.98	-16.51
* 11000.00	Peak	V	-	-	-68.44	9.77	48.32	73.98	-25.66
16500.00	Peak	V	-	-	-69.29	15.94	53.64	68.23	-14.59


Table 7-201. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 159 of 384

V 10.6 10/27/2023



Plot 7-277. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.116 – RU26)



Plot 7-278. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.116 — RU26)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 4

Distance of Measurements: 3 Meters


Operating Frequency: 5580MHz

Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11160.00	Average	V	-	-	-79.38	9.79	0.00	37.41	53.98	-16.57
* 11160.00	Peak	V	-	-	-68.66	9.79	0.00	48.13	73.98	-25.85
16740.00	Peak	V	-	-	-68.12	15.16	0.00	54.03	68.23	-14.20
* 22320.00	Average	V	-	-	-61.59	-7.64	-9.54	28.22	53.98	-25.76
* 22320.00	Peak	V	-	-	-50.50	-7.64	-9.54	39.32	73.98	-34.66
27900.00	Peak	V	-	-	-52.90	-4.48	-9.54	40.08	68.23	-28.15
33480.00	Peak	V	-	-	-50.38	-4.38	-9.54	42.70	68.23	-25.53

Table 7-202. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 160 of 384



Plot 7-279. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.144 – RU26)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5720MHz
Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	V	-	-	-81.36	13.73	39.37	53.98	-14.61
* 11440.00	Peak	V	-	-	-70.37	13.73	50.36	73.98	-23.62
17160.00	Peak	H	-	-	-71.14	24.19	60.05	68.23	-8.18

Table 7-203. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 161 of 384

V 10.6 10/27/2023



Plot 7-280. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.149 – RU26)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 4
Distance of Measurements: 3 Meters
Operating Frequency: 5745MHz
Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	H	-	-	-84.69	19.09	41.41	53.98	-12.57
* 11490.00	Peak	H	-	-	-73.68	19.09	52.41	73.98	-21.57
17235.00	Peak	V	-	-	-73.85	28.01	61.16	68.23	-7.07


Table 7-204. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 162 of 384

V 10.6 10/27/2023



Plot 7-281. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.157 – RU26)



Plot 7-282. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.157 — RU26)


Mode:	802.11be (20MHz BW)
Data Rate:	MCS0
RU Index:	4
Distance of Measurements:	3 Meters
Operating Frequency:	5785MHz
Channel:	157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
11570.00	Average	H	-	-	-84.46	19.10	0.00	41.64	53.98	-12.34
11570.00	Peak	H	-	-	-73.20	19.10	0.00	52.90	73.98	-21.08
17355.00	Peak	V	-	-	-73.65	27.88	0.00	61.23	68.23	-7.00
23140.00	Peak	V	-	-	-51.07	-7.17	-9.54	39.21	68.23	-29.02
28925.00	Peak	V	-	-	-52.17	-3.95	-9.54	41.34	68.23	-26.89
34710.00	Peak	V	-	-	-51.65	-4.65	-9.54	41.16	68.23	-27.07

Table 7-205. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 163 of 384

V 10.6 10/27/2023



Plot 7-283. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.165 – RU26)

Mode: 802.11be (20MHz BW)
 Data Rate: MCS0
 RU Index: 4
 Distance of Measurements: 3 Meters
 Operating Frequency: 5825MHz
 Channel: 165


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11650.00	Average	V	-	-	-84.50	19.42	41.93	53.98	-12.05
* 11650.00	Peak	V	-	-	-73.08	19.42	53.34	73.98	-20.64
17475.00	Peak	V	-	-	-73.89	28.77	61.88	68.23	-6.35

Table 7-206. Radiated Measurements CDD Primary (RU26)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 164 of 384

V 10.6 10/27/2023

RU242



Plot 7-284. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.36 – RU242)


Mode: 11be (20MHz BW)
Data Rate: MCS0
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 5180MHz
Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10360.00	Peak	H	-	-	-72.70	17.24	51.54	68.23	-16.69
* 15540.00	Average	V	-	-	-85.28	24.96	46.68	53.98	-7.30
* 15540.00	Peak	V	-	-	-73.58	24.96	58.38	73.98	-15.60


Table 7-207. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 165 of 384

V 10.6 10/27/2023



Plot 7-285. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.40 – RU242)



Plot 7-286. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.40 — RU242)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 61

Distance of Measurements: 3 Meters

Operating Frequency: 5200MHz


Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10400.00	Peak	H	-	-	-73.31	16.99	0.00	50.69	68.23	-17.55
* 15600.00	Average	V	-	-	-85.25	24.96	0.00	46.72	53.98	-7.26
* 15600.00	Peak	V	-	-	-73.56	24.96	0.00	58.40	73.98	-15.58
* 20800.00	Average	V	-	-	-62.14	-7.57	-9.54	27.75	53.98	-26.23
* 20800.00	Peak	V	-	-	-49.37	-7.57	-9.54	40.53	73.98	-33.45
26000.00	Peak	V	-	-	-50.66	-5.94	-9.54	40.86	68.23	-27.38
* 31200.00	Average	H	-	-	-63.98	-3.75	-9.54	29.73	53.98	-24.25
* 31200.00	Peak	H	-	-	-51.92	-3.75	-9.54	41.79	73.98	-32.19

Table 7-208. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 166 of 384

V 10.6 10/27/2023



Plot 7-287. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.48 – RU242)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 61

Distance of Measurements: 3 Meters

Operating Frequency: 5240MHz


Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10480.00	Peak	H	-	-	-73.51	17.56	51.05	68.23	-17.18
* 15720.00	Average	H	-	-	-85.62	25.64	47.02	53.98	-6.96
* 15720.00	Peak	H	-	-	-74.59	25.64	58.05	73.98	-15.93

Table 7-209. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device		Page 167 of 384

V 10.6 10/27/2023



Plot 7-288. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.52 – RU242)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 61

Distance of Measurements: 3 Meters

Operating Frequency: 5260MHz


Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10520.00	Peak	H	-	-	-73.63	17.56	50.93	68.23	-17.31
* 15780.00	Average	V	-	-	-85.78	25.65	46.87	53.98	-7.11
* 15780.00	Peak	V	-	-	-74.78	25.65	57.87	73.98	-16.11


Table 7-210. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 168 of 384

V 10.6 10/27/2023



Plot 7-289. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.56 – RU242)



Plot 7-290. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.56 — RU242)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 61

Distance of Measurements: 3 Meters


Operating Frequency: 5280MHz

Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10560.00	Peak	H	-	-	-73.81	17.98	0.00	51.16	68.23	-17.07
* 15840.00	Average	V	-	-	-85.82	25.77	0.00	46.95	53.98	-7.03
* 15840.00	Peak	V	-	-	-73.83	25.77	0.00	58.94	73.98	-15.04
* 21120.00	Average	H	-	-	-60.70	-7.55	-9.54	29.21	53.98	-24.77
* 21120.00	Peak	H	-	-	-49.10	-7.55	-9.54	40.81	73.98	-33.17
26400.00	Peak	V	-	-	-50.90	-5.42	-9.54	41.14	68.23	-27.09
* 31680.00	Average	H	-	-	-62.55	-4.05	-9.54	30.86	53.98	-23.12
* 31680.00	Peak	H	-	-	-50.86	-4.05	-9.54	42.55	73.98	-31.43

Table 7-211. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 169 of 384



Plot 7-291. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.64 – RU242)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 5320MHz
Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 10640.00	Average	H	-	-	-85.02	18.08	40.06	53.98	-13.92
* 10640.00	Peak	H	-	-	-73.98	18.08	51.10	73.98	-22.87
* 15960.00	Average	H	-	-	-85.65	25.92	47.27	53.98	-6.71
* 15960.00	Peak	H	-	-	-74.52	25.92	58.40	73.98	-15.58

Table 7-212. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 170 of 384

V 10.6 10/27/2023



Plot 7-292. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.100 – RU242)


Mode: 802.11be (20MHz BW)
Data Rate: MCS0
RU Index: 61
Distance of Measurements: 3 Meters
Operating Frequency: 5500MHz
Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11000.00	Average	H	-	-	-84.51	18.09	40.58	53.98	-13.40
* 11000.00	Peak	H	-	-	-73.48	18.09	51.61	73.98	-22.37
16500.00	Peak	V	-	-	-73.19	27.52	61.33	68.23	-6.90


Table 7-213. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 171 of 384

V 10.6 10/27/2023



Plot 7-293. Radiated Spurious Emissions above 1GHz CDD Primary (11be – Ch.116 – RU242)



Plot 7-294. Radiated Spurious Emissions 18 GHz - 40GHz CDD Primary (11be Ch.116 — RU242)

Mode: 802.11be (20MHz BW)

Data Rate: MCS0

RU Index: 61

Distance of Measurements: 3 Meters

Operating Frequency: 5580MHz

Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	Average	H	-	-	-84.24	18.84	0.00	41.60	53.98	-12.38
* 11160.00	Peak	H	-	-	-72.72	18.84	0.00	53.12	73.98	-20.86
16740.00	Peak	H	-	-	-73.94	27.77	0.00	60.82	68.23	-7.41
* 22320.00	Average	V	-	-	-61.65	-7.57	-9.54	28.25	53.98	-25.73
* 22320.00	Peak	V	-	-	-50.76	-7.57	-9.54	39.14	73.98	-34.84
27900.00	Peak	V	-	-	-52.65	-4.48	-9.54	40.33	68.23	-27.90
33480.00	Peak	H	-	-	-50.80	-4.28	-9.54	42.38	68.23	-25.85

Table 7-214. Radiated Measurements CDD Primary (RU242)

FCC ID: BCGA3461 IC: 579C-A3461		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2509100081-14-R3.BCG	Test Dates: 09/15/2025 - 12/31/2025	EUT Type: Tablet Device	Page 172 of 384

V 10.6 10/27/2023