

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-1
SAR System Validation Summary

SAR System	Freq. (MHz)	Date	Probe SN	DAE	Probe Cal Point		Cond. (σ)	Perm. (ϵ_r)	CW VALIDATION			MOD. VALIDATION		
									SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
L	2450	3/30/2026	7539	1450	cDASY6	2450	1.856	37.819	PASS	PASS	PASS	PASS	OFDM/TDD	PASS
S	5250	6/9/2026	3914	728	DASY8	5250	4.487	34.834	PASS	PASS	PASS	PASS	OFDM	N/A
S	5600	6/9/2026	3914	728	DASY8	5600	4.843	34.176	PASS	PASS	PASS	PASS	OFDM	N/A
S	5750	6/10/2026	3914	728	DASY8	5750	4.995	33.911	PASS	PASS	PASS	PASS	OFDM	N/A
S	5850	6/10/2026	3914	728	DASY8	5850	5.107	33.723	PASS	PASS	PASS	PASS	OFDM	N/A

NOTE: The probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: IPH-05126	RF EXPOSURE TEST REPORT	Error! Reference source not found.	Approved by: Technical Manager
DUT Type: Portable Digital Transceiver	This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		APPENDIX E: Page 1 of 1