

Report on the FCC and IC Testing of the Marquardt GmbH

Model: OR1

In accordance with FCC 47 CFR Part 1 I and ISSED RSS-102

Prepared for: Marquardt GmbH
Schloss-Straße 16
78604 Rietheim-Weilheim
Germany

FCC ID: IYZOR1
IC: 2701A-OR1



Product Service

Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

Date: 2026-03-02

Document Number: TR-713354185-00 | Revision 1

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Project Management	Alexander Deese	2026-03-02	 SIGN-ID 1112036
Authorised Signatory	Alex Fink	2026-03-02	 SIGN-ID 1112049

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

Engineering Statement:

This measurement shown in this report were made in accordance with the procedures described on test pages.
All reported testing was carried out on a sample equipment to demonstrate limited compliance with with FCC 47 CFR Part 1 I and ISSED RSS-102.

The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Alexander Deese	2026-03-02	 SIGN-ID 1112036

Laboratory Accreditation

DAkkS Reg. No. D-PL-11321-11-03

DAkkS Reg. No. D-PL-11321-11-04

Laboratory recognition

Registration No. BNetzA-CAB-16/21-15

Industry Canada test site registration

3050A-2

Executive Statement:

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 1 I:2023 and ISSED RSS-102:2023



DISCLAIMER AND COPYRIGHT

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question. It does not imply a general statement regarding the quality of products from regular production. For further details please see Testing, Certification, Validation and Verification Regulations, chapter A-3.3.

© 2026 TÜV SÜD Product Service.

Trade Register Munich
HRB 85742
VAT ID No. DE129484267
Information pursuant to Section 2(1)
DL-InfoV (Germany) at
www.tuvsud.com/imprint

Supervisory Board:
Holger Lindner (Chairman)
Board of Management:
Wolfgang Hübl (CEO)
Karl Meier
Patrick van Welij

Phone: +49 (0) 9421 56 82-0
Fax: +49 (0) 9421 56 82-199
www.tuvsud.com

TÜV SÜD Product Service GmbH
Äußere Frühlingsstraße 45
94315 Straubing
Germany



Content

1	Report Summary.....	2
1.1	Modification Report	2
1.2	Introduction.....	2
1.3	Brief Summary of Results	3
1.4	Product Information	4
1.5	Test Configuration	5
1.6	Modes of Operation.....	5
1.7	EUT Modifications Record	5
1.8	Test Location.....	5
2	Test Details.....	6
2.1	RF Exposure	6
3	Photographs of Test Setups	10
4	Measurement Uncertainty	11



1 Report Summary

1.1 Modification Report

Alternations and additions to this report will be issued to the holders of each copy in the form of a complete document. The current version replaces all previous versions.

<i>Revision</i>	<i>Description of changes</i>	<i>Date of Issue</i>
0	First Issue	2026-02-09
1	Related Documents corrected to ANSI C63.10:2020.	2026-03-02

Table 1: Report of Modifications

1.2 Introduction

Applicant	Marquardt GmbH
Manufacturer	Marquardt GmbH
Model Number(s)	OR1
Serial Number(s)	---
Number of Samples Tested	1
Test Specification(s) / Issue / Date	FCC 47 CFR Part 1 I and ISED RSS-102, Issue 6: 2023
Test Plan/Issue/Date	Test mode Description of NH2; Version 1.1
Order Number	6200727724
Date	2024-12-09
Date of Receipt of EUT	2025-10-10
Start of Test	2025-10-17
Finish of Test	2025-10-17
Name of Engineer(s)	Michael Ingerl, Alexander Deese
Related Document(s)	ANSI C63.10:2020



1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 1 I, is shown below.

<i>Section</i>	<i>Specification Clause</i>	<i>Test Description</i>	<i>Result</i>
2.1	1.1307 15.247(i)	RF Exposure	Pass

Table 2: Results according to FCC 47 CFR

A brief summary of the tests carried out in accordance withISED RSS-102, is shown below.

<i>Section</i>	<i>Specification Clause</i>	<i>Test Description</i>	<i>Result</i>
2.1	6.3	RF Exposure	Pass

Table 3: Results according to RSS-102



1.4 Product Information

1.4.1 Technical Description

The OR1 is a NFC reader module mounted on the B-pillar of the car. It uses the NFC technology to grant access to the car. The OR1 connects to smartphones, wearables and NFC tags to authorize door opening.

The OR1 acts as an interface between car electronics control Unit and applications on NFC devices. The car ECU requests the OR1 which communicates with the NFC device on the integrated antenna using a magnetic field.

<i>Frequency Band</i>	13.110 – 14.010 MHz
<i>Number of frequency channels:</i>	1
<i>Supply Voltage:</i>	12 V
<i>Supply Frequency:</i>	DC (0 Hz)
<i>Highest clock frequency (radio part):</i>	13.56 MHz
<i>Highest clock frequency (non-radio part):</i>	---
<i>Antenna:</i>	Integrated PCB loop antenna, approx.. 30 x 25 mm

1.4.2 List of Antennas

The EUT has a dedicated integrated antenna.



1.5 Test Configuration

The EUT was configured in stand-alone mode.

1.6 Modes of Operation

Tests were performed with the EUT continuously polling and with the EUT continuously reading a tag.

1.7 EUT Modifications Record

The table below details modifications made to the EUT during the test program.
The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	As supplied by the customer	Not Applicable	Not Applicable

Table 4

1.8 Test Location

TÜV SÜD Product Service conducted the following tests at our Straubing test laboratory:

Test Name	Name of Engineer(s)
Radiated Emissions	Michael Ingerl

Office Address:

Äußere Frühlingstraße 45
94315 Straubing
Germany



2 Test Details

2.1 RF Exposure

2.1.1 Specification Reference

FCC 47 CFR Part 2 J, Clause 2.1093
KDB 447498 D01 V06, section 4.3.1
ISED RSS-Gen, Clause 3.4
ISED RSS-102, Clause

2.1.2 Equipment under Test and Modification State

OR1; S/N ---; Modification State 0

2.1.3 Date of Test

2025-10-17

2.1.4 Environmental Conditions

Ambient Temperature	22 °C
Relative Humidity	45 %

2.1.5 Test Method

The test is based on radiated emission tests of the device. See test report TR-713354185-05 for details. Maximum output was calculated through following equation:

$$P = \frac{(E \cdot d)^2}{30 \cdot G}$$

P: Maximum output power (in W)
E: Electric field strength (in V/m)
d: Distance to antenna (in m)
G: Linear antenna gain (= 1)



2.1.6 Specification Limits

47 CFR, Part 1, § 1.1307(b)(3)

- (i) For single RF sources (i.e. any single fixed RF source, mobile device, or portable device, as defined in paragraph(b)(2) of this section): A single RF source is exempt if:
- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiate power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by

$$P_{th}(mW) = \begin{cases} ERP_{20cm} (d/20 \text{ cm})^x, & d \leq 20 \text{ cm}; \\ ERP_{20cm}, & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right); f \text{ in GHz}$$

and

$$ERP_{20cm}(mW) = \begin{cases} 2040 f, & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060, & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the test separation distance (cm);

- (C) Or using the table below and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value described for that frequency. For the exemption in the table to apply, R must be at least $\lambda/2\pi$ where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF source frequency (MHz)	Threshold ERP (Watts)
0.3 – 1.34	$1920 R^2$
1.34 – 30	$3450 R^2 / f^2$
30 – 300	$3.83 R^2$
300 – 1500	$0.0128 R^2 f^2$
1500 – 100000	$19.2 R^2$

- (ii) For multiple RF sources: Multiple RF sources are exempt if:
- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of 2 cm between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- (B) In case of fixed RF sources operating in the same time-averaging period, or of multiple or portable RF sources within a device in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{\text{Evaluated}_k}{\text{ExposureLimit}_k} \leq 1$$



RSS-102, section 6.3

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in the table below:

f (MHz)	Exemption Limits (mW) at separation distance of									
	≤ 5 mm	10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm	≥ 50 mm
≤ 300	45	116	139	163	189	216	246	280	319	362
450	32	71	87	104	124	147	175	208	248	296
835	21	32	41	54	72	96	129	172	228	298
1900	6	10	18	33	57	92	138	194	257	323
2450	3	7	16	32	56	89	128	170	209	245
3500	2	6	15	29	50	72	94	114	134	158
5800	1	5	13	23	32	41	54	74	102	128

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for route evaluation are multiplied by a factor of 5. For limb-worn devices where the 10 grams value applies, the exemption limits for routine evaluation are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

For medical implants devices, the exemption limit for routine evaluation is set at 1 mW. The output power of a medical implant device is defined as the higher of the conducted or e.i.r.p. to determine whether the device is exempt from the SAR evaluation.



2.1.7 Test Results

47 CFR, Part 1, § 1.1307(b)(3)

The carrier in the 13.56 MHz frequency band is evaluated acc. to § 1.1307(b)(3)(i)(A).

Frequency (MHz)	E-Field (dBμV/m)	Distance (m)	Maximum out-put power (mW)	Exemption limit (mW)	Evaluation
13.56	21.96	30	0.000004711	1.0	Pass

No evaluation for multiple frequencies, since exemption acc. to § 1.1307(b)(3)(i)(A), is exempt from this evaluation.


RSS-102, section 6.3

The prediction distance (for the limit is estimated wit 0 mm (≤ 5 mm)):

Frequency (MHz)	E-Field (dBμV/m)	Distance (m)	Maximum out-put power (pW)	Exemption limit (mW)	Evaluation
13.56	21.96	30	0.000004711	45.00	Pass

No calculation regarding multiple output frequencies applicable.

3 Photographs of Test Setups





4 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

<i>Radio Interference Emission Testing</i>		
<i>Test Name</i>	<i>kp</i>	<i>Expanded Uncertainty</i>
Conducted Voltage Emission		
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB
100 kHz to 200 MHz (50Ω/5μH AMN)	2	± 3.6 dB
Discontinuous Conducted Emission		
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB
Conducted Current Emission		
9 kHz to 200 MHz	2	± 3.5 dB
Magnetic Fieldstrength		
9 kHz to 30 MHz (with loop antenna)	2	± 3.9 dB
9 kHz to 30 MHz (large-loop antenna 2 m)	2	± 3.5 dB
Radiated Emission		
30 MHz to 300 MHz	2	± 4.9 dB
300 MHz to 1 GHz	2	± 5.0 dB
1 GHz to 6 GHz	2	± 4.6 dB
Test distance 10 m		
30 MHz to 300 MHz	2	± 4.9 dB
300 MHz to 1 GHz	2	± 4.9 dB
The expanded uncertainty reported according to CISPR16-4-2: 2011 + A1 + A2 + Cor1 is based on a standard uncertainty multiplied by a coverage factor of $k_p = 2$, providing a level of confidence of $p = 95.45\%$		

Table 5 Measurement uncertainty based on CISPR 16-4-2



<i>Radio Interference Emission Testing</i>		
<i>Test Name</i>	<i>kp</i>	<i>Expanded Uncertainty</i>
Occupied Bandwidth	2	± 5 %
Conducted Power		
9 kHz ≤ f < 30 MHz	2	± 1.0 dB
30 MHz ≤ f < 1 GHz	2	± 1.5 dB
1 GHz ≤ f ≤ 40 GHz	2	± 2.5 dB
1 MS/s power sensor (TS8997)	2	± 1.5 dB
Occupied Bandwidth	2	± 5 %
Power Spectral Density	2	± 3.0 dB
Radiated Power		
25 MHz – 6 GHz	1.96	±4.4 dB
1 GHz – 18 GHz	1.96	±4.7 dB
18 GHz – 40 GHz	1.96	±4.9 dB
40 GHz – 325 GHz	1.96	±6.1 dB
Conducted Spurious Emissions	2	± 3.0 dB
Radiated Spurious Emissions	2	± 6.0 dB
Voltage		
DC	2	± 1.0 %
AC	2	± 2.0 %
Time (automatic)	2	± 5 %
Frequency	2	± 10 ⁻⁷
The expanded uncertainty reported according to ETSI TR 100 028:2001 is based on a standard uncertainty multiplied by a coverage factor of kp = 2, providing a level of confidence of p = 95.45%		

Table 6 Measurement uncertainty based on ETSI TR 100 028

The measurement uncertainty in the laboratory is less than or equal to the maximum measurement uncertainty according to CISPR16-4-2: 2011 + A1 + A2 + Cor1 (U_{CISPR}) and as specified in the test report below. This normative regulation means that the measured value is also the value to be assessed in relation to the limit value.



Product Service

Test Name	Expanded Uncertainty
Occupied Bandwidth	±5 %
Conducted Power	
9 kHz ≤ f < 30 MHz	±1.0 dB
30 MHz ≤ f < 1 GHz	±1.5 dB
1 GHz ≤ f ≤ 40 GHz	±2.5 dB
1 MS/s power sensor (2.4 / 5 GHz band)	±1.5 dB
Power Spectral Density	±3.0 dB
Radiated Power	
25 MHz – 26.5 GHz	±6.0 dB
26.5 GHz – 66 GHz	±8.0 dB
40 GHz – 325 GHz	±10.0 dB
Conducted Spurious Emissions	±3.0 dB
Radiated Field Strength 9 kHz – 40 GHz	±6.0 dB
Voltage	
DC	± 1.0 %
AC	± 2.0 %
Time (automatic)	± 5 %
Frequency	± 10 ⁻⁷

Table 7 Decision Rule: Maximum allowed measurement uncertainty

End of Test Report