

Radiofrequency radiation exposure evaluation: mobile devices

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

a) EUT RF Exposure Evaluation operations, Worst Case mode

Test Mode	Conducted Power (dBm)	Conducted Power (mW)	ERP (dBm)	ERP (mW)	Minimum Separation Distances (cm)	Limit (mW)
BLE	4.92	3.10	4.77	2.99	20	3060
2.4GHz band Wi-Fi	14.21	26.36	14.06	25.46		

IC requirements: The EUT shall comply with the requirement of RSS-102 section 4 Exposure Limits.

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

a) EUT RF Exposure Evaluation standalone operations, Worst Case mode

Test Mode	Maximum e.i.r.p (dBm)	Maximum e.i.r.p (W)	Limit (W)
2.4GHz band Wi-Fi	16.16	0.041304	2.68
BLE	6.92	0.004920	2.68

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”