

RF EXPOSURE REPORT

Applicant	:	DORAN MFG, LLC
Applicant Address	:	4362 Glendale Milford Rd, Cincinnati OH 45242 United States
Manufacturer	:	DORAN MFG, LLC
Manufacturer Address	:	4362 Glendale Milford Rd, Cincinnati OH 45242 United States
Equipment Under Test	:	Doran TPMS Sensor for Truck
Model No.	:	3684-C
Series Model No.	:	N/A
Trade Mark	:	
FCC ID	:	VZ43684S
Report No.	:	LS-R26032016-3F04
Issue Data	:	Apr. 22, 2026



LabSure Testing Services (Suzhou) Co., Ltd.

Table of Contents

1.	General information.....	5
1.1.	Description of Equipment.....	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement.....	6
2.2.	Estimation result.....	6

Test Report Declare

Applicant	:	DORAN MFG, LLC
Address	:	4362 Glendale Milford Rd, Cincinnati OH 45242 United States
Manufacturer	:	DORAN MFG, LLC
Address	:	4362 Glendale Milford Rd, Cincinnati OH 45242 United States
Equipment under Test	:	Doran TPMS Sensor for Truck
Model No.	:	3684-C
Trade Mark	:	
FCC ID	:	VZ43684S

Standard Used:



KDB 447498 D04 Interim General RF Exposure Guidance v01

We Declare:

The equipment described above is tested by LabSure Testing Services (Suzhou) Co.,Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and LabSure Testing Services (Suzhou) Co.,Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	LS-R26032016-3F04		
Sample No:	Y26032016-01		
Date of Receipt:	Mar. 31, 2026	Date of Test:	Apr. 07, 2026

Prepared By: 	Reviewed By: 	Authorized By: 
Bacon Dong/Engineer	Leon Wu/Director	Chris Zhong/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of LabSure Testing Services (Suzhou) Co., Ltd. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification. The results reported herein have been performed in accordance with the laboratory's terms of accreditation.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Apr. 22, 2026	

1. General information

1.1. Description of Equipment

EUT Description	: Doran TPMS Sensor for Truck
Model Number	: 3684-C
Serial Number	: N/A
Hardware Version	: N/A
Software Version	: N/A
Sample Type	: Vehicle Device
EUT function description	: Please refer to user manual of this device
Power supply	: 3Vdc (internal CR2050HR)
Type of Modulation	: FSK
Support Frequency	: 433.92MHz
Conducted Power	: -1.35 dBm (Measured values)
Antenna Type	: Loop antenna
Device Type	: mobile device

1.2. Assess laboratory

Lab Information	Company Name: LabSure Testing Services (Suzhou) Co.,Ltd. Address: Phase II, No.16 Runsheng Road, Suzhou Industrial Park, Suzhou, People's Republic of China. Tel: +86-0512-62531270, E-mail: labsure@lab-sure.com, www.lab-sure.com
Accreditation Certificate	A2LA (Certificate No.: 7346.01) LabSure Testing Services (Suzhou) Co.,Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1397) LabSure Testing Services (Suzhou) Co.,Ltd. has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 32952; CAB No.:CN0182) LabSure Testing Services (Suzhou) Co.,Ltd. has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
Note 1: All tests measurement facilities use to collect the measurement data are located at Phase II, No.16 Runsheng Road, Suzhou Industrial Park, Suzhou, China. Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS. Note 3: The test anechoic chamber in LabSure Testing Services (Suzhou) Co.,Ltd. had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.	

2. RF Exposure Evaluation

2.1. Requirement

Per § 1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions.

This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

2.2. Estimation result

Type of Modulation	Band (MHz)	Conducted Power (dBm) (Measured values)	Conducted Power Tune-up (dBm)	Conducted Power Tune-up (mW)	Limit (mW)
FSK	433.92	-1.35	-1	0.79	1

Conclusion: The measurement results comply with Code of Federal Regulations 47 Subchapter A, Part 1, Subpart 1 §1.1307, regardless of separation distance

END OF REPORT