



Appendix B

RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: Amplifier

Trade Mark: Russound

Test Model: P75BT

Environmental Conditions

Temperature:	24.6° C
Relative Humidity:	52.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Emiya Lin
Supervised by:	Simba Huang



Contents

Page

COVER PAGE

1	Duty Cycle	3
1.1	Test Result	3
1.2	Test Graphs	4
2	Maximum Conducted Output Power	7
2.1	Test Result	7
2.2	Test Graphs	9
3	-6dB Bandwidth	12
3.1	Test Result	12
3.2	Test Graphs	13
4	Maximum Power Spectral Density Level	16
4.1	Test Result	16
4.2	Test Graphs	18
5	Band Edge	21
5.1	Test Result	21
5.2	Test Graphs	22
6	Conducted RF Spurious Emission	26
6.1	Test Result	26
6.2	Test Graphs	27
7	Restrict Band	33
7.1	Test Result	33
7.2	Test Graphs	36





1 Duty Cycle


1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor	1/T (kHz)
BLE 1M	2402	85.6	0.68	0.47
BLE 1M	2440	85.6	0.68	0.47
BLE 1M	2480	85.59	0.68	0.47
BLE 2M	2402	86.94	0.61	0.93
BLE 2M	2440	86.53	0.63	0.93
BLE 2M	2480	86.4	0.63	0.93

1.2 Test Graphs











2 Maximum Conducted Output Power


2.1 Test Result

Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	-2.66	30	Pass
BLE 1M	2440	0.82	30	Pass
BLE 1M	2480	0.18	30	Pass
BLE 2M	2402	2.45	30	Pass
BLE 2M	2440	1.91	30	Pass
BLE 2M	2480	1.3	30	Pass

2.2 Test Graphs











3 -6dB Bandwidth


3.1 Test Result

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE 1M	2402	0.698	0.5	Pass
BLE 1M	2440	0.716	0.5	Pass
BLE 1M	2480	0.767	0.5	Pass
BLE 2M	2402	1.38	0.5	Pass
BLE 2M	2440	1.248	0.5	Pass
BLE 2M	2480	1.398	0.5	Pass

3.2 Test Graphs









4 Maximum Power Spectral Density Level


4.1 Test Result

Mode	Frequency (MHz)	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE 1M	2402	-18.69	≤8	Pass
BLE 1M	2440	-15.22	≤8	Pass
BLE 1M	2480	-15.94	≤8	Pass
BLE 2M	2402	-16.57	≤8	Pass
BLE 2M	2440	-17.12	≤8	Pass
BLE 2M	2480	-18.09	≤8	Pass

4.2 Test Graphs











5 Band Edge


5.1 Test Result


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-43.32	-20	Pass
BLE 1M	2480	-38.88	-20	Pass
BLE 2M	2402	-43.15	-20	Pass
BLE 2M	2480	-38.12	-20	Pass

5.2 Test Graphs











6 Conducted RF Spurious Emission


6.1 Test Result


Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-36.8	-20	Pass
BLE 1M	2440	-41.08	-20	Pass
BLE 1M	2480	-40.35	-20	Pass
BLE 2M	2402	-40.73	-20	Pass
BLE 2M	2440	-39.94	-20	Pass
BLE 2M	2480	-40.11	-20	Pass


6.2 Test Graphs


















7 Restrict Band


7.1 Test Result


Mode	Frequency (MHz)	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
BLE 1M	2402	2310	-47.26	3.33	-	51.33	Peak	74	Pass
BLE 1M	2402	2310	-56.72	3.33	0.68	42.55	Average	54	Pass
BLE 1M	2402	2341.2	-45.34	3.33	-	53.25	Peak	74	Pass
BLE 1M	2402	2337.936	-53.39	3.33	0.68	45.88	Average	54	Pass
BLE 1M	2402	2390	-49.48	3.33	-	49.11	Peak	74	Pass
BLE 1M	2402	2390	-57.18	3.33	0.68	42.09	Average	54	Pass
BLE 1M	2480	2483.5	-47.25	3.33	-	51.34	Peak	74	Pass
BLE 1M	2480	2483.5	-54.14	3.33	0.68	45.13	Average	54	Pass
BLE 1M	2480	2495.08	-46.84	3.33	-	51.75	Peak	74	Pass
BLE 1M	2480	2483.8	-53.92	3.33	0.68	45.35	Average	54	Pass
BLE 1M	2480	2500	-47.58	3.33	-	51.01	Peak	74	Pass
BLE 1M	2480	2500	-56.06	3.33	0.68	43.21	Average	54	Pass
BLE 2M	2402	2310	-49.14	3.33	-	49.45	Peak	74	Pass
BLE 2M	2402	2310	-55.98	3.33	0.61	43.22	Average	54	Pass
BLE 2M	2402	2343.696	-44.87	3.33	-	53.72	Peak	74	Pass
BLE 2M	2402	2339.28	-53.69	3.33	0.61	45.51	Average	54	Pass
BLE 2M	2402	2390	-48.19	3.33	-	50.4	Peak	74	Pass
BLE 2M	2402	2390	-56.38	3.33	0.61	42.82	Average	54	Pass
BLE 2M	2480	2483.5	-47.89	3.33	-	50.7	Peak	74	Pass
BLE 2M	2480	2483.5	-55	3.33	0.63	44.22	Average	54	Pass
BLE 2M	2480	2487.424	-42.74	3.33	-	55.85	Peak	74	Pass
BLE 2M	2480	2483.512	-55.02	3.33	0.63	44.2	Average	54	Pass
BLE 2M	2480	2500	-50.11	3.33	-	48.48	Peak	74	Pass
BLE 2M	2480	2500	-55.4	3.33	0.63	43.82	Average	54	Pass

7.2 Test Graphs









---The End---