



Radio Test Report

Report No.: STS2605391W01

Issued for

NEXXT SOLUTIONS

3505 N.W 107TH AVE. MIAMI, Florida 33178, United States

Product Name: Smart Camera

Brand Name: N/A

Model Name: NHC-OP40SL

Series Model(s): N/A

FCC ID: X4YHACOP40SL

Test Standards: 47 CFR Part 2, 22H

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: NEXXT SOLUTIONS
Address.....: 3505 N.W 107TH AVE. MIAMI, Florida 33178, United States

Manufacturer's Name: Sungale Electronics (Shenzhen) Limited
Address.....: No. 1302, DaHong High-Tech Park, No. 6-18, Xinhe Road,
Xinqiao, BaoAn, Shenzhen 518125, CHINA

Product Description

Product Name: Smart Camera
Brand Name: N/A
Model Name: NHC-OP40SL
Series Model(s): N/A

Test Standards.....: 47 CFR Part 2, 24
Test Procedure: KDB 971168 D01 v03r01, ANSI C63.26(2015)

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test.....:

Date of receipt of test item: 19 May 2026
Date (s) of performance of tests : 19 May 2026 to 17 June 2026
Date of Issue: 18 June 2026
Test Result: Pass

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1 SUMMARY OF TEST RESULTS	5
1.1 INTRODUCTION	6
2 PRODUCT INFORMATION	7
3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
4 MEASUREMENT INSTRUMENTS	13
5 TEST ITEMS	14
5.1 CONDUCTED OUTPUT POWER&TRANSMITTER RADIATED POWER	14
5.2 PEAK TO AVERAGE RATIO	16
5.3 OCCUPIED BANDWIDTH	17
5.4 FREQUENCY STABILITY	18
5.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	20
5.6 BAND EDGE	21
5.7 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	23
APPENDIX-PHOTOS OF TEST SETUP	31

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	18 June 2026	STS2605391W01	ALL	Initial Issue



1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

The radiated emission testing was performed according to the procedures of KDB 971168 D01 v03r01 and ANSI C63.26(2015)

Test Description	FCC Rules	Band	Test Limit	Test Result
Conducted Output Power	2.1046	/	Reporting Only	PASS
Transmitter Radiated Power	24.232(c)	B2	EIRP < 2Watt	
Peak-to-Average Ratio	24.232(d)	B2	< 13 dB	PASS
Occupied Bandwidth	2.1049	/	Reporting Only	PASS
Frequency Stability	2.1055	/	< 2.5 ppm	PASS
	24.235	B2		
Spurious Emission at Antenna Terminals	2.1051	/	< 43+10log10(P[Watts])	PASS
	24.238(a)	B2		
Band Edge	2.1051	/	Please refer to standard	PASS
	24.238(a)	B2		
Field Strength of Spurious Radiation	2.1053	/	< 43+10log10(P[Watts])	PASS
	24.238(a)	B2		



1.1 INTRODUCTION

TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2 PRODUCT INFORMATION

Product Name	Smart Camera
Brand Name	N/A
Model Name	NHC-OP40SL
Series Model(s)	N/A
Model Difference	N/A
Tx Frequency:	LTE Band 2: 1850 MHz ~ 1910 MHz
Rx Frequency:	LTE Band 2: 1930 MHz ~ 1990 MHz
Max RF Output Power:	LTE Band 2: 23.85 dBm
Modulation Characteristics:	LTE: QPSK /16QAM
SIM Card:	SIM 1
Antenna:	External Antenna
Antenna gain:	LTE Band 2: 0 dBi
GPRS/EDGE Class:	Multi-Class12
Extreme Vol. Limits:	DC 4.25V~5.75V
Extreme Temp. Tolerance:	-20℃~60℃
Power Rating	DC 5V from adapter
Adapter	N/A
Battery	N/A
Hardware version number:	N/A
Software version number:	N/A
** Note: The High Voltage 5.75V and Low Voltage 4.25V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage, the antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.	



Test Channel List			
Band2	Bandwidth	Frequency(MHz)	Channel
L	1.4M	1850.7	18607
	3M	1851.5	18615
	5M	1852.5	18625
	10M	1855	18650
	15M	1857.5	18675
	20M	1860	18700
M	1.4/3/5/10M/15M/20M	1880	18900
H	1.4M	1909.3	19193
	3M	1908.5	19185
	5M	1907.5	19175
	10M	1905	19150
	15M	1902.5	19125
	20M	1900	19100

EMISSION DESIGNATOR

Condition	Band	Bandwidth (MHz)	UL Channel	RB Size	RB Position	Modulation	Power (dBm)	Gain (dBm)	EIRP (dBm)	Verdict
NVNT	Band2	1.4	18607	1	#0	QPSK	23.05	0	23.05	PASS
NVNT	Band2	1.4	18607	1	#Mid	QPSK	23.55	0	23.55	PASS
NVNT	Band2	1.4	18607	1	#Max	QPSK	22.70	0	22.70	PASS
NVNT	Band2	1.4	18607	3	#0	QPSK	23.28	0	23.28	PASS
NVNT	Band2	1.4	18607	3	#Mid	QPSK	23.47	0	23.47	PASS
NVNT	Band2	1.4	18607	3	#Max	QPSK	23.01	0	23.01	PASS
NVNT	Band2	1.4	18607	6	#0	QPSK	22.10	0	22.10	PASS
NVNT	Band2	1.4	18607	1	#0	16QAM	22.07	0	22.07	PASS
NVNT	Band2	1.4	18607	1	#Mid	16QAM	22.62	0	22.62	PASS
NVNT	Band2	1.4	18607	1	#Max	16QAM	21.78	0	21.78	PASS
NVNT	Band2	1.4	18607	3	#0	16QAM	22.49	0	22.49	PASS
NVNT	Band2	1.4	18607	3	#Mid	16QAM	22.66	0	22.66	PASS
NVNT	Band2	1.4	18607	3	#Max	16QAM	22.18	0	22.18	PASS
NVNT	Band2	1.4	18607	6	#0	16QAM	21.22	0	21.22	PASS
NVNT	Band2	1.4	18900	1	#0	QPSK	23.10	0	23.10	PASS
NVNT	Band2	1.4	18900	1	#Mid	QPSK	23.76	0	23.76	PASS
NVNT	Band2	1.4	18900	1	#Max	QPSK	22.84	0	22.84	PASS
NVNT	Band2	1.4	18900	3	#0	QPSK	23.65	0	23.65	PASS
NVNT	Band2	1.4	18900	3	#Mid	QPSK	23.82	0	23.82	PASS
NVNT	Band2	1.4	18900	3	#Max	QPSK	23.44	0	23.44	PASS
NVNT	Band2	1.4	18900	6	#0	QPSK	22.44	0	22.44	PASS
NVNT	Band2	1.4	18900	1	#0	16QAM	22.24	0	22.24	PASS
NVNT	Band2	1.4	18900	1	#Mid	16QAM	22.95	0	22.95	PASS
NVNT	Band2	1.4	18900	1	#Max	16QAM	22.09	0	22.09	PASS
NVNT	Band2	1.4	18900	3	#0	16QAM	22.75	0	22.75	PASS
NVNT	Band2	1.4	18900	3	#Mid	16QAM	22.96	0	22.96	PASS
NVNT	Band2	1.4	18900	3	#Max	16QAM	22.58	0	22.58	PASS
NVNT	Band2	1.4	18900	6	#0	16QAM	21.53	0	21.53	PASS
NVNT	Band2	1.4	19193	1	#0	QPSK	23.02	0	23.02	PASS
NVNT	Band2	1.4	19193	1	#Mid	QPSK	23.43	0	23.43	PASS
NVNT	Band2	1.4	19193	1	#Max	QPSK	22.52	0	22.52	PASS



NVNT	Band2	1.4	19193	3	#0	QPSK	23.18	0	23.18	PASS
NVNT	Band2	1.4	19193	3	#Mid	QPSK	23.33	0	23.33	PASS
NVNT	Band2	1.4	19193	3	#Max	QPSK	22.83	0	22.83	PASS
NVNT	Band2	1.4	19193	6	#0	QPSK	21.92	0	21.92	PASS
NVNT	Band2	1.4	19193	1	#0	16QAM	21.89	0	21.89	PASS
NVNT	Band2	1.4	19193	1	#Mid	16QAM	22.21	0	22.21	PASS
NVNT	Band2	1.4	19193	1	#Max	16QAM	21.18	0	21.18	PASS
NVNT	Band2	1.4	19193	3	#0	16QAM	22.26	0	22.26	PASS
NVNT	Band2	1.4	19193	3	#Mid	16QAM	22.42	0	22.42	PASS
NVNT	Band2	1.4	19193	3	#Max	16QAM	21.96	0	21.96	PASS
NVNT	Band2	1.4	19193	6	#0	16QAM	21.02	0	21.02	PASS
NVNT	Band2	3	18615	1	#0	QPSK	22.80	0	22.80	PASS
NVNT	Band2	3	18615	1	#Mid	QPSK	23.37	0	23.37	PASS
NVNT	Band2	3	18615	1	#Max	QPSK	21.70	0	21.70	PASS
NVNT	Band2	3	18615	8	#0	QPSK	22.00	0	22.00	PASS
NVNT	Band2	3	18615	8	#Mid	QPSK	22.20	0	22.20	PASS
NVNT	Band2	3	18615	8	#Max	QPSK	21.88	0	21.88	PASS
NVNT	Band2	3	18615	15	#0	QPSK	21.87	0	21.87	PASS
NVNT	Band2	3	18615	1	#0	16QAM	22.25	0	22.25	PASS
NVNT	Band2	3	18615	1	#Mid	16QAM	22.81	0	22.81	PASS
NVNT	Band2	3	18615	1	#Max	16QAM	21.03	0	21.03	PASS
NVNT	Band2	3	18615	8	#0	16QAM	20.97	0	20.97	PASS
NVNT	Band2	3	18615	8	#Mid	16QAM	21.15	0	21.15	PASS
NVNT	Band2	3	18615	8	#Max	16QAM	20.81	0	20.81	PASS
NVNT	Band2	3	18615	15	#0	16QAM	20.86	0	20.86	PASS
NVNT	Band2	3	18900	1	#0	QPSK	22.86	0	22.86	PASS
NVNT	Band2	3	18900	1	#Mid	QPSK	23.85	0	23.85	PASS
NVNT	Band2	3	18900	1	#Max	QPSK	22.10	0	22.10	PASS
NVNT	Band2	3	18900	8	#0	QPSK	22.39	0	22.39	PASS
NVNT	Band2	3	18900	8	#Mid	QPSK	22.63	0	22.63	PASS
NVNT	Band2	3	18900	8	#Max	QPSK	22.33	0	22.33	PASS
NVNT	Band2	3	18900	15	#0	QPSK	22.33	0	22.33	PASS
NVNT	Band2	3	18900	1	#0	16QAM	22.03	0	22.03	PASS
NVNT	Band2	3	18900	1	#Mid	16QAM	23.10	0	23.10	PASS
NVNT	Band2	3	18900	1	#Max	16QAM	21.32	0	21.32	PASS
NVNT	Band2	3	18900	8	#0	16QAM	21.36	0	21.36	PASS
NVNT	Band2	3	18900	8	#Mid	16QAM	21.58	0	21.58	PASS
NVNT	Band2	3	18900	8	#Max	16QAM	21.25	0	21.25	PASS
NVNT	Band2	3	18900	15	#0	16QAM	21.25	0	21.25	PASS
NVNT	Band2	3	19185	1	#0	QPSK	22.71	0	22.71	PASS
NVNT	Band2	3	19185	1	#Mid	QPSK	23.41	0	23.41	PASS
NVNT	Band2	3	19185	1	#Max	QPSK	21.80	0	21.80	PASS
NVNT	Band2	3	19185	8	#0	QPSK	22.05	0	22.05	PASS
NVNT	Band2	3	19185	8	#Mid	QPSK	22.18	0	22.18	PASS
NVNT	Band2	3	19185	8	#Max	QPSK	21.80	0	21.80	PASS
NVNT	Band2	3	19185	15	#0	QPSK	21.89	0	21.89	PASS
NVNT	Band2	3	19185	1	#0	16QAM	21.65	0	21.65	PASS
NVNT	Band2	3	19185	1	#Mid	16QAM	22.30	0	22.30	PASS
NVNT	Band2	3	19185	1	#Max	16QAM	20.49	0	20.49	PASS
NVNT	Band2	3	19185	8	#0	16QAM	20.99	0	20.99	PASS
NVNT	Band2	3	19185	8	#Mid	16QAM	21.26	0	21.26	PASS
NVNT	Band2	3	19185	8	#Max	16QAM	20.90	0	20.90	PASS
NVNT	Band2	3	19185	15	#0	16QAM	21.05	0	21.05	PASS
NVNT	Band2	5	18625	1	#0	QPSK	22.76	0	22.76	PASS
NVNT	Band2	5	18625	1	#Mid	QPSK	22.58	0	22.58	PASS



NVNT	Band2	5	18625	1	#Max	QPSK	22.32	0	22.32	PASS
NVNT	Band2	5	18625	12	#0	QPSK	21.81	0	21.81	PASS
NVNT	Band2	5	18625	12	#Mid	QPSK	21.71	0	21.71	PASS
NVNT	Band2	5	18625	12	#Max	QPSK	21.63	0	21.63	PASS
NVNT	Band2	5	18625	25	#0	QPSK	21.77	0	21.77	PASS
NVNT	Band2	5	18900	1	#0	QPSK	23.03	0	23.03	PASS
NVNT	Band2	5	18900	1	#Mid	QPSK	23.28	0	23.28	PASS
NVNT	Band2	5	18900	1	#Max	QPSK	23.11	0	23.11	PASS
NVNT	Band2	5	18900	12	#0	QPSK	22.40	0	22.40	PASS
NVNT	Band2	5	18900	12	#Mid	QPSK	22.38	0	22.38	PASS
NVNT	Band2	5	18900	12	#Max	QPSK	22.26	0	22.26	PASS
NVNT	Band2	5	18900	25	#0	QPSK	22.32	0	22.32	PASS
NVNT	Band2	5	19175	1	#0	QPSK	22.70	0	22.70	PASS
NVNT	Band2	5	19175	1	#Mid	QPSK	22.85	0	22.85	PASS
NVNT	Band2	5	19175	1	#Max	QPSK	22.84	0	22.84	PASS
NVNT	Band2	5	19175	12	#0	QPSK	22.20	0	22.20	PASS
NVNT	Band2	5	19175	12	#Mid	QPSK	22.07	0	22.07	PASS
NVNT	Band2	5	19175	12	#Max	QPSK	21.85	0	21.85	PASS
NVNT	Band2	5	19175	25	#0	QPSK	22.10	0	22.10	PASS
NVNT	Band2	10	18650	1	#0	QPSK	23.09	0	23.09	PASS
NVNT	Band2	10	18650	1	#Mid	QPSK	22.76	0	22.76	PASS
NVNT	Band2	10	18650	1	#Max	QPSK	22.38	0	22.38	PASS
NVNT	Band2	10	18650	25	#0	QPSK	22.07	0	22.07	PASS
NVNT	Band2	10	18650	25	#Mid	QPSK	21.87	0	21.87	PASS
NVNT	Band2	10	18650	25	#Max	QPSK	21.54	0	21.54	PASS
NVNT	Band2	10	18650	50	#0	QPSK	21.82	0	21.82	PASS
NVNT	Band2	10	18900	1	#0	QPSK	23.36	0	23.36	PASS
NVNT	Band2	10	18900	1	#Mid	QPSK	23.61	0	23.61	PASS
NVNT	Band2	10	18900	1	#Max	QPSK	23.12	0	23.12	PASS
NVNT	Band2	10	18900	25	#0	QPSK	22.55	0	22.55	PASS
NVNT	Band2	10	18900	25	#Mid	QPSK	22.53	0	22.53	PASS
NVNT	Band2	10	18900	25	#Max	QPSK	22.26	0	22.26	PASS
NVNT	Band2	10	18900	50	#0	QPSK	22.41	0	22.41	PASS
NVNT	Band2	10	19150	1	#0	QPSK	22.72	0	22.72	PASS
NVNT	Band2	10	19150	1	#Mid	QPSK	23.34	0	23.34	PASS
NVNT	Band2	10	19150	1	#Max	QPSK	22.87	0	22.87	PASS
NVNT	Band2	10	19150	25	#0	QPSK	22.25	0	22.25	PASS
NVNT	Band2	10	19150	25	#Mid	QPSK	22.23	0	22.23	PASS
NVNT	Band2	10	19150	25	#Max	QPSK	21.91	0	21.91	PASS
NVNT	Band2	10	19150	50	#0	QPSK	22.08	0	22.08	PASS
NVNT	Band2	15	18675	1	#0	QPSK	22.96	0	22.96	PASS
NVNT	Band2	15	18675	1	#Mid	QPSK	22.64	0	22.64	PASS
NVNT	Band2	15	18675	1	#Max	QPSK	22.55	0	22.55	PASS
NVNT	Band2	15	18675	36	#0	QPSK	21.85	0	21.85	PASS
NVNT	Band2	15	18675	36	#Mid	QPSK	21.65	0	21.65	PASS
NVNT	Band2	15	18675	36	#Max	QPSK	21.64	0	21.64	PASS
NVNT	Band2	15	18675	75	#0	QPSK	21.91	0	21.91	PASS
NVNT	Band2	15	18900	1	#0	QPSK	22.99	0	22.99	PASS
NVNT	Band2	15	18900	1	#Mid	QPSK	23.47	0	23.47	PASS
NVNT	Band2	15	18900	1	#Max	QPSK	23.26	0	23.26	PASS
NVNT	Band2	15	18900	36	#0	QPSK	22.65	0	22.65	PASS
NVNT	Band2	15	18900	36	#Mid	QPSK	22.67	0	22.67	PASS
NVNT	Band2	15	18900	36	#Max	QPSK	22.15	0	22.15	PASS
NVNT	Band2	15	18900	75	#0	QPSK	22.44	0	22.44	PASS
NVNT	Band2	15	19125	1	#0	QPSK	22.92	0	22.92	PASS



NVNT	Band2	15	19125	1	#Mid	QPSK	23.17	0	23.17	PASS
NVNT	Band2	15	19125	1	#Max	QPSK	22.97	0	22.97	PASS
NVNT	Band2	15	19125	36	#0	QPSK	22.28	0	22.28	PASS
NVNT	Band2	15	19125	36	#Mid	QPSK	22.32	0	22.32	PASS
NVNT	Band2	15	19125	36	#Max	QPSK	21.95	0	21.95	PASS
NVNT	Band2	15	19125	75	#0	QPSK	22.11	0	22.11	PASS
NVNT	Band2	20	18700	1	#0	QPSK	22.98	0	22.98	PASS
NVNT	Band2	20	18700	1	#Mid	QPSK	22.69	0	22.69	PASS
NVNT	Band2	20	18700	1	#Max	QPSK	22.75	0	22.75	PASS
NVNT	Band2	20	18700	50	#0	QPSK	21.96	0	21.96	PASS
NVNT	Band2	20	18700	50	#Mid	QPSK	21.85	0	21.85	PASS
NVNT	Band2	20	18700	50	#Max	QPSK	21.63	0	21.63	PASS
NVNT	Band2	20	18700	100	#0	QPSK	21.77	0	21.77	PASS
NVNT	Band2	20	18900	1	#0	QPSK	22.91	0	22.91	PASS
NVNT	Band2	20	18900	1	#Mid	QPSK	23.58	0	23.58	PASS
NVNT	Band2	20	18900	1	#Max	QPSK	22.69	0	22.69	PASS
NVNT	Band2	20	18900	50	#0	QPSK	22.38	0	22.38	PASS
NVNT	Band2	20	18900	50	#Mid	QPSK	22.44	0	22.44	PASS
NVNT	Band2	20	18900	50	#Max	QPSK	22.56	0	22.56	PASS
NVNT	Band2	20	18900	100	#0	QPSK	22.13	0	22.13	PASS
NVNT	Band2	20	19100	1	#0	QPSK	23.08	0	23.08	PASS
NVNT	Band2	20	19100	1	#Mid	QPSK	23.16	0	23.16	PASS
NVNT	Band2	20	19100	1	#Max	QPSK	22.98	0	22.98	PASS
NVNT	Band2	20	19100	50	#0	QPSK	22.23	0	22.23	PASS
NVNT	Band2	20	19100	50	#Mid	QPSK	22.20	0	22.20	PASS
NVNT	Band2	20	19100	50	#Max	QPSK	22.59	0	22.59	PASS
NVNT	Band2	20	19100	100	#0	QPSK	21.99	0	21.99	PASS
NVNT	Band2	5	18625	1	#0	16QAM	22.34	0	22.34	PASS
NVNT	Band2	5	18625	1	#Mid	16QAM	22.18	0	22.18	PASS
NVNT	Band2	5	18625	1	#Max	16QAM	21.91	0	21.91	PASS
NVNT	Band2	5	18625	12	#0	16QAM	20.89	0	20.89	PASS
NVNT	Band2	5	18625	12	#Mid	16QAM	20.82	0	20.82	PASS
NVNT	Band2	5	18625	12	#Max	16QAM	20.62	0	20.62	PASS
NVNT	Band2	5	18625	25	#0	16QAM	20.70	0	20.70	PASS
NVNT	Band2	5	18900	1	#0	16QAM	22.23	0	22.23	PASS
NVNT	Band2	5	18900	1	#Mid	16QAM	22.58	0	22.58	PASS
NVNT	Band2	5	18900	1	#Max	16QAM	22.42	0	22.42	PASS
NVNT	Band2	5	18900	12	#0	16QAM	21.31	0	21.31	PASS
NVNT	Band2	5	18900	12	#Mid	16QAM	21.45	0	21.45	PASS
NVNT	Band2	5	18900	12	#Max	16QAM	21.31	0	21.31	PASS
NVNT	Band2	5	18900	25	#0	16QAM	21.42	0	21.42	PASS
NVNT	Band2	5	19175	1	#0	16QAM	22.11	0	22.11	PASS
NVNT	Band2	5	19175	1	#Mid	16QAM	22.31	0	22.31	PASS
NVNT	Band2	5	19175	1	#Max	16QAM	22.27	0	22.27	PASS
NVNT	Band2	5	19175	12	#0	16QAM	21.29	0	21.29	PASS
NVNT	Band2	5	19175	12	#Mid	16QAM	21.15	0	21.15	PASS
NVNT	Band2	5	19175	12	#Max	16QAM	20.94	0	20.94	PASS
NVNT	Band2	5	19175	25	#0	16QAM	21.06	0	21.06	PASS



3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 and ANSI C63.26 2015 Power Meas. License Digital Systems with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

LTE:

Test Mode		
Band	Radiated TCs	Conducted TCs
LTE Band 2	QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz/15MHz/ 20MHz)	16QAM Link (1.4MHz / 3MHz / 5MHz)
Note 1: All modes and data rates and positions were investigated.		



4 MEASUREMENT INSTRUMENTS

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	TP502V4-P	Toprie	N/A	2025.10.09	2026.10.08
Wireless Communications Test Set	R&S	CMW 500	117239	2025.09.26	2026.09.25
Signal Generator	Agilent	83752A	3610A02740	2026.02.04	2027.02.03
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2026.02.05	2027.02.04
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2026.02.04	2027.02.03
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Video Controller	SKET	FCS C-3	N/A	N/A	N/A
Bilog Antenna	TESEQ	CBL6111D	45873	2025.09.21	2026.09.20
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1314	2025.09.27	2027.09.26
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	N/A	N/A	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC Power Supply	Zhaoxin	RXN 605D	20R605D11010081	N/A	N/A
Test SW	EMC Test Software	25.5 en			
	EZ-EMC	Ver.STSLAB-03A1 RE			
RF Connected Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	TP502V4-P	Toprie	N/A	2025.10.09	2026.10.08
Wireless Communications Test Set	R&S	CMW 500	131428	2026.02.04	2027.02.03
Signal Analyzer	Agilent	N9020A	MY52440124	2026.02.04	2027.02.03
RF Automatic Test System	Maiwei	MW200-SFCB	N/A	N/A	N/A
Temperature & Humidity Test Chamber	Safety test	AG80L	171200018	2026.02.04	2027.02.03
Programmable Power Supply	Agilent	E3642A	MY40002025	2025.09.26	2026.09.25
POWER DIVIDER	eastsheep	PD-0.5/0.6-2S	N/A	2026.02.24	2027.02.23
Test SW	MTS 8200	2.0.0.0			

5 TEST ITEMS

5.1 CONDUCTED OUTPUT POWER&TRANSMITTER RADIATED POWER

TEST OVERVIEW

CONDUCTED OUTPUT POWER:

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

TRANSMITTER RADIATED POWER (EIRP/ERP)

Determining ERP and/or EIRP from conducted RF output power measurements according to ANSI C63.26 2015 Section 5.2.5.5.

In many cases, RF output power limits are specified in terms of the ERP or the EIRP. Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are defined as the product of the power supplied to the antenna and its gain (relative to a dipole antenna in the case of ERP, and relative to an isotropic antenna in the case of EIRP); however, when working in decibels (i.e., logarithmic scale), the ERP and EIRP represent the sum of the transmit antenna gain (in dBd or dBi, respectively) and the conducted RF output power (expressed in dB relative to watts or milliwatts). The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation (1) as follows:

$$(1) \text{ ERP or EIRP} = P_{\text{Meas}} + GT$$

$$\text{ERP} = \text{EIRP} - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

GT gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

For devices utilizing multiple antennas, see 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

The following equations demonstrate the mathematical relationship between ERP and EIRP:


a) $\text{ERP} = \text{EIRP} - 2.15$, where ERP and EIRP are expressed in consistent units.

b) $\text{EIRP} = \text{ERP} + 2.15$, where ERP and EIRP are expressed in consistent units.

TEST PROCEDURES

1. The transmitter output port was connected to the system simulator.
2. Set eut at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

TEST SETUP





TEST RESULT

The test data please reference to attachment “STS2605391W01_Appendix LTE”.

5.2 PEAK TO AVERAGE RATIO


TEST OVERVIEW

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 db.

TEST PROCEDURES

1. The testing follows FCC KDB 971168 v03r01 section.
2. The eut was connected to the peak and av system simulator& spectrum analyzer.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Set the test probe and measure average power of the spectrum analysis,

TEST SETUP



TEST RESULT

The test data please reference to attachment “STS2605391W01_Appendix LTE”.

5.3 OCCUPIED BANDWIDTH

TEST OVERVIEW

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.


The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

All modes of operation were investigated and the worst case configuration results are reported in this section.

TEST PROCEDURE

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

TEST SETUP



TEST RESULT

The test data please reference to attachment "STS2605391W01_Appendix LTE".

5.4 FREQUENCY STABILITY

TEST OVERVIEW

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26 2015.

The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE


Temperature Variation

1. The testing follows FCC KDB 971168 D01 section 9.0
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Voltage Variation

1. The testing follows FCC KDB 971168 D01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25 \pm 5^\circ \text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

TEST SETUP





TEST RESULT

The test data please reference to attachment "STS2605391W01_Appendix LTE".

5.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

TEST OVERVIEW

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7:


The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

TEST PROCEDURE

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0. and ANSI C63.26-2015-Section 5.7.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log(P)]$ (dB)
 $= [30 + 10 \log(P)]$ (dBm) - $[43 + 10 \log(P)]$ (dB)
 $= -13 \text{ dBm}$.

TEST SETUP



TEST RESULT

The test data please reference to attachment “STS2605391W01_Appendix LTE”.



5.6 BAND EDGE

TEST OVERVIEW

1. §22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

2. §24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed

3. §27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4. §27.53(m)(4)

For operations in the 2500 MHz ~ 2570 MHz band this section, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

5. §27.53 (g)

For operations in the 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

TEST PROCEDURE

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0 and ANSI C63.26-2015-Section 5.7
2. Start and stop frequency were set such that the band edge would be placed in the center of the Plot.
3. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
4. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
5. The band edges of low and high channels for the highest RF powers were measured.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$


Band 7:

$$= P(W) - [55 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [55 + 10\log(P)] \text{ (dB)}$$

$$= -25\text{dBm}.$$

TEST SETUP



TEST RESULT

The test data please reference to attachment "STS2605391W01_Appendix LTE".



5.7 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

TEST OVERVIEW

Radiated spurious emissions measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power and at the appropriate frequencies.


It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

TEST PROCEDURE


1. The testing FCC KDB 971168 D01 Section 5.8 and ANSI C63.26-2015-Section 5.5.
2. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $> 2 \times$ span/RBW
6. Detector = Peak
7. Trace mode = max hold
8. The trace was allowed to stabilize
9. Effective Isotropic Spurious Radiation was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna.
 $P_{Mea} = S.G \text{ Level} + \text{Ant-Cable loss}$; $\text{Margin} = P_{Mea} - \text{Limit}$.

TEST SETUP

For radiated test from 30MHz to 1GHz



For radiated test from above 1GHz



TEST RESULT

- Note:**
- (1) Spurious emissions which are attenuated by more than 20dB below the permissible value for frequency below 1000MHz.
 - (2) Above 3.5GHz amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value
 - (3) Test is divided into three directions, X/Y/Z. X pattern for the worst.



BAND 2

LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3701.34	-33.44	12.60	12.93	-33.77	-13.00	-20.77	H
5552.05	-34.83	13.10	17.11	-38.84	-13.00	-25.84	H
7402.57	-32.52	11.50	22.20	-43.22	-13.00	-30.22	H
3701.34	-35.62	12.60	12.93	-35.95	-13.00	-22.95	V
5552.05	-34.51	13.10	17.11	-38.52	-13.00	-25.52	V
7402.57	-32.64	11.50	22.20	-43.34	-13.00	-30.34	V
LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3760.20	-33.86	12.60	12.93	-34.19	-13.00	-21.19	H
5640.29	-34.15	13.10	17.11	-38.16	-13.00	-25.16	H
7519.95	-32.36	11.50	22.20	-43.06	-13.00	-30.06	H
3760.20	-35.37	12.60	12.93	-35.70	-13.00	-22.70	V
5640.29	-35.02	13.10	17.11	-39.03	-13.00	-26.03	V
7519.95	-33.19	11.50	22.20	-43.89	-13.00	-30.89	V
LTE Band 2 / 1.4MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3818.60	-34.07	12.60	12.93	-34.40	-13.00	-21.40	H
5727.45	-35.08	13.10	17.11	-39.09	-13.00	-26.09	H
7637.17	-33.00	11.50	22.20	-43.70	-13.00	-30.70	H
3818.60	-35.85	12.60	12.93	-36.18	-13.00	-23.18	V
5727.45	-34.20	13.10	17.11	-38.21	-13.00	-25.21	V
7637.17	-32.86	11.50	22.20	-43.56	-13.00	-30.56	V



LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3703.19	-34.28	12.60	12.93	-34.61	-13.00	-21.61	H
5554.17	-35.28	13.10	17.11	-39.29	-13.00	-26.29	H
7405.68	-32.43	11.50	22.20	-43.13	-13.00	-30.13	H
3703.19	-35.00	12.60	12.93	-35.33	-13.00	-22.33	V
5554.17	-34.67	13.10	17.11	-38.68	-13.00	-25.68	V
7405.68	-31.75	11.50	22.20	-42.45	-13.00	-29.45	V
LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.81	-33.71	12.60	12.93	-34.04	-13.00	-21.04	H
5640.18	-34.25	13.10	17.11	-38.26	-13.00	-25.26	H
7520.16	-32.93	11.50	22.20	-43.63	-13.00	-30.63	H
3759.81	-35.41	12.60	12.93	-35.74	-13.00	-22.74	V
5640.18	-34.06	13.10	17.11	-38.07	-13.00	-25.07	V
7520.16	-32.47	11.50	22.20	-43.17	-13.00	-30.17	V
LTE Band 2 / 3MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3817.10	-34.02	12.60	12.93	-34.35	-13.00	-21.35	H
5725.52	-34.66	13.10	17.11	-38.67	-13.00	-25.67	H
7634.24	-32.58	11.50	22.20	-43.28	-13.00	-30.28	H
3817.10	-34.64	12.60	12.93	-34.97	-13.00	-21.97	V
5725.52	-34.13	13.10	17.11	-38.14	-13.00	-25.14	V
7634.24	-32.58	11.50	22.20	-43.28	-13.00	-30.28	V



LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3705.19	-34.50	12.60	12.93	-34.83	-13.00	-21.83	H
5557.57	-34.19	13.10	17.11	-38.20	-13.00	-25.20	H
7409.83	-33.02	11.50	22.20	-43.72	-13.00	-30.72	H
3705.19	-34.61	12.60	12.93	-34.94	-13.00	-21.94	V
5557.57	-34.18	13.10	17.11	-38.19	-13.00	-25.19	V
7409.83	-32.51	11.50	22.20	-43.21	-13.00	-30.21	V
LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.93	-34.26	12.60	12.93	-34.59	-13.00	-21.59	H
5640.07	-35.19	13.10	17.11	-39.20	-13.00	-26.20	H
7520.00	-32.82	11.50	22.20	-43.52	-13.00	-30.52	H
3759.93	-35.03	12.60	12.93	-35.36	-13.00	-22.36	V
5640.07	-34.77	13.10	17.11	-38.78	-13.00	-25.78	V
7520.00	-32.47	11.50	22.20	-43.17	-13.00	-30.17	V
LTE Band 2 / 5MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3815.01	-34.58	12.60	12.93	-34.91	-13.00	-21.91	H
5722.09	-35.03	13.10	17.11	-39.04	-13.00	-26.04	H
7629.90	-33.15	11.50	22.20	-43.85	-13.00	-30.85	H
3815.01	-35.14	12.60	12.93	-35.47	-13.00	-22.47	V
5722.09	-34.15	13.10	17.11	-38.16	-13.00	-25.16	V
7629.90	-33.04	11.50	22.20	-43.74	-13.00	-30.74	V



LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3710.07	-33.70	12.60	12.93	-34.03	-13.00	-21.03	H
5565.27	-35.11	13.10	17.11	-39.12	-13.00	-26.12	H
7419.83	-33.09	11.50	22.20	-43.79	-13.00	-30.79	H
3710.07	-35.43	12.60	12.93	-35.76	-13.00	-22.76	V
5565.27	-34.40	13.10	17.11	-38.41	-13.00	-25.41	V
7419.83	-33.18	11.50	22.20	-43.88	-13.00	-30.88	V
LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.98	-33.57	12.60	12.93	-33.90	-13.00	-20.90	H
5640.07	-34.47	13.10	17.11	-38.48	-13.00	-25.48	H
7519.95	-33.45	11.50	22.20	-44.15	-13.00	-31.15	H
3759.98	-35.83	12.60	12.93	-36.16	-13.00	-23.16	V
5640.07	-33.95	13.10	17.11	-37.96	-13.00	-24.96	V
7519.95	-31.98	11.50	22.20	-42.68	-13.00	-29.68	V
LTE Band 2 / 10MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3810.07	-34.14	12.60	12.93	-34.47	-13.00	-21.47	H
5714.73	-34.65	13.10	17.11	-38.66	-13.00	-25.66	H
7620.27	-32.27	11.50	22.20	-42.97	-13.00	-29.97	H
3810.07	-34.88	12.60	12.93	-35.21	-13.00	-22.21	V
5714.73	-35.09	13.10	17.11	-39.10	-13.00	-26.10	V
7620.27	-31.96	11.50	22.20	-42.66	-13.00	-29.66	V



LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3715.04	-33.55	12.60	12.93	-33.88	-13.00	-20.88	H
5572.14	-34.42	13.10	17.11	-38.43	-13.00	-25.43	H
7430.58	-32.23	11.50	22.20	-42.93	-13.00	-29.93	H
3715.04	-35.93	12.60	12.93	-36.26	-13.00	-23.26	V
5572.14	-33.80	13.10	17.11	-37.81	-13.00	-24.81	V
7430.58	-32.54	11.50	22.20	-43.24	-13.00	-30.24	V
LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.95	-34.80	12.60	12.93	-35.13	-13.00	-22.13	H
5639.98	-34.72	13.10	17.11	-38.73	-13.00	-25.73	H
7520.06	-33.45	11.50	22.20	-44.15	-13.00	-31.15	H
3759.95	-35.41	12.60	12.93	-35.74	-13.00	-22.74	V
5639.98	-33.83	13.10	17.11	-37.84	-13.00	-24.84	V
7520.06	-31.91	11.50	22.20	-42.61	-13.00	-29.61	V
LTE Band 2 / 15MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3805.17	-34.16	12.60	12.93	-34.49	-13.00	-21.49	H
5707.52	-35.14	13.10	17.11	-39.15	-13.00	-26.15	H
7610.18	-32.19	11.50	22.20	-42.89	-13.00	-29.89	H
3805.17	-35.69	12.60	12.93	-36.02	-13.00	-23.02	V
5707.52	-34.42	13.10	17.11	-38.43	-13.00	-25.43	V
7610.18	-31.77	11.50	22.20	-42.47	-13.00	-29.47	V



LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Lowest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3720.15	-34.81	12.60	12.93	-35.14	-13.00	-22.14	H
5580.43	-34.70	13.10	17.11	-38.71	-13.00	-25.71	H
7439.74	-32.83	11.50	22.20	-43.53	-13.00	-30.53	H
3720.15	-34.59	12.60	12.93	-34.92	-13.00	-21.92	V
5580.43	-34.75	13.10	17.11	-38.76	-13.00	-25.76	V
7439.74	-32.38	11.50	22.20	-43.08	-13.00	-30.08	V
LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Middle							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3760.10	-33.54	12.60	12.93	-33.87	-13.00	-20.87	H
5640.26	-34.27	13.10	17.11	-38.28	-13.00	-25.28	H
7520.20	-33.23	11.50	22.20	-43.93	-13.00	-30.93	H
3760.10	-35.94	12.60	12.93	-36.27	-13.00	-23.27	V
5640.26	-33.83	13.10	17.11	-37.84	-13.00	-24.84	V
7520.20	-33.15	11.50	22.20	-43.85	-13.00	-30.85	V
LTE Band 2 / 20MHz / QPSK / RB Size 1 Offset 0/ The Worst Test Results for Highest							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3799.83	-34.28	12.60	12.93	-34.61	-13.00	-21.61	H
5700.11	-34.86	13.10	17.11	-38.87	-13.00	-25.87	H
7600.15	-32.69	11.50	22.20	-43.39	-13.00	-30.39	H
3799.83	-34.57	12.60	12.93	-34.90	-13.00	-21.90	V
5700.11	-33.89	13.10	17.11	-37.90	-13.00	-24.90	V
7600.15	-31.77	11.50	22.20	-42.47	-13.00	-29.47	V



APPENDIX-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※