



Test Report - FCC Part 1.1310/ MPE

Applicant: Radio Activity srl

Signature:

A handwritten signature in black ink, appearing to read "Tim Royer".

Sr. EMC Engineer
EMC-003838-NE



Name & Title: Tim Royer, Lab Manager

Date of Signature 2026-06-06

Signature:

A handwritten signature in black ink, appearing to read "Osvaldo F.".

Name & Title: Osvaldo Fernandez, Test Technician

Date of Signature 2026-06-06

Prepared By: Mark Learner, Technical Writer

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

1.	APPLICANT INFORMATION.....	3
2.	LOCATION OF TESTING.....	3
2.1	TEST LABORATORY	3
3.	TEST SAMPLE(S) (EUT/DUT).....	3
3.1	DESCRIPTION OF THE EUT.....	4
4.	TEST METHODS & APPLICABLE REGULATORY LIMITS.....	5
4.1	TEST METHODS/STANDARDS/GUIDANCE:.....	5
4.1.1	<i>FCC Limits for Maximum Permissible Exposure (MPE)</i>	5
4.2	EQUATIONS	6
5.	RF EXPOSURE RESULTS	7
6.	HISTORY OF TEST REPORT CHANGES.....	8

1. Applicant Information

Applicant: RADIO ACTIVITY S.R.L
Address: VIA PRIVATA CASCIA, 11,
MILANO, 20128 ITA

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
CAB identifier number #US0111
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 2026-04-21

Dates of Testing: 2026-04-25 – 2026-05-29

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	Y9M-KA040E
Brief Description	PMR digital transceiver/repeater
Model(s) #	KA-040e
Firmware version	-
Software version	-
Serial Number	-

Technical Characteristics	
Frequency Range	39-50MHz
RF O/P Power (Max.)	Rated 1 to 50W
Modulation	FM/PM (12.5-20-25kHz), 4FSK, C4FM
Bandwidth & Emission Class	11K0F3E, 11K0G3E, 14K0F3E, 14K0G3E, 16K0F3E, 16K0G3E, 8K10F1E, 8K10F1D, 7K60FXE, 7K60FXD
Number of Channels	1 working channel (2 logical channels for DMR); up to 200 programmable channels
Duty Cycle	Up to 100%
Antenna Connector	SMA
Voltage Rating (AC or Batt.)	13.2Vdc, negative to GND, 10A max

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	39-50MHz	N/A	Max allowed per manufacturer 6 dBi

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging Time (minutes)
A Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
B Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

4.2 Equations

POWER DENSITY

$$E(V/m) = \text{SQRT} (30 * P * G) / d$$

$$Pd(W/m^2) = E^2 / 377$$

$$S = \text{EIRP} / (4 * \text{Pi} * D^2v)$$

Where:

S = Power density, in mW/cm²

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of mW/cm² to units of W/m² by multiplying by 10.

DISTANCE

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

$$\text{Source-based time-average EIRP} = (DC / 100) * \text{EIRP}$$

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW

5. RF Exposure Results

MPE

Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limit (cm)
39-50 MHz	20	53.00	6.00	100%	199.5262	39.694 mW/cm ²	0.2 mW/cm ²	1 mW/cm ²	281.76

RESULT: Pass at DISTANCE 281.76 cm

6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_27537-26_FCC 1.1310_MPE_1	1	Initial release	2026-06-06
	3	Updated Page 7	7/17/2026
	4	Updated Page 4,7	8/5/2026
	5	Updated Page 7	8/6/2026

END OF TEST REPORT
